
Index

- Acousto-optic switches, 41
- ACTS. *See* Advanced Communications Technologies and Services (ACTS)
- Actuation forces
 - micromirrors, 33
- Administrative group
 - LSA, 130
- Advanced Communications Technologies and Services (ACTS), 88
- Advertisement messages, 123
- All-optical buffering, 66
- All-optical crossconnects
 - (OOO crossconnects), 26
- All-optical flip-flop memory, 65
- All-optical label swapping (AOLS), 61, 66
- All-optical packet
 - delineation and synchronization, 65
- All-optical packet switch fabrics, 66
- All-optical 3R regeneration, 64
- All-optical signal processing, 65
- All-optical switches, 42
- All-optical transparency
 - expanding islands, 12f
- All-optical wavelength conversion, 67
- American National Standards Institute (ANSI), 3
- ANSI. *See* American National Standards Institute (ANSI)
- AOLS. *See* All-optical label swapping (AOLS)
- Arrayed waveguide gratings (AWGs)
 - and tunable, 62
- ASON. *See* Automatically switched optical network (ASON)
- Asynchronous (slotted) network, 58
- Asynchronous Transfer Mode (ATM), 114f, 133, 136, 182f
 - electronic switches, 26, 88
 - frame relay, 96, 124
 - layer, 2, 9f, 114, 117, 124
 - switch, 151, 171
 - TE, 113
- ATM. *See* Asynchronous Transfer Mode (ATM)
- Automatically switched optical network (ASON), 160
 - control plane, 162
 - GMPLS, 160–166
 - logical interfaces, 161
- Automatic port/neighbor and topology discovery, 18
- AWG. *See* Arrayed waveguide gratings (AWGs) and tunable
- Banyan network, 47
 - 8 × 8, 49f
- Batch fabrication, 25
- Benes, 47
- Best Fit, 208
- BGP. *See* Border Gateway Protocol (BGP)
- Bit-level synchronization, 65
- Blocking characteristics, 44
 - Clos network, 46
- BORA. *See* Burst Overlap Reduction Algorithms (BORA)
- Border Gateway Protocol (BGP), 122

- Bottom of stack
 - label stack entry, 121
- Broadband applications, 9
 - categories, 9
 - examples, 10
- Broadband services, 1
- Broadcast-and-select architecture
 - advantage, 63
- Broadcast-and-select networks, 5–6
- Broadcast-and-select packet switch, 89
 - architecture, 90f
- Broadcast-and-select WDM network
 - passive star coupler, 6f
- Bubble switch element, 41f
- Bubble switches, 40
- Buffering requirement
 - OBS, 172
- Buffers, 70f
- Building large switches
 - architecture, 44
- Bundled link
 - TE parameters, 143–144
- Burst assembly
 - combined timer/threshold-based algorithm, 184f
 - OBS, 181–186
- Burst assembly algorithms
 - OBS, 182–185
- Burst losses, 173
- Burst offset (T_{offset}), 176
- Burst Overlap Reduction Algorithms (BORA), 211
- Burst scheduling
 - OBS, 202–211
- Burst segmentation
 - OBS, 214–220

- Call and connection separation, 164
- Call controller
 - ASON control plane, 162
- Call segment
 - support, 164
- Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA), 99
- CC_Id. *See* Control Channel Id (CC_Id)
- Cell encoder, 69
- Centralized deflection, 232
- Challenges
 - optical network switching, 16–17
- Class isolation, 226f
- Clos, 45
 - Clos network
 - blocking characteristics, 46
 - three-stage, 46f
 - Components
 - network architecture, 14
 - ConfigAck message, 158
 - Configurations
 - fiber delay lines, 175
 - SONET/SDH network, 4
 - Connection controller
 - ASON control plane, 162
 - CONNECT message, 195
 - Constraint based routing
 - MPLS, 127–128
 - Constraint routing-LSP (CR-LSP), 128
 - Contention resolution
 - OBS, 212–222
 - OPS, 79–85
 - Contention scenarios, 222f
 - Control Channel Id (CC_Id), 158
 - Control packets, 204
 - processing time, 176
 - Converter-sharing architecture, 72
 - Converters partition, 87
 - Core mesh network, 14
 - requirements, 15
 - Cost minimization
 - network architecture, 14
 - Cost per transferred bit, 96
 - Crankback signaling, 165
 - CR-LSP. *See* Constraint routing-LSP (CR-LSP)
 - Crossbar, 44
 - Cross-gain modulation (XGM), 68
 - Crossovers, 43
 - Cross-phase modulation (XPM), 68
 - Crosstalk, 24, 43
 - CSMA/CA. *See* Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA)
 - Current network, 8–10

- Data and Voice Integration over DWDM (DAVID) project, 100–102
 - architecture, 101
- Data vortex packet switch, 62, 92–94
- DAVID. *See* Data and Voice Integration over DWDM (DAVID) project
- DECLARATION message, 195
- Dedicated 1 + 1
 - GMPLS routing protocols, 150
- Dedicated 1 : 1
 - GMPLS protection capabilities, 150

- Deflection routing
 - OBS, 213–214, 232
 - OPS, 84–85
- Delayed wavelength reservation
 - OBS signaling, 190f
- Delay unit, 82
- Dense wavelength division multiplexing (DWDM), 151, 177
 - layer, 2, 101–102, 113, 114f, 135
 - optical network, 4
- Digital optical switches, 38
- Dilation, 43
- Discovery messages, 123
- Distributed deflection, 232
- Drives
 - optical network advancement, 9f
- Durability, 24
- DWDM. *See* Dense wavelength division multiplexed (DWDM)
- Dynamic reliability, 24

- Ease of fabrication, 25
- EDFA. *See* Erbium Doped Fiber Amplifiers (EDFA)
- Edge routers, 174
 - architecture, 174f
- Electrical-to-optical (EO) conversion, 3
- Electromagnetic actuation, 34
- Electronic ATM switches, 26
- Electronic random access memory, 79
- Electro-optic directional coupler switch, 36f
- Electro-optic lithium niobate switches, 36, 62
- Electro-optic switches, 36
- Electrostatic actuation, 33
- Enabling technologies
 - OPS, 63–68
- Encoding type
 - LSP, 137
- Enhanced
 - GMPLS routing protocols, 149–152
- E-NNI. *See* External Network–Network Interface (E-NNI)
- EO. *See* Electrical-to-optical (EO) conversion
- Erbium Doped Fiber Amplifiers (EDFA), 4
- Exclusive monitoring, 29
- Experimental
 - label stack entry, 121
- Explicit attribute scope
 - link attributes, 149
- Explicit setup/explicit release, 188, 191f
- Explicit setup/implicit release, 188, 192f

- Extended label association, 165
- Extended restart capabilities, 164–165
- External Network–Network Interface (E-NNI), 161
- Extinction ratio (on-off switches), 24
- Extra traffic
 - GMPLS protection capabilities, 150

- Fabric
 - optical switches, 29–42
- Fabric technology
 - and architecture, 62–63
- Fast provisioning, 11, 11f
- FEC. *See* Forwarding equivalence classes (FECs)
- FEC-to-NHLFE (FTN) maps, 119
- Fiber delay lines
 - configurations, 175
- Fiber delay lines (FDLs), 80, 80f
- Fiber-switch capable (FSC), 151
 - interfaces, 136
- First-fit algorithm, 198
- First-fit wavelength assignment, 199f
- Fixed-length traffic, 57
- Flexible upgrade, 96
- Flipped signal, 41
- FDLs. *See* Fiber delay lines (FDLs)
- Forwarding equivalence classes (FECs), 115, 119
- Forward resource reservation scheme, 186
- Four-wave mixing (FWM), 5, 67
- Frame relay, 96, 124
- FSC. *See* Fiber-switch capable (FSC)
- FTN maps, 119
- FWM. *See* Four-wave mixing (FWM)

- Generalized multiprotocol label switching (GMPLS), 18, 19, 113–165
 - ASON, 160–165
 - architecture, 161–162
 - features, 138–145
 - labels, 134
 - protocol suite, 146–159, 147f
 - link management protocol, 157–159
 - routing protocols, 147–151
 - signaling protocols, 152–156
- Generic path selection and maintenance attributes
 - traffic trunks, 126
- GMPLS. *See* Generalized multiprotocol label switching (GMPLS)
- Group scheduling, 211

- Head dropping vs. tail dropping
 - segmentation policies, 216f
- Header-packet transmission, 61
 - approaches, 61f
- Horizon scheduling algorithm, 204, 205f
- HORNET. *See* Hybrid Optoelectronic Ring Network (HORNET) project
- Hub node, 102
- Hybrid networks, 13
- Hybrid Optoelectronic Ring Network (HORNET) project, 98–99
- Hybrid switching architectures, 179

- IETF. *See* Internet Engineering Task Force (IETF)
- ILM. *See* Incoming label map (ILM)
- Immediate wavelength reservation
 - OBS signaling, 189f
- Implicit setup/explicit release, 188, 191f
- Implicit setup/implicit release, 189, 192f
- Incoming label map (ILM), 119
- Information Society Technology (IST) Program, 100
- Ingress edge routers, 174
- Inherent multicast capability, 25
- Inheritable attributes
 - support
 - link attributes, 149
- I-NNI. *See* Internal Network–Network Interface (I-NNI)
- Input synchronization, 58f
- Insertion loss, 24
- Interface switching capability descriptor
 - GMPLS routing protocols, 150–151
- Interference level
 - nodes, 200
- Interferometric switches, 37
- Interlayer attributes
 - support
 - link attributes, 148
- Intermediate System to Intermediate System (IS-IS), 129
- Internal Network–Network Interface (I-NNI), 161
- International Telecommunication Union (ITU), 3, 160
- Internet Engineering Task Force (IETF), 115
- Internet protocol (IP)
 - layer and optical layer interaction, 2
 - over WDM, 2, 113–114
 - traffic, 2
- IS-IS. *See* Intermediate System to Intermediate System (IS-IS)

- IST. *See* Information Society Technology (IST) Program
- ITU. *See* International Telecommunication Union (ITU)

- JumpStart signaling
 - architecture, 193–194
 - functional requirements, 193
 - long bursts, 194f
 - short burst, 194f

- KEEPALIVE message, 195
- Keep-alive signal generation, 18
- Keys to Optical Packet Switching (KEOPS), 88–89

- Label
 - distribution adjacency, 118
 - distribution peers, 118
 - label stack entry, 121
 - switching interfaces, 152t
- Label Distribution Protocol (LDP), 123
- Labeled optical burst switching (LOBS), 179–180
 - network node architecture, 180f
- Labeled packet, 117
- Label stack entry
 - bottom of stack, 121
 - experimental, 121
 - TTL, 121
- Label switched path (LSP), 116f, 120, 125, 126, 128–129, 137, 154–157, 160, 180–181
 - bandwidth, 150–151
 - control, 118
 - encoding type, 137
 - hierarchy, 142f
 - PID, 138
 - tunnels, 120, 131–133
- Label switching routers (LSR), 115, 116f, 117–124, 133, 135, 141, 144–145, 149–156, 180
- Label switching support, 193
- Lambda-Switch Capable (LSC), 151
 - interface, 136
- Large switches
 - building optical switches, 42–49
 - considerations, 43
- Latest Available Unused Channel (LAUC) algorithm, 204
- Latest Available Unused Channel with Void Filling (LAUC-VF), 206, 207f

- LAUC. *See* Latest Available Unused Channel (LAUC) algorithm
- Layer-2 switch capable (L2SC), 151
 - interfaces, 136
- LDP. *See* Label Distribution Protocol (LDP)
- Lightpaths
 - defined, 25
 - provisioning, 25
- Linear networks, 4
 - PWA and PWA link, 201f
- Link attributes, 148–149
- Link bundling, 143
- Link ID
 - TE, 144
- Link Management Protocol (LMP)
 - GMPLS, 157–159
 - procedures, 146, 147f, 158–162
- Link protection type, 150
- Link resource manager
 - ASON control plane, 162
- Link State Advertisements (LSAs), 129
 - attributes, 130
- LinkSummary message, 159
- Link type
 - TE, 143
- Liquid-crystal optical switch.
 - 1 × 2, 39f
- Liquid-crystal switches, 38–39
- Lithium niobate, 36, 67
- LMP. *See* Link Management Protocol (LMP)
- Load-balancing techniques, 196
- LOBS. *See* Labeled optical burst switching (LOBS)
- Local access networks (third level), 8
- Local and remote identifiers
 - TE, 144
- Local and remote interface IP addresses
 - TE, 144
- Local Control Channel Id, 158
- Local deflection, 231
- Logical interfaces
 - ASON, 161
- Long bursts
 - JumpStart signaling, 194f
- Loss, 173
- LSA. *See* Link State Advertisements (LSAs)
- LSC. *See* Lambda-Switch Capable (LSC)
- L2SC. *See* Layer-2 switch capable (L2SC)
- LSP. *See* Label switched path (LSP)
- LSR. *See* Label switching routers (LSR)

- MAC. *See* Medium access control (MAC) protocol
- Mach-Zehnder interferometers (MZIs), 37, 64
- Magnetic actuation, 34
- MAN. *See* Metropolitan area network (MAN)
- Manual configuration
 - network architecture, 14
- Maximum bandwidth
 - LSA, 130
- Maximum Ending Void, 208
- Maximum LSP bandwidth
 - TE, 144
- Maximum reservable bandwidth
 - LSA, 130
 - TE, 144
- Maximum Starting Void, 208
- Medium access control (MAC)
 - protocol, 6, 97
- MEMS. *See* Micro-electro mechanical switches (MEMS)
- Metric
 - TE, 144
- Metro network, 97f
- Metropolitan area network (MAN), 8, 93, 96
 - ring nodes, 102
- Metropolitan area packet switched networks, 95–106
- Micro-electrical mechanical switches (MEMS), 62
 - based devices, 35
 - reliability, 35
 - three dimensional
 - disadvantages, 33
 - optical switches, 32
 - technology, 32f
 - two dimensional
 - device, 31
 - technology, 31f
- Micromirrors
 - actuation forces, 33
- Micro-opto-electro-mechanical systems (MOEMS), 30
- Min-EV. *See* Minimum Ending Void (Min-EV)
- Minimum Ending Void (Min-EV), 208
- Minimum Starting Void (Min-SV)
 - algorithm, 206
- Min-SV. *See* Minimum Starting Void (Min-SV) algorithm
- MOEMS. *See* Micro-opto-electro-mechanical systems (MOEMS)
- MPLS. *See* Multiprotocol Label Switching (MPLS)
- Multicast capability, 25
- Multicast communication support, 193
- Multicasting, 235f
 - OBS, 233–234

- Multimode fiber, 2
- Multiprotocol Label Switching (MPLS), 114, 115–132, 181
 - constraint based routing, 127–128
 - label distribution, 117–123
 - operations, 115–116
 - routing protocol extensions, 129–130
 - signaling protocol extensions, 131–132
 - traffic engineering, 124–126
- MZI. *See* Mach-Zehnder interferometers (MZIs)

- Network cost, 12
- Network hierarchy, 9f
- Network provisioning, 29
- Network reliability
 - OBS, 232
- Next hop label forwarding entries (NHLFEs), 119
- Nodes
 - interference level, 200
- Nonadaptive wavelength assignment
 - algorithms, 198
- Nonblocking space switch, 69
- NonPreemptive Minimum Overlap Channel (NP-MOC) algorithm, 218, 218f
 - delay-first, 219
 - with void filling, 219
 - segment-first, 220
 - with void filling, 220
- Notification messages, 123
- NP-MOC. *See* NonPreemptive Minimum Overlap Channel (NP-MOC) algorithm
- n-Stage Planar Architecture, 47

- OADM. *See* Optical add-drop multiplexers (OADMs)
- OBS. *See* Optical burst switching (OBS)
- OE. *See* Optical-to-electrical (OE) conversion
- OEO. *See* Optical to electrical to optical (OEO)
- Offset time
 - OBS, 171
- One-way reservations
 - OBS, 171
- On-the-fly path setup, 194
- OOO crossconnects. *See* All-optical crossconnects (OOO crossconnects)
- Opaque switching, 15
- Open Shortest Path First (OSPF), 129
- OPS. *See* Optical packet switching (OPS)

- Optical add-drop multiplexers (OADMs), 28
- Optical add/drop multiplexing, 28
- Optical burst switching (OBS), 18, 19, 171–234
 - burst assembly, 181–186
 - algorithms, 182–185
 - predictive assembly algorithms, 186
 - burst scheduling, 202–211
 - scheduling algorithm implementation, 209
 - scheduling algorithms without void filling, 204–205
 - scheduling algorithms with void filling, 206–208
 - characteristics, 171
 - contention resolution, 212–222
 - burst segmentation, 214–220
 - deflection routing, 213–214
 - prioritized, 221–222
 - network and node architecture, 173–176
 - labeled optical burst switching, 179–180
 - wavelength-routed optical burst switched networks, 177–178
 - protection and restoration, 228–234
 - multicasting, 233–234
 - network reliability, 232
 - 1 + 1 protection, 229
 - restoration via deflection routing, 232
 - quality of service support, 223–227
 - offset-based, 224–226
 - routing and wavelength assignment, 195–201
 - routing, 196
 - wavelength assignment, 197–201
 - signaling, 187–194
 - delayed wavelength reservation, 190f
 - immediate wavelength reservation, 189f
 - JumpStart signaling architecture, 193–194
- Optical burst switching (OBS) network
 - architecture, 172f
 - parameters, 176
 - burst assembly, 182f
- Optical crossconnect (OXC), 25, 35, 175
 - defined, 134
- Optical fiber, 1
- Optical fiber communication
 - initial use, 3
- Optical header transmission
 - approaches, 60
- Optical layer equipment, 13
- Optical micro-electro-mechanical systems (optical MEMS), 30–36
- Optical network, 11–12
 - advancement
 - drives, 9f

- evolution, 1–7, 114f
 - broadcast-and-select networks, 5–6
 - wavelength-routed networks, 7
- paradigms adoption, 19f
- switching, 13–17
 - challenges, 16–17
 - opaque switching, 15
 - optical switching, 14
- Optical packet switching (OPS), 18, 55–107
 - architecture, 69f, 87–95
 - data-vortex packet switch, 92–94
 - KEOPS, 88–89
 - WASPNET, 90–91
 - contention resolution, 79–85
 - buffering, 79–84
 - deflection routing, 84
 - deployment, 56
 - design alternatives, 56–62
 - electronic vs. optical control, 61
 - fabric technology and architecture, 61–62
 - header format, transmission, processing, 58–60
 - synchronous vs. asynchronous, 56–57
 - enabling technologies, 63–68
 - all-optical buffering, 66
 - all-optical packet delineation and synchronization, 65
 - all-optical packet switch fabrics, 66
 - all-optical 3R regeneration, 64
 - all-optical signal processing, 65
 - all-optical wavelength conversion, 67
 - flexibility, 84
 - general architecture, 69–70
 - metropolitan area packet switched networks, 95–106
 - DAVID Project, 100–102
 - HORNET Project, 98–99
 - RingO Project, 103–106
 - quality of service support, 86–87
 - wavelength conversion, 71–77
 - limited range wavelength converters, 78
- Optical performance monitoring, 27
- Optical signal monitoring, 28
- Optical spectral monitoring, 27
- Optical switches, 23–50
 - applications, 25–30
 - network provisioning, 29
 - optical add/drop multiplexing, 28
 - optical crossconnects, 25
 - optical signal monitoring, 28
 - protection and restoration, 26–27
 - building large switches, 42–49
 - fabrics, 29–42
 - acousto-optic switches, 41
 - all-optical switches, 42
 - bubble switches, 40
 - electro-optic switches, 36
 - liquid-crystal switches, 38–39
 - optical MEMS, 30–36
 - optomechanical switches, 30
 - semiconductor optical amplifier switches, 42
 - thermo-optic switches, 37
 - parameters, 24
 - performance evaluation, 23–24
 - protection schemes, 27f
- Optical switching
 - advantages, 14–16
- Optical switching paradigms, 18–19
- Optical-to-electrical (OE) conversion, 3, 4
- Optical to electrical to optical (OEO) conversions, 11–18, 19f, 55, 67, 172
- switching, 26
- Optimal prediction, 187
- Optimized resource utilization, 96
- Optoelectronic conversions
 - elimination, 13
- Optomechanical switches, 30
- OSPF. *See* Open Shortest Path First (OSPF)
- Out-of-band signaling, 179
- Overhead bytes
 - advantages, 16
- Overlapping burst, 212f
- Overlay model, 125
- OXC. *See* Optical crossconnect (OXC)

- Packet delays, 57
- Packet delineation, 65
- Packet format
 - synchronous OPS network, 60f
- Packet routing, 89
- Packet-switch capable (PSC)
 - interfaces, 136
 - interfaces (1–4), 151
- Packet switches, 55
- Packet traversing a label switched path, 116f
- Passive architecture
 - drawback, 103
- Passive star coupler
 - broadcast-and-select WDM network, 6f
- Patch switching, 196
 - pure strategies, 197
- Payload transparent operation, 180

- PDL. *See* Polarization-dependent loss (PDL)
- Persistent connections, 193
- Phase-matched signal, 41
- Physical impairments, 17
- PID, 137
 - LSP, 138
- Point-to-point networks, 4
- Polarization-dependent loss (PDL), 24
- Polarization-independent acousto-optic switch, 41f
- Policing attributes
 - traffic trunks, 127
- Port count, 24
- Power consumption/driving voltage, 25
- Predictive assembly algorithms
 - OBS, 186
- Preemption attributes
 - traffic trunks, 127
- Pretransmission delay, 173
- Priority attributes
 - traffic trunks, 126
- Priority-based wavelength assignment (PWA), 201f
 - algorithm, 200
- Proactive burst scheduling, 211
- Processing time (T_{proc})
 - control packet, 176
- Protection schemes
 - optical switches, 27f
- Protection switching, 27
- Protocol controller
 - ASON control plane, 162
- Provisioning
 - lightpaths, 25
- Provisioning process, 10
- PSC. *See* Packet-switch capable (PSC)
- PWA. *See* Priority-based wavelength assignment (PWA)

- Quality of service support
 - extra offset time, 225f

- Raman amplification, 5
- Random algorithm, 198
- Rearrangeably nonblocking 8×8 switch, 47f, 48f
- RELEASE message, 195
- RELEASE packet, 190
- Remote identifiers
 - TE, 144
- Remote interface IP addresses
 - TE, 144
- Repeatability, 25

- Resilience attributes
 - traffic trunks, 127
- Resource classes
 - TE, 144
- Resource Reservation Protocol (RSVP), 122
- Restoration routing
 - OBS, 232
- Ring networks, 4
- Ring nodes, 102
- Ring Optical network (RingO)
 - project, 103
 - architecture, 104f
 - timeslots, 106
- Ring topologies, 97
- Routing and wavelength assignment
 - OBS, 195–201
- Routing and wavelength assignment (RWA), 8, 179
- Routing controller
 - ASON control plane, 162
- Routing protocol extensions
 - MPLS, 129–130
- Routing protocols
 - GMPLS, 147–151
- RSVP. *See* Resource Reservation Protocol (RSVP)
- RWA. *See* Routing and wavelength assignment (RWA)

- Scalability, 25
 - network architecture, 14
- Scheduling algorithm implementation
 - OBS, 209
- Scheduling algorithms, 202
 - output, 202
- Scheduling algorithms without void filling
 - OBS, 204–205
- Scheduling algorithms with void filling
 - OBS, 206–208
- SCM. *See* Subcarrier multiplexing (SCM)
- SDH. *See* Synchronous Digital Hierarchy (SDH)
- Segmentation-based channel scheduling
 - algorithms, 217
- Self-routing address scheme, 62
- Semiconductor optical amplifiers (SOAs), 42, 72
- Semiconductor optical amplifier switches, 42
- Separation of attributes
 - link attributes, 148
- Separation of control information and data
 - OBS, 171
- Serial transmission, 61
- Session messages, 123
- SESSION RELEASE message, 195

- SETUPACK, 194
- SETUP message, 194
- Shared per link (SPL), 73
 - architecture, 75f
- Shared per node (SPN), 72
 - architecture, 74f
- Shared Risk Link Group (SRLG), 149
- Short burst
 - JumpStart signaling, 194f
- Shortest Path First (SPF), 130
- Signaling
 - engine, 175
 - OBS, 187–194
- Signaling protocols
 - extensions
 - MPLS, 131–132
 - GMPLS, 152–156
- Simple control algorithm, 76
- Single-hop communication, 105
- Single-mode fiber, 3
- Single per channel (SPC) architecture, 73, 73f
- Single-wavelength optical networks, 4
- Slotted network, 58, 59f
- Slotted packet switched network, 57
- Slow-light buffers, 66
- Smart IP layer, 2
- Smart optical layer, 2
- SOA. *See* Semiconductor optical amplifiers (SOAs)
- Soft-permanent connection capability, 164
- SONET. *See* Synchronous Optical Network (SONET)
- Spanke, 47
- Spanke–Benes (n-Stage Planar Architecture), 47
- SPC. *See* Single per channel (SPC) architecture
- SPF. *See* Shortest Path First (SPF)
- SPL. *See* Shared per link (SPL)
- SPN. *See* Shared per node (SPN)
- SRLG. *See* Shared Risk Link Group (SRLG)
- Static optical layer, 10
- Static reliability, 24
- Store-and-forward paradigm, 79
- Strict-sense nonblocking 4×4 switch, 48f
- Subcarrier multiplexing (SCM), 60, 66
 - headers, 99
- Support for call segment, 164
- Support for crankback, 165
- Support for inheritable attributes
 - link attributes, 149
- Support of interlayer attributes
 - link attributes, 148
- Survivability, 26
- Survivable HORNET metropolitan area network
 - architecture, 100f
- Survivable ring architecture, 100
- Switches. *See also* specific type
 - building large optical switches, 42–48
 - considerations, 43
 - 4×4 , 45
- Switch fabric, 93, 175
- Switching
 - defined, 13
 - granularity
 - OBS, 171
 - time, 24
- Switching granularity
 - OBS, 171
- Switch reconfiguration time (T_{oxc}), 176
- Synchronous Digital Hierarchy (SDH), 2, 3, 4
- Synchronous network, 58
- Synchronous OPS network
 - packet format, 60f
- Synchronous Optical Network (SONET), 3
 - network elements, 3
 - SDH layer, 2
 - SDH network configurations, 4
- Synchronous switch architecture, 76

- TAG. *See* Tell-and-Go (TAG)
- Tail dropping vs. head dropping segmentation
 - policies, 216f
- TAW. *See* Tell-and-Wait (TAW)
- TDM. *See* Time division multiplex (TDM) capable
- TE. *See* Traffic engineering (TE)
- Telecommunication networks
 - architecture and evolution, 9
- Telecommunication traffic, 1
- Tell-and-Go (TAG), 187
- Tell-and-Wait (TAW), 187
- Terminal multiplexers, 3
- Thermo-optic digital optical switch
 - 2×2 , 39f
- Thermo-optic interferometric switch
 - 2×2 , 37f
- Thermo-optic switches, 37
- 3D MEMS
 - disadvantages, 33
 - optical switches, 32
 - technology, 32f
- Three-stage Clos network, 46f, 63
- Time
 - switching, 24

- Time division multiplex (TDM) capable, 151
 - interfaces, 136
- Timer-based burst assembly algorithm, 183
- Time to live (TTL)
 - label stack entry, 121
- TLV. *See* Type-Length-Value (TLV) encoding
- TOWC. *See* Tunable optical wavelength converters (TOWC)
- Traffic engineering (TE), 179
 - link, 148
 - metric
 - LSA, 130
 - MPLS, 124–126
 - objective, 124
 - parameters
 - bundled link, 143–144
- Traffic parameter attributes
 - traffic trunks, 126
- Traffic trunks
 - attributes, 126
 - generic path selection and maintenance
 - attributes, 126
 - policing attributes, 127
 - preemption attributes, 127
 - priority attributes, 126
 - resilience attributes, 127
 - traffic parameter attributes, 126
- Transmission on separate wavelength, 60
- Transparency, 96
- Transparent-based restoration, 17
- TTL. *See* Time to live (TTL)
- Tunable optical wavelength converters (TOWC), 68, 72, 77
- Two-axis actuated tilting mirror, 33
- 2D MEMS device, 31
- 2D MEMS technology, 31f
- Two-level differentiation, 87
- Type-Length-Value (TLV) encoding, 123

- UNI. *See* User–Network Interface (UNI)
- Unnumbered links, 142
 - support, 149
- Unprotected
 - GMPLS protection capabilities, 150
- Unreserved bandwidth
 - LSA, 130
 - TE, 144
- Unslotted network, 59f
- User–Network Interface (UNI), 161

- Vendors
 - network architecture, 14
- Virtual output queuing (VOQ) structure, 106
- Void filling, 83
- VOQ. *See* Virtual output queuing (VOQ) structure

- WAN. *See* Wide area network (WAN)
- WASPNET. *See* Wavelength Switched Packet Network (WASPNET)
- Wavelength assignment
 - OBS, 197–201
- Wavelength conversion
 - OPS, 71–77
 - limited range wavelength converters, 78
- Wavelength conversion capability, 17, 72
- Wavelength converters, 67
 - characteristics, 68
- Wavelength converters (WC), 68
- Wavelength division multiplexing (WDM)
 - link, 26
 - OPS architecture, 70f
 - technique, 4, 8
- Wavelength reservation, 191f, 192f
- Wavelength-routed networks, 7
- Wavelength-Routed Optical Burst Switched (WR-OBS)
 - network, 177–178
 - architecture, 178
- Wavelength-routed optical networks (WRONs), 177
- Wavelength-routed WDM network, 7f
- Wavelength routing, 55
 - switch, 91f
- Wavelength Switched Packet Network (WASPNET), 90–91
- WC. *See* Wavelength converters (WC)
- WDM. *See* Wavelength division multiplexing (WDM)
- Weighted Best Fit, 208
- Wide area network (WAN), 93
- Winner path, 197
- WR-OBS. *See* Wavelength-Routed Optical Burst Switched (WR-OBS)
- WRON. *See* Wavelength-routed optical networks (WRONs)

- XGM. *See* Cross-gain modulation (XGM)