

INDEX

- Absolute value, 101
Absorbents, 238
Absorption, 261, 264
Acetic acid, 165, 170
Acetylene, 309
Acid buffers, 116
Acidic species, intumescent systems, 136
Acidolysis, 166
Acid sites, 299
Acrolein, 1
Acrylonitrile, 199
Acrylonitrile-butadiene-styrene (ABS)
 -AO/OMT, 208, 218
 characteristics of, 18, 20, 42, 119–120, 166,
 208–210, 218, 225
 -DB, 209, 216, 218
 -DB-AO, 208, 210
 -DB/OMT, 208, 216, 218
 -OMT, 209–210, 218
 /OMT/DB, 209
 /OMT/DB-AO nanocomposite, 194–195,
 208, 210
 -OMT-TPP nanocomposites, 196
 organoclay nanocomposites, 194
Additive(s)
 anisotropic, 117
 characteristics of, 10, 14, 20, 69, 83, 108,
 110–111, 166–167, 206, 349, 384, 387
 commercial, 193
 halogenated, 191–228
 loadings, 333, 341
 in polymer decomposition, 115–116
 intumescent systems, 133, 137, 142–143,
 151
 nanocomposite morphology, 115
Adsorption, 200, 239, 243–244, 254
Advanced technologies, 123
Aerospace applications, 385, 387
Afterglowing, 18, 269
Agglomerates, polymer-CNT, 96–98, 101–104
AIO₄, 138
Aircraft safety, 375
Al(OH)₃, 384–385
Alcohol groups, 201, 247, 256
Alignment, 56–58, 244, 272, 385–386
Aliphatic(s)
 bonds, 247
 bromine, 10
 characteristics of, 326
 flame retardants, 7–8
 linkings, 6
 -polyetherimide layered-silicate
 nanocomposites, 70
 surfactants, 256

- Alkali cations, 46, 50
- Alkyl
 ammonium, 34, 165, 197, 222, 239–243, 329, 362, 364
 -cationic surfactants, 35
 phosphates, 136
 -substituted triaryl phosphates (ArPs), 196
 surfactant film, 33
- Alloys, 387
- Alumina trihydrate (ATH), 164, 174–176, 331, 345–346, 348
- Aluminophosphates, 143, 145–146, 156–157
- Aluminosilicates, 31, 34, 41, 139–141, 143–144, 153, 200, 334
- Aluminum
 characteristics of, 132, 236
 oxide, 269–270
 oxide/hydroxide layers, 139
 trihydroxide, *see* Aluminum trihydroxide (ATH); Alumina trihydrate (ATH)
- Aluminum trihydroxide (ATH), 7, 15–16, 18–21, 144, 168–169, 175, 261, 266
- Amgard MPC, 337–338
- Amides, 136
- Amines/amine groups, 136, 223, 225, 260, 272, 342
- 3-Aminobenzenesulfonate, 256, 258, 264–265, 270
- Aminocarboxylate (12-aminolaurate), 265–266
- Ammonium
 cation, 223
 pentaborate, 17
 phosphate salts, decomposition of, 12
 polyphosphate, *see* Ammonium polyphosphate (APP)
 salt-modified silicate (SBAN-400), 216–217
 salts, 136, 214, 240–241
 -treated clays, 248
- Ammonium polyphosphate (APP)
 characteristics of, 14, 19, 133–135, 138, 144–145, 166, 168, 193, 216–217, 266, 268, 272, 334, 337–340, 342, 34–346
 -PA6, 144, 147–148
 /pentaerythritol, 339
 -PER system, 133–134, 136–138, 143, 337, 340
- Amorphous
 carbons, 312
 phase, intumescent systems, 137
- Anaerobic pyrolysis, 116
- Anhydrous alumina, 15, 18
- Anion exchange capacity (AEC), 238
- Anionic clays
 characterized, 237–239, 254, 256
 combustion behavior, 266–271
 epoxy nanocomposites based on, 255–266, 277–278
- Anisotropic
 nanocomposite morphology, 112
 nanoscaled particles, 123
- Annealing, 39
- Antiblaze products, 345–346
- Antidripping agents, 123–124
- Antimony
 characterized, 196
 -halogen reaction, 10
 oxides, 69
 pentoxide, 21
 tribromide, 224
 trihalide, 224
 trioxide (AO), 10, 20, 192, 224
- AP750, 133–134
- Apolar polymers, 33, 35
- Aqueous copolymeric emulsions, 331
- Arc discharge, 177
- Aromatic(s)
 esters, 133
 flame retardants, 7–8
 fusion of, 6
 groups, 6, 18
 phosphate esters, 12
 phosphates (ArP), 193, 199, 214–215, 217, 227
 polybrominated, 192
 rings, 10
- Aromatization, 6, 10, 248
- Aspect ratio, 54, 57–58, 236–237, 361
- Assessment methodology of nanocomposite fire behavior
 differentiated analysis of fire properties, 121–123
 fire scenarios, types of, 123–124
- ASTM standards
 D2863, 4
 D6113, 4
 E1354, 169
- Atomic force microscopy (AFM), 55, 370
- Atomic hydrogen, 9
- Automotive fire safety, 132, 375, 379
- Back-coatings, 20, 331, 343–344
- Barrier(s)
 effects, 223, 227, 265–266
 formation, 107–108, 112–113, 117–121, 227–228
 to heat flux, 5

- layers, 124
 - properties, 56–60, 164
- Basal reflection, 42, 44
- Batch processes, 40–41, 363–364
- Bending, 164
- Benzyl chloride groups, 197
- Benzyl dimethylamine (BDMA), 246–247, 251
- Benzyl(hydrogenated tallow alkyl)dimethyl quaternary ammonium-modified montmorillonite, 275
- Benzyltetrahydrothiophenium, 253, 255
- Bifunctional epoxies, 247
- Biodegradability/biodegradation, 23, 60
- Bis-A/novolac, 276
- Bisphenol A diglycidyl ether, 108
- Bis(2-hydroxyethyl) ammonium montmorillonite, 249–250, 253, 264, 266
 - methyl tallow alkylammonium, 246
- Blowing agents, 136, 270
- Boiling temperature, 223
- Boltzmann distribution, 93
- Bond angle and distance, 91
- Borates, 16–18, 136
- Boric acid, 134–136
- Boron compounds, 16, 18
- Borophosphate, 155
- Borosiloxane elastomer, 138, 154
- Brabender mixer, 151, 165
- Bragg peak, 111
- Brominated
 - compounds, organic, 164
 - epoxy oligomers, 20
 - esters, 21
 - flame retardants, 8, 22
 - resins, 277
- Bromine, 7, 10, 200, 216. *See also* Brominated
- Bubbling process, 113, 135–136, 167, 223, 225, 236, 302, 313–314
- Bulk polymers/polymerization, 47, 135, 204, 331–335, 357
- Bundle design, 184–186
- Burning. *see* Fire; Flame; Ignition
 - behavior, 71
 - time, 109–110, 118, 120, 335, 343
- Butyl, 34
- By-product migration, 223

- Cable
 - coaxial, 175–176
 - sheathings, 331, 348
- Calcium carbonate, 10
- Candlelike combustion, 207
- Caprolactam, 69, 81

- Carbodiimides, 201, 272
- Carbon
 - black (CB), 307–309
 - characteristics of, 132, 269–270
 - char-silicate layer, 113
 - dioxide (CO₂), 10, 123–124, 149, 214, 226, 266, 269–270
 - nanofibers (CNFs), 286, 311–315, 375
 - nanotube. *see* Carbon nanotube (CNTs)
 - silicate structures, 251
- Carbonaceous, generally
 - char, 115–116, 201, 223, 225, 292
 - residue, 269
 - silica shield, 223, 336
 - structures, 201, 248
- Carbon-carbon bonds, 143, 380
- Carbonization
 - agents, 147
 - process, 136
- Carbon monoxide. *see* CO
- Carbon nanotube (CNTs)
 - bundles, 91–92, 94, 97
 - CNT interactions, 94, 101
 - general properties of, 32–33, 41–42, 49, 55, 78, 83, 89–91, 132, 164, 167, 177, 299–315, 356, 372, 375, 377
 - LDPE compounds, flammability of, 179, 181–182
 - molecular mechanics, 92–93
 - multiwalled. *see* Multiwalled carbon nanotubes (MWCNTs)
 - polymer interactions, 94
 - purification of, 177
 - synthesis, 177
- Carcinogens, 22
- Carpets, latex backcoatings, 20
- Catalysis/catalytic effects, 7, 15, 19, 83, 124, 138, 177, 223–224, 227, 236, 238, 240, 270, 273, 309
- Catastrophic fire razing, 131
- Cation(s)
 - characteristics of, 138, 140, 363
 - clays and. *see* Cationic clays
 - exchange capacity (CEC), 36, 238, 255
- Cationic clays
 - characteristics of, 237
 - combustion behavior of polymeric nanocomposites, 251–255
 - epoxy nanocomposites based on, 244–255, 277
 - thermal decomposition of polymeric nanocomposites, 248–249

- Cellulosic materials, 11–12, 16–17
- Ceramics, 132, 235, 238, 277, 336
- Chain-end scission, 6
- Char/charring
- carbonaceous, 69–70, 79–80
 - fire retardancy mechanisms, 112
 - formation stages, 6, 10, 12–13, 113–115, 134–135, 193, 223, 227–228, 267, 307, 335, 345, 381, 385
 - former agents, intumescent systems, 136, 144–146
 - intumescent systems, 134–135
 - mechanical stabilization of, 117–118
 - polymers, 167
 - promotion sources, 7
 - pyrolysis residue and, 71
 - reinforcement of, 124
 - silicate surface layer, 114
 - sources of, 69
 - strength, 151, 155
 - structure, 19
 - yield, 5, 69
- Charge density, 241–242
- Chemical(s), *see specific chemicals*
- corrosive, 236
 - decomposition, 116
 - reactions, intumescent systems, 136
 - toxic/toxicity, 22, 236
 - tubes, thermal- and plasma-enhanced vapor-growth deposition, 299
 - vapor, 305
- China clay, 139, 141
- Chirality, 94
- Chlorinated paraffin (CPW), 196
- Chlorine, 7, 13
- Chloroalkyl phosphates, 14
- Chlororganophosphates, 11
- Cigarettes, smoldering, 5
- Circular fillers, 57
- Clay(s)
- char, 72–73, 76
 - characteristics of, 132, 237
 - dispersion, 78, 108–109
 - intumescent systems, 144–145
 - in nanocomposite morphology, 113
 - modified, 116
 - nano-dispersed montmorillonite, 132
 - organically modified silicate, 113–114
 - organo-modified, 157
 - rich nanocomposites, 379
 - sheets, 223, 226, 237, 381
 - surfactants, 215
 - synthetic, 165
 - types of, *see specific types of clays*
- Cloisite clays, 273, 275, 326, 328, 331–332, 338–341, 345–346, 348
- CO
- characteristics of, 1–2, 5, 164, 252, 276, 299
 - production, 207, 318
 - release, amount of, 213–214
 - yield, 172
- Coadditives, 192, 224
- Coatings, 134–136, 140, 142, 155–157, 331, 343–344. *See also* Back-coatings
- Cobalt, 309
- Coherent structures, 143
- Cohesive energies, 91
- Coking, 69
- Colloidal particles, 384–385
- Combinatorial entropy, 94
- Combustion, 5–6, 112–113, 115, 123–124, 133, 193, 251–255
- Combustion gases, 22
- Commercial/commercialization
- clays, 326–327, 341
 - hurdles, 357–358, 377–379
 - polymers, flame retardant mechanisms, 7–8
- Commodity polymers, 20
- Compatibilizers, 90, 105, 111–112, 359
- Complex nanocomposite morphology, 112
- Composites, 344–347
- Compounding, 169
- Compression, 38, 164
- Computer monitors, 2
- Concentration, significance of, 40
- Condensation/condensation phase, 7, 10–11, 20, 115, 137, 153, 223–225, 227, 247, 252, 257, 261, 310, 381, 383
- Cone calorimeter measurements, 179
- Cone calorimetry tests
- applications, generally, 4, 122, 138, 167, 169, 208–216, 331, 346, 382–383
 - barrier effects, 120
 - combustion of polymeric nanocomposites, 266–268
 - epoxies, 251, 254, 267
 - films, fibers, and textiles, 335
 - flammability performance, 21, 315–316, 382
 - halogenated flame retardants, 206
 - intumescent systems, 132–133, 138, 149, 153–155
 - macroscale techniques, 372
 - nanoscale oxide-based nanocomposites, 292–293
 - organoclays, 171–175, 184–185
 - polymer-clay nanocomposites, 81
 - polystyrene nanocomposites, 69–70
 - polyurethane nanocomposites, 273

- thermoset fire retardant nanocomposites, 270–271
- vinyl ester nanocomposites, 276, 347
- viscosity, 117–118
- Confocal microscopy, 317
- Construction industry, 134
- Consumer Products Safety Council (CPSC), 2
- Cooling, 117
- Copolymers, 168, 344
- Copper, 153
- Corrosion
 - corrosive chemicals, 236
 - corrosive gases, 374
 - corrosiveness, 210
- Cost of fire, 2
- Cost-performance trade-off, 20
- Cotton fabric, 344
- Cresyl diphenyl phosphate, 193, 196. *See also* Tricresylphosphate (TCP)
- Cross-links/cross-linking, 6, 10, 15, 19, 38, 56, 81, 225–226, 237, 241, 243, 274–276, 288, 291, 294, 318, 359
- Crown ethers, 329
- Crystalline phosphates, 19
- Crystallinity, 47
- Crystallization, effects on
 - amorphization by filler, 46
 - general, overview, 47–49
 - heterogeneous nucleation by fillers, 46–48
 - new crystal structures, development of, 45–46
 - one-dimensional nanofillers, 49–50
- Crystic 471 PALV, 345
- Curing
 - agents, 241–244, 260
 - kinetics, 240
- Cussler-Aris relations, 57
- Cyanate ester clay, 367
- Cyanuric acid, 15
- Cyclic(s)
 - organophosphate, 340
 - phosphate, 337
- Cycloaliphatic
 - epoxies, 253, 255
 - flame retardants, 7–8
- Data collection methods, 367–368
- Deacetylation, 165
- Decabromodiphenyl (DB)
 - AO, 208, 217, 224–225
 - DBDPO, 217
 - oxide, 20, 192, 224
- Decomposition
 - fire retardancy mechanisms, 112–116, 214, 327
 - intumescent systems, 145–146
 - kinetics, 228
 - nanocomposite morphology, 112–113, 115–116
 - pathways, 124
 - stages, 227
 - three-step, 116
 - two-step, 116
- Deformation, 117
- Degradation processes, 201, 328, 362–363, 365, 372, 381, 384
- Degrees of freedom, 102
- Dehalogenation, 10
- Dehydration, 15, 265
- Dehydrochlorination, 6
- Dehydrogenation, 7, 224
- Dehydroxylation, 328
- Delamination, 108–112, 256, 366
- Demixing, 112–113
- Density/densities, 91, 101, 111, 239, 245, 276, 327
- Depolymerization, 143, 201
- Derakane 411–350, 275
- Devolatization, 360
- Dextrins, 136
- Diameter, polymer-CNT composites, 94, 96, 98, 103–104
- 4,4'-Diaminodiphenyl sulfone (DDS), 260
- Diammonium pyrophosphate (PY)/PER systems, 142
- Dibenzofurans, 22
- Dibromostyrene (DBS), 332–333
- Dichloromethane, 272
- Dicyandiamide, 136
- Dielectric constant, 370
- Differential scanning calorimetry, 15–16, 46–47, 49
- Diffraction, 259, 366–368
- Diffusion, 5, 113, 236, 240, 250–251, 260, 274–275
- Diglycidyl ester of bisphenol A (DGEBA) systems, 239–241, 243, 246–247, 249–252, 255–257, 260–261, 264–265, 270
- Diglycol, 198
- 9,10-Dihydro-9-oxa-10-phosphaphenanthrene-10-oxide (DOPO), 250
- Dimers/Dimerization, 136, 201, 272, 316
- Dimethyl di(octadecyl) ammonium (DMDODA), 364
- Dimethyldistearylammonium, 169, 329, 331

- Dimethylformamide (DMF), 300
- Dimethyl hydrogenated-tallow
(2-ethylexyl)ammonium montmorillonite,
250
- Dimethyl-*n*-hexadecyl-4-vinylbenzylammonium
(VB16), 332
- Dimethylhexadecylamine, 197
- Dimethylhexadecylimidazolium (DMHDIM),
329, 364
- Dimethylsiloxanes, 18
- Dioctadecyl, 34
- Dioctyl sulfosuccinate LDH nanocomposites,
256
- Dioxins, 22
- Dipentaerythritol-melamine phosphate,
345–346
- Diphenyl 4-vinylphenyl phosphate (DPVPP),
197, 203, 215
- Direct-current arc discharge, 299
- Discotic liquid crystals, 111
- Dispersion
barrier effects, 59
carbon nanotubes, 300–302, 305
characteristics of, 37–39, 330–331,
344–345, 369–370, 373
clays, 237, 240
foams, 347
graphite oxide, 297
halogenated additives, 219
nanocomposite morphology, 316–317
oligomeric silsequioxanes, 294
polymer-carbon nanotubes, 94
research trends, 355–365, 382, 385,
387–338
- Dissociation energy, 91
- Distance, polymer-CNT composites, 98
- Distorted polymers, 94
- Distribution, fire retardancy mechanisms,
108–110, 112
- Divalent metals, 19
- Dodecyl sulfate-modified LDH, 266
- Donor-acceptor interaction, 33
- Double bonds, 6, 10
- Downward-burning materials, 207–208
- Dripping, 117–118, 124, 132, 137, 165, 236,
274, 372, 383
- Dryng processes, 109
- d*-spacing, 38, 244, 246–247, 256–257,
259–260, 274–275
- DTA, 327–328
- DTA-TGA, 345
- DuPont, 69
- Dynamical mechanical analysis (DMA), 261,
246–247
- Eco-friendly approaches, 124
- Ecological issues, 124
- Effective filler, 54
- Elastomeric products, 15
- Elastomers, 14, 16, 52
- Electric products, 121
- Electrical enclosure applications, 332
- Electrochemical reactions, 238
- Electromagnetic properties, 375, 387
- Electron(s)
conductivity, 41–42
de Broglie wavelength, 31
density allocation, 111
diffraction, 297
-withdrawing effect, 11
- Electronic environment, 2, 121, 132
- Elongation, 168
- Emulsion, 357
- Endothermic decomposition/dissociation, 7, 115
- Energy transfer, 228
- Engineering plastics, 20, 196
- Enthalpy, 34–35, 99, 103, 359
- Entropy, 90, 93–94, 99
- Environmental concerns, 192, 377
- Environmentally friendly flame retardants,
22–23
- Environmental requirements, 22–23
- Epoxide monomers, 241–242
- Epoxy/epoxies
anionic clays, *see* Epoxy nanocomposites
based on anionic clays
-APP formulation, 266, 269–271
bifunctional, 247
brominated, 20
cationic clays, *see* Epoxy nanocomposites
based on cationic clays
chains, curing agents, 241–244
characteristics of, 108–109, 237, 247,
251–253, 268–269
-clay nanocomposites, 240
decomposition, 116–117
glass, 245–246
-graphite composites, 296–297
-LDH1/LDH2, 266–270
-magadiite nanocomposite, 247
matrix, 358
methacrylate, 264
-MMT1/MMT2, 266–270
morphology, 119, 121
nanocomposites, *see* Epoxy nanocomposites
neat, 247–248, 264–265
polyfunctional, 267
resins, 6, 8, 18, 108–109, 122, 196, 247–248
thermal decomposition, 247–251

- thermal stability, 249–250
- Epoxy nanocomposites based on anionic clays
 - characterization of, 255–256, 261, 277
 - combustion behavior, 266–271
 - preparation procedures, 256–260
 - thermal decomposition, 261–266
- Epoxy nanocomposites based on cationic clays
 - characterization of, 244–247, 277
 - combustion behavior, 251–255
 - preparation procedures, 240–244
 - thermal decomposition, 247–251
- Equipment damage, 192
- Escape time, 2, 163–164
- Esterification, 156
- Ethylene-butyl acrylate-maleic anhydride terpolymer, 138–139
- Ethylene-co-vinyl acetate (EVA)
 - APP/PA6, 149–150, 154
 - APP/PA6-NPSi, 150, 152
 - APP/PA6-O, 149–150, 152
 - APP/PA6-OLDH, 150
 - ATH-organoclay composition, 175–176
 - characteristics of, 165, 331, 348
 - matrix, 334
 - MDH-zinc borate-talc, 167
 - MNWT, 310–311
 - organoclay-based, *see* EVA/organoclay-based nanocomposites
- EVA/organoclay-based nanocomposites
 - flammability properties of, 171–173
 - processing and structure of, 169–170
 - thermal stability of, 170–171
- Ethylene glycol, 38, 256
- Euroclasses B1ca/B2ca/Cca/Dca, 173
- Europe
 - cable flame tests, 186
 - halogen-containing flame retardants, 22
- European Chemical Industry Council, 2
- European SBI, 121
- European Union
 - commercialization hurdles, 192, 377
 - fire and environmental regulations, 373, 375
- Evaporation, 196
- Excess enthalpy interactions, 35
- Exfoliated ordered/disordered, defined, 112
- Exfoliation
 - adsorption process, 243–245
 - anionic clays, 256
 - barrier effects, 118
 - carbon-based nanocomposites, 297
 - cationic clays, 241–243, 250–252
 - future trends, 356, 382, 385
 - halogenated additives, 219, 222–223, 228
 - in situ polymerization and, 199
 - nanoscale analysis techniques, 368–371
 - nanostructured morphology, 108–112, 118, 194–196
 - organoclays, 165
 - polymer nanocomposite analysis, 359, 365–366
 - system application requirements, 326
- Exothermic, generally
 - decomposition, 263–264
 - enthalpy, 92
 - neutrality, 104
 - reactions, 9
- Extinction, 1, 163, 276
- Extragallery polymerization, 240, 242–243, 260
- Extrapolation studies, 123
- Extrusion, 39, 107, 112, 143–144

- Fabrics, 334. *See also specific types of fabrics*
- Failure temperature, 134
- Fatalities, demographic studies, 2
- Federal Aviation Administration, 375
- Federal Motor Vehicle Safety Standard 302 (FMVSS 302), 375
- Feedback, thermal, 119
- Fibers, 334–343. *See also* Nanofibers
- Filler(s), *see* Nanofillers
 - aspect ratio, 57–58
 - filler separation, 43
 - inert, 113–115, 124
- Films, 334–343
- Fire, generally
 - behavior of, *see* Fire behavior of nanocomposites
 - codes, 379
 - death/fatalities, mortality rates, 164
 - doors, 121
 - growth index (FIGRA), 121–124, 345–346, 383
 - hazards, 1, 163–164
 - penetration, 121
 - risk, 163–164, 374, 382, 385
 - safety standards, 132, 228, 375, 379
 - scenarios, 108
 - tests, 108. *See also* Cone calorimetric tests; UL-94 tests
- Fire behavior of nanocomposites
 - assessment of fire retardancy, 121–125
 - barrier for heat and mass transport, 113, 118–121
 - decomposition and permeability, 115–116
 - inert filler and char formation, 113–115
 - viscosity and mechanical reinforcement, 117–118

- Flame
- inhibition, 115, 117–118
 - propagation rate, 9
 - retardancy, *see* Fire retardancy
 - spread, 1, 22, 108, 120–124, 163, 165, 344, 375, 378, 383
 - synthesis, 299
 - zone, 20, 116
- Flame retardancy
- general mechanisms, 7
 - highly dispersed flame retardants, 20–22
 - polymetric materials, 2
 - selection criteria, 20
 - specific mechanisms, 7–20
- Flame retardant nonhalogen (FRNH) cables, 176
- Flammability, generally
- cone calorimetric test, 206, 208–216
 - fundamentals of, 379–383
 - implications of, 108, 121–124
 - LOI and UL-94 tests, 207–208, 216–222
 - performance materials, 379
 - properties, significance of, 206–208
 - reduction mechanism, 379
 - research studies, *see* Flammability research tests/testing, 3–5, 118, 120
- Flammability research
- commercial hurdles, 357–358, 377–379
 - fire and environmental regulations, 373–376
 - future outlook, 383–388
 - importance of, 355–356
 - nanoparticles, current environmental health and safety status, 376
- Flashover, 164
- Flory-Huggins theory, 35, 92
- Fluorescence, 370
- Fluorinated flame retardants, 7
- Fluorinated synthetic mica (FSM), 78–79, 197, 220–221
- Fluorohectorites, 34, 165, 197, 241
- Fluoropolymers, 164
- Foaming processes, 378
- Foams/foamed materials, 5, 347–348, 378
- Force field, 90, 102
- Forced flaming, 124
- Fracture, 164
- Frederickson-Bicerano equation, 57
- Free energy, 35, 90, 99
- Free radicals
- chain-terminating agents, 224
 - characteristics of, 136, 143, 360
- FTIR, 257, 264
- Fuel
- gas, 224
 - release, 385
 - vapor, 223
- Functional groups, 90, 94, 328–329, 336, 338, 359
- Furniture, nonflame retardant, 22
- Future research directions, 22, 60–61, 348–349, 383–388
- Gamma-irradiated high-density (HDPE)/EVA nanocomposites, 165
- Gas(es)
- escape, rate of, 83
 - permeability, 115
 - phase, 7, 115, 117, 223–225, 227, 270, 307
 - pressure, 137
 - trapped, 137
- Gas chromatography/mass spectroscopy (GC-MS), 81–82
- Gasification
- implications of, 69–70, 76, 80
 - test, 288, 302–305, 308, 310, 313
- Gels, 236
- Gene therapy, 238
- General Motors, 68
- Glass, 19, 117, 217
- Global dispersion, 365
- Glow wire test, 117
- Glycerin, 198
- Grafting densities, 36
- Graphical assessment methodologies, 122–123
- Graphite, 6, 10, 41, 91, 103, 286
- Graphite oxide (GO), 295–299
- “Green” labeling, 2
- Halides/halide ions, 136, 329
- Haloalkyl phosphates, 136
- Halogen bombs, 9
- Halogen-free systems, 18, 107, 123, 236, 277
- Halogen/halogenated flame retardants, 7–11, 19, 20, 22, 70, 192–193, 210, 216, 224–225, 345, 374, 378
- Halogen radicals, 10
- Halpin-Tsai model, 52
- Hamaker constants, 34–35
- Health threats, 192
- Heat
- absorption, 122
 - barriers, 134
 - capacity, 93, 101, 117
 - combustion, 116
 - constant, 116
 - dispersion, 18
 - distortion temperature, 20, 236

- exposure, 5
- flux, 123, 133–134, 141, 172–174, 179, 209–211, 213, 254, 270, 336
- insulation, sources of, 15
- release, amount of, 1, 163. *See also* Heat release rate (HRR)
- shield, 289
- transfer, 79, 115, 135–136, 151–152, 223, 227
- transport, 113, 118–121
- Heat release rate (HRR)
 - carbon-based nanotubes, 179, 182–185, 297–298, 300–303, 306, 311–312, 318
 - char formation, 114–115
 - composites, 344
 - in differentiated analysis, 121–122
 - epoxy nanocomposites, 251–253, 268–269
 - EVA/organoclay-based nanocomposites, 172
 - films, fibers, and textiles, 336
 - flammability properties and, 206, 212, 214–215
 - halogenated nanocomposites, 208–216
 - intumescent systems, 147, 150, 208–216
 - nanocomposite morphology, 108–114, 118–119, 123
 - nonintumescent additives, 226–227
 - organoclays, 163, 169, 172–173
 - oxide-based nanocomposites, 286–287, 290, 292–295
 - polymer-carbon nanocomposites, 89
 - polymer-clay nanocomposites, 81, 83, 355
 - polymer nanocomposites, 379
 - polystyrene nanocomposites, 69–71
 - significance of, 1, 4–5, 21, 110–111, 315–316
 - thermoset fire retardant nanocomposites, 236, 264
 - transport, 118
 - vinyl ester nanocomposites, 277–278
- Heat-sink mechanisms, 115
- Heavy metals, 377
- Hectorite, 237. *See also* Fluorohectorites
- Helium, 170
- Heterochain polymers, 11
- Heterocyclic groups, 6
- Hexadecyltrimethylammonium
 - bentonite, 255
 - bromide, 194
 - chloride-modified montmorillonite, 273
 - silicate, 253–254
- Hexadecyltriphenylphosphonium
 - bentonite, 255
 - phosphonium silicate, 253–254
- Hexafluorophosphate salts, 329
- Hexahydrophthalic anhydride, 261
- High aspect ratio fillers, 31–32, 58
- High-energy mixing, 104
- High-impact polystyrene (HIPS), 8, 20, 120, 166
- High-pressure carbon monoxide (HiPCo), 299
- High-resolution electron microscopy (HREM), 195, 198
- High-shear-rate/high-temperature extrusion, 37
- High-thermal-stability epoxies, 249–250
- High-throughput processes, 330
- High-valency metals, 19
- Histograms, 287
- Hoffman-Weeks plots, 47
- Hofmann elimination, 223, 248, 360, 362
- Horizontal burning tests, 166
- Horizontal combustion, 14
- Hot polymer, 10
- Hot radicals, 9
- Hot zone, 146
- Hybrid cars, 375
- Hybrid materials, 32, 43, 60, 132, 387
- Hydrocarbon(s)
 - characteristics of, 9
 - fire heating curve, 135
 - oxidation of, 18
 - polymers, 14
- Hydrochloric acid, 309
- Hydrogen
 - abstraction, 166
 - bonding, 45, 52, 55, 380
 - bromide (Hbr), 224
 - chloride, 1, 17
 - cyanide, 1
 - halides, 9–10, 374
 - storage, 177
- Hydrotalcite-like compounds (HTLcs), 237
- Hydroxides, 20, 32, 334, 387
- Hydroxybenzenesulfonate, 256
- Hydroxyl groups, 9, 12, 40, 165, 253, 255, 347, 380
- Hydroxy radicals, 9, 227
- Ignitability, 1, 5, 108, 121–122, 124, 163
- Ignition
 - delay time, 315
 - sources, 2–3, 22
 - tests, 318
 - time of, 70, 81, 116
 - time to, 5, 120, 122, 149, 172, 206, 252, 273, 299, 310, 316, 332, 335, 343, 381–382
- Imidazolium, 248, 329, 360, 363–364
- Immiscible material, 365, 372

- Immobile molecules, 93
 Imperial Chemical Industries (ICI), 68
 In situ polymerization, 40–41, 68, 81, 90, 109, 193, 198–200, 240, 243–244, 256, 286, 296–297, 326, 347, 356–360
 Incombustible residue, 123
 Incompressible fluids, 136
 Industrial applications, 357. *See also specific industries*
 Inert additives, 108
 Inert fillers, 113–115, 118, 124
 Inert gases, 10, 347
 Information technology equipment (ITE), 373–374
 Infrastructure elements, 132
 Injection molding, 39, 107, 112, 363, 368, 386
 Inorganic(s)
 acids, 136
 additives, 200
 clays, 381–382
 fillers, 41
 hydroxides flame retardants, 15–16
 ions, 360
 nanocomposites, 31
 Insoluble additives, 20
 Insulated wires, 186
 Insulators, 299
 Intensity of fire, 163
 Intercalation, 108–110, 112, 194–200, 220, 223, 228, 236–237, 239–241, 244, 251–252, 257, 259, 267, 269, 272, 275, 326, 365–366, 370–371, 381–382
 Interchain aminolysis, 166
 Interfacial coupling, 50, 53–56
 Intergallery polymerization, 260
 International cable fire test
 IEC 60332–3–24, 174–175
 IEC 60950 test, 2–3
 International Standards Organization (ISO)
 standards, 4
 Intragallery polymerization, 240, 275
 Intumescent systems
 additives, 193
 basics of, 13, 132–138, 164, 334
 char resistance, 153
 coatings, 14
 defined, 133
 nanocomposite morphology, 117–118
 nanofillers in, 147–153
 in polymer nanocomposites, 143–147
 recent advances in, 153–157
 two peak, 134
 zeolites in, 138–143
 Iodine, 7
 Ion exchange, 165, 197, 200, 237, 256–257, 329, 358
 Ionic conductivity, 164
 Ions, *see specific types of ions*
 Iron, 309
 Irradiances, 119–123
 Isocyanates, 201, 271–272
 Isoprene, 69
 Isopropylphenyl diphenyl phosphate, 193, 196
 Jacketing compounds, 168
 Japan, *see Pacific Rim*
 halogen-containing flame retardants, 22
 manufacturing standards, 2–3
 Jeffamine D230, 260
 Kabelwerk Eupen AG, 331, 348, 378
 Kenyite, 370
 Kinetics, impact of, 36, 39–40, 46, 92–93, 104, 111–112
 Kneading, 39
 Laboratory flammability tests, 3–5. *See also*
 Flammability, generally; Cone calorimetry tests
 Labyrinth effect, 236
 Lamellar talc, 167
 Large-scale evaporation distillation, 360
 Laser ablation, 177, 299
 Lattice, hexagonal, 92, 99
 Lauryl acrylate oligomer systems, 363
 Layered double hydroxides (LDHs), 41, 132, 147–148, 151, 157, 166, 236–239, 255–258, 260–262, 360, 370, 384
 Layered silicate-polymer nanocomposites, 112–113, 115–118, 121–123
 L/D ratio, 365
 Legislation, fire and environmental, 131–132, 375
 Length scales, 121
 Lethality, sources of, 1–2. *See also* Fire deaths
 Lewis acid-base interaction, 33
 Lewis acids, 20
 L44 PA, 331
 Life-cycle assessment model, 22
 Lifschitz-van der Waals (LW) interactions, 33
 Limiting oxygen index (LOI)
 assessment techniques, 120, 122–123
 clays, 251
 coating, 343–344
 composites, 344
 films, fibers, and textiles, 337–343
 flammability properties, 207–208
 future directions for, 383
 highly dispersed flame retardants, 21

- intumescent systems, 132, 144–145, 150, 154, 157
- laboratory tests and, 4
- oxide-based nanocomposites, 286
- UL-94 test, 216–222
- viscosity, 117
- zeolites, 138–141
- Loading, significance of, 21, 32, 58, 358, 360, 384
- Low-density polyethylene (LDPE), 169, 181–182
- LRAM3.5, 138–139, 141–143
- Macrofillers, 60
- Macromolecular surfactants, 35
- Macroscale analysis techniques, 372–373
- Macroscale dispersion, 365
- Magadiite, 244, 247, 249, 276, 370
- Magnesium
 - aluminum carbonate LDH, 256–257, 261, 263
 - characteristics of, 261
 - hydroxide [MgH/Mg(OH)₂], 7, 15–16, 18–19, 21, 164, 167–168, 211, 225, 236, 334, 384–385
 - hydroxide -red phosphorus (MH-RP), 194, 217, 225
 - RP-OMT additives, 211
 - oxide (MgO), 225, 269–270
 - phosphate, 156
 - silicate, 18
- Magnetic alignment, 386
- Maleic anhydride (MA), 38, 40
- Manganese dioxide, 19, 138
- Mannitol, 136, 143
- Manufacturing industry, 22
- Mass loss rate (MLR)
 - carbon-based nanocomposites, 309, 314–315
 - epoxy nanocomposites, 251
 - films, fibers, and textiles, 335
 - flammability properties, 207, 210, 213–216
 - nontumescent additives, 226
 - organoclays, 165, 172
 - polymer-clay nanocomposites, 69–70
 - propylene-clay nanocomposites, 78
 - polymer nanocomposites, 355, 380–381
 - research trends, 355, 384
- Mass transfer, 227–228
- Mass transport, 113, 118–121, 166, 251, 299
- Material design, 131–132
- Material property tests, 372–373
- Material science research, 132, 177, 192
- Mechanical properties
 - intumescent systems, 143–145, 153
 - nanofiller, 51–56, 60,
 - organoclays, 164
 - polymer-organoclay nanocomposites, 204–209
 - significance of, 349, 378
- Mechanical reinforcement, nanocomposite morphology, 117–118
- Melam/melem/melon, 14
- Melamine
 - characteristics of, 13–14, 21, 136, 193, 201, 226
 - cyanurate (MCA), 15, 210–211, 217
 - flame retardants, 14–15
 - phosphate (MMP), 136, 197, 221–222, 334, 337–338, 345–346
 - polyphosphate (MPP), 198, 202, 212, 214, 217, 272–273
 - salts, 197, 220
- Melt, generally
 - blending, 110, 165, 168–169, 193–197, 200, 203, 215, 217, 219, 221, 286, 296, 309, 363
 - compounding, 174, 356, 362–365, 370
 - dripping, 117, 157
 - flow, 21–22, 117, 165
 - hydrodynamics, 136
 - intercalation, 326
 - polymer processing, 328
 - processing, 37–39, 42, 347
 - viscosity, 111, 113, 117, 123–124, 333
- Melting point, 50
- Metallic additives, 83, 134
- Metals, *see specific metals*
 - characteristics of, 10, 235
 - hydroxides, 16, 115, 193, 237, 333
 - oxides, 19, 21, 192, 168, 288–289
- Metallocene-based polyolefin processes, 360
- Methacrylate butadiene systems, 363
- Methylenedianiline (MDA), 251
- 4-Methyl hexahydrophthalic anhydride, 108
- Methyloctadecylammonium ion (C18A1M), 244, 247–249
- Methylol melamine, 136
- Methylphenylsiloxanes, 18
- Methyl tetrahydrophthalic anhydride, 249, 252
- Mg61
 - ABS, 257–260
 - HBS, 257–258
 - TS, 258, 260
- Mica, 81, 165. *See also* Melamine, mica
- Microcalorimetry, 81
- Microcoat, 270–271
- Microcomposites, 107, 109–110, 266–267, 275–276, 289, 365, 280

- Microdispersion, 131, 153, 334, 348, 365
- Microfillers, 266
- Microparticles, 334
- Microreactors, 124
- Microscale
 analysis techniques, 371–372
 particles, 285, 365
- Microscopy, applications of, 47. *See also specific types of microscopy*
- Migration, in nanocomposite morphology, 112–113, 223, 236
- Military applications, 385, 387
- Miller indexing, 257
- Miscibility, 92, 94. *See also Immiscibility*
- Mixing process, 94, 101–104
- Mobility, carbon nanotubes, 93
- Molding processes, 37, 39, 107, 112, 362–363, 368, 386
- Molecular
 interactions, nanocomposite morphology, 113
 mechanics, 90–91. *See also Polymer-CNT composites, molecular mechanics*
 weight, significance of, 10, 110, 272, 330, 362
- Molten organic liquids, 380
- Monomers, 116, 136, 199–200, 239–240, 316
- Montmorillonite (MMT)
 dispersion, 37–40
 flame retardant mechanisms, 223–224
 halogenated flame retardant additives, 216, 221
 intumescent systems, 148, 155
 nanocomposites, 16, 32, 34–35, 51, 73–75, 79, 108–109, 115–116, 144, 146, 164–168, 237, 241, 243, 272, 276–277, 329–331, 360, 369–370, 377
 thermal degradation, 202
 thermoset fire retardants nanocomposites, 243–244
- Mordenite, 138, 140
- Morphology, *see specific types of nanocomposites*
 analysis, 369–370
 influential factors, 111–114, 381
- Mori-Tanaka model, 53
- Motion, carbon nanotubes, 93
- MPC1000, 339
- Multicellular structures, 117
- Multifunctional materials, 131–132, 386–387
- Multiwalled carbon nanotubes (MWCNTs)
 cable with MWCNTs-organoclays-ATH, 182–186
 carbon nanotubes, 305–311
 characteristics of, 92, 99–100, 104–105, 117, 167, 169, 286
 charred, crack density and surface results, 179
 EVA-MWCNT/EVA-MWCNTY-organoclay compounds, flammability of, 177–179
 in LDPE, 181
 organoclays distinguished from, 178
 properties of, 178
 synthesis and purification of, 177
- Myristytrimethylammonium bromide, 296
- Nanoclays, 16, 19, 21, 146, 330, 345
- Nanocoat, 270–271
- Nanocomposite
 characteristics of, 107–109
 defined, 31, 164
 formation, *see Nanocomposite formation*
 intumescent, 157
 mechanical properties, 164, 349
 morphology, significance of, 108–113
 principal fire retardancy mechanisms, *see Fire behavior of nanocomposites*
 system applications, *see Nanocomposite system applications*
 technology, 378
- Nanocomposite formation
 clay particles, 109
 fire retardancy mechanisms and, 110
 mechanical property improvements, 55–56
 synthetic routes, *see Nanocomposite formation synthetic routes*
- Nanocomposite formation synthetic routes
 in situ polymerization schemes, 40–41
 master batch approaches, 40
 melt processing, 37–40
 overview of, 36–37
 solution-aided dispersion and brute-force melt processing, 37–39
 static melt intercalation, 39
- Nanocomposite system applications
 bulk polymeric components, 331–334
 coatings, 343–344
 composites, 344–347
 films, fibers, and textiles, 334–343
 foams, 347–348
 future directions, 348–349
 requirements for, 326–331
- Nanocor, 327, 332
- Nanodispersion, 117, 131, 153, 326, 347, 361, 366
- Nanofibers, 356, 372
- Nanofillers
 barrier properties, effects on, 56–60
 carbon-based, 377

- characteristics of, 15, 21–22, 36, 132–133, 157, 164–167, 236, 355–356, 358–359, 368, 373, 384–385, 387
- in intumescent systems, 147–153
- mechanical properties, 51–56
- one-dimensional, 49–53
- polymer crystallization, effects of, 45–50
- Nanomers
 - I.28E, 119
 - L30P, 331
- Nanoparticles
 - carbon-based nanocomposites, 295–315
 - characteristics of, 285–286, 318
 - compatibility, 326–327
 - current environmental health and safety status, 376
 - defined, 85
 - dispersion, 366
 - flame retardant mechanisms, 315–318
 - future directions for, 387–388
 - oxide-based nanocomposites, 286–295
 - safe handling, 376
- Nanoscale particles, *see* Nanoparticles
- Nanosilica, 236–237
- Nanostructured morphology, 108–111
- Nanotechnology, 376–377
- Nanotube(s)
 - bundles, 90, 101
 - carbon, *see* Carbon nanotubes
 - characteristics of, 286
 - nanotube interactions, 103
 - radius, 99–100
- Naphtha, 38
- National Bureau of Standards, 2. *See also*
 - National Institute of Standards and Technology (NIST)
- National Institute for Occupation Safety and Health (NIOSH), 376
- National Institute of Standards and Technology (NIST), 2, 4, 67–68, 70, 76, 78, 135–136, 171, 235n
- National Research Council of Canada, 385–386
- Natural clays, 138, 377
- Neutron scattering, 369
- Nielsen's equation, 57–58
- Nitrogen, 11–13, 69, 77, 115–116, 143, 170, 247, 250, 288, 302–304, 328–329
- Nitrogen-containing flame retardants (NFRs), 193
- Nonbonded interactions, 91
- Noncharring material, 109, 114, 118–119
- Nonclassification (NC), 151
- Noncombustible gases, 7
- Nonflammable flame retardant gases, 14
- Nonhalogenated additives, 193
- Nonhalogenated fire retardant materials, 22, 378
- Nonintumescent phosphorus-containing flame retardants, 192–193
- Nonintumescent phosphorus flame retardant additives, nanocomposites combined with, 225–227
- Nonoxidative decomposition, 170
- NPSi, intumescent systems, 150–151
- Nuclear magnetic resonance (NMR) spectroscopy, 111, 369–370
- Nucleation, 46, 378
- Nylon-6/montmorillonite (MMT) material, 32
- Octadecylammonium ion (C18A), 244, 247, 249, 253
- Octadecyltrimethyl ammonium-modified montmorillonite, 119, 253
- Octamethyl POSS, 343
- Octaphenylcyclotetrasiloxane, 18
- Olefins, 39, 223, 225
- Oligomers/oligomeric, generally
 - brominated ammonium-modified clay (OLB-clay), 197, 204, 215–216
 - dimethylhexadecylammonium salts, 216
 - ions, 363
 - nanocomposite formation, 116, 200
 - phosphate (OLP), 193, 203–204, 227
 - phosphate ammonium salt, 197, 214
 - polycation treatments, 364
 - triethyl, 216
 - trimethyl, 216
- One-dimensional nanofillers, 41, 49–50
- Onium ions, 240–241, 272, 358
- Open-flame tests, 70
- Optical microscopy, 47, 317, 371–372
- Optimization, system-specific, 110
- Organic(s)
 - additives, 200
 - aluminosilicophosphate complexes, 143
 - compounds, 113–114
 - inorganic layer, nanocomposite morphology, 113
 - layered silicates, 124
 - phosphorus, 11
 - polymers, 291
 - surfactants, 197
 - reatments, 358–363, 365, 381–382
 - vapor, 376
- Organoclays, 132–133, 164–165, 167–170, 174–176, 201, 228, 310, 358–359, 368
- Organo-modified, *see* Organo-modified hexadecyltrimethylammonium bromide (OMT)
 - clays, 132, 148, 150–151, 154–155, 240, 243

- Organo-modified, *see* Organo-modified
 hexadecyltrimethylammonium bromide (OMT) (*continued*)
 LDH (OLDH), 147–148, 150–151, 155–156
 montmorillonite (OMMT), 289–290
 Organo-modified with
 hexadecyltrimethylammonium bromide (OMT)
 characteristics of, 201–202, 204, 214, 216–217, 224–228
 -MPP, 226
 Organophilic ion, 360
 Organophosphate(s)
 additives, 332
 characteristics of, 136, 227
 Orthophosphates, 136–137
 Orthophosphoric acid, 145
 OTI 95 634 standard, 134
 Oxidation, 13, 18, 115–116
 Oxidative
 decomposition, 170
 degradation, 75
 dehydrogenation, 7
 Oxide nanoparticles, 83
 Oxygen, 70, 113, 116, 250–251, 310
 Oxygen-containing polymers, 11, 13
 Oxyhalides, 10

 Pacific Rim, 373
 Packing injection molding, 37
 Paint, intumescent, 134
 Paraffins, chlorinated, 8
 Particle size, significance of, 21, 334. *See also*
 Nanoparticles
 Particle-particle interactions, 236
 Paste rheology, 331
 Patents, 68, 193, 197, 216, 220, 222, 228
 Path tortuosity, 56, 58–59
 PCFF force field, 91, 96, 103–104
 Peak heat release rate (PHRR)
 assessment techniques, 121–122
 barrier effects, 118–121
 bulk polymers, 332–333
 carbon-based nanocomposites, 297, 310, 318
 char formation, 113
 composites, 345–346
 epoxy nanocomposites, 251–253, 255, 267, 270
 films, fibers, and textiles, 335–336, 343
 flammability properties, 206–217
 intumescent systems, 132
 nanofillers, 147, 149–150
 organoclays, 166, 168, 172–174, 178–179, 183–184, 186
 polymer nanocomposites, 379, 381
 polystyrene nanocomposites, 69
 polyurethane nanocomposites, 273
 research trends, 383–384
 vinyl ester nanocomposites, 276–277
 Pendant groups, 6, 11, 214
 Pentaerythritol (PER)
 characteristics of, 133–134, 136, 143, 151, 337
 phosphate, 334, 337–338
 Percolation, 32
 Permeability, 56–58, 60, 115–116, 164, 236, 261, 263, 270, 272
 Persistence, bioaccumulation, and toxicity (PBT), 373
 pH, 256
 Phenol-formaldehyde resins, 136
 Phenolic-graphite composites, 297
 Phenyl phosphate, 217
 1-Phenylvinylphosphonic acid (PVPA), 197
 Phosphate esters, 12, 21
 Phosphate-pendant groups, 214
 Phosphates, 11, 136, 192. *See also specific phosphates*
 Phosphines, 193
 Phosphocarbonate, 142–143, 145–146
 Phosphonates, 193
 Phosphonium
 bentonite, 122
 compounds, 193
 salts, 248
 Phosphoric acid, 136, 227
 Phosphorus
 -based flame retardants, 11–14, 20, 200
 -containing flame retardants (PFRs), 192–193
 -nitrogen synergism, 12
 oxynitride (PON), 15
 Phosphorylation, 12–13
 Physical barrier effects, 5, 118, 124, 133
 Physical theory, 10
 Plasticizing effect, 205–206, 240, 245. *See also*
 Plastics
 Plastics, 8, 20, 22
 P-O-C bonds, 142–143
 Polar interactions, 33
 Polarity, 110
 Poly(acrylic acid), 256
 Polyacrylonitrile, 6, 343
 Polyactide foams, 347
 Polyamides, 13, 136, 157, 164, 210, 223. *See also specific polyamides*

- Polyamide-6 (PA6)
 characteristics of, 16, 41, 52, 55–56, 69, 79, 81, 83, 120, 132, 136, 138, 143–144, 146–147, 166–168, 197, 205, 208–212, 218, 223–225, 227, 326–327, 330, 332, 335–336, 338–339, 340–341, 357, 359, 363, 365, 371–372, 382
 /DB-AO, 208–209, 218
 /MCA, 210, 217–218
 -MCA-OMT, 210
 /MH-RP, 205, 212, 225
 multiwall carbon nanotube (MWNT) system, 117, 119, 167
 montmorillonite (MMT) systems, 41, 45–46, 52, 270, 334
 -n/DB-AO (PA6/OMT/DB-AO), 208, 211, 218
 -n/MCA, 218
 /OMT/DB-AO nanocomposites, 225
 /OMT-MCA, 217, 221–222
 /OMT/MH, 225
 /OMT/MH-RP, 205–206, 212, 225
 /OMT (PA6–1), 205, 208–212, 218
 /organoclay nanocomposite, 194–195
 -3, 218
 -2, 218
- Polyamide-6,6 films, 337, 339, 341
- Polyamide-12 (PA-12), 50
- Polyaromatic(s)
 characteristics of, 137
 hydrocarbons (PAHs), 22
 structures, 10, 142–143, 247
- Polybutadiene, 199
- Poly(butylene terephthalate (PBT)), 6, 197, 217, 219–220
- Polycaprolactone (PCL), 69
- Polycarbonate (PC)
 -ABS, 20
 bisphenol A-based, 6
 characteristics of, 12, 18–19, 21
- Polycarbosilane (PCS), 292
- Poly(dimethyl siloxane) (PDMS), 54–55, 59, 116
- Polyester
 characteristics of, 227
 fabrics, 343
 resin, 345
 unsaturated, 20
- Polyethylene (PE)
 characteristics of, 6, 16, 40, 42, 52, 55, 83, 164, 166, 168, 216–217
 -hydrocalcite nanocomposites, 166
 -SWNT, 305
- Poly(ethylene-co-vinyl acetate) (EVA)
 -alumina trihydrate system, 378
 characteristics of, 19, 69, 79, 82–83, 144, 146–148, 164–168, 334, 382
 decomposition of, 170
 fire mechanism of, 173–174
 intercalation vs. exfoliation of, 174
 melt blending of, 186
 MWNT, 309
 NMR investigation, 173–174
 /organoclay-based nanocomposites, 169–173
- Poly(ethylene oxide) (PEO)
 characteristics of, 256
 /Na⁺ montmorillonite nanocomposites, 46
- Poly(ethylene terephthalate (PET)), 6, 219, 292, 327, 330–331, 335–336, 343
- Polyfunctional epoxies, 247
- Polyhedral oligomeric silsequioxanes (POSSs)
 characteristics of, 132, 147, 155, 157, 276, 286, 289–295, 343–345, 384
 FQ, 292–294
- Polyhydric compounds, 136
- Polyisocyanurate foams, 378
- Poly lactide (PLA), 330
- Polymer(s)
 applications, 164
 backbone, 5–6
 chains, 56, 96, 101–102, 112, 241
 charring, 123, 136, 143
 -CNT composites, *see* Polymer-CNT composites
 combustion, 5–6
 deacetylation process, 165
 decomposition of, 121
 film, 33
 inorganics, 35, 53
 laboratory flammability test, 3–5
 /layered-silicate (PLS), 44–45, 191–192, 248
 matrix, 41, 50–51, 56, 60, 94–96, 104, 108, 111, 173, 175, 196–197, 200, 206, 222–225, 227–228, 236, 326, 333, 358–360, 365–366, 370
 melt, 123, 329–330
 mix, 90
 molecular weight, 110
 noncharring, 114–115
 nanocomposites, *see* Polymer nanocomposites
 -particle interactions, 236
 polarity of, 110
 -polymer interactions, 94, 101
 pyrolysis, 112–113
 science, 177
 solid state, 112
 wrapping, 90

- Polymer-clay nanocomposites
 characteristics of, 67–68, 81–83, 206, 355–358, 379–380
 historical perspectives, 68–69
 polystyrene nanocomposites, 69–75
 propylene-clay nanocomposites, 75–81
- Polymer-CNT composites, molecular mechanics
 application to PS-CNT composites, 96–100
 characteristics of, 92–93, 104–105
 limitations, 100–104
 methodology, 93–96
 uncertainties, 100–104
- Polymerization, 356, 377. *See also specific types of polymerization*
- Polymer nanocomposites
 analysis techniques, 365–373
 characteristics of, 31–33, 236, 311–312
 clay, *see* Polymer-clay nanocomposites
 defined, 31
 dispersion characterization, 42–45
 effects of nanofillers on material properties, 45–60
 flammability fundamentals, 379–383
 flammability research, *see* Flammability research
 formation, synthetic routes for, 36–42
 future research directions, 60–61
 inorganic, 31
 in intumescent systems, 143–147
 -montmorillonite, 57, 59
 morphologies, 60
 nanoscale filler dispersion, thermodynamics of, 33–36
 organoclays, *see* Polymer-organoclay nanocomposites
 -SWNT nanocomposites, 299
 synthesis procedures, 356–365
 thermal decomposition, 264–266
- Polymer-organoclay nanocomposites
 characteristics of, 191–192, 227–228
 flame retardant mechanism, 222–227
 flammability properties, 206–222
 mechanical properties, 204–206
 preparation methods and morphological study, 193–200
 thermal stability, 201–204
- Poly(methyl methacrylate) (PMMA)
 characteristics of, 6, 21, 39, 78, 89–90, 116, 119–120, 167, 286–290, 295, 326
 -CNF, 312
 -MWNT nanocomposites, 305–307
 PR-1, 314
 PR-24, 313
 -silica nanocomposites, 166
 -SWNT nanocomposites, 299–304
- Polymethylsiloxane, 18
- Polyolefins, 14, 18, 20, 52, 222, 326, 331, 360–361, 378
- Polyols, 12, 21, 143, 272
- PolyOne Corporation, 378
- Poly(oxymethylene) (POM), 197
- Polyoxypropylene diamine, 261, 264
- Polyphenylene ether (PPE), 12
- Poly(phenoloxidase), 20
- Poly(phenylene sulfide) (PPS), 197
- Polyphosphoric acid (PPA), 19, 145, 201, 225–227, 265
- Polypropylene (PP)
 -ATH composites, 168
 -CB nanocomposites, 309–310
 characteristics of, 6, 8, 10, 39, 40, 42, 50, 55, 79, 83, 114, 133–134, 164, 166, 210, 225, 294, 332, 334, 342, 365
 -clay, 75–81, 221
 -GF laminates, 270–271
 -graphite, 295–296
 montmorillonite nanocomposites, 69, 75, 77–78, 80–81, 108–110, 115, 117, 204
 -MWNT nanocomposites, 305–309, 315–316
 /PER, 139, 141
 -POSS, 294
 /POSS-FQ, 295
 -PP interactions, 295
 /PR-1, 314
 -sodium MMT, 222
- Poly(propylene glycol)bis(2-aminopropyl), 259
- Poly(propylene-graft-maleic anhydride) (PP-g-MA), 108–111, 115, 119–121, 197, 208, 210, 221–222, 266
- Polypropylene-graft-maleic anhydride/organoclay (PP-g-MA/OMT/DB-AO) nanocomposites, 196, 204, 208
- Polysilastyrene (PSS), 292
- Poly(silsesquioxanes), 343
- Polystyrene (PS)
 beads, 69
 characteristics of, 6, 10, 14, 20, 34, 92, 114, 296, 327, 326, 332–333, 361, 363, 372
 -clay, 297
 -CNT composites, 90, 92, 95–100, 104
 foams, 347
 nanocomposites, 69–75, 83, 119–120, 166, 199, 203, 214–215, 218
 /OLP-clay, 214
 -OMT-ArP nanocomposites, 199, 202, 214–215, 218

- OMT-TCP nanocomposites, 205
- organoclay nanocomposites, 197, 205, 216
- /polyammonium montmorillonite systems, 38
- silica, 166
- Poly(styrene sulfonate), 256
- Poly(tetrafluoroethylene) (PTFE), 11, 219–220
- Polytetramethylene ether-glycol-*b*/polyamide-12 (PTME-PA), 292–293
- Polyurethane (PU)
 - characteristics of, 6, 14, 201, 227
 - foams, 5, 21, 378
 - nanocomposites, *see* Polyurethane nanocomposites
 - Poly(urethane-co-ureas), 59
- Polyurethane nanocomposites
 - characterization of, 198–199, 201, 205–206, 212, 214, 218, 227, 237, 271–272
 - combustion behavior, 272–274
 - MPP, 201, 205–206, 213, 216, 218
 - OMT, 201–202, 205–206, 213, 216, 218
 - OMT-MPP, 198–199, 201, 205–206, 213, 216, 218, 226
 - POSS FQ2, 294
 - preparation procedures, 271–272
 - thermal stability, 272–274
- Poly(vinyl alcohol)
 - characteristics of, 38, 59, 326
 - /graphite oxide nanocomposites, 297
 - /MMT nanocomposites, 45
- Poly(vinyl chloride) (PVC)
 - characteristics of, 6, 16–17, 20–21, 164, 331
 - EVA, 332
- Poly(vinylsilossequioxane), 343
- Poly(vinyl sulfonate), 256
- Postpolymerization processing, 360–361
- Potassium perfluorobutanesulfonate, 11
- Potential energy, 91, 93, 101–103
- Precipitation, 113
- Pregraphitization stage, intumescent systems, 137
- Prepared vinyl ester (PVE), 155
- Proban CC, 337–339
- Processing aids, 359
- PR-1, 312–313
- Property loss statistics, 164
- Protection elements, 121
- Protective barriers, 166–167, 237
- Protective char, 193
- Protective equipment, 376
- Protective layer, 223, 225–226
- PR-24LHt, 312–313
- Pseudo-two-dimensional layered inorganic fillers, 31
- PVDF, 46
- PVOH, 177, 327
- PV-TPU, 332
- Pyrolysis, 69–71, 75, 78, 83, 112–113, 116, 119, 123–124, 142, 379, 386
- Pyrophosphates, 193
- Quantitative evaluation, 111
- Quantum effects, 93
- Quaternary alkylammonium, 252
- Quaternary ammonium, 329, 331
- Quaternary ammonium-modified montmorillonite, 248, 252. *See also* Alkyl, ammonium; Cationic clays
- Radiant heat, 163
- Radiative gasification, 70–71, 76
- Radical recombination reactions, 166, 381
- Radical scavenging, 13
- Radical trap theory, 10
- Rate of heat release (RHR), 133–134, 140–142, 146. *See also* Heat release rate (HRR)
- Reaction kinetics, 223
- Reactive injection molding (RIM), 362
- Recyclable flame retardant thermoplastics, 22–23
- Recycling, 22–23, 374
- Red phosphorus (RP), 11, 13–14, 16, 193, 211, 225, 334
- Reduction of hazardous substances (RoHS), 377
- Refining operations, 380
- Reflection, 42, 44, 366–368
- Refractive index, 21
- Regulations, fire and environmental, 373–376
- Reinforcement, mechanical, 117–118
- Relative flammability, 81
- Relaxation time (T_1), 369–370
- Resident time, 110
- Residue layer, nanocomposite morphology, 113
- Resilience, significance of, 32
- Resin transfer molding (RTM), 362
- Resorcinol bis(diphenyl phosphate) (RDP), 193
- Resorcinol diphosphate (RDP), 155, 203, 214, 218, 276–277, 333, 345
- Rheological behavior, 44, 111–112, 153, 358, 380
- Rheological effects, 326, 331, 333, 344, 349, 373, 377
- Rheometer, high-temperature, 152
- Riser test, for cable, 176, 186
- Room temperature, 163

- Safe handling considerations, 376
- Salts, 21. *See also specific types of salts*
- Sample thickness, significance of, 120–121
- Sanidic liquid crystals, 111
- Saponite, 237
- SbBr₃, 10
- Sb₂O₃, 10, 21, 217, 219, 224. *See also*
Antimony, oxides
- Scanning electron microscopy (SEM) studies,
156, 225–226, 303–304, 306, 316,
371–372
- Scattering, 366–367
- Schrödinger equation, 93
- Self-extinguishability, 69–70, 122–123, 167,
208, 219, 267, 375, 385
- Self-polymerization, 239
- Semiconductors, 31
- Shear
force, 94
rate(s), 110–111, 117, 174, 330
sensitivity, 333
stress, 54, 111, 329–330
- Shield-forming mechanism, 336
- Si₈O₁₂, 291, 384
- Silica, 21, 132, 286–288, 344
- Silicate
clays, 45, 52, 153, 255, 286
-epoxy matrix, 246
layers, 110–113
structures, 36, 68, 110, 243
surface layer, 113
-triazine intercalation, 220
- Silicon, 18–19, 237
- Silicones, 10, 16
- Silicophosphate groups, 143, 145–146, 157
- Siloxanes, 18, 385
- Simultaneous thermal analysis (STA), 264
- Single-layer design, 184–186
- Single-walled CNTs (SWCNTs)
carbon nanotubes, 299–305, 312–315
characteristics of, 89–92, 99, 104–105, 167,
286
in LDPE, 181–182
organoclays and, 169
synthesis and purification of, 177
- Sintering, 21
- SiO₂, 147
- SiO₄, 138
- Small-angle x-ray scattering (SAXS), 43–44
- Small-molecule flame retardants, 199
- Smectic systems, 112
- Smoke
acidic, 192
dense, 192
gases, 235
generation, 210, 344, 346, 374
obscuration, 121, 163, 250
production, 123–124, 163
release, 207, 227
spread, 375
suppression, 19
toxicity, 1, 121, 163–164, 192, 220
- Sodium
borate, 16
hydroxide, 309
montmorillonite, 255, 327
zeolites, 138
- Sol-gel formation, 326
- Solid flame retardants, 21
- Solid particle pressure, 137
- Solubility, 60
- Soluble additives, 20
- Solution blending, 193–197, 200, 292, 326
- Solvent
blending, 286, 356, 360–362
casting, 37
resistance, 164
uptake, 236
- Sonication, 37, 104, 240, 361
- Soot, formation of, 9
- Sorbitol, 136, 143
- Southern Clay Products, 326–327, 331–332,
345
- Soxhlet extraction, 363
- Space environment, 132
- Specific extinction area (SEA), 207, 213–215,
270
- Specific heat, 155
- Spectroscopic applications, 142, 145
- Stabilizers, 238
- Stable products, long-term, 22–23
- Stand-alone flame retardants, 124
- Starch, 136
- Steady-state
HRR/PHRR, 119–120
significance of, 109
- Steel plate, 134
- Stiffness, significance of, 32, 42, 60
- Stoichiometry, 243, 259–260
- Strain energy, 91
- Strength, significance of, 32, 42
- Structural design, 385
- Structure-property relationships, 108, 111, 124,
358, 373
- Styrene, *see* Polystyrene (PS)
characteristics of, 69, 197, 274, 363
-acrylonitrile (SAN), 166, 199
-butyl acrylate (St-BA), 297–298

- butyl acrylate copolymer/graphite oxide (St-BA/GO) nanocomposites, 297–298
- Subway safety, 375
- Sulfates, 136
- Sulfonate group, 11, 265, 269
- Sulfuric acid, 136
- Süd-Chemie, 327
- Superacid, 253
- Surface
 - area, polymer-carbon nanotube composites, 94, 96, 102, 104
 - chemistry, 334
 - density, polymer-carbon nanotube composites, 103
 - energy, 98–99, 112, 236–237
 - layer, 113, 124
 - potential energy, 236–237
 - tension, 34, 102–103
- Surfactants, 90, 241, 296
- Suspension polymerization, 357
- Sustainability, 132
- Swelling agents, 38, 256, 260
- Syndiotactic polystyrene (sPS), 46
- Synergism, 9, 12, 19
- Synergistic effects, 113, 117, 125, 132, 138–143, 147–153, 193, 214, 217, 222, 225, 227–228, 255, 272, 334, 336–337, 348
- Synthetics
 - clays, 370
 - fibers, 334, 336
 - polymers, 1
- Tactoids, 110, 242, 246, 372
- Talc, 18, 138, 167
- Telecommunication cables, 220
- Television sets, 2
- Temperature, significance of, 93, 101, 110–111, 113, 121, 134–135
- Tensile
 - moduli, 55
 - properties, 55, 164, 236, 244, 349
 - strength, 53, 205–206, 261–262, 270
- tert*-Butylphenyl diphenyl phosphate, 193, 196
- Tetrafluoroborate salts, 329
- Tetraglycidylidiaminodiphenylmethane (TGDDM) epoxies, 250–251, 255
- Tetrahydrofuran (THF), 292
- Tetramethylsilane, 174
- Tetraphenylphosphonium-modified montmorillonite, 109, 119
- Textiles, 157, 331, 334–344
- T_g , 275, 277
- Thermal conductivity, 41–42, 117
- Thermal decomposition, 5–6, 8, 12, 17, 19, 115–116, 225, 247–251
- Thermal degradation, 165–166, 192, 224, 239, 248, 330, 332, 345, 361, 375, 385
- Thermal expansion, 270
- Thermal motion, 93
- Thermal oxidation, 19, 165–166
- Thermal properties, significance of, 236
- Thermal stability/stabilization
 - carbon-based nanocomposites, 295–296, 299
 - cationic clays, 237
 - epoxy nanocomposites, 240
 - films, fibers, and textiles, 336
 - halogenated additives, 201–204
 - nanofillers, 151
 - organoclays, 164–167, 170–171
 - polymer nanocomposites, 358, 360–361, 363
 - significance of, 20
 - system applications, 329
- Thermocouples, 80, 134–135
- Thermodynamic(s)
 - filler dispersion, 32–36, 40, 43
 - fire retardancy mechanisms and, 112
 - nanocomposite morphology, 112
 - nanofiller effects, 52
 - nanoscale filler dispersion, 33–36, 38
 - neutrality, 100
 - significance of, 90
 - stability, 99, 104, 111, 356
- Thermogravimetric
 - analysis, *see* Thermogravimetric analysis (TGA)
 - curves, 148
 - measurement, 15–17, 114
- Thermogravimetric analysis (TGA)
 - carbon-based nanocomposites, 297, 319
 - carbon nanotube nanocomposites, 177
 - composites, 345–346
 - epoxy nanocomposites, 248–249, 263–265
 - films, fibers, and textiles, 335
 - halogen additives, 201–204, 207
 - intumescent systems, 155
 - nanofillers, 150
 - organoclays, 165, 169, 170–172, 175
 - oxide-based nanocomposites, 293
 - polymer-clay nanocomposites, 81–82
 - polymer nanocomposites, 364, 372
 - polypropylene-clay nanocomposites, 75–76
 - polystyrene nanocomposites, 72–73
 - system applications, 327–329
- Thermooxidative, generally
 - conditions, 142
 - decomposition, 116
 - degradation, 223, 225

- Thermooxidative, generally (*continued*)
 thermogravimetric investigations, 116
- Thermoplastic(s)
 characteristics of, 14, 23, 31, 107, 131, 143, 335, 357–360, 362, 377
 charring, 117
 defined, 235
 melt blending process, 110
 nanocomposite morphology, 112–113
 noncharring, 117
 polyesters, 13
 polymers, 82–83, 193
 polyurethanes (TPUs), 143–144, 331–332
- Thermoset(s)
 characteristics of, 107, 131
 composites, 385
 nanocomposites, *see* Thermoset fire retardant nanocomposites
 resins, 135, 377–378
- Thermoset fire retardant nanocomposites
 characteristics of, 235–237
 clays, 237–239
 epoxy based on anionic clays, 255–271
 epoxy based on cationic clays, 240–255
 morphology, 113
 polymer, 357–359
 polyurethane, 271–274
 research methodologies, 239–240
 vinyl ester, 274–277
- Throughput techniques, 155
- Time-temperature curve, 121–122
- Time to ignition, *see* Ignition, time to
- Titanium oxide (TiO₂), 132, 147, 288–290
- Toluene diisocyanate (TDI), 198
- 4-Toluenesulfonate, 256, 258, 264
- Total heat
 evolved (THE), 108–109, 114–115, 118, 120–124, 254–255
 release (THR), 69, 83, 149, 172, 206–207, 214–216, 335, 345, 356, 379
- Toxic chemicals, 236
- Toxic gases, 163, 227, 235
- Toxicity, 210
- Toxic smoke, 1, 121, 163–164, 192, 220
- Toyota, 69, 77, 359
- Train safety, 375
- Translucence, 164
- Transmission electron microscopy (TEM)
 additives, halogen and nonintumescent, 194, 196–197, 199
 carbon-based nanocomposites, 297, 299–300, 305, 312–313
 epoxy nanocomposites, 244–245, 259
 EVA nanocomposites, 174
 fire and environmental regulations and, 373
 intumescent systems, 147
 nanocomposite morphology, 316–317
 nanostructured morphology, 110–111
 organoclays, 170
 oxide-based nanocomposites, 286–287
 polymer nanocomposites, 366, 368–371
 polymer nanotechnology, 43–44
 polystyrene nanocomposites, 70, 72
- Transparency, 60
- Trapping mechanisms, 236
- Trichlorobenzene, 37
- Tricresylphosphate (TCP), 136, 155, 193, 196, 202–203, 205, 214, 218, 276–277, 333, 345
- Trimers/trimerization, 136, 201, 272, 316
- Trimethyloctadecylammonium ion (C18A3M), 244, 247–249
- Triphenyl phosphate (TPP), 196
- Tri(1,3-dichloroisopropyl) phosphate, 14
- Tri-(2-chloroisopropyl), 14
- Trixylylphosphate (TXP), 193, 196, 202–203, 214, 218, 333
- TTA, 260
- Turbostratic char, 6
- Twin-screw extruders, 38, 363, 365
- Two-dimensional fillers, 36
- U.S. Environmental Protection Agency (EPA), 192
- Ube/Toyota, 357
- UL-1410 test, 3
- UL-1666 fire test, 83, 176–177, 186
- UL-1950 test, 3
- UL-910 Steiner tunnel test, 68, 220
- UL-94 test
 characteristics of, 3–4, 6, 8, 19, 21, 69, 83, 116, 120–121, 123, 132, 168, 173, 216–222
 horizontal burning, 254, 266–269, 277–278
 ignition tests, 318
 nanoscale oxide-based nanocomposites, 287
 V classifications, *see* UL-94 test V classifications
 vertical burning, 117, 225
- UL-94 test V classifications
 implications of, 138, 333, 383
- V-1, 4, 22, 208, 374
- V-2, 4, 21–22, 117, 208, 274, 332, 378
- V-0, 4, 11, 13, 22, 68, 116, 133, 150, 216, 219–221, 332, 334, 378
- Uncharrrable polymers, 5
- Underwriters' Laboratories UL-94, *see* UL-94 tests

- United Kingdom, fire fatality rates, 2
- United States
- environmental concerns, 192
 - fire fatality rates, 2–3
- Untika, 357
- Upholstery, federal standards for, 2
- Urea-formaldehyde resins, 136
- Ureas, 136, 271–272
- Urethane-urea systems, 56
- UV
- degradation, 378
 - stability, 8, 378
- van der Waals force, 92, 99, 103, 241, 299
- Vapor-grown carbon nanofibers (VGCNs), 311
- Vapor-phase effects, 227, 336, 383
- Ventilation, 121
- Vermiculite, 241
- Vinyl acetate, 69, 165, 168
- 4-Vinylbenzylammonium chloride, 296
- 4-Vinylbenzylchloride, 197
- Vinylbenzyltrimethylammonium-modified montmorillonite (VMC), 275
- Vinyl ester (VE) nanocomposites
- characteristics of, 274–276, 345–346
 - combustion behavior, 276–277
 - preparation procedures, 274
 - resins, 345, 347
 - thermal stability, 276–277
- Vinyl phosphates, 197
- 1-Vinylphosphonic acid (VPA), 197
- Viscoelasticity, 137
- Viscosity
- bulk polymers, 333
 - epoxy nanocomposites, 242
 - future research directions, 385–386
 - intumescent systems, 117–118, 151, 154
 - nanostructured morphology, 111
 - organoclays, 167
 - oxide-based nanocomposites, 289
 - polymer-carbon nanotube composites, 93
 - polymer-clay nanocomposites, 83
 - polymer nanocomposites, 358, 378
 - retardancy effects, 113, 117–118
 - system applications, 329–331
 - thermoset nanocomposites, 236
- Volatile products, 1, 5, 12–13, 91, 116, 121, 163, 201, 223–224, 310
- Volatility, 196
- Volatilization, 223, 225, 227, 247–249, 336
- V ratings, *see* UL-94 test V classification
- Vycar PVC, 344
- Waste disposal, electrical and electronic devices, 22
- Waste Electronic and Electrical Equipment (WEEE) protocol, 373
- Water (H₂O)
- characteristics of, 10, 115, 226, 247, 270, 272
 - solubility, 143–144
 - vapor, 58, 225, 261, 263
- White phosphorus, 14
- Wicking, 117, 124
- Wide-angle x-ray scattering (WAXS), 366
- World Health Organization (WHO), 192
- X-ray crystallography, 93
- X-ray diffraction (XRD), 37–38, 42–44, 60, 72, 75–76, 111, 147, 194–199, 207, 222, 243–244, 251, 256–258, 260, 267, 275, 296–297, 345, 365–370, 373
- Xylene, 305
- Young's modulus, 52, 205, 244, 261–262, 270
- Zeolites, 19, 132, 138–143
- Zero-point energy, 93
- Zinc
- borate, 17–19, 138, 167–168, 334
 - hydroxystannate, 168
 - sulfide, 19
- ZSM-5 zeolite, 138–140