
INDEX

- AB-Crosslinked copolymers, 52–54
- ABS plastics
 crazing, 561
 impact resistance, 575
 mechanical strength, 575
 morphology, 561
- Actin, 804–805
- Adhesion, 566–569, 671–675
- Adhesive,
 definition, 415
 forms of, 667–668
 fracture, 668–669
 strength, 668–669
 work of, 639
- Adsorption, 646–651
- Affine deformation, 446, 466–468
 Molecular relaxation, 522–524
- Alkanes, 2–4
- Aluminum, 739
- Amino acids, 800–803
- Amorphous state, 197–238
 chain conformation, 211–217
 diffusion in, 217–226
 dynamics in, 217–226
 long-range interactions, 203–210
 models of, 179–182
 molecular dimensions in, 207
 residual order, 198–199
 short-range interactions, 199–203
 studies on, 200
- Analyses, *see also* Instruments
 chain structure, 31–45
 NMR, 40–42
- Anionic polymerization, 108
- Applications of polymers, 9, 21, 743–748
 blends and composites, 745–747
 conducting polymers, 783–786
 crystalline polymers, 4, 201–265,
 757–762
 damping, 412–414
 dendrimers, 775–779
 elastomers, 480–488, 760–762
 fibers, 307–311, 342–343
 glass transitions, 412–414
 homopolymers, 743–745
 liquid crystals, 342–243
 motor oil, 145–148
 NLO, 788–789
 plastics, 815–816
 polyethylene, 2–4, 757–762
 sheet molding compounds, 741–743
 silk, 769–772
 solutions and precipitates, 146
 supercritical fluid solutions, 782
- Arrhenius equation, 174
- Atomic force microscopy, 626–631
- Avrami equation, 274–278
 experimental range, 277
 parameters, 277
- Axial correlation, 201

- Bacteria produced polyesters, 772
- Balloon swelling, 543
- Biaxial stress envelope, 572
- Bicomponent fibers, 543
- Bingham plastic, 546
- Biomedical polymers, 603–606, 675–677
- Biopolymers, 795–807
 see also cellulose
 see also natural rubber
- Biotechnology
 actin, 804–805
 amino acids, 800–803
 bacteria produced polyesters, 772
 biomedical polymers, 603–606
 biopolymers, 795–807
 blood containing polymers, 676–677
 bone cements, 675–676
 dental restoratives, 604–605
 DNA, 797–800
 drug delivery, 181–183
 hip joints, 605–606
 meat-like textures, 769
 muscle tissue, 804–807
 myosin, 804–807
 optical tweezers, 794–795
 proteins, 60, 95, 807
 zanthan gum, 539–540
- Birefringence, 166–168
- Blends, *see also* Multicomponent polymer materials
 characterization, 165–172
 copolymer miscibility, 163–165
 interfacial chain conformation, 644–646
 interfacial tension, 617–618
 miscible and immiscible, 692–693
 polymer, 45, 130–148, 399–403, 480–488, 644–646, 687–616, 760
 spherulites in, 266–269
- Block copolymers, 51–53, *see also* Multicomponent polymer materials
 ABC triblock copolymers, 713–717
 crystallizable, 717
 interfaces at, 633–635
 morphology, 168–172, 713–717
 motor oils in, 145–148
 order-disorder transitions, 710–713
 PS-PB-BS, 171, 403, 482–484
 spherulites in, 266–269
 structure, 483
- Blood-contacting polymers, 676–677
- Boltzmann's relation, 80
- Bone cements, 675–676
- Boron trioxide, 411
- Bragg's law, 246
- Bread dough, 765–769
- Brittle-ductile transition, 570–572
- Brewster angle, 655–657
- Brush structure, 648–649
- Bulk modulus, 352–354
- Carbon black, 485–488, 697–698
see also tires
 rubber in, 721–722
- Carbon nanotubes, 724–727
- Carnot cycle
 elastomers, 450–453
 gas, 450–451
- Cationic polymerization, 108
- Ceiling temperature, 485
- Cellulose
 crystallinity, 11, 240–242
 molecular weight distribution, 103
 permeability, 174–175
 polymorphic forms, 253
 production statistics, 624
 structure, 68
 types of, 242
 unit cell, 242
- Cellulose triacetate
 density, 75
 mechanical strength, 575
 solubility parameter, 75
 transition behavior, 371
- Cellulose tributyrate
 density, 75
 fusion temperature, 240
 solubility parameter, 75
- Cellulose tricaproate
 osmotic pressure, 90
 theta solvent for, 90
- Cellulose trinitrate
 Flory-Huggins χ_1 value, 85
 intrinsic viscosity, 114
- Center notched sample, 586–588

- Chain conformation
see Affine deformation
see also Rod-shaped structures
see Amorphous state
see Light-scattering
see Random coil
see Relaxations
see SANS
- Chain
 polymerization, 10–12, 108
 pull-out, 596–598
 structure, 13
- Chain pullout, 596–598
 energy, 597, 599
 temperature, 597–598
- Chain structure, 29–70
- Characteristic ratio, 212
- Cheese, 553–556
- Chicle, 9
- Cholesteric structures, 327–328
- Classification charts
 blends, 689
 composites, 690–691
 interfaces, 678
- Clay, montmorillonite, 728–732
- Cohesive energy density, 74–76, 357–358
- Cohesive fracture, 624
- Coatings
 definition, 415
- Cole-Cole plot, 374–375
- Colligative properties, 87–88
- Colloids, 184–186
see also Latexes
 chains attached, 648–649, 657–659
- Combustion, 808–812
- Compliance, 352–354
see also Modulus
- Complex Young's modulus, 355
- Composites, 485–488, 690–692, 721–743
see also Multicomponent polymer materials
 fiber reinforced, 581–585
 glass transitions, 696–698
 matrix and fiber roles, 741
 matrix materials, 582–584
 mechanical properties, 739
 molecular, 584–585
 toughening mechanisms, 739–741
- Compressibility, 353
- Conducting polymers, 783–786
- Conductivity, 782–786
- Configuration, 29–70
 head-to-head, 30
 head-to-tail, 30
 sequences, 39–42
 stereochemistry, 36–42, 760–762
 trans-gauche, 30–31, 55–56
- Conformation, 29–70, 211–213, 326–328
see also Amorphous state
see also Crystalline state
see also Liquid crystalline state
 blend interphase, 644–646
 solution interfaces at, 647–651
- Constants and conversion factors, inside front cover
- Contact angles, 619–622
- Conversion factors, inside front cover
- Copolymers, 45–47
see also block copolymers
see also graft copolymers
see also IPNs
see also polymer blends
 alternating, 47
 fusion temperature, 334–336
 glass transition behavior, 399–404
 periodic, 47
 random, 47
 statistical, 46–47
 unspecified, 45–46
- Copper, 355
- Correlation length, 192–195
see also screening length
- Correlation distance, 640–643
- Crack growth mechanism, 590–592
- Craze, 489, 512–513, 607–608, 630–631
- Creep, 507–515, 519–520
see also stress relaxation
 physical aging and, 528–529
- Critical entanglement chain length, 533–537
- Crosslinkers, 108–109
- Crosslinked polymers, 18–19, 427–506
see also Gelation
see also Rubber elasticity
see also Thermosets
 adhesion and, 668–669
 micronetworks, 429–430

- Crosslinks, 18–19
see also Gelation
 chemistry, 108–109
 effect on T_g , 394–395
 functionality, 460–461
 micronetworks and, 429–430
 physical, 462–465
 polymers and 427–506
 thermoreversible, 474–475
- Crystalline state, 4–10, 239–324
 Avrami equation, 274–278
 cellulose, 241–242
 chemical structure effect, 305–307
 cold drawing, 569–570
 crystal structure determination,
 253–256
 fibers, 307–311
 folded chains, 258–260
 fringe micelle model, 256–258
 fusion thermodynamics, 299–305
 glass transition and 404–407
 hierarchical structure, 311–312
 Hoffman's nucleation theory, 279–
 280
 Hoffman's three regimes, 281–287
 Hoffman-Weeks equilibrium, 304–305,
 762
 Keith-Padden kinetics, 278–279
 kinetics of crystallization, 271–290
 light-scattering patterns, 263–264
 mechanical behavior, 566
 molecular dimensions, 294
 percent crystallinity, 244–245, 269–
 271
 polyethylene, 249, 758–759
 reentry problem, 290–299
 single crystals, 258–260
 spherulites, 260–265
 surface tension, 618–619
 switchboard model, 260
 unit cells, 245–256
 X-ray analyses, 245–256
- Crystallinity, percent, 269–271
see also Crystalline state
- Crystal structure, 245–260
- Crystallization kinetics, 271–290
 analysis, 284–290
 regimes, 284–290
- Cyclic Polymers, 128–129
- Damping, 412–414
- Dashpots, 510
 failure and, 559–560
- Davies equation, 702
- Deborah number, 521
- Debye-Scherrer powder method,
 246–247
- de Gennes, 219–222, 817
 reptation theory, 219–222
 self-similar polymer grid, 659–661
- Demonstrations, classroom
 Carnot cycle, 450–453
 gelation, 497–501
 glass transition, 423–425
 rubber elasticity, 501–502
 swelling of elastomers, 503–505
- Denaturing proteins, 429
- Dendritic polymers, 773–779
 applications, 777–778
 intrinsic viscosity, 775–776
 morphology, 775–778
- Density, polymers, 75
- Dental Restoratives, 604–605
- Depletion zones, 651–652
- Dielectric behavior, 372–373
- Diffusion, 172–180
see also Permeability
 barriers with nanocomposites, 734–
 735
 branched chains, 222–223
 calculations, 236–237
 case II, 181
 coefficients, 223–227
 drug delivery, 181–183
 Fickian, 180–181
 fractal interfaces, 665–666
 gases into polymers, 172–180
 kinetics, 182–183
 non-linear chains, 222–223
 polymer chains, 217–226
 self, 219–222
 short times, 525
 transdermal, 183
 tube coefficient, 537–538
- Dilatant, 546
- Dilatometry, 366–368
- Dilute solution-solid interface, 646–652
- Dilute solutions, *see also* Molecular
 weight

- see also* Solutions, polymer
 NMR, 47–49
 Dispersion 361
 polymerization, 780–781
 Ditactic polymers, 69–70
 Divinyl benzene, 433
 DNA, 797–800
 Watson and Crick model, 797–800
 Domain sizes, *see also* Polymer blends
 block copolymers, 168–172, 710–718
 IPNs, 168–169, 718–721
 Dolittle equation, 385
 Drag reduction, 812–815
 Drago constants, 671–675
 Drug delivery, 181–183
 Dynamic light-scattering, 100–102, 657–659
 Dynamic mechanical behavior, 362–365, 369–372, 412–414
 damping and, 412–414
 dynamic viscosity, 544
 five regions in, 362–365
 instrumentation for, 368
 Dynamics, macromolecular, 217–226
 Dynamic viscosity, 544

 Ehrenfest's relation, 411
 Elastomers, *see also* Rubber elasticity
 current usage, 480–488
 definition, 415
 dienes, 481–482
 saturated, 482
 structure, 483
 types of, 481–485
 viscoelastic rupture, 578–581
 Electrical behavior, 782–786
 Electron diffraction, 207–209, 247
 End-groups, 87
 End-to-end distance, 211–214, 526
 see also Radius of gyration
 Energy well, 584–596
 Engineering
 molecular, 21–22
 plastics, 815–816
 Entanglement, *see also* Diffusion
 see also Reptation
 critical chain length, 553–555
 Entropic barrier theory, 288–290

 EPDM
 structure, 482
 properties, 757–760
 supercritical fluids in, 779–780
 Epoxy resin
 adhesives, 674–675
 composites, 582–583
 IPN, 404
 mechanical properties, 575, 739
 nanocomposites, 733–734
 NMR spectra, 373
 rubber toughened, 739
 thermoset as, 763–765
 Equation of state
 gases, 439–442
 network, 445–449
 rubber elasticity, 434–449
 single chain, 442–445
 theories, phase separation, 157–159
 ESCA, 619–625
 see also Instruments
 Example calculations
 adhesives, 527–528
 blend transition temperatures, 694–696
 block copolymers, 172
 bound fraction, 647–648
 chain and two colloid particles, 649–651
 composite moduli, 699–700
 crack growth, 665–666
 critical strain energy release rate, 588
 Davies equation, 702
 fold surface free energy, 280–281
 fractal-like interfaces, 665–666
 free energy of mixing, 84–85
 interphase thickness, 640
 intrinsic viscosity, 117
 melt viscosity, 535–536
 melting point depression, 301–302
 miscibility limit, 156–157
 molecular characteristics, 526–527
 percent crystallinity, 244–245
 phase inversion, 708–709
 rubber elasticity, 448–449
 solubility parameter, 77–79
 surface tensions, 617
 swelling data, 473
 viscoelasticity of polystyrene, 526–527

- WLF equation, 389–390
work done on stretching, 449
- Excimer
formation, 60
probes, 165–168
- Expansion coefficient
chains, 84
linear, 366
volume, 363, 366–368, 378
- Extended chain crystals, 297–299
- Failure, viscoelastic, 578–581
- Fatigue crack propagation, 592–593
- Fibers, 307–311, 342–343
carbon, 582–584
composites in, 581–585, 722–723
definition, 415
drawing, 569–570
formation, 342–343
liquid crystals, from, 342–343
reinforced plastics, 699–700, 722–723
- Fick's laws, 173–181
Fickian diffusion, 177
Permeability, 180
- Fillers, 18–19
carbon black, 485–488
fibers, 699–700, 722–723, 739–741
reinforcing, 485–488
silica, 485–488
- Film formation, 185–188
- Fire retardancy, 808–812
- First-order transitions, 362–366
see also fusion
see also melting
liquid crystals, 328–331
crystalline polymers, 2–9, 239–324
- Floor temperature, 484–485
- Flory-Huggins χ_1 , 84
liquid crystals, in, 340
theta solvents, 148–149
- Flory-Rehner equation, 472–473, 503–506
- Flory-Stockmayer equation, 110–111
- Flory θ -solvent, 112–113
chain dimensions, 203–207
- Flory θ -temperature, 89–91
polystyrene in cyclohexane, 148–150
- Folded chain model, 258–260
see also Crystalline state
- Forward-recoil spectrometry, 632–633
- Four element model, 511–513
cheese application, 553–556
- Fox equation, 400–403
- Fractals, 665–667, 686
estimation of dimensions, 686–687
- Fractionation
molecular weights, 148–150
near walls, 661–662
- Fracture, 560–584, 736–740
see also Strain energy release rate
energy, 622–625
multicomponent, 723–727
surfaces, 622–625
- Freely jointed chain, 211–212
- Free radicals, 10–13, 104–105
- Free volume
expansion coefficients and, 381–384
glass transition requirements, 381
hole size, 390–391
theory, 381–396
WLF equation and, 384–389
- Frequency effects, 380–381
- Friction, 601–603, 627–631
- Friction force microscopy, 630–631
- Fringe micelle model, 256–258
see also Crystalline state
- Front factor, 445–448, 461
- Fusion, 241–244, 299–305
see also Crystalline state
see also Melting
alkanes, 2–4
glass transitions and, 406
- Gas separations, 179–180
with polymer blends, 180
- Gaussian coil, 98–99
see also random coil
- Gelatin, 478–479, 497–501
- Gelation, 108–110, 473–477
gel point, 429–430, 475–477
hydrogels, 477–478
melt viscosity and, 475–477
polymerization during, 475–477
- Gel permeation chromatography, 11–130
current research, 125–127
detectors, 125–127
HPLC, 119–120
instrumentation, 117–130

- theory, 119–120
 universal calibration, 127–128
- Gels, 478–479
 see gelation
- Gibbs-DiMarzio theory, 393–394
- Glass
 mechanical properties, 737–739
 viscosity, 361–362
- Glass-rubber transition, 8–10, 350–426
 chemical structure and, 408–410
 copolymerization and, 399–404
 crystallinity and, 404–408
 damping effects, 412–415
 demonstration experiment, 423–426
 Fox equation for, 400–403
 free volume theory, 382–384
 frequency effects, 377–381
 fusion and, 406–407
 iso-free volume state, 382–384
 kinetic theory, 390–392
 measurement of, 366–375
 melting and, 406–408
 molecular weight and, 397–399,
 403–404
 multicomponent materials of, 687–706
 polymerization during, 399–404
 pressure effects, 410–412
 region, 358
 temperature, 350–426
 theories, 381–397
 thermodynamic theory, 392–397
 thin films, 662–664
 time effects, 377–381
 WLF equation and, 384–389
- Glass transition region, 8–10, 358
 see also Glass-rubber transition
- Glassy region, 358
 see also Plastics
 surface tension, 618–619
- Graft copolymers, 51–54
 phase separation, 168–170
- Griffith equation, 585–586
- Group molar attraction constants, 77–79
- Guth-Smallwood equation, 701–702
- Halpin-Tsai equations, 702–705
- Handbooks, 24
- Heat capacity, 3665–367
- Healing, 393–394
 see also Fracture
- Heat distortion temperature, 406–408
- Hierarchical structure, 311–312
- Hip joints, 605–606
- HIPS, see also Multicomponent polymer materials
 fracture, 736–739
 mechanical strength, 573–576
 morphology, 168–169, 737–739
- History of polymers, 20–21
 advances, 816–818
 crystalline unit cell, 240–241
 liquid crystals, 338–340
 major advances, 650–652
 random coils, 232–236
 rubber elasticity, 430–432
- Hoffman's nucleation theory, 279–280
- Hoffman's three regimes, 281–284
- Hoffman-Weeks equilibrium, 304–305,
 762
- Hosemann's paracrystalline model,
 293–297
- HPLC, 119–121
- Hydrogels, 477–478
- Hyperbranched polymers, 773–775, 779
- Ideal solution, 79–80
- Identification code, recycling, 12–14
- Industrial polymers, 20–21, 745–748
- Inorganic elastomers, 484–485
- Instruments, 31–36, 199–201, 544–546,
 619–644
 attenuated total reflection, 619–620
 Auger electron spectroscopy, 619–620
 Brewster angle reflectometry, 655–657
 capillary viscometers, 544–546
 Charpy impact, 573–574
 Chaudhury-Whitesides apparatus,
 619–620
 cone-and-plate viscometer, 544–546
 dielectrics, 372–373
 dilatometry, 366–368
 DSC, 165–168, 328–331
 dynamic light-scattering, 101–103,
 619–620, 657–659
 electron diffraction, 199–201, 207–209,
 247
 electron microscopy, 199–201, 165–172

- ESCA, 32–33, 622–626
 evanescent wave, 622–626
 falling ball, 544–546
 force-balance apparatus, 652–655
 forward recoil spectroscopy, 619–620
 FRES, 632–633
 GPC, 117–130
 HPLC, 120–121
 infrared, 33–34, 43–45, 56–58, 163–165,
 247–248, 291
 intrinsic viscosity, 110–117, 775–776
 Izod impact, 573
 light-scattering, 91–103, 142–144,
 165–168, 619–621, 640–643
 mass spectrometry, 32–33, 130–134
 neutron reflectometry, 635–640
 neutron scattering, 95–98, 203–207
 NMR, 32–33, 40–42, 47–51, 165–168,
 291–292
 osmometers, 88–91
 positron annihilation, 391–392
 Raman, 29, 38, 20933–34, 43–45, 248
 SANS, 203–207, 292–297, 465–469,
 619–621, 640–643
 SAXS, 199–209
 scanning probe microscopy, 627–631
 SEM, 619–620, 626–627
 SIMS, 619–620, 631–632
 stress-optical, 191–192
 surface forces apparatus, 652–655
 tables of, 31–32, 165–168, 199–200,
 366–367
 TIRF, 665
 torsional braid analysis, 369–372
 XPS, 31–33, 622–626
 X-ray, 31–33, 207–209, 246–247,
 640–643
- Interfaces**, 614–687
 adhesion, 637–640, 667–675
 areas, 640–644
 bound chains, 648–649
 chain conformation, 647–649
 contact angles, 619–622
 correlation distance, 640–643
 depletion zones, 651–652
 dilute solution-solid, 646–652
 fractal-like interfaces, 665–667
 fracture energy, 637–640
 interior surfaces, 640–644
 polymer, 593–594, 613–686
 Porod's law and, 643–644
 ripple experiment, 636–637
 self-similarity, 660–661
 thermodynamics, 523–526, 615–618
 thickness, 637–640
- Interfacial tension**, 617–618
- Interpenetrating polymer networks**,
 54, 168–170, 403–404, 710–711,
 718–721
see also simultaneous interpenetrating
 networks
 metastable phase diagrams, 719–
 722
 phase domain size, 710–711
- Interphase**, 614–615
see also Interface
 thickness, 637–640
- Intrinsic viscosity**, 6–8, 110–117
see also viscosity
 equivalent sphere model, 112–113
 Mark-Houwink-Sakurada equation,
 113–115
 dendrimers of, 775–776
- Inverse Langevin function**, 459–460
- Ionomers**, 172
- IPN**, 168–170
see also Interpenetrating polymer
 network
- Isomerism**
 geometric, 42–43
 meso and racemic, 39–40
 optical, 42
 repeat unit, 36–42
 substitutional, 43
 tacticity, 37, 760–761
- Keith-Padden kinetics**, 278–279
see also crystalline polymers
- Kelvin element**, 510–511
- Kerner equation**, 701
- Kevlar®**, 331–334, 582–584
- Kinetic theory of T_g** , 390–392
- Kneading of bread dough**, 767–769
- Kuhn segments**, 199, 213
- Latexes**, 184–186
 diffusion in, 223–227
 non-drip paint, 646–647

- LCST, 153–172
- Light-scattering, 91–103
 calibration, 142–144
- Limiting oxygen index, 809
- Liquid crystalline state, 325–349
 fibers from, 342–344
 formation requirements, 345–346
 history, 338–340
 lyotropic, 331–334
 mechanical behavior, 668–669
 phase diagrams, 327–328
 properties, 344–345
 rod-shaped chains, 326
 side chains, 336–338
 thermodynamics, 338–341
 thermotropic, 334–336
 viscosity, 342–344
- Liquid flow region, 360–361
- Liquid-liquid transition, 375–377
- Lithium niobate, 788–789
- Loops, 647–648
- Loss modulus, 355
- Lower critical solution temperature, 153–172
- Lyotropic liquid crystals, 331–334
- Macromers, 71–73
- Macromolecular hypothesis, 19–20, 816–818
- Magnetic behavior, 372
- MALDI/TOF, 130–134
 calibration, 133
 on oligomers and telomers, 132–133
- Mark-Houwink-Sakurada equation, 113–115
 exponents, 113–115
- Mass spectrometry, 130–134
 for oligomers and telomers, 132–134
- Master curve, 379–381
- Mathematical treatments
 fractals, 665–667, 686
 scaling laws, 192–196
 self-similarity, 660–661
 statistical thermodynamics, 80–82, 442–450
- Maxwell element, 510–511
- Meat-like texture, 769
- Mechanical behavior, 557–612
see also Modulus
- brittle-ductile transition, 570–573
 cold drawing, 569–570
 crack growth, 587–588
 crazing, 560–562, 570–573
 cyclic deformations, 588–593
 definitions, 350–355
 deformation, 560–569
 diffusion effects, 593–594
 elastomers, 576–581
 fatigue, 588–593
 fracture, 560–569
 impact resistance, 573–576
 mechanical strength, 573–576
 molecular aspects, 593–601
 rubber toughening, 573–576d
 tensile strength, 564–565, 600–601
 thermodynamics, 557–560
 time and temperature effects, 565–567
 viscoelastic rupture, elastomers, 573–581
- Mechanical terms, 350–355
 modulus, 350–351
 Young's modulus, 350–351
- Melting, 239–244, 299–305
see also Crystalline state
see also Fusion
see also Liquid crystalline state
- Melting point depression, 300–302
- Melt viscosity, 533–538
 molecular weight dependence, 533–538
 WLF constants, 533
- Metalocene polymerization, 107–108, 758–760
- Micronetwork, 429–430
- Microstructure, 31–32
see also chain structure
 instruments for, 31–36, 40–42
- Miller indices, 245–246
- Minor chain, 593–594
- Miscibility window, 163–165
see also Polymer blends
- Modern polymer topics, 757–824
 biopolymers, 795–808
 bread doughs, 765–769
 conducting polymers, 782–786
 dendritic polymers, 773–779
 electrical behavior, 782–783

- fire retardancy, 808–812
- non-linear optics, 786–789
- optical tweezers, 794–795
- polyolefins, 757–762
- silk fibers, 769–772
- supercritical fluid solutions, 779–782
- thermosets, 762–765
- Modulus, 8–10, 350–355
 - bulk, 353
 - loss, 355
 - multicomponent polymer materials, 698–706
 - shear, 350–351
 - Young's, 350–352
- Molecular basis
 - creep, 508–510
 - fracture, 560–564, 593–599
 - interdiffusion, 599–600
 - molecular weight requirements, 599–600
 - relaxation, 521–525
 - stress relaxation, 508–510
 - tensile strength, 600–601
- Molecular composites, 584–585
- Molecular friction, 596–599, 627–630
- Molecular weight, 6–8
 - averages, 6–8, 85–87
 - between crosslinks, 434–437
 - between entanglements, 434–437
 - commercial polymers, 103
 - determination, 87–103
 - distributions, 4–8, 107–108
 - instrumentation, 134
 - number average, 87–91
 - summary, 134–135
 - tensile strength effect, 4–6, 593–601
 - weight average, 91–103
 - z-average, 85–87
- Molecules
 - see also* Polymer
 - little to big, 2–3
 - relationships among, 526–527
 - size and shape, 71–73
- Mooney-Rivlin equation, 453–455
- Mori-Tanaka theory, 705–706
- Morphology
 - see also* Craze
 - block copolymers, 168–172
 - carbon blacks, 721–722
 - composite materials, 698–706, 721–723
 - IPNs, 168
 - multiphase materials, 168, 706–710
- Motor oil, 145–146
- Multicomponent polymers, 51–55, 186, 687–756
 - see also* Blends
 - see also* Multicomponent polymer materials
 - see also* Phase separation
 - identification, 54–55
- Multicomponent polymer materials, 153–172, 186, 399–404, 687–756
 - adhesives, 667–675
 - applications, 741–748
 - classification, 688–672
 - fiber-reinforced, 722–723
 - fracture behavior, 736–741
 - glass transition, 693–698
 - matrix role, 741
 - metastable phase diagram, 719–721
 - modulus, 698–706
 - morphology, 168–172, 706–710
 - phase diagrams for, 710–721
 - phase diagrams, 154–156, 163–165
 - phase inversion, 707–708
 - rubber-toughened plastics, 737–739
 - sheet molding compounds, 741–743
 - TTT cure diagram, 718–719
- Muscle tissue, 804–807
 - actuators, 792–793
- Mushroom
 - chain conformation, 648–649
 - nanostructure, 773
- Myosin, 804–807
- Nanotechnology, 723–736
 - carbon black, 485–488, 697–698
 - carbon nanotubes, 724–727
 - montmorillonite clays, 728–736
 - fire retardancy and, 808–812
- Natural polymers
 - see also* Cellulose
 - see also* Natural rubber
 - fibers, 309–311
 - products, 16–18, 769–772
- Natural rubber, 8–10, 185
 - see also* Natural polymers
 - see also* Polyisoprene

- diffusion coefficients, 175–178
- force-temperature, 469–472
- glass transition, 394–395, 410–412
- latex, 185
- melting temperature, 479–480
- stress-strain behavior, 434–437
- thermoelastic behavior, 470–472
- tires in, 485–488
- WLF parameters, 533–534
- Nematic structures, 326–327
- Networks, 108–110
- see also* Crosslinked polymers
- see also* Rubber elasticity
- defects, 461
- structure, 432–434
- swelling, 461–462
- Neutron reflectometry, 635–637
- Neutron scattering, 95–98, 203–207
- see also* Instruments
- see also* SANS
- Newton's law, 351–352
- NMR, 40–42
- see also* Instruments
- solid state, 49–51
- strain analysis, 56–58
- Nobel prize winners, 237–238
- Nomenclature and structure, 12–16, 26–29, 45–47, 51–55
- Non-drip latex paint, 646–647
- Nonlinear optics, 786–789
- Normal stresses, 540–544
- Nucleation and growth, 159–163
- Number-average molecular weight, 85–91
- see also* Molecular weight
- Nylon, 405–406
- see also* Polyamide
- glass transition, 405–406
- Oligomer, 71–73
- Optical tweezers, 794–795
- Order-disorder
 - block copolymers, 710–713
 - polymers in, 209–211
- Orientation function, 199–203
- Osmotic pressure, 88–91
- Paint, non-drip, 415, 646–647
- see also* Latexes
- Pancake, 648–649
- PEEK
 - composite, 582–584
 - fiber reinforced, 722–723
 - structure, 722
- Percolation, 427–429
- Permeability, 178–183
- see also* Diffusion
- Permselectivity, 179–181
- see also* Diffusion
- Persistence length, 201, 213
- Phantom network, 464–465
- Phase diagrams, 148–172
- block copolymers, 710–713
- liquid crystalline-solvent, 327–328, 338–341
- metastable IPN, 719–721
- polymer-polymer, 153–172, 694–696, 710–721,
- polymer-solvent, 148–150
- Phase inversion, 707–708
- Phase separation, 145–172
- see also* Phase diagrams
- blends, 163–165
- ionomers, 172
- IPNs, 168
- kinetics, 159–163
- polymer-solvent, 148–150
- thermodynamics, 156–159
- Phenol-formaldehyde resin, 564–565
- mechanical strength, 573–576, 762–765
- Phenolphthalein, 410–412
- Photophysics, 58–63
- Physical aging, 528–529
- Plastics, *see* individual polymers
- definition, 415
- engineering, 815–816
- surface tension, 615–619
- Plastic zone, 586–588
- Plasticizers, 18–19, 361
- Poisson's ratio, 350–355
- Polyacetylene, 783–786
- Polyamide 6, 536–537
- Polyamide, 66
- see also* Poly(hexamethylene adipamide)
- characteristic ratio, 211–216
- density, 74–76

- fatigue, 592–593
- hydrogen bonding, 252–253
- tensile strength, 564–565
- Polyamides
 - see also* Nylon
 - characteristic ratio, 212
 - density, 74–76
 - glass transition, 345
 - nanocomposites with, 729–730
 - solubility parameter, 74–76
 - synthesis, 14–18
- cis*-Polybutadiene
 - characteristic ratio, 211–212
 - density, 74–76
 - equation of state parameters, 157–159
 - interfacial tension, 617–618
 - intrinsic viscosity, 113–115
 - mechanical properties, 736–741
 - molecular characteristics, 526–528
 - permeability, 175
 - rubbery plateau, 360
 - solubility parameter, 74–76
 - structure, 28, 481–482
 - thermoelastic, 469–472
 - theta solvents, 89–91
- Poly(butadiene-*stat*-styrene)
 - see also* Rubber
 - Flory-Huggins χ_1 value, 84
- Poly(*n*-butyl acrylate), 89–91
- Poly(butyl methacrylate)
 - diffusion coefficient, 223–224
 - equation of state parameters, 157–159
 - interfacial tension, 617–618
 - MALDI/TOF, 130–132
 - surface tension, 615–617
- Polycatenane, 773–775
- Polycarbonate
 - block copolymers, 622–626
 - characteristic ratio, 211–212
 - fatigue, 592–593
 - infrared spectra, 43–45
 - mechanical strength, 573–576
 - surface tension, 615–617
 - tensile strength, 564–565
- Polychloroprene
 - interfacial tension, 617–618
 - melting behavior, 479–480
 - structure, 481–482
 - surface tension, 615–617
- Poly(decamethylene adipate)
 - see also* Polyester
 - critical entanglement chain length, 536–537
- Poly(2,6-dimethylphenylene oxide), 157–159
- Poly(dimethyl siloxane)
 - block copolymers, 622–626
 - bond interchange, 508–510
 - critical entanglement chain length, 536–537
 - equation of state parameters, 157–159
 - Flory-Huggins χ_1 value, 84
 - glass transition temperature, 358
 - interfacial tension, 617–618
 - melt viscosity, 533–535
 - molecular characteristics, 526–527
 - stress-strain behavior, 576–581
 - structure, 482
 - supercritical fluids in, 779–780
 - surface tension, 615–617
 - thermoelastic, 470–472
 - viscoelastic behavior, 8–10
- Polydispersity, 107–108
 - polymerization method, 107–108
- Polyester
 - bacteria produced, 772
 - melt viscosity, 533–535
 - synthesis, 14–16
 - unsaturated, 564–565
- Poly(ethyl acrylate)
 - synthesis, 10–14
 - intrinsic viscosity, 113–115
 - thermoelastic, 470–472
- Polyethylene
 - characteristic ratio, 211–212
 - copolymers, 47–49, 760–762
 - critical entanglement chain length, 535–538
 - crystallinity, 8–10
 - density, 74–76
 - equation of state parameters, 157–159
 - fusion, 2–6, 239–240
 - glass transition, 404–405
 - interfacial tension, 617–618
 - kinetics of crystallization, 280–290

- mechanical properties, 736–741
- molecular characteristics, 526
- permeability, 175
- production, 757–760
- properties, 757–760
- solubility parameter, 74–76
- spherulites, 260–265
- surface tension, 615–617
- tensile strength, 564–565
- thermoelastic, 470–472
- theta solvent 91–92
- unit cell, 248–249
- Poly(ethylene glycol) *see* Poly(ethylene oxide)
- Poly(ethylene oxide)
 - bound to latexes, 657–659, 795
 - bound to mica, 652–655
 - characteristic ratio, 211–212
 - crystallization kinetics, 271–274
 - density, 74–76
 - Flory-Huggins χ_1 parameter, 84
 - fusion, 239–241
 - IR and Raman spectra, 43–45
 - molecular characteristics, 526–527
 - solubility parameter, 74–76
 - surface tension, 615–617
 - turbulent flow reduction, 145–148, 814–815
 - water soluble, 814–815
- Poly(ethylene terephthalate)
 - crystallization kinetics, 271–274
 - fusion, 239–240
 - permeability, 175
 - surface tension, 615–617
 - synthesis, 14–16
 - tensile strength, 564–565
 - transitions, 368–369
- Poly(ethyl methacrylate)
 - permeability, 175
 - WLF parameters, 533
- Poly(hexamethylene adipamide)
 - see also* Polyamide 66
 - fusion, 239–240
 - structure, 26–29
- Polyimide, 764–765
- Polyisobutene (Polyisobutylene)
 - critical entanglement chain length, 533–535
 - density, 74–76
 - equation of state parameters, 157–159
 - glass transition, 410–412
 - master curve, 379–380, 531–533
 - melt viscosity, 531–533
 - solubility parameter, 74–76
 - WLF parameters, 533
- cis*-Polyisoprene
 - see also* Natural rubber
 - block copolymers, 710–713
 - characteristic ratio, 211–212
 - Flory-Huggins χ_1 parameter, 84
 - fusion, 239–240, 479–480
 - glass transition temperature, 358, 410–412
 - mechanical properties, 736–737
 - molecular characteristics, 526
 - thermoelastic, 470–472
- trans*-Polyisoprene, 470–472
- Polymer *see also* individual polymers
 - characteristic ratio, 211–212
 - crystallinity, 239–234
 - cyclic, 128–129
 - density, 74–76
 - electroactive, 789–794
 - equation of state parameters, 157–159
 - evidence of, 312–314
 - fatigue, 588–593
 - fusion properties, 239–240
 - glass transition, 410–412
 - impact resistance, 573–576
 - intrinsic viscosity, 113–115
 - light-emitting, 789–790
 - mechanical strength, 573–576
 - molecular aspects, 593–601
 - molecular characteristics, 526–528
 - molecular weights, 71–144
 - muscle actuators, 792–793
 - nomenclature and structure, 12–16, 26–29, 45–47, 51–55
 - permeability, 173–175
 - piezoelectric, 790–792
 - solubility parameters, 74–76
 - solutions, 73–84, 145–172
 - structures and nomenclature, 12–16, 26–28, 45–47, 51–55
 - thermoelastic, 469–472
 - theta solvents, 89–91
 - WLF parameters, 533

- Polymerization, *see* Synthesis
- anionic, 107–108
 - chain polymerization, 10–14, 103–104
 - dispersion, 780–782
 - free radical, 10–14
 - metallocene, 107–108, 758–760
 - step, 14–18, 105–107
 - Ziegler-Natta, 107–108, 758–760
- Poly(methyl methacrylate)
- biaxial stress envelope, 570–573
 - characteristic ratio, 211–212
 - critical entanglement chain length, 533–537
 - density, 74–76
 - diffusion coefficient, 223–237
 - equation of state parameters, 157–159
 - fatigue, 588–593
 - fracture surfaces, 622–626
 - glass transition, 394–397, 410–412
 - GPC, 125–127
 - interfacial tension, 617–618
 - intrinsic viscosity, 113–115
 - IPNs of, 719–721
 - mechanical properties, 724
 - mechanical strength, 573–576
 - melt viscosity, 533–535
 - molecular characteristics, 526–528
 - NMR analysis, 40–42
 - oil resistance, 145–148
 - PS fracture energy with, 626–627
 - solubility parameter, 74–76
 - stress relaxation, 527–528
 - surface tension, 615–617
 - tacticity, 40–42
 - tensile strength, 564–565
 - viscoelastic behavior, 8–10
 - XPS spectra, 622–626
- Poly(*p*-methyl styrene), 391–392
- Polyolefins, 12–14, 757–762
- see also* EPDM
 - see also* Polyethylene
 - see also* Polypropylene
 - unit cells, 249–252
- Poly(oxyethylene)
- fusion, 239–240
 - lamellae, 260–265
- Poly(oxytetramethylene), 89–91
- Polyphenylene, 783–786
- Poly(2,6-phenylene oxide), 588–592
- Poly(phenylene sulfide), 783–786
- Poly(phenyl quinoline), 783–786
- Polyphosphazine, 482
- a*-Polypropylene, 271–274
- it*-Polypropylene
- characteristic ratio, 211–212
 - crystallization kinetics, 271–274
 - equation of state parameters, 157–159
 - fusion, 239–241
 - intrinsic viscosity, 113–115
 - mechanical strain, 56–58
 - production, 757–758
 - supercritical fluids in, 779–780
 - tensile strength, 564–565
- syn*-Polypropylene, 760
- Poly(propylene oxide), 536–537
- Polypyrrole, 783–786
- Polyrotaxane, 773–774
- Polystyrene
- block copolymers with, 168–172, 403–404, 482–484, 710–713
 - bound to mica, 652–655
 - characteristic ratio, 211–212
 - crazing, 570–573, 596–597
 - critical entanglement chain length, 536–537
 - density, 74–76
 - diffusion coefficient, 223–224
 - dynamic mechanical behavior, 369–372
 - equation of state parameters, 157–159
 - fatigue, 588–593
 - filled, 698–699
 - Flory-Huggins χ_1 value, 84
 - frequency dependence, transitions, 380–381
 - glass transition temperature, 358, 394–395, 410–412
 - GPC, 125–127
 - hole size, 391–392
 - house paints in, 145–146
 - interfacial tension, 617–618
 - intrinsic viscosity, 113–115
 - mechanical properties, 737–739, 765
 - mechanical strength, 573–576
 - melt viscosity, 533–535
 - molecular characteristics, 526–528

- phase separation from PVME, 159–163
- PMMA fracture energy interface, 622–626
- production, 757–758
- pull-out energy, 596–597
- ripple experiment, 636–637
- shear storage modulus, 462–464
- solubility parameter, 74–76
- supercritical fluids in, 779–780
- surface tension, 615–617
- tensile strength, 564–565
- theta solvents, 89–91
- transition summary, 376–377
- WLF parameters, 526–527
- Young's modulus, 354–355
- Polysulfone, 588–593
- Polytetrafluoroethylene
 - density, 74–76
 - fusion, 239–240
 - solubility parameter, 74–76
 - surface tension, 615–617
 - tensile strength, 564–565
- Polytetrahydrofuran, 113–115
- Polythiophene, 783–786
- Polytrifluorochloroprene, 372–373
- Polyurethanes
 - IPN of, 719–721
 - structure, 482–484
 - varnishes, shellac, and adhesives as, 145–148
 - WLF parameters, 533
- Poly(vinyl acetate)
 - characteristic ratio, 211–212
 - critical entanglement chain length, 536–537
 - equation of state parameters, 157–159
 - expansion coefficient, 378–379
 - glass transition, 410–412
 - interfacial tension, 617–618
 - intrinsic viscosity, 113–115
 - surface tension, 615–617
 - viscoelastic behavior, 8–10
- Poly(vinyl alcohol), 37–39
- Poly(vinyl chloride)
 - density, 74–76
 - diffusion coefficients, 175–178
 - fatigue, 588–593
 - fusion, 239–240
 - glass transition, 410–412
 - mechanical strength, 564–565
 - physical aging, 528–529
 - plasticization, 145–148
 - production, 757–758
 - solubility parameter, 74–76
 - tacticity, 37–39
 - tensile strength, 564–565
- Poly(vinylidene chloride), 175
- Poly(vinylidene fluoride), 588–590
- Poly(vinyl methyl ether), 159–163
- Porod's law, 643–644
- Positron annihilation lifetime
 - spectroscopy, 391–392
- Pressure-sensitive adhesives, 670
- Processing
 - blends and composites, 741–748
 - melts, 538–547
 - sheet molding compounds, 741–748
 - spinning fibers, 307–311
- Production of polymers, 751–758
- Proteins, 67–71, 107–108, 807
 - amino acids, 800–803
 - bread doughs in, 765–769
 - denaturing, 429
 - globular, 429–430
 - structure, 429–430
 - wine clarification, 145–148
- Pseudoplastic, 546–547
- Radial correlation, 199–203
- Radius of gyration, 91–103, 203–207, 213–214, 521–525
- Raleigh scattering, 202–203
 - see also* Light-scattering
- Random coil, 213
 - see also* End-to-end distance
 - see also* Radius of gyration
 - history, 232–236
 - light-scattering and, 98–99
 - rubber elasticity and, 434–437
 - relationships, molecular parameters, 526
- Raster analysis, 627
- Recycling, 12–14
- Reduced variables shift factor, 529–533
 - see also* WLF equation
- Relaxation, 361
 - time, 515–519

- Renewable resources, 769–772
see Natural
- Reptation, 219–222, 521–525, 737–738, 636–637
see also Diffusion
- Retardation time, 515–529
- Rheology, 538–547
see also Viscoelasticity
 cheese, 553–556
 dynamic viscosity, 544
 normal stresses, 540–544
 viscosity shear dependence, 539–540
 Weissenberg effect, 540–549
- Ripple experiment, 636–637
- Rod-shaped structures, 326, 344–345
- Rosin, 410–412
- Rouse relaxation time, 521–525
- Rouse-Bueche theory, 217–219
- Rubber
 demonstrations, 497–506
 modulus, 354–355
 network structure, 432–434
- Rubber elasticity, 427–506
 Carnot cycle, 450–453
 concepts, 434–437
 continuum theories, 453–459
 crosslinks and, 427–429, 460–461
 demonstration experiments, 497–506
 equations of state, 442–445
 Flory-Rehner equation, 472–473
 fusion behavior, 479–480
 internal energy, 469–472
 melting and, 479–480
 Mooney-Rivlin equation, 453–455
 phantom network, 464–465
 refinements, 459–469
 strain and melting, 479–480
 thermodynamics, 437–439
 thermoelastic behavior, 469–470
 thermoplastic, 482–484
- Rubbery flow region, 260
- Rubbery plateau region, 358–360
- Saffman-Taylor meniscus instability, 597–599
- Salicin, 410–412
- SANS, 223–237, 521–525
see also Instruments
see also Small-angle neutron scattering
- SBR
see also Poly(butadiene-*stat*-styrene)
 carbon black in, 696–698
 IPNs with, 168
 tires in, 485–488
- Scaling laws, 150–153, 192–196, 599–600, 659–660
- Scanning electron microscopy, 626–627
see also Instruments
 bread doughs of, 766–767
- Scanning probe microscopy, 627–631
- Schatzki crankshaft motion, 375–376
- Screening length, 150–153
see also Correlation length
- Schlieren texture, 341–342
- Secondary ion mass spectroscopy, 631–632
- Second-order non-linear optics, 788–789
- Selenium, 410–412
- Self-assembly, 773
- Self-similarity, 660–661
- Semi-dilute regime, 150–153, 192–197
- Separations, gas, 179–180
- Sessile
 bubble, 619–622
 drop, 619–622
- Shear bands, 570–573, 737–739
- Shear modulus, 350–351
- Sheet molding compounds, 728–729
- Side-chain liquid crystals, 336–338
- Silanes, 584
- Silica, 585–588
- Silicone rubber, 482–484
see also Poly(dimethyl siloxane)
- Silk fibers, 769–772
 spinning, 769–772
- Size exclusion chromatography, 117–118
- Simultaneous interpenetrating polymer networks
see also Interpenetrating polymer networks
 epoxy/acrylic, 403–404
- Small-angle neutron scattering, 203–207
see also Instruments
see also SANS
 locations for, 203–207
 orientation and 521–525

- rubber elasticity and, 465–469
- scattering lengths, 203–207
- Smectic structures, 326–327
- Sodium carboxymethyl cellulose, 145–148
- Sol-gel transition, 427–429
- Solid state NMR 49–51
- Solubility parameter, 73–79, 165–168
 - experimental, 74–76
 - tables, 73–79
 - theory, 77–79
- Solutions, polymer
 - concentrated, 145–150
 - dilute, 47–49, 82–84, 150–153
 - formation, 73
 - semi-dilute, 150–153
 - thermodynamics, 79–85, 135–136
- Specific strength, 582–584
- Specific interfacial surface area, 640–643
- Spherulites, 260–269
 - see also* Crystalline state
- Spinning processes, 307–309
 - silk, 769–772
- Spinodal decomposition, 159–163
- Spreading coefficient, 617–618
- Springs
 - failure in 559–560
 - viscoelastic, 510–511
- Starch
 - bread doughs in, 765–769
 - structure, 67–70
- Steel, 737–739
- Step polymerization, 14–18, 107–108
- Steric stabilization, 652–655
- Stereochemistry, 36–42
- Stirling's approximation, 80–82
- Stokes-Einstein equation, 657–659
- Storage modulus, 355
 - see also* Modulus
- Strain energy functions, 455–459
- Strain energy release rate, 559–560, 573, 586–588, 637–640
 - see also* Fracture energy
- Strain optical coefficient, 199–203
- Strain to break, 578–581
- Stress intensity factor, 586–588
- Stress-optical coefficient, 199–203
- Stress relaxation, 517–518
 - energy of activation, 552–553
- Stress-strain behavior
 - elastomers, 434–437
 - plastics, 562–565
 - poly(dimethyl siloxane), 576–580
- Structures and nomenclature, 16, 26–28
- Styrene-butadiene rubber, 8–10
 - see also* SBR
- Strain, analysis, 56–58
 - see also* Stress-strain behavior
- Sulfur
 - crosslinker, 430–431
 - polymeric, 484–485
 - vulcanization, 430–431
- Supercritical fluid solutions, 779–782
- Superposition, time-temperature, 529–533
- Surface forces apparatus, 652–655
- Surface tension, 619–622
 - entropy, 615–617
- Surfaces, 614–686
 - see also* Interfaces
 - surface tension, 619–622
 - free, 612–614
 - interior, 640–644
 - modifications, 670–671
- Surfactants, 184–186
- Suspensions, 184–186
- Swelling, 173
 - hydrogels, 747–748
- Swelling coefficient, 76–77
- Switchboard model, 260
 - see also* Crystalline state
- Symbols and definitions, XXXV
- Synthesis, 10–16
 - see also* Polymerization
- Tacticity, 37–39
 - glass transition effects, 408–410
 - polypropylene, 760–761
- Tails, 647
- Takayanagi models, 513–515
- Tan delta, 362–366, 485–488
- Tensile strength,
 - molecular weight and, 4–6, 594–599
 - plastics of, 564–565
- Texture, 769
- Thermodynamics
 - mixing, 79–85
 - phase separation, 153–172

- solution, 135–136
- statistical, 80–82
- Thermoplastic elastomers, 482–484
 - see also* Block copolymers
- Thermosets, 762–765
 - see* Epoxies
 - see* phenol-formaldehyde resins
- Thermotropic liquid crystals, 334–336
- Thin Films, 662–664
- Third-order nonlinear optics, 786–787
- Time dependence
 - dilatometry, 378–379
 - mechanical relaxation, 379–380
- Time-temperature superposition, 529–533
- Time-temperature-transformation, 398–399
- Tire
 - composition, 585–588
 - skid resistance, 585–588
- Trains, 644–646
- Trans-gauche conformation, 30–31, 55–56
- Transitions, 8–10
 - see also* Fusion
 - see also* Glass transitions
 - see also* Liquid crystals
 - see also* Melting
 - see also* Order-disorder
 - see also* Second-order
 - other, 375–376
- Transverse lengths, 640–643
- TTT diagram, 398–399, 718–719
 - IPNs, 718–719
- Tubes, 219–222, 521–525
 - see also* Reptation
- Tweezers, optical, 794–795
- UCST, 153–156
- Universal calibration, 127–128
- Upper critical solution temperature, 153–156
- Urea-formaldehyde polymers, 765
- Viscoelasticity, 8–10, 355–366, 507–556
 - cheese of, 553–556
 - creep, 507–514
 - five regions, 355–365
 - four element model, 511–513, 553–556
 - Kelvin element, 510–511
 - Maxwell element, 510–511
 - molecular basis, 508–510
 - physical aging and, 528–529
 - procedure X, 518
 - relaxation time, 515–528
 - retardation time, 515–528
 - rheology, 538–547
 - springs and dashpot models, 510–514
 - stress relaxation, 507–514, 552–553
 - Takayanagi models, 513–515
 - time-temperature superposition, 529–533
 - time-temperature-transformation, 398–399
 - viscosity shear dependence, 539–540
 - viscosity, melt and, 533–538
 - Voigt element, 510–511
- Viscosity
 - see also* Melt viscosity
 - Bingham plastic, 546–547
 - complex, 544
 - dilatant, 546–547
 - drag reduction, 812–813
 - flow models, 546–547
 - glass transition and, 361–362
 - intrinsic, 111–117
 - melt, 350–351, 546–547
 - Newtonian, 546–547
 - pseudoplastic, 546–547
 - relative, 111–112
 - specific, 111–112
 - viscosity-average molecular weight, 85–87, 113–115
- Vitrification, 150
 - see also* Glass transition
 - time-temperature-transformation, 398–399
 - phase separation and, 150
- Voigt element, 510–511
- Von Mises criterion, 570–573
- Vulcanization, 430–431
- WAXS, 207–209
 - see also* Instruments
- Wear, 601–603
- Web sites for polymers, 24–25
- Weight-average molecular weight, 85–87, 91–103
 - see also* Molecular weight

- Weissenberg effect, 540–544
Wide angle X-ray scattering, 207–209
WLF equation, 384–389, 533
 universal constants, 553
Wood, 737–739
 see also Cellulose
Work of adhesion, 637–640
- Xanthan gum, 539–540
XPS, 622–626
 see also ESCA
X-ray diffraction, 207–209
- Young's equation, 619–622
Young's modulus, 350
 see also Modulus
 composites, 698–699
 numerical values, 354–355, 724
 thermosets and thermoplastics, 737–739
- Z-average molecular weight, 85–87
Zanthan gum, 539–540
Ziegler-Natta polymerizations, 107–108,
 758–760
Zimm plot, 98, 203–207

