

## INDEX

---

- 16-bit cyclic redundancy check (CRC-16), 425
- Abacus switch, 336
- Accounting management (AM), 16
- Acknowledgment (ACK), 429, 580
- Active queue management, 164
- Address
  - aggregation, 26
  - broadcaster (AB), 330, 338, 356
  - copy, 222–224
  - interval, 305
  - lookup, 25
  - prefix, 25
- Admission control, 118
- Agere system interface (ASI), 548
- Aggregated flow queue (AFQ), 573
- Application programming interface (API), 564
- Application specific
  - instruction processor (ASIP), 539
  - integrated circuit (ASIC), 29, 351, 538
  - standard product (ASSP), 562
- Approximated Longest Queue Drop (ALQD), 172
- APSARA, 251, 252
- Arbiter (AR), 589
- Area-based quadtree (AQT), 95
- Arithmetic logic unit (ALU), 549
- Arrayed-waveguide grating (AWG), 477
- Arrival reassemble queue (ARQ), 573
- Assured forwarding (AF), 127, 572
- Asynchronous transfer mode (ATM), 2, 337, 539
  - ATM
    - routing and concentration (ARC), 337, 351
    - switch chip, 207
  - ATLANTA Switch, 398
  - Augmented banyan switches, 186
  - Availability, 116
  - Average rate, 116
  - Backbone routers, 3
  - Backlogged period for session, 144
  - Backpressure (BP), 349
    - scheduler (BPS), 571
  - Bandwidth, 115
  - Banyan, 284
    - switch, 176
  - Banyan-based switch, 185, 192, 193
  - Base index, 39
  - Batcher-
    - banyan, 288
    - sorting, 287
  - BC-16-16, 53
  - Beginning of packet (BOP), 422
  - Bernoulli arrival process, 196
  - Best-effort (BE), 599
  - Binary
    - network, 333
    - search, 47
    - trie (1-bit trie), 29
  - Birkhoff-von Neumann switch, 438
  - Bit selection, 60

*High Performance Switches and Routers*, by H. Jonathan Chao and Bin Liu  
Copyright © 2007 John Wiley & Sons, Inc.

**606**

- Bitmap
  - compression, 37
  - intersection, 92
- Bit-vector, 37
- Block, 60
- Blocking, 179
- Border gateway protocol (BGP), 6, 29
- Broadcast
  - and select, 470
  - banyan network, (BBN), 304
  - channel number, (BCN), 304
- Buffer
  - management, 163
  - memory controller (BMC), 602
  - reserved cell counter (BRC), 423
- Buffered multi-stage concentration network (BMCN), 357
- Burst Size, 117
- Bursty traffic, 196, 197
- Byte-Focal switch, 446, 459
  
- Cable television (CATV), 1
- Call detailed records (CDR), 16
- Carrier routing system (CRS-1), 11
- Cell
  - copy, 220–222
  - duplicator (CD), 329
- Cell loss
  - performance, 201–205
  - probability, 199–201
  - priority (CLP), 131
- Central
  - module (CM), 382
  - processing unit (CPU), 8, 543
- Channel grouping principle, 323
- Checksum, 541
- Circuit switching, 176
- Class
  - A, B, C, D, 26
- Class of service (CoS), 549
  - queue (CSQ), 415
- Classful
  - addresses, 26
  - addressing, 25
- Classification by packet inspection (ClassPI), 564
- Classifier, 77
- Classless inter-domain routing (CIDR), 26
- Clock multiplex unit (CMU), 580
- Clos network, 333, 382, 473, 490
  - switch, 194, 195
- Code word, 39
  - array (CWA), 54
- Combined input and output queuing (CIOQ), 190, 579
- Command line interface (CLI), 18
  
- Committed
  - access rate (CAR), 129
  - burst size (CBS), 123
  - information rate (CIR), 123
- Common
  - management information protocol (CMIP), 16
  - switch interfaces (CSIX), 583
- Complementary metaloxide-semiconductor (CMOS), 15, 353
- Complete
  - cell interleaving (CCI), 418
  - packet interleaving (CPI), 418
- Compressed
  - next hop array (CNHA), 54
  - pointer array (CPA), 72
- Concentration module (CM), 355
- Concentrator, 320
  - based growable switch architecture, 218
- Concurrent
  - matching algorithm for Clos network (c-MAC), 392
  - round-robin dispatching (CRRD), 400
- Configuration management (CM), 16
- Connection request (CRQ), 580
- Content addressable memory (CAM), 8, 57, 213–215, 539
- Content inspection engine (CIE), 562
- Contention resolution device (CRD), 472
- Continue of Packet (COP), 423
- CoolCAM, 60
- Copy index (CI), 304
- Core
  - language processor (CLP), 544
  - routers, 13
- Credit update (CRT), 422
- Critical Cell First (CCF), 276
- Crossbar (XB), 589
  - switch, 183, 184
- Crosspoint
  - buffer (XB, XPB), 191, 370
  - buffered (CIXB), 368
  - with one-cell crosspoint buffers (CIXB-1), 371
  - queueing, 191
- Cross-producing scheme, 91
- Cyclic redundancy check (CRC), 541
- Cyclic running adder network (CRAN), 312
- Clos switches
  - Three-stage, 187
  
- Data queue (DQ), 561
- Data recovery unit (DRU), 580
- Data-aligned synchronous link (DASL), 544
- Deficit round robin (DRR), 8, 140
- Delay, 198
  - variation, 116

- Densewave division multiplexing (DWDM), 1
- Departure
  - sequence (DS), 160
  - time (DT), 160
- Derandomized algorithm with memory, 250
- Destination
  - address (DA), 285
  - ID (DID), 568
  - queue (DQ), 418
- Differentiated service (DiffServ), 8, 121
- Digital subscriber line (DSL), 1, 539
- DIR-24-8-BASIC, 51
- Direct memory access (DMA), 565
- Disjoint prefix binary trie, 30
- DOUBLE, 266–267
- DQ flag (DQF), 423
- Drop front on full, 164
- DS, 121
  - codepoint (DSCP), 121, 127
- Dual round-robin matching (DRRM), 241–245, 400
  - Exhaustive (EDRRM), 248–249, 392
- Dual shuffle-exchange, 297
- Dual-level matching algorithm for Clos network (d-MAC), 383, 395
- Double data rate synchronous dynamic random access memory (DDR SDRAM), 542
- Dummy address
  - encoder (DAE), 303
  - interval, 304
- Dyadic protocol processor unit (DPPU), 544
- Dynamic packet interleaving (DPI), 419
- Dynamic random access memory (DRAM), 8, 539
  - Rambus (RDRAM), 552
- Earliest deadline first (EDF), 450
  - queue (EDFQ), 589
  - using a three-dimensional queue (EDF-3DQ), 450
- Early packet discard (EPD), 8
- Edge-coloring, 405
- Edge routers, 2
- Egress
  - line card (ELC), 391
  - queuing engine (EQE), 593. *See also* ingress queuing engine (IQE)
  - traffic manager (TME), 414
- EGT-PC, 84
- Electrical-to-optical, 7
- Electro-absorption modulator (EAM), 500
- Element management system (EMS), 17
- Eligibility test, 157
- Embedded processor complex (EPC), 544
- Emulation, 190
- End of packet (EOP), 422, 576. *See also* start of packet (SOP)
- End-to-end, 13
- Enqueuer/dequeuer/scheduler (EDS), 544
- Enterprise networks, 2
- Erbium doped fiber amplifier (EDFA), 479
- Euler partition algorithm, 388
- Exact covering, 264, 265
- Excess bandwidth scheduler (EBS), 571
- Excess burst size (EBS), 123
- Exhaustive Service
  - iSLIP with Hamiltonian Walk (HE-iSLIP), 255–257
  - match with Hamiltonian Walk (EMHW), 255
- Expedited forwarding (EF), 128, 572
- External column memory (XCM), 552
- Fabric shelf controller (FSC), 8
- Fairness index, 146
- Fast pattern processor (FPP), 547
- Fault management (FM), 16
- Feedback priority (FP), 341
- Fiber delay line (FDL), 469, 503
- Field
  - extraction engine (FEE), 565
  - level trie (FLT), 85
  - level trie classification (FLTC), 85
  - programmable gate array (FPGA), 22, 434
- Finite state machines, 540
- FIRM, 241
- First-come-first-serve (FCFS), 446
- First-in-first-out (FIFO), 402
- Fixed size synchronous frame-based matching, 267
- Flow
  - group ID (FGID), 425
  - ID (FID), 426
  - identification number (FIN), 574
  - queue (FLQ), 573
  - aware router, 77
- Forward congestion indication (FCI), 575
- Forwarding
  - engine(s), 6
  - table(s), 6, 25
- Frame relay, 2, 539
- Frame-based
  - matching, 262
  - matching algorithm for the Clos network (f-MAC), 383, 391
  - maximal weight matching, 268, 269
  - maximum weight matching, 268
  - multiple iteration weighted matching, 269, 270
  - Asynchronous variable-size frame-based matching, 270–273
- Framer, 7
- Full frames first (FFF), 446, 451
- Full ordered frames first (FOFF), 446, 455
- Full-duplex, 7

- Fully interconnected switch, 185
- Functional programming language (FPL), 549
- Generalized processor sharing (GPS), 141
- General-purpose processors (GPP), 538
- Generic cell rate algorithm (GCRA), 131
- Geom/G/1 queueing model, 198, 199
- Gigabit ethernet, 1
- Global mask register (GMR), 557
- Graphical user interface (GUI), 18
- Grid of tries, 83
- Group expansion ratio, 325
- Guaranteed bandwidth (GBW), 599
  - scheduler (GBS), 571
- Hamiltonian walk, 250
- Head-of-flow (HOF), 455
- Head-of-line (HOL), 139, 189, 439
  - blocking, 225, 324
- Hewlett-Packard's openview (HPOV), 16
- Hierarchical intelligent cutting (HiCut), 97
- High-priority (HP), 584. *See also* lower-priority (LP)
- High-speed serial links (HSSL), 580
- Hot-spot, 417
- HyperCuts, 98
- ID group, 64
- Independent process, 227
- Index
  - reference (IR), 304
  - SRAM, 61
  - TCAM, 61
- Ingress
  - line card (ILC), 391
  - queuing engine (IQE), 593. *See also* egress queuing engine (EQE)
  - traffic manager (TMI), 414
- Input
  - arbitration (IA), 371
  - buffered (IB), 344
  - grooming module (IGM), 500
  - header buffer (IHB), 552
  - link group (ILG), 602
  - module (IM), 382
  - module arbiter (IMA), 393
  - optical module (IOM), 477
  - port arbiter, 393
  - port controller (IPC), 292, 328
  - segmentation module (ISM), 180, 181
  - output pair queuing (IOPQ), 599
    - buffered switch(es), 177, 197
- Instruction RAM (IRAM), 552
- Instruction-level-parallelism (ILP), 541
- Integrated service (IntServ), 20, 117
- Intermediate stage controller (ISC), 358
- Internal column memory (ICM), 552
- International standard organization (ISO), 16
- Internet
  - architecture board (IAB), 67
  - engineering task force (IETF), 26
  - operating system (IOS), 12
  - protocol (IP), 1, 539
  - protocol version 6 (IPv6), 67
  - service provider (ISP), 2, 77
- Interval, 87
- IP address, 6
  - lookup, 538
- IP router, 176
- IPsec, 539
- IPv4
  - compatible address, 67
  - mapped address, 67
- IPv6, 539
- ISP peering agreement, 3
- Iterative round-robin
  - matching (iRRM), 233, 234
  - with SLIP (iSLIP), 234–240, 371
- Java Database Connectivity (JDBC), 19
- JUNOS, 10
- k-bit trie, 34
- Knockout-based switch, 316
- Last in highest priority (LIHP), 276–278
- LAURA, 252
- LC-trie, 35
- Leaf pushing, 31
- Leaky bucket, 131
- Least significant bit (LSB), 25
- Line card (LC), 7–10
  - shelf controller (LSC), 8
- Line expansion ratio, 324
- Line of crosspoint buffers (LXPB), 380
- Linked list approach, 208–213
- Load-balanced Birkhoff-von Neumann (LB-BvN), 438
- Local area network (LAN), 18
- Longest
  - internal buffer first (LBF), 379
  - prefix matching (LPM), 6, 47, 545
- Longest queue
  - drop (LQD), 172
  - first (LQF), 229, 378
  - first and round-robin (LQF\_RR), 378
- Look-aside (LA), 554
- Lookup
  - stride, 33
  - table, 541
- Loss rate, 116
- Lower-priority (LP), 584. *See also* high-priority (HP)

- Lowest output occupancy cell first (LOOFA), 278–281
- Lulea Trie, 37
- M/D/1 queue, 198
- Mailbox switch, 446, 456
- Management
  - controller (MC), 6
  - information base (MIB), 18, 544
- Mappable, 39
- Maximal matching, 231
- Maximum
  - burst size (MBS), 577
  - matching, 229
  - reserved cells (MRC), 422
  - size matching (MSM), 230
  - weight matching (MWM), 229
    - approximate, 229, 230
- Max-min scheduling, 136
- Mean waiting time, 201
- Media and switch fabric (MSF), 552
- Medium access control (MAC), 543
- Memory
  - access cycle, 207
  - subsystem (MS), 589
  - /space/memory (MSM), 398
- Memoryless multi-stage concentration network (MMCN), 354
- MERGE procedure, 252–254
- Micro-electro-mechanical system (MEMS), 1, 510
- Microengine (ME), 552
- Million packets per second (mpps), 29
- Million searches per second (MSPS), 560
- Minimum switching, 265, 266
- m-Matching, 383
- Most
  - critical buffer first (MCBF), 379
  - significant bit (MSB), 25, 362
  - urgent cell first algorithm (MUCFA), 274, 275
- Multi-bit trie, 33
- Multicast, 177
  - class queue (MCQ), 578
  - contention resolution unit (MCRU), 342
  - grouping network (MGN), 330, 336
  - logical queue, 220
  - output buffered ATM switch (MOBAS), 327
  - pattern (MP), 338
  - pattern masker (MPM), 330, 338
  - shared-memory switches, 220
  - translation table (MTT), 328, 337
- Multi-
  - cell FDL assignment (MUFA), 512
  - database lookup, 558
  - hit lookup, 558
  - plane switches, 187
  - plane switching, 191
  - protocol label switching (MPLS), 2
  - rack, 8
- Multiple-path switches, 181
- Multistage interconnection networks (MIN), 284
- Nesting level, 107
- Network
  - element (NE), 16
  - instruction set computing (NISC), 546
  - interfaces, 6
  - management system (NMS), 16
  - processing forum (NPF), 539, 554
  - processing unit (NPU), 554
  - processor(NP), 7, 538
  - search engine (NSE), 556
- Next hop
  - array (NHA), 53
  - IP address (NIP), 70
- Non-volatile random access memory (NVRAM), 12
- Number of copies (CN), 304
- OC-192, 75
- Off-chip, 541
- Offset address, 34
- Oldest cell first (OCF), 229
- Oldest cell first (OCF\_OCF), 376
- On-chip, 541
- On-off model, 196
- Open shortest path forwarding (OSPF), 6
- Operation cycles (OC), 566
- Operational support system (OSS), 16
- Operations, administration, and maintenance (OAM), 17
- Operator/number specification, 79
- Optical
  - burst switching (OBS), 510
  - cross-connect (OXC), 1, 5
  - interconnection network (OIN), 475, 477
  - switch fabrics, 262, 263
  - switching, 4
  - transport, 4
- Optical-to-electrical, 7
- Optimized processing core (TOPcore), 550
- Original equipment manufacturers (OEM), 541
- Output
  - arbitration (OA), 367
  - buffer switch, 316
  - buffered switch(es), 177, 199
  - contention, 179
  - demultiplexing module (ODM), 490
  - header buffer (OHB), 552
  - link group (OLG), 603
  - module (OM), 382
  - module arbiter (OMA), 393
  - optical module (OOM), 477

- port contention, 176, 177, 225
- port controller (OPC), 294, 328
- queue, 575
- queueing (OQ), 188
  - emulation, 274
- reassembly module (ORM), 181
- Outstanding packet counter (OPC), 425
- Packet
  - acknowledgment (PACK), 426
  - classification, 8, 79, 538
  - delay, 115
  - fair queuing (PFQ), 142
  - forwarding engine (PFE), 11
  - over SONET (POS), 539
  - processing, 538
  - scheduler, 118
  - scheduling, 136, 177
  - switching, 538
  - transmit controller (PTC), 564
- Parallel
  - iterative matching (PIM), 232, 233
  - packet
    - classification (P<sup>2</sup>C), 93
    - switch (PPS), 192
  - shared-memory switches, 218–220
- Parallel-to-serial, 7
- Partial packet
  - discard (PPD), 8, 575
  - interleaving (PPI), 418
- Path ID (PID), 415
- Path-compressed trie, 31
- Pattern description language (PDL), 564
- Pattern-processing engine (PPE), 549
- PCB, 434
- Peak
  - burst size (PBS), 123
  - information rate (PIR), 123
  - rate (PCR), 116, 577
- Per hop behavior (PHB), 126, 572
- Performance management (PM), 16
- Peripheral component interconnect (PCI), 544
- PetaStar, 490
- Phase-lock-loop (PLL), 580
- Physical
  - interface card (PIC), 11
  - layer (PHY), 542
- Ping-pong arbitration unit (PAU), 475, 482
- Pipeline maximal matching (PMM), 245–247
- Pipelined search, 45
- Point of presence (POP), 2
- Pointer array (PA), 70
- Point-to-point, 303
- Polling based matching algorithms, 254
- Port queue (PQ), 574
- Post-order splitting, 62
- Prefix
  - aggregation, 28
  - pruning, 58
  - /length specification, 79
- Priority queue (PQ), 589
- Processing element (PE), 542
- Protocol
  - data unit (PDU), 19, 549
  - independent cell (PIC), 574
- Push-in
  - arbitrary out (PIAO), 275, 276
  - first out (PIFO), 276
- QoS control, 188
- Quad data rate (QDR), 552
- Quality of service (QoS), 8, 114, 293, 539
- Queue
  - loss (QL), 349
  - manager (QM), 602
  - outstanding cell count (QOC), 422
  - reserved cell (QRC), 422
- Queuing engine (QE), 589
- Random drop on full, 164
- Random early detection (RED), 164, 572
  - fair (FRED), 168
  - stabilized (SRED), 170
  - weighted (WRED), 167, 569
- Random early packet discard (REPD), 8
  - weighted, 8
- Random traffic, 196
- Randomized algorithm with memory, 250
- Randomized matching algorithms, 249
- Range
  - mapping, 110
  - splitting, 91
- Re-assembly Queue (RAQ), 391
- Recirculation switches, 187
- Reconfiguration frequency, 263
- Recursive Flow Classification (RFC), 103
- Reduced instruction set computer (RISC), 12, 540
- Reference maximum threshold (RMT), 574
- Re-issue multi-database lookup, 558
- Resequencing buffer (RSQB), 359, 424
- Residual error rate (RER), 116
- Ring
  - head-end (RHE), 288
  - reservation, 471
- RIO, 167
- Round robin (RR), 138, 371, 571
  - deficit (DRR), 591
  - modified deficit round robin (MDRR), 591
  - greedy scheduling (RRGS), 247
  - priority (PRR), 577
  - weighted (WRR), 577, 591
  - modified, 591

- Round robin (RR) (*Continued*)
  - smoothed deficit, 571
- Round-trip time (RT), 371
- Route
  - controller(RC), 6
  - lookup, 538
  - processor interface (RPI), 552
- Router, 5
- Routing, 177
  - address (RA), 312
  - information protocol (RIP), 6
  - module (RM), 337
  - protocol, 6
  - switch processor (RSP), 547
  - table, 6
- RSVP, 117
- RTT outstanding counter (ROC), 422
- Rule, 77
  - encoding, 110
- Running
  - adder network (RAN), 303
  - sum (RS), 303
- Scheduling
  - input module (SIM), 391
  - output module (SOM), 391
- Search key encoding, 110
- Security management (SM), 16
- Segment, 31
- Segmentation and reassembly (SAR), 574
- Self routing, 176
- Self-clocked fair queueing (SCFQ), 153
- Semiconductor optical amplifier (SOA), 477
- Sequence number (SN), 428
- Sequential FDL assignment (SEFA), 512
- SERENA, 254
- Serializer/deserializer (SERDES), 15
- Serial-to-parallel, 7
- Service
  - access point (SAP), 115
  - level agreement (SLA), 122
  - provider, 3
- Session busy period, 144
- Set pruning trie, 82
- Shared-medium switch, 181, 182
- Shared-memory
  - queueing, 188
  - switch, 181, 182, 183, 207, 316
- Shortest internal buffer first (SBF), 379
- Shuffle-exchange, 296
- Silicon packet processor (SPP), 12
- Simple network management protocol (SNMP), 16
- Single cell packet (SCP), 423
- Single-path switches, 181
- Skip value, 31
- Small switch module (SSM), 337
- Smallest eligible virtual finish time first (SEFF), 157
- Soft state, 121
- Software
  - development kit (SDK), 564
  - managed table (SMT), 545
- Space-division switching (SDS), 181
- Space-time-space approach, 215, 216
- Speedup, 179, 190
- Spurious IP packet rate, 116
- Stable matching, 273
- Start of packet (SOP), 575. *See also* End of packet (EOP)
- Starting
  - copy number (SCN), 313
  - indicator (SI), 312
- State-of-the-art, 1
- Static random access memory (SRAM), 8, 29, 539
- Store-process-forward, 541
- Stream editor (SED), 572
- Strong law of large numbers (SLLN), 268
- Structured query language (SQL), 19
- Suitable ID, 60
- Sunshine switch, 284
- Sustained rate (SCR), 577
- Switch
  - core (SW), 589
  - element (SWE), 288, 321, 330
  - fabric, 6, 176, 538
  - priority (SP), 293
- Switching, 177
  - cell-mode, 179
  - packet-mode, 180, 181
- Synchronous
  - digital hierarchy (SDH), 7
  - optical network (SONET), 7, 343
  - static RAM (SSRAM), 552
- System
  - busy period, 144
  - packet interface (SPI), 552
  - peripheral interface level 3 (SPI-3), 562
  - virtual time, 146
- System-level architectural model (SLAM), 559
- Tail drop, 163
- Tandem banyan switching fabric (TBSF), 294
- Ternary content addressable memory (TCAM), 8. *See also* CAM
- Thread-level parallelism (TLP), 541
- Three dimensional queue (3DQ), 450
- Throughput, 115, 179, 190
- Time
  - division multiplexing (TDM), 344, 594

- slot, 176
  - division switching (TDS), 181
  - stamp-based, 424
  - to-live (TTL), 6
- Token bucket, 133
- Traffic
  - conditioning agreement (TCA), 123
  - management, 538
  - manager (TM), 7
  - model, 196
  - policing, 134
  - shaping, 135
- Transceiver, 7
- Transponder, 7
- Tree
  - bitmap, 42
  - polling, 470
  - search engine (TSE), 545
- TrueWay switch, 414
- Trunk
  - number (TN), 303
  - number translator (TNT), 304
- Tunable
  - filters, 480
  - wavelength converter (TWC), 509
- Tuple space, 107
- Type of service (TOS), 121
- Unicast, 177
  - IPv6 address, 67
- Unshielded twisted path (UTP), 9
- Unshuffle-exchange network (USN), 297
- Usage parameter control (UPC), 8, 129
- Variable bit rate (VBR), 577
- Variant randomize matching algorithm, 251
- Vertical cavity surface emitting laser (VCSEL), 10
- Very
  - high-speed integrated circuit hardware description language (VHDL), 436
  - large scale integration (VLSI), 21, 285, 367
  - long instruction words (VLIW), 543
- Virtual
  - channel identifier (VCI), 328
  - clock (VC), 8, 150
    - shaped (SVC), 572
  - connection (VC), 421
  - finish time, 146
  - input queue (VIQ), 429
  - output
    - port arbiter (VOPA), 393
    - queue (VOQ), 8, 368, 391, 402
      - Eligible (EVOQ), 371, 379
  - path
    - capacity allocation (VPCA), 409
    - queue (VPQ), 415
  - private network(VPN), 539, 564
  - time, 146
- VoIP, 539
- Washington university gigabit switch (WUGS), 217–218
- Wavelength
  - converter (WC), 504
  - multiplexing division (WDM), 468
- Weighted fair queuing (WFQ), 8, 146, 571
- WF<sup>2</sup>Q+, 158
- Wide-area-network (WAN), 5, 18
- Wire-speed, 539
- Word frame, 72
- Worst-case
  - fair weighted fair queueing (WF2Q), 155
  - fairness WFQ (WF2Q+), 8
- Zero bus turnaround (ZBT), 560