

# Index

- AB-class input, 99
- absolute capacity value, 5
- accumulation mode, 33–35, 39, 41, 43, 81, 82
- accumulation mode NMOS varactor, 41
- accumulation range, 40
- accumulation zone, 33, 35–37, 40, 48
- active circuit, 100–104, 106, 109, 112–114
- active element, 1
- adjustable single-channel converter (ASCC), 96
- air coplanar probes (ACP), 54
- amplifier, 92, 93, 96
- anode, 11, 15, 16
- anodic bonding process, 7
- ASCC tuner, 97
- autocoupling, 58, 60, 63, 64
- autocoupling impedances, 64
- avalanche breakdown, 15, 18
  
- balun, 101, 121
- barium strontium titanate (BST), 7
- bias voltage, 11, 12, 14, 16, 19, 21, 41, 43–47, 49, 50
- bonding wires, 99
- bondwire, 57, 58
- broadband, 73
- BST varactors, 8
- bulk, 32, 38–40
  
- cables connectors, 53
- calibration, 55, 67–70
- calibration methods, 55
- calibration reference tolerances, 67, 68
- capacitance, 1, 3–5, 11, 12, 14–16, 18–29, 31–38, 40, 41, 43–51, 56–58, 67, 74–77, 79–82, 85–87, 90, 91, 93, 95, 96, 99, 104–106, 108–112
- capacitance value per unit area, 34, 40
- capacitance variation range, 4, 111
- capacitor, 1, 81, 91, 99
- carrier diffusion, 13
- carriers, 16, 38–40, 81, 82, 87
- cathode, 11, 15, 16
- CATV header channel processor, 97
- centre-tapped coils, 106
- channel resistance, 49, 105
- CMOS, 8, 9, 30, 31, 38, 51, 52, 57, 72, 88, 101–103, 114, 122
- coil, 94, 96, 107–111
- common centroid configurations, 101
- component, 53, 55, 67, 69–72, 96, 103, 115, 121
- component degradation, 67, 70, 71
- conductance, 96, 100, 106, 112–114
- connection lines, 4, 35, 65, 109
- connection track impedance, 60
- contact, 14, 18, 35, 37, 56, 57, 60, 63, 64, 71, 85, 115

- contact impedance, 60, 63
- contact perimeter, 18
- contact resistance, 63, 71
- cooper, 6
- coupling between the two ports, 60
- c-plane sapphire substrate, 7
- current consumption, 105, 114, 115
  
- DC voltage, 32
- de-embedding, 59, 61, 62, 65, 66
- de-embedding process, 62, 65, 66
- de-embedding system, 59
- defect electrons, 12, 16, 39, 41, 43
- degradation of the components, 70
- depletion mode, 34, 36
- depletion range, 40
- depletion zone, 11–18, 20, 21, 25, 34, 36, 37, 41, 74–76, 79
- design rules, 1, 85, 86, 109, 114
- device under test (DUT), 57, 60, 61
- dielectric material, 6
- diffusion area, 18
- diode, 15, 18
- discrete varactor, 5, 6
- dissipation matrix, 2
- distance between islands, 21, 23, 24, 109
- doping zones, 18
- double gated contact, 50, 115
- drain, 32, 36–39, 41, 45, 79, 104
- drain/source, 32, 45, 79
  
- effective silicon area, 3, 5, 28–30, 85, 87
- electric field, 13, 14, 27, 35–38
- electrical conditions, 53
- electrical phenomena, 11, 13, 34–36
- electrons, 12, 16, 33, 38–41, 43
- empty zone, 41, 87
- external connection, 6, 17, 27, 28, 30, 50, 74, 99, 100
  
- flatband voltage, 33, 38, 40
- flicker noise, 116
- free electrons, 41, 43
  
- frequency, 3–6, 8, 9, 25–28, 30, 43, 50, 51, 53–55, 58, 67, 68, 71, 73, 79, 85, 86, 88, 91–99, 101, 103, 105–111, 115, 117–119, 122
- frequency range, 5, 6, 27, 53–55, 58, 68, 71, 73, 86, 105, 111
  
- gate, 31–35, 37–41, 43, 45–50, 79–82, 86–88, 104, 105, 115
- gate contact, 35, 37, 115
- gate length, 45–49, 82, 86
- gate metal, 35
- gate oxide, 31, 33–35, 37, 39–41, 47, 79, 86
- gate width, 45, 49, 50, 82, 86
- geometrical shape, 57
- Gilbert cell, 99, 101
- ground, 11, 14, 16, 57–60, 62, 63, 100
- guard ring, 57–59
  
- harmonics, 100, 116
- HBT transistor, 101
- holes, 33, 34, 38, 39
  
- IC design, 89
- imaginary part, 3, 11, 27
- impedance range, 53
- impedance to ground, 60
- incident wave, 2
- inductance, 4, 27, 30, 35, 37, 50, 74, 76, 77, 79, 80, 83, 105, 107, 109, 111, 112
- inductive effect, 13
- inductive part, 27
- inductor, 4, 27, 99, 105–109, 112
- insertion loss, 54, 91, 92
- Integrated varactor, 1, 4–6, 8, 19, 30, 53, 54, 56, 59, 66, 85, 89, 106, 108
- Integrated VCO, 89
- interconnection lines, 4
- interdigit varactor, 17–19, 22, 29, 30
- inverse voltage, 11, 12, 15
- inversion channel, 43
- inversion mode, 32, 41, 43, 81, 82
- inversion zone, 34, 41, 48

- inverted polarization voltage, 75–77  
island varactor, 17, 18, 29, 30, 85, 109
- junction capacitance, 14
- layout, 19, 72, 109, 114  
LC tank, 1, 89, 93, 94, 96  
linear element, 1  
load, 55, 69, 92, 93  
LRM, 55  
LRRM, 55  
LTI system, 95
- magnetic field, 13, 27, 35–37  
manufacturing process, 47, 67, 69, 99, 106, 109, 111  
matrix varactor, 17, 18, 29  
maximum capacitance, 3, 12, 29, 34, 86  
measurement equipment, 23  
measurement techniques, 53  
metal connections, 27, 32, 74, 76, 77, 79, 80, 83, 86  
metal track, 11, 13, 35, 37, 47, 60, 85, 109  
metallization, 51  
micro-electromechanical system (MEMS), 6  
micro-machining, 6  
mobility of the electrons, 41  
model, 4, 9, 48, 56, 59, 61, 63–65, 67, 73–75, 78–80, 90, 97, 103, 106, 108, 110, 112  
modelling of varactors, 1, 4, 73  
moderate inversion zone, 41
- N + diffusion, 37  
narrowband, 73  
N-channel MOSFET transistor, 32  
NMOS varactor, 31–36, 38–46, 48–50, 78, 80, 86, 87  
noise, 92, 93, 95, 96, 99, 100, 102, 109, 110, 115, 116, 118, 120, 122  
noise power, 95  
non-integrated varactor, 6  
nonlinear dielectric tuneability, 7  
non-linear element, 1
- N-type doping, 11  
number of islands, 20–22, 25, 76, 109
- ohmic loss, 13, 14, 35–38, 60  
one-port element, 2  
on-wafer, 54, 57, 72, 89, 120  
on-wafer measurement, 89, 120  
oscillation frequency, 94, 95, 99, 105, 108, 109, 111, 115, 117  
output power, 99, 101, 102, 114, 115, 117, 119, 121  
oxide layer, 70, 80
- P model, 92, 97  
P well, 15, 16  
P + diffusion, 13, 85  
pad dimensions, 57  
parameters under test, 53  
parasite inductance, 4  
parasitic capacitance, 28, 32, 35–38, 47, 48, 50, 56, 60, 74, 75, 77, 81, 82, 95, 99, 104–106, 109, 114, 115  
parasitic resistance, 41, 51, 79  
passivation, 71  
passive elements, 1, 3, 56, 58, 89, 90  
passive filter, 89–91  
passive network, 3  
PCB, 57, 106, 118, 119  
phase noise, 95, 96, 99, 100, 102, 109, 110, 115, 116, 118, 120  
physical specifications, 53  
PLL, 99, 106, 118–122  
PMOS channel, 40  
PN zone, 11  
PN-junction varactor, 1, 11–20, 24, 28, 29, 31, 32, 50, 74, 76, 78, 85–87, 109  
P-type doping, 11
- quality factor, 3, 6, 7, 11, 16, 17, 19, 20, 22, 24–26, 28–30, 32, 38, 43–46, 48, 49, 51, 67, 85–87, 96, 109, 110, 112
- reference plane, 55, 61  
reflected wave, 2

- reflection coefficients, 3
- reliability, 55, 67, 110
- resistivity, 13, 14, 24, 35–38, 75, 77, 78, 82
- resistor, 1, 102
- return loss, 90
- RF I-V, 53
- RF magnetron substrate, 7
- RF designers, 53, 123
  
- sacrificial layer, 7
- scalability, 45
- self-resonance frequency, 3, 4
- short-open-load-thru (SOLT), 55
- SiGe, 8, 9, 30, 38, 57, 88, 122
- silicon surface, 33
- simplified electric model, 75, 80
- simulation results, 89, 106, 115, 116
- single-open, 62–65
- single-short, 62–64
- size of islands, 86, 109
- size of Nwell, 20, 24, 25
- slab, 15
- SMA, 55
- SMA adapters, 55
- source, 32, 36–38, 41, 45, 66, 79, 100, 102, 105
- s-parameter, 2, 3
- standard deviation, 68–72
- standard technologies, 8
- sticking process, 6
- stored inductive energy, 4
- strong inversion zone, 41
- substrate, 7, 11, 14–16, 32–34, 36–38, 43, 56–58, 60, 67, 69, 75, 79, 80, 82, 100, 109
  
- surface micromachining process, 6
- suspended plates, 7
  
- tank losses, 100, 104
- test pads, 57
- test probes heating up, 67, 69, 70
- test probes, 53–57, 67–70
- test structure configuration, 56
- test structure pads, 54
- test structures, 56, 57, 59–62, 66
- test system, 53, 55, 56, 66, 67, 69, 70
- test system verification, 67
- test technique, 53
- thermal drift, 93, 116
- thermal noise, 93, 116
- threshold voltage, 33, 34, 38, 40, 41
- thru, 55, 62, 64, 65
- tracks, 13, 14, 23, 47, 48, 60, 79, 85, 109, 114, 119
- transformer, 1
- transconductance, 93, 102, 104, 105, 114
- transmission coefficients, 3
- triterminal element, 59
- tuning range, 3, 4, 9, 20–22, 24, 25, 28, 29, 31, 32, 34, 43, 44, 46, 48, 49, 51, 76, 85–87, 96, 99, 105–107, 109–112, 115
- two-port test structure, 56, 65
  
- varactor, 1, 3–5, 7–9, 11–13, 15–20, 22, 24–53, 55, 56, 59, 60, 65, 66, 72–83, 85–96, 99, 105–112, 115, 118
- varactor size, 45
- vector network analyzer (VNA), 53
- Voltage Control Oscillator (VCO), 8
- voltage-variable capacitor, 1
  
- width of the islands, 21