

Index

- Absolute-intensity optical emission
 - spectrum, plume plasma optical emission, 419–422
- Acceleration region, Hall thruster operation, 332–333
- Accelerator grid, ion thrusters:
 - basic properties, 189–190
 - configurations, 190–196
 - design principles, 196–200
 - electron backstreaming, 208–216
 - high-voltage considerations, 216–224
 - carbon-carbon composite materials, 221–223
 - electrode breakdown, 217–218
 - hold-off and conditioning, 224
 - molybdenum electrodes, 218–221
 - pyrolytic graphite, 223
 - lifespan analysis, 225–235
 - barrel erosion, 230–232
 - grid models, 227–229
 - pits-and-grooves erosion, 232–235
 - optics, 200–208
 - grid expansion and alignment, 206–208
 - ion trajectories, 200–204
 - perveance limits, 204–206
 - recycling behavior, 137–141
- Accommodation and accommodation
 - coefficient, plume emissions, spacecraft interactions, 412–413
- Acronyms and abbreviations table, 448–450
- Adatom production, hollow cathodes,
 - barium loss rates, 295–296
- Alternating current (AC), radiofrequency (rf) ion thrusters, 155–158
- Alumina walls, Hall thrusters, dominant power-loss mechanisms, 349–357
- Ambipolar diffusion coefficient:
 - hollow cathode:
 - insert region plasma, 257–270
 - orifice region plasma, 277–280
 - plume-region plasma, 284–292
 - with magnetic fields, 69–71
 - without magnetic fields, 65–66
 - primary electron motion and ionization, 178–182
 - radiofrequency (rf) ion thrusters, 153–158
 - ring-cusp ion thruster models, ion confinement, 111–116
- Anode wall:
 - discharge stability, 134–137
 - performance efficiency, 343–345
 - ring-cusp ion thruster, ion confinement, 110–116
- Antenna design, radiofrequency (rf) ion thrusters, 151–158
- Aperture design, ion thruster accelerator grid:
 - alignment and expansion, 207–208
 - diameter calculations, 190–194
- Arakawa/Yamada model, primary electron motion and ionization, 176–182
- Arc initiation:
 - hollow cathode operation, 310–315
 - ion thruster accelerator grid:
 - electrodes, hold-off and conditioning, 224
 - high-voltage parameters, 217–218
- Arcjet, basic properties, 4

- Arrhenius temperature dependence, hollow cathodes, barium depletion model, 299–302
- Atmospheric Emissions Photometric Imaging (AEPI), plume plasma optical emission, 419–422
- Atomic mass units (AMU), ion mass, 447
- Atom sputtering rate:
 - hollow cathodes, barium loss rates, 295–296
 - ion thruster accelerator grid, barrel erosion, 231–232
- Avogadro's number, 447
- Axial electric field, Hall thrusters, 326–329
- Axial magnetic field, radiofrequency (rf) ion thrusters, 149–158
- Axial plasma density, hollow cathode:
 - insert region plasma, 264–270
 - plume-region plasma, 286–292
- Axial scale length, Hall thruster operation, 329–330
- Azimuthal drift:
 - Hall thrusters, 327–328
 - operating principles, 332–333
 - oscillations, 376–379
- Background density, plume emissions, neutral gas plumes, 407–408
- Backstreaming limit, ion thruster accelerator grid, 213–216
- Barium depletion model, hollow cathodes:
 - lifetime analysis, 298–302
 - operation, 309–315
- Barium-oxide cathodes:
 - insert plasmas, evaporation analysis, 293–296
 - thermionic electron emission, 252–255
- Barometric law:
 - fluid plasma, momentum conservation, 48
 - hybrid Hall thruster models, magnetic field transport, 369
 - primary beam expansion plume models, 406–407
- Barrel erosion, ion thruster accelerator grid, lifetime analysis, 225–235
- Beam current:
 - discharge loss, 126–133
 - ion thruster plasma generator design, 96–100
 - ring-cusp ion thruster models, density calculations, 119–120
- Beam divergence:
 - Hall thruster efficiency, 343–345
 - ion thruster efficiency, 29
 - thrust properties, 23–24
- Beam plasma potential, ion thruster accelerator grid, electron backstreaming, 209–216
- Beam/plume characteristics, electrical thrusters, 9–10
- Beam power, thruster efficiency, 30
- Beam steering, ion thruster accelerator grid expansion and alignment, 207–208
- Beam utilization efficiency, dielectric-wall Hall thruster efficiency, 343, 361–362
- Bessel functions, Fick's law, 64–65
- Bias voltage, accelerator grid, 208–216
- Bohm current:
 - discharge chamber, power and energy balance, 125–126
- Hall thrusters:
 - dielectric-wall Hall thruster efficiency, 360–362
 - dominant power-loss mechanisms, 348–357
 - hollow cathodes, insert region plasma, 260–270
 - ion thruster plasma generator design, 93–100
 - radiofrequency (rf) ion thrusters, 153–158
 - ring-cusp ion thruster models, ion confinement, 111–116
- Bohm diffusion:
 - hybrid Hall thruster models, transverse electron transport, 368–369
- Kaufman ion thrusters, 142–147
- with magnetic fields, 69–71
- pre-sheath potential, 78–79
- Bohm sheath criterion:
 - plasma boundary sheaths, 82–84
 - pre-sheath potential, 79
 - summary of, 86–88
- Bohm velocity:

- Hall thrusters, dominant power-loss mechanisms, 351–357
- ion thruster plasma generator design, 95–100
- primary beam expansion plume models, 404–407
- Boltzmann's constant:
 - Debye plasma boundary sheaths, 74–75
 - electrical thruster density and ingestion, 32–34
 - hollow cathodes, barium depletion model, 299–302
 - hybrid Hall thruster models, magnetic field transport, 369
 - plasma boundary sheaths, 87–88
 - plasma physics, particle energies and velocities, 44–46
 - pre-sheath potential, 77–79, 78–79
- Boris-type particle-pushing algorithm, primary electron motion and ionization, 176–182
- Boron nitride, Hall thrusters, dominant power-loss mechanisms, 349–357
- Boundary sheaths, plasma physics, 71–88
 - Child-Langmuir sheaths, 79–81
 - Debye sheaths, 73–75
 - double sheaths, 84–86
 - generalized sheath solution, 81–84
 - pre-sheaths, 76–79
 - summary of effects, 86–88
- Breathing mode oscillations, Hall thrusters, 377–379
- Bulk-material insert life, hollow cathodes, 302–304
- Carbon-carbon composite materials, ion thruster accelerator grid electrodes, 221–223
 - hold-off and conditioning, 224
- Cathode common potential:
 - Hall thruster potential and current distributions, 337–341
 - plume emissions, solar array interactions, 416–418
- Cathode efficiency, Hall thruster performance, 341–345
- Cathode pressure estimates, 463–466
- Centripetal force, plasma physics, single particle motions, 40–43
- CEX-2D optics code, ion thruster accelerator grid trajectories, 200–204
- Channel physics, hall thruster, 365–379
 - hybrid models, 366–372
 - continuity and energy, 369–371
 - ion current, 371–372
 - magnetic field transport, 369
 - transverse electron transport, 366–369
 - lifetime analysis, 379–383
 - oscillations, 376–379
 - steady-state models, 372–376
- Channel plasma, dielectric-wall Hall thruster efficiency, 362–365
- Charge density, fluid plasma particle conservation, 49–51
- Charged particle collisions, partially ionized gas diffusion, 55–60
- Charge-exchange (CEX) reactions:
 - hollow cathodes:
 - insert region plasma, 257–270
 - orifice region plasma, 271–280
 - ion thruster accelerator grid:
 - barrel erosion, 230–232
 - erosion models, 227–229
 - lifetime analysis, 225–235
 - pits-and-grooves erosion, 232–235
 - particle collisions, 57–60
 - plume emissions, 395
 - neutral gas plumes, 407–408
 - secondary-ion generation, 408–410
- Chemical-vapor-deposition (CVD), ion thruster accelerator grid electrodes, carbon-carbon composite materials, 221–223
- Child-Langmuir law:
 - ion thruster accelerator grid, perveance limit, 205–206
 - plasma boundary sheaths, 79–84, 88
- Classical diffusion, with magnetic fields, 66–71
- Clausius factor:
 - discharge chamber neutral and primary densities, 120–124
 - electrical thruster density and ingestion, 34
 - ion thruster accelerator grid, 230–232
 - Monte Carlo, 483–486

- Clustering factor (*cont.*)
 radiofrequency (rf) ion thrusters, 157–158
- Closed-drift thruster, 328–329
- Cold gap, ion thruster accelerator grid expansion and alignment, 206–208
- Collisionality parameter:
 discharge chamber neutral and primary densities, 122–124
 electron relaxation and thermalization times, 479–482
 hollow cathodes, insert region plasma, 256–270
 microwave ion thrusters, 163–171
 radiofrequency (rf) ion thrusters, 150–158
- Collision frequency, hybrid Hall thruster models, transverse electron transport, 368–369
- Collisions, partially ionized gas diffusion, 55–60
- Collision transfer momentum, fluid plasma, conservation of, 47–48
- COMETS satellite, ion thrusters, 429–440
- Communications satellites, flight ion thrusters, 431–440
- Conductance correction factor, electrical thruster density and ingestion, 33–34
- Confinement factor, discharge loss, 128–133
- Contamination, plume emissions, spacecraft interactions, 413–415
- Continuity equations:
 fluid plasma:
 energy conservation, 52–54
 particle conservation, 48–51
 hybrid Hall thruster models, 369–371
- Convective derivative, fluid plasma, momentum conservation, 47–48
- Cosine distribution, plasma physics, particle energies and velocities, 45–46
- Coulomb collision, particle collisions, 58–60
- Coulomb-transfer rating, ion thruster accelerator grid, 217–218
 molybdenum electrodes, 219–221
- Coupling voltages, hollow cathode operation, 311–315
- Cross-field diffusion coefficient:
 Kaufman ion thrusters, 142–147
 magnetic field diffusion, 69–71
 primary electron motion, 178–182
- Cross-field electron transport:
 Hall thruster operation, 330–333
 hybrid Hall thruster models, 368–369
- Cross-over values, Hall thrusters, dominant power-loss mechanisms, 350–357
- Current cutback, recycling behavior, 139–141
- Current density:
 Child-Langmuir sheaths, 79–81
 hollow cathode geometry, 249–251
 plume measurements, 398–400
- Current distribution, Hall thruster operation, 337–341
- Current fractions:
 discharge loss, 127–133
 microwave ion thrusters, 166–171
 radiofrequency (rf) ion thrusters, 152–158
- Current utilization efficiency, Hall thruster, multiply charged ion corrections, 346–347
- Current-versus-voltage predictions, hybrid ion thrusters, steady-state equations, 372–376
- Cutoff frequencies, microwave ion thrusters, 161–171
- Cyclotron frequency, plasma physics, single particle motions, 39–43
- Debye sheaths:
 floating potential, 87–88
 plasma boundary sheaths, 73–75
 thickness properties, 83–84
- Deep Space missions, 3
 flight ion thrusters, 431–440
- Density gradient:
 hybrid Hall thruster models, magnetic field transport, 369
 Kaufman ion thrusters, 145–147
- Depletion life models, dispenser cathodes in insert plasmas, 293–296
- Diagnomagnetic drift, magnetic field diffusion, 68–71
- Dielectric discharge, radiofrequency (rf) ion thrusters, 157–158

- Dielectric materials, Hall thrusters, 325–329
- Dielectric-wall Hall thrusters:
 - dominant power-loss mechanisms, 347–357
 - efficiency of, 359–362
 - ionization length and scaling, 335–337
 - lifetime analysis, 380–383
 - metallic-wall comparisons with, 364–365
 - operation, 331–333
- Diffusion coefficient:
 - ambipolar diffusion, 65–66
 - hollow cathodes, orifice region plasma, 271–280
- Diffusion-driven particle motion:
 - with magnetic fields, 66–71
 - without magnetic fields, 60–66
 - partially ionized gases, 55–71
- Diffusion equation, Fick's law, 61–65
- Diffusion thickness, ring-cusp ion thruster models, 114–116
- Direct-current-discharge plasma generators:
 - basic principles, 91–93
 - ion thruster, 100–107
 - anode wall ion confinement, 110–117
 - discharge chamber:
 - neutral and primary densities, 120–124
 - power and energy balance, 124–126
 - discharge loss, 126–133
 - discharge stability, 133–136
 - electron confinement, 108–110
 - excited neutral production, 117–120
 - generalized 0-D ring-cusp model, 102–105
 - magnetic multipole boundaries, 105–107
 - recycling behavior, 137–142
- Discharge chamber:
 - neutral and primary densities, 120–124
 - power and energy balance, 124–126
 - recycling behavior, 137–141
 - two-dimensional models, 171–182
 - neutral atom model, 172–175
 - performance valuation, 179–182
 - primary electron motion and ionization, 176–179
- Discharge current:
 - Hall thruster:
 - performance efficiency, 342–345
 - potential and current distributions, 339–341
 - hollow cathode geometry, 246–248
 - barium depletion model, 301–302
 - bulk material insert life, 302–304
 - orifice region plasma, 275–280
- Discharge loss:
 - direct-current-discharge plasma generators, 126–133
 - Hall thruster performance, dominant power-loss mechanisms, 347–357
 - ion thruster plasma generator design, 96–100
 - Kaufman ion thrusters, 144–147
 - microwave ion thrusters, 167–171
 - radiofrequency (rf) ion thrusters, 154–158
- Discharge stability, 133–137
- Discharge voltage:
 - Hall thruster, efficiency, 342–345
 - hollow cathode operation, 312–315
 - Kaufman ion thrusters, 147
- Dispenser cathodes:
 - barium depletion model, 298–302
 - insert plasmas, lifetime analysis, 293–296
 - poisoning of, 304–306
- Dispersion relation, microwave ion thrusters, 161–162
- Dissipated power, basic principles, 30–32
- Distribution function, plasma physics,
 - particle energies and velocities, 44–46
- Divergent magnetic field thruster, direct-current-discharge plasma generators, 101–107
- Dominant power-loss mechanisms, Hall thruster performance, 347–357
 - dielectric-wall Hall thruster efficiency, 359–362
- Double ion generation:
 - Hall thruster efficiency, 343–345
 - ring-cusp ion thruster models, neutral ionization/excitation, 119–120
 - two-dimensional discharge chamber models, 180–182
- Double sheaths:
 - hollow cathodes:
 - insert region plasma, 256–270
 - plume-region plasma, 287–292

- Double sheaths (*cont.*)
 - plasma boundaries, 84–86
- Double-to-single ion content, computation of, 26–27
- Downstream reference electron density, ion thruster accelerator grid trajectories, 201–204
- Drift velocity, hollow cathode geometry, 246–248

- Efficiency, Hall thruster performance models, 341–345
 - dielectric walls, 359–362
- Electrical efficiency, thruster design, 27–30
- Electrical propulsion (EP):
 - defined, 1–2
 - early applications of, 2–3
 - electrical thruster types, 3–5
 - historical background, 2–3
- Electrical thrusters:
 - beam/plume characteristics, 9–10
 - efficiency, 27–30
 - force transfer, 18–21
 - neutral densities and ingestion, 32–34
 - power dissipation, 30–32
 - rocket equation, 15–18
 - specific impulse, 25–27
 - thrust force, 21–24
 - types of, 3–4
- Electric Propulsion Interactions Code (EPIC), plume emissions:
 - measurement, 398
 - sputtering and contamination, 415
- Electric thrusters, plume emissions, 394–395
- Electrode breakdown, ion thruster accelerator grid high-voltage parameters, 217–218
- Electromagnetic thrusters, basic properties, 21
- Electron backstreaming, ion thruster accelerator grid, 208–216
- Electron bombardment:
 - direct-current-discharge plasma generators, 91–93
 - Hall thrusters, dominant power-loss mechanisms, 347–357
- Electron-bombardment Ion Thruster Assembly (EITA), flight ion thrusters, 434–440
- Electron confinement:
 - ion thruster plasma generator design, 98–100
 - 0-D ring-cusp model, 108–110
- Electron cyclotron resonance heating, microwave ion thrusters, 162–171
- Electron distribution, ion thruster plasma generator design, 94–100
- Electron-electron collision frequency, particle collisions, 58–60
- Electron energy equation:
 - hollow cathode, plume-region plasma, 285–292
 - hybrid Hall thruster models, 370–371
- Electron energy loss, 467–469
- Electron flux, plasma physics, particle energies and velocities, 45–46
- Electron heating, hollow cathodes, 247–248
- Electron-ion collision frequency, particle collisions, 58–60
- Electron-neutral collisions, 60
 - microwave ion thrusters, 164–171
- Electron relaxation times, 479–482
- Electron temperature:
 - discharge chamber neutral and primary densities, 121–124
- Hall thrusters:
 - dominant power-loss mechanisms, 348–357
 - plasma electron temperature, 357–359
- hollow cathode, plume-region plasma, 286–292
- hollow cathodes:
 - insert region plasma, 257–270
 - orifice region plasma, 273–280
- ion thruster plasma generator design, 96–100
- microwave ion thrusters, 167–171
- primary beam expansion plume models, 406–407
- radiofrequency (rf) ion thrusters, 154–158
- Electrospray/field emission electric propulsion thruster, basic properties, 4–5
- Electrostatic force, ion and Hall thrusters, 20–21

- Emitted current, discharge chamber neutral and primary densities, 121–124
- Energy balance model:
 - discharge chamber, 124–126
 - hollow cathodes, insert region plasma, 259–270
 - hybrid Hall thruster models, 369–371
- Energy conservation, fluid plasma, 51–54
- Energy-loss mechanisms, ion thruster plasma generator design, 98–100
- Engineering Test Satellite (ETS), 3
 - flight ion thrusters, 429–440
- Erosion:
 - Hall thrusters, lifetime analysis, 380–383
 - hollow cathodes, keeper electrode wear and life, 306–309
 - ion thruster accelerator grid, 225–235
 - plume emissions, solar array interactions, 415–418
- Euler-Lagrange equations, primary electron motion and ionization, 176–182
- European Space Agency Artemis space craft, flight ion thrusters, 434–440
- European Space Agency (Small Mission for Advanced Research in Technology), flight ion thrusters, 440–443
- Excitation cross section:
 - particle collisions, 57–60
 - radiofrequency (rf) ion thrusters, 152–158
 - ring-cusp ion thruster models, 117–120
 - xenon, 471–474
- Excitation reaction rate coefficient:
 - Hall thrusters, plasma electron temperature, 358–359
 - ion thruster plasma generator design, 97–100
 - xenon Maxwellian plasmas, 475–477
- Excited neutral ion production, ring-cusp ion thruster models, 117–120
- Extended life test (ELT):
 - hollow cathodes:
 - barium depletion model, 301–302
 - orifice region plasma, 280–281
 - ion thruster accelerator grid:
 - backstreaming limit calculations, 215–216
 - keeper erosion, 306–307
 - pits-and-grooves erosion, 233–235
- Fick's law:
 - diffusion equation and, 61–65
 - magnetic field diffusion, 68–71
- Field emission electric propulsion (FEEP) thrusters, basic properties, 4–5
- Flatness parameter:
 - discharge chamber power and energy balance, 126
 - ion thruster accelerator grid:
 - barrel erosion, 231–232
 - electron backstreaming, 216
- Flight data, plume emissions, 396–398
- Flight thrusters:
 - Hall thrusters, 440–443
 - ion thrusters, 429–440
- Floating potential, plasma boundary sheaths, 87–88
- Fluid plasma, 46–54
 - energy conservation, 51–54
 - momentum conservation, 46–48
 - particle conservation, 48–51
- Force transfer, ion and Hall thrusters, 18–21
- Fourier transform, ring-cusp ion thruster models, magnetic multipole boundaries, 106–107
- Fowler-Nordheim plot, ion thruster accelerator grid electrodes, hold-off and conditioning, 224
- Frictional contributions, fluid plasma energy conservation, 53–54
- Gap dimensions, ion thruster accelerator grid expansion and alignment, 206–208
- Gas flow rate:
 - Hall thruster efficiency, 341–345
 - hollow cathodes:
 - insert region plasma, 256–270
 - orifice region plasma, 276–280
 - unit conversions, 463–466
- Gaussian beam density, primary beam expansion plume models, 402–407
- Gauss's law, ion thruster accelerator grid, electron backstreaming, 211–216
- Geometric configuration, hollow cathodes, 248–251
 - insert region plasma, 256–270
- Geosynchronous satellites, plume emissions, 393–394

- Grid models, ion thruster accelerator
erosion, 227–229
- Hall current, Hall thrusters:
basic properties, 328–329
operation, 330–333
- Hall-effect thrusters (HETs), classification,
325
- Hall thruster:
basic properties, 4, 325–329
channel physics and numerical modeling,
365–379
hybrid models, 366–372
continuity and energy, 369–371
ion current, 371–372
magnetic field transport, 369
transverse electron transport,
366–369
lifetime analysis, 379–383
oscillations, 376–379
steady-state models, 372–376
efficiency measurements, 28–30
flight thrusters, 440–443
force transfer, 18–21
geometry, 6–9
lanthanum hexaboride cathodes, 254–255
lifetime analysis, 379–383
operating principles and scaling, 329–341
crossed-field structure and current,
330–333
ionization length, 334–337
potential and current distributions,
337–341
performance models, 341–365
dielectric wall efficiency, 359–362
dielectric wall vs. metallic wall
comparison, 364–365
dominant power loss mechanisms,
347–357
efficiency, 341–345
metallic wall TAL efficiency, 363
multiply charged ion correction,
345–347
plasma electron temperature, 357–359
plumes:
basic properties, 393–395
flight data, 396–398
laboratory measurements, 398–400
measurements, 395–396
natural gas plumes, 407–408
payload interactions, 418–422
microwave phase shift, 418–419
physical properties, 395–400
plasma optical emission, 419–422
primary beam expansion, 400–407
secondary-ion generation, 408–410
spacecraft interactions, 410–418
particle momentum, 412–413
solar arrays, 415–418
sputtering and contamination,
413–415
power dissipation, 32
thrust properties, 22–24
- Heat-exchange terms, fluid plasma energy
conservation, 52–54
- Helical electron motion, microwave ion
thrusters, 163–171
- High-frequency oscillations:
hollow cathode, plume-region plasma,
291–292
hollow cathodes, keeper electrode wear
and life, 307–309
- “High power” orbit insertion mode, flight
ion thrusters, 432–440
- High-temperature regions, Hall thrusters,
plasma electron temperature,
358–359
- High-voltage parameters, ion thruster
accelerator grid, 216–224
carbon-carbon composites, 221–223
electrode breakdown, 217–218
hold-off and conditioning, 224
molybdenum electrodes, 218–221
pyrolytic graphite, 223
- Hold-off behavior, ion thruster accelerator
grid electrodes, 224
- Hollow cathodes:
configurations, 248–251
geometric properties, 244–245
historical overview, 243–248
insert region plasma, 256–270
keeper electrode wear and life, 306–309
lifespan testing, 292–306
barium depletion model, 298–302
bulk-material inserts, 302–304
inert plasma, dispenser cathodes,
293–296
poisoning, 304–306

- temperature characteristics, 296–298
 - operating principles, 309–315
 - orifice region plasma, 270–281
 - plume-region plasma, 283–292
 - thermal models, 281–283
 - thermionic electron emitter, 251–255
- Hot gap, ion thruster accelerator grid
 - expansion and alignment, 206–208
- Hybrid two-dimensional ion thruster
 - models, flow diagram, 172–173
- Idealized design, ion thruster plasma
 - generator, 93–100
- Incident flux, Hall thruster ionization length
 - and scaling, 334–337
- Inductive plasma discharge, radiofrequency (rf) ion thrusters, 151–158
- Inert gas propellants, ring-cusp ion thruster
 - models, neutral ionization/excitation, 118–120
- In-flight measurements, plume emissions, 396–398
- Ingestion, electrical thrusters, 32–34
- Input power calculations, Hall thrusters,
 - plasma electron temperature, 357–359
- Insert region plasma, hollow cathodes, 256–270
- Insert temperatures, hollow cathode
 - lifetimes, 296–298
- Ion acoustic velocity:
 - discharge chamber power and energy balance, 126
 - fluid plasma particle conservation, 51
 - Hall thrusters, plasma electron temperature, 357–359
 - hollow cathodes, insert region plasma, 258–270
 - radiofrequency (rf) ion thrusters, 156–158
- Ion beam current:
 - ion thruster plasma generator design, 94
 - plume plasma optical emission, 420–422
- Ion bombardment:
 - Hall thrusters:
 - dominant power-loss mechanisms, 347–357
 - lifetime analysis, 379–383
 - hollow cathodes:
 - barium depletion model, 298–302
 - keeper electrode wear and life, 306–309
 - orifice region plasma, 279–280
- Ion charge number:
 - ion thruster accelerator grid, electron backstreaming, 212–216
 - particle collisions, 58–60
- Ion confinement:
 - microwave ion thrusters, 168–171
 - radiofrequency (rf) ion thrusters, 156–158
 - ring-cusp ion thruster models, 110–116
- Ion conservation equation, Hall thruster
 - oscillations, 376–379
- Ion continuity equations, primary beam
 - expansion plume models, 401–407
- Ion current:
 - hollow cathodes, insert region plasma, 261–270
 - hybrid Hall thruster models, 371–372
- Ion density:
 - Hall thrusters, dominant power-loss mechanisms, 351–357
 - hollow cathodes, insert region plasma, 258–270
 - ion thruster accelerator grid trajectories, 201–204
- Ion distribution function, hybrid Hall thruster, ion current, 371–372
- Ion energy distribution, hollow cathodes,
 - keeper electrode wear and life, 307–309
- Ion exhaust velocity, thrust properties, 22–24
- Ion flux:
 - Hall thrusters:
 - dominant power-loss mechanisms, 354–357
 - lifetime analysis, 380–383
 - hybrid Hall thruster models, transverse electron transport, 367–369
 - plume emissions, 396–398
- Ion generation rate, ion thruster accelerator
 - erosion, 228–229
- Ion heating, hollow cathodes, 247–248
- Ion-ion collision frequency, particle
 - collisions, 58–60

- Ionization cross sections, 471–474
- Ionization energy loss, hybrid Hall thruster models, 370–371
- Ionization potential, discharge chamber power and energy balance, 125–126
- Ionization reaction rates, xenon Maxwellian plasmas, 475–477
- Ionization region:
 - discharge chamber model, 172–182
 - two-dimensional models, 176–182
 - Hall thruster operation, 334–337
 - hollow cathodes:
 - orifice region plasma, 272–280
 - plume-region plasma, 285–292
 - ion thruster plasma generator design, 93–100
 - Kaufman ion thrusters, 146–147
 - radiofrequency (rf) ion thrusters, 152–158
- Ion Larmor radius, Hall thruster operation, 331–333
- Ion plasma density, two-dimensional discharge chamber models, 180–182
- Ion production cost, ion thruster accelerator grid, backstreaming limit calculations, 213–216
- Ion source term, primary electron motion and ionization, 177–182
- Ion thrusters:
 - accelerator grid:
 - accelerator basics, 196–200
 - basic properties, 189–190
 - configurations, 190–196
 - electron backstreaming, 208–216
 - high-voltage considerations, 216–224
 - carbon-carbon composite materials, 221–223
 - electrode breakdown, 217–218
 - hold-off and conditioning, 224
 - molybdenum electrodes, 218–221
 - pyrolytic graphite, 223
 - lifespan, 225–235
 - barrel erosion, 230–232
 - grid models, 227–229
 - pits-and-grooves erosion, 232–235
 - optics, 200–208
 - grid expansion and alignment, 206–208
 - ion trajectories, 200–204
 - perveance limits, 204–206
 - flight thrusters, 429–440
 - plasma generators:
 - basic properties, 4, 91–93
 - DC electron-discharge system, 100–102
 - discharge chamber:
 - neutral and primary densities, 120–124
 - power and energy balance, 124–126
 - two-dimensional computer models, 171–182
 - discharge loss, 126–133
 - discharge stability, 133–137
 - electron confinement, 108–110
 - excited neutral production, 117–120
 - force transfer, 18–21
 - geometry, 6–7
 - idealized design, 93–100
 - ion confinement, 110–116
 - Kaufman ion thrusters, 142–147
 - magnetic multipole boundaries, 105–107
 - microwave ion thrusters, 158–171
 - particle collisions, 56–60
 - performance efficiency, 27–30
 - power dissipation, 30–32
 - radiofrequency ion thrusters, 148–158
 - recycling behavior, 137–142
 - 0-D ring-cusp model, 102–105
 - limitations, 141–142
 - plumes:
 - basic properties, 393–395
 - flight data, 396–398
 - laboratory measurements, 398–400
 - measurements, 395–396
 - neutral gas plumes, 407–408
 - payload interactions, 418–422
 - microwave phase shift, 418–419
 - physical properties, 395–400
 - plasma optical emission, 419–422
 - primary beam expansion, 400–407
 - secondary-ion generation, 408–410
 - spacecraft interactions, 410–418
 - particle momentum, 412–413
 - solar arrays, 415–418
 - sputtering and contamination, 413–415

- Japan Aerospace Exploration Agency (JAXA), flight ion thrusters, 435–440
- Jet power, thrust properties, 21–24
- Kaufman ion thruster:
 - basic properties, 142–147
 - direct-current-discharge plasma generators, 102
 - flight ion thrusters, 434–440
- Keeper electrodes:
 - bias voltage, discharge loss, 127–133
 - Hall thruster performance efficiency, 342–345
 - hollow cathodes:
 - geometry, 246–248
 - operating principles, 309–315
 - lifetime analysis, 306–309
- Knudsen-flow models, discharge chambers, 173–175
- Laboratory plume measurements, 398–400
- Lagrangian algorithm, primary beam expansion plume models, 405–407
- Landau damping, fluid plasma energy conservation, 54
- Langmuir condition:
 - hollow cathode, plume-region plasma, 287–292
 - plasma double sheaths, 85–86
- Langmuir probe, plume emissions, solar array interactions, 416–418
- Lanthanum hexaboride:
 - Hall thrusters, lifetime analysis, 379–383
 - hollow cathodes:
 - bulk material insert life, 302–304
 - poisoning of, 305–306
 - thermionic electron emission, 254–255
- Larmor radius:
 - Hall thruster operation, crossed-field structure and the Hall current, 330–333
 - Kaufman ion thrusters, 143–147
 - microwave ion thrusters, 163–171
 - plasma physics, single particle motions, 40–43
 - 0-D ring-cusp model, electron confinement, 108–110
- Lattice atoms, hollow cathodes, barium loss rates, 294–296
- Life demonstration test (LDT), hollow cathodes:
 - barium depletion model, 298–302
 - bulk-material inserts, 302–304
 - inert plasma, dispenser cathodes, 293–296
 - insert life analysis, 292–306
 - orifice region plasma, 279–281
 - poisoning, 304–306
 - temperature characteristics, 296–298
- Lifetime analysis:
 - extended life test:
 - hollow cathodes:
 - barium depletion model, 301–302
 - orifice region plasma, 280–281
 - ion thruster accelerator grid:
 - backstreaming limit calculations, 215–216
 - pits-and-grooves erosion, 233–235
 - Hall thrusters, 379–383
 - hollow cathodes:
 - barium depletion model, 298–302
 - bulk material inserts, 304–306
 - keeper electrodes, 306–309
 - thermionic electron emission, 255
 - inert plasmas, dispenser cathodes, 293–296
 - ion thruster accelerator grid, 225–235
 - barrel erosion, 230–232
 - grid models, 227–229
 - pits-and-grooves erosion, 232–235
- Linearization, fluid plasma particle conservation, 49–51
- Lorentz equation, two-dimensional discharge chamber model, primary electron motion and ionization, 176–182
- Lorentz force:
 - fluid plasma, momentum conservation, 46–48
 - ion and Hall thrusters, 20–21
 - plasma physics, single particle motions, 39–43
- Loss rates, barium cathodes, lifetime analysis, 293–296
- Low-frequency oscillation, Hall thruster, 377–379

- Mach number, hollow cathode, plume-region plasma, 286–292
- Magnetic field electron transport, hybrid Hall thruster models, 369
- Magnetic-layer thrusters, classification, 325
- Magnetic mirror, plasma physics, single particle motions, 43
- Magnetic multipole boundaries, ion thruster plasma generators, 0-D ring-cusp model, 105–107
- Magnetized electrons, Hall thruster operation, 331–333
- Magnetoplasmadynamic (MPD) thruster, basic properties, 5
- Mass-conservation equations, fluid plasma particle conservation, 48–51
- Mass ratio, plasma boundary sheaths, 72–73
- Mass utilization efficiencies:
 - dielectric-wall Hall thrusters, 361–362
 - discharge chamber neutral and primary densities, 120–124
 - discharge loss, 131–134
 - Hall thruster:
 - ionization length and scaling, 336–337
 - performance models, 343–345
 - Hall thruster operation, 334–337
 - ion thruster plasma generator design, 98–100
 - microwave ion thrusters, 167–171
 - radiofrequency (rf) ion thrusters, 156–158
 - recycling behavior, 139–141
- Maximum magnetic field strength, ring-cusp ion thruster models, ion confinement, 114–116
- Maxwellian distribution:
 - discharge loss, 127–133
 - discharge stability, 134–137
 - Hall thrusters, dominant power-loss mechanisms, 348–357
 - hollow cathodes:
 - insert region plasma, 256–270
 - keeper electrode wear and life, 309
 - ionization/excitation reactions, 475–477
 - ion thruster accelerator grid trajectories, 201–204
 - electron backstreaming, 209–216
 - microwave ion thrusters and, 166–171
 - radiofrequency (rf) ion thrusters, 151–158
 - ring-cusp ion thruster models, 117–120
 - Maxwellian electron “field particles,” 479–482
- Maxwell’s equations:
 - Debye plasma boundary sheaths, 73–75
 - fluid plasma particle conservation, 48–51
 - ion thruster plasma generator design, electron velocity distribution function, 94–100
 - microwave ion thrusters, 159–160
 - plasma physics, 38–39
 - particle energies and velocities, 44–46
- Maxwell three-dimensional magnetic field solver, ring-cusp ion thruster models, 107
- Mean collision time, discharge chamber neutral and primary densities, 122–124
- Mean confinement time:
 - electron confinement, 108–110
 - ion thruster plasma generator design, 95–100
- Mean free path calculations:
 - Hall thrusters, ionization length and scaling, 335–337
 - hollow cathode:
 - barium depletion model, 300–302
 - plume-region plasma, 285–292
 - particle collisions, 56–60
- Mean ion free path, hollow cathodes, orifice region plasma, 272–280
- Metallic-wall Hall thrusters:
 - dielectric-wall Hall thruster comparison with, 364–365
 - lifetime analysis, 383
 - thruster with anode layer (TAL), 363
- Microwave ion thrusters, 158–171
- Microwave phase shift, plume-payload interactions, 418–419
- Miniature Xenon Ion Thruster (MiXI), 439–440
- Mirror ratio, microwave ion thrusters, 168–171
- Mobility, non-magnetic field diffusion, 60–66
- Molybdenum electrodes, ion thruster accelerator grid, 218–221

- barrel erosion, 231–232
- hold-off and conditioning, 224
- Momentum conservation, fluid plasma, 46–48
- Momentum equation:
 - plume emissions:
 - primary beam expansion models, 400–407
 - spacecraft interactions, 412–413
 - primary electron motion and ionization, 177–182
- Momentum-transferring collision
 - frequency, hybrid Hall thruster models, transverse electron transport, 367–369
- Mono-energetic primary electrons, ion thruster plasma generators, 0-D ring-cusp model, 104–105
- Monte-Carlo calculations:
 - Clausing factor, 483–486
 - discharge chamber models, 174–182
 - radiofrequency (rf) ion thrusters, 157–158
 - two-dimensional discharge chamber model, primary electron motion and ionization, 176–182
- Multi-dimensional modeling, discharge chamber, 171–182
- Multiply charged ion correction, Hall thruster performance, 345–347
- MUSES-C ECR thruster, 170–171
- NASA Evolutionary Xenon Thruster (NEXT), flight ion thrusters, 437–440
- NASA Glenn Research Center (GRC), flight ion thrusters, 435–440
- NASA-173Mv Hall thruster:
 - basic properties, 329
 - performance efficiency, 344–345
- NASA Solar Electric Propulsion Technology Applications Readiness (NSTAR):
 - direct-current-discharge plasma generators, 102
 - discharge chamber models, 174–182
 - discharge loss, 131–133
 - electron backstreaming, 210–216
 - flight ion thruster, 430–440
 - hollow cathodes:
 - barium depletion model, 301–302
 - insert region plasma, 256–270
 - keeper electrode wear and life, 307–309
 - orifice region plasma, 271–280
 - thermal models, 281–283
 - lifetime analysis, 226–235
 - barrel erosion, 230–232
 - insert temperatures, 297–298
 - perveance limit, 205–206
 - plume emissions flight data, 396–398
 - primary electron motion and ionization, 176–182
 - ring-cusp ion thruster models, ion confinement, 116
 - throttle table, 432
 - two-dimensional discharge chamber model, 179–182
- Net flux calculations:
 - Hall thrusters, dominant power-loss mechanisms, 354–357
 - hollow cathodes, barium loss rates, 295–296
- Neutral atom model, discharge chamber, 172–175
- Neutral gas density:
 - discharge chambers, 120–124
 - two-dimensional models, 174–182
 - electrical thrusters, 32–34
 - Hall thruster operation, 334–337
 - hollow cathode, 249–251
 - insert region plasma, 263–270
 - orifice region plasma, 276–280
 - plume-region plasma, 283–292, 285–292
 - ion thruster accelerator grid, erosion models, 227–229
 - ion thruster plasma generator design, 94
 - microwave ion thrusters, 167–171
 - plume emissions, 407–408
 - plume plasma optical emission, 420–422
 - radiofrequency (rf) ion thrusters, 149–158
 - recycling behavior, 137–141
 - view-factor model, 172–182
- Neutral gas excitation, ion thruster plasma generator design, 93–100

- Neutral gas temperatures, discharge stability, 133–137
- Neutral ion production:
 - hybrid Hall thruster models, continuity and energy, 369–371
 - ring-cusp ion thruster models, 117–120
- Neutral particle conservation equation, Hall thruster oscillations, 376–379
- Neutral particle velocity:
 - Hall thruster:
 - ionization length and scaling, 334–337
 - oscillations, 377–379
 - hollow cathode, orifice region plasma, 276–280
- Newton's second law, ion and Hall current force, 20–21
- Nomenclature table, 447–448
- Non-contact temperature measurement, hollow cathode lifetimes, 296–298
- Non-magnetic diffusion and mobility, partially ionized gases, 60–66
 - ambipolar diffusion, 65–66
 - Fick's law, 61–65
- Non-Maxwellian distribution function:
 - discharge loss, 132–133
 - hybrid ion thrusters, steady-state equations, 374–376
 - ion thruster plasma generator design, 100
- Non-uniform plasmas, 0-D ring-cusp model, 141–142
- North-south station keeping, plume emissions, 393–394
- Nuclear Electric Xenon Ion Thruster System (NEXIS):
 - discharge loss, 130–134
 - flight ion thrusters, 437–440
 - hollow cathode geometry, 245–248
 - barium depletion model, 301–302
 - plume-region plasma, 283–292
 - hollow cathodes, insert region plasma, 262–270
 - ion thruster accelerator grid, electron backstreaming, 216
 - plume emissions, sputtering and contamination, 413–415
 - primary beam expansion plume models, 405–407
 - recycling behavior, 139–141
 - ring-cusp ion thruster models, 107
 - electron confinement, 109–110
- Numerical modeling, Hall thruster, 365–379
 - hybrid models, 366–372
 - continuity and energy, 369–371
 - ion current, 371–372
 - magnetic field transport, 369
 - transverse electron transport, 366–369
 - lifetime analysis, 379–383
 - oscillations, 376–379
 - steady-state models, 372–376
- Ohmic heating, particle collisions, 59–60
- Ohm's law:
 - hollow cathode, insert region plasma, 269–270
 - hybrid Hall thruster models, 366–372
 - transverse electron transport, 366–369
 - particle collisions, 59–60
- On-axis potentials:
 - electron backstreaming, ion thruster accelerator grid, 208–216
 - Hall thruster potential and current distributions, 338–341
- One-dimensional models:
 - Hall thrusters, 365–366
 - hollow cathodes, plume-region plasma, 283–292
 - hybrid Hall thrusters, steady-state equations, 372–376
- Optics codes, ion thruster accelerator grid, 200–208
 - barrel erosion, 230–232
 - grid expansion and alignment, 206–208
 - ion trajectories, 200–204
 - perveance limits, 204–206
 - pits-and-grooves erosion, 232–235
- Orifice dimensions, hollow cathode geometry, 248–251
 - orifice region plasma, 271–280
- Orifice heating, hollow cathodes, 247–248
- Oscillations:
 - fluid plasma particle conservation, 50–51
 - Hall thrusters, 376–379
 - hollow cathode operation, 313–315
 - Over-perveance, ion thruster accelerator grid trajectories, 202–204
- O-waves, microwave ion thrusters, 160–161

- Oxide cathodes, thermionic electron emission, 252–255
- Parallel electron velocity, microwave ion thrusters, 163–171
- Park's formula, primary beam expansion plume models, 405–407
- Partially ionized gas diffusion, plasma physics, 54–71
 - collisions, 55–60
 - diffusion and mobility, 60–66
 - ambipolar diffusion, 65–66
 - Fick's law, 61–65
 - with magnetic field diffusion, 66–71
 - ambipolar B particle diffusion, 69–71
- Particle conservation, fluid plasma, 48–51
- Particle energies and velocities:
 - ion thruster plasma generators, 0-D ring-cusp model, 103–105
 - Kaufman ion thrusters, 142–147
 - plasma physics, 43–46
- Particle gyration, plasma physics, 41–43
- Particle-in-cell (PIC) model:
 - Hall thruster, 365–366
 - ion current, 371–372
 - ion thruster accelerator grid trajectories, 202–204
 - plume emissions:
 - primary beam expansion models, 405–407
 - secondary-ion generation, 408–410
- Particle-pushing algorithm, primary electron motion and ionization, 176–182
- Particle simulation, two-dimensional discharge chamber model, 176–182
- Paschen breakdown mechanism, molybdenum electrodes, ion thruster accelerator grid, 219–221
- Path length calculations:
 - hollow cathodes:
 - insert region plasma, 256–270
 - orifice region plasma, 272–280
 - ion thruster accelerator grid, erosion models, 229
- Payload interactions, plume emissions, 418–422
 - microwave phase shift, 418–419
 - plasma optical emissions, 419–422
- Peak electron temperature, Hall thrusters, 358–359
- Penetration distance, particle collisions, 56–60
- Performance models:
 - discharge loss, 130–133
 - Hall thruster, 341–365
 - dielectric wall efficiency, 359–362
 - dielectric wall vs. metallic wall comparison, 364–365
 - dominant power loss mechanisms, 347–357
 - efficiency, 341–345
 - metallic wall TAL efficiency, 363
 - multiply charged ion correction, 345–347
 - plasma electron temperature, 357–359
 - ion thruster discharge chamber, two-dimensional models, 179–182
 - ion thruster plasma generator efficiency, 27–30
- Perpendicular electron mobility:
 - hybrid Hall thruster models:
 - continuity and energy, 369–371
 - transverse electron transport, 367–369
 - magnetic field diffusion, 67–71
- Perturbed electron current density, microwave ion thrusters, 160–161
- Perveance limit, ion thruster accelerator grid, 204–206
- Phillips type S thruster, hollow cathodes, thermionic electron emission, 252–255
- Pits and grooves erosion, ion thruster accelerator grid, lifetime analysis, 225–235
- Plasma ball definition, hollow cathode, plume-region plasma, 287–292
- Plasma contactors, plume emissions, 419–422
- Plasma currents, plume emissions, solar array interactions, 415–418
- Plasma density:
 - discharge chamber power and energy balance, 126
 - Fick's law, 62–65
 - Hall thruster operation, 333
 - hollow cathodes:
 - geometry, 245–251

- Plasma density (*cont.*)
- insert region plasma, 262–270
 - orifice region plasma, 273–280
 - oscillation patterns, 313–315
 - hybrid ion thrusters, steady-state equations, 374–376
 - ion thruster plasma generator design, 94–100
 - Kaufman ion thrusters, 144–147
 - microwave ion thrusters, 162–171, 165–171
 - plume emissions, 396–398
- Plasma electron temperature, Hall thrusters, 357–359
- Plasma frequency, fluid plasma particle conservation, 48–51
- Plasma generators, thruster efficiency, 27–30
- Plasma ion flux, hollow cathodes, barium loss rates, 295–296
- Plasma optical emission, plume-payload interactions, 419–422
- Plasma physics:
- boundary sheaths, 71–88
 - Child-Langmuir sheaths, 79–81
 - Debye sheaths, 73–75
 - double sheaths, 84–86
 - generalized sheath solution, 81–84
 - pre-sheaths, 76–79
 - summary of effects, 86–88
 - fluid plasma, 46–54
 - energy conservation, 51–54
 - momentum conservation, 46–48
 - particle conservation, 48–51
 - hollow cathodes:
 - insert region plasma, 256–270
 - orifice region plasma, 270–281
 - overview, 37–38
 - partially ionized gas diffusion, 54–71
 - collisions, 55–60
 - diffusion and mobility, 60–66
 - ambipolar diffusion, 65–66
 - Fick's law, 61–65
 - with magnetic field diffusion, 66–71
 - ambipolar B particle diffusion, 69–71
 - particle energies and velocities, 43–46
 - single particle motions, 39–43
- Plasma potential:
- discharge stability, 134–137
- Hall thrusters, dominant power-loss mechanisms, 354–357
- hollow cathodes:
- barium depletion model, 298–302
 - bulk-material insert life, 302–304
 - geometry, 245–248
 - keeper electrode wear and life, 307–309
 - ion thruster accelerator grid, electron backstreaming, 209–216
 - Kaufman ion thrusters, 144–147
 - microwave ion thrusters, 165–171
 - radiofrequency (rf) ion thrusters, 153–158
 - recycling behavior, 139–141
- Plasma regions, hollow cathode geometry, 243–248
- Plate-and-ball testing, molybdenum electrodes, ion thruster accelerator grid, 219–221
- Plume emissions:
- hollow cathode operation, 311–315
 - ion and Hall thrusters:
 - basic properties, 393–395
 - flight data, 396–398
 - laboratory measurements, 398–400
 - measurements, 395–396
 - natural gas plumes, 407–408
 - payload interactions, 418–422
 - microwave phase shift, 418–419
 - physical properties, 395–400
 - plasma optical emission, 419–422
 - primary beam expansion, 400–407
 - secondary-ion generation, 408–410
 - spacecraft interactions, 410–418
 - particle momentum, 412–413
 - solar arrays, 415–418
 - sputtering and contamination, 413–415
- Plume-region plasma, hollow cathodes, 283–292
- Poiseuille flow rate, hollow cathodes, orifice region plasma, 273–280
- Poisoning, hollow cathodes:
- lifetime analysis, 304–306
 - thermionic electron emission, 254–255
- Poisson's equation:

- Debye plasma boundary sheaths, 74–75
- electron backstreaming, ion thruster accelerator grid, 208–216
- force transfer, 18–21
- plume emissions, secondary-ion generation, 409–410
- Positive-going anode sheath:
 - discharge stability, 135–137
 - Hall thrusters, dominant power-loss mechanisms, 351–357
- Potential distribution, Hall thruster operation, 337–341
- Potential drop, ion thruster plasma generators, 0-D ring-cusp model, 103–105
- Power balance model:
 - Hall thrusters, plasma electron temperature, 357–359
 - hollow cathode, insert region plasma, 264–270
- Power dissipation:
 - basic principles, 30–32
 - discharge chamber energy balance, 124–126
- Power processing unit (PPU), flight ion thrusters, 431–440
- Power supplies:
 - direct-current-discharge plasma generators, 92–93
 - Hall thruster potential and current distributions, 340–341
 - ion thruster plasma generators:
 - electrode breakdown, 217–218
 - 0-D ring-cusp model, 105
- Predator-prey oscillations:
 - Hall thrusters, 377–379
 - hollow cathode operation, 313–315
- Pre-sheath potential, plasma boundary sheaths, 76–79
- Pressure gradient force:
 - fluid plasma, momentum conservation, 46–48
 - hollow cathodes, insert region plasma, 257–270
- Pressure increase, recycling behavior, 139–141
- Primary beam expansion, plume models, 400–407
- Primary electron densities:
 - discharge chambers, 120–124
 - two-dimensional models, 176–182
 - discharge loss, 132–133
 - discharge stability, 133–137
 - Hall thruster potential and current distributions, 339–341
 - ion thruster plasma generator design, 100
 - Kaufman ion thrusters, 145–147
 - 0-D ring-cusp model, 108–110
- Propellant flow rate:
 - ring-cusp ion thruster models, neutral ionization/excitation, 119–120
 - thruster efficiency, 28–30
- Propellant mass:
 - rocket equation, 17–18
 - thrust properties, 21–24
- Pulsed plasma thruster (PPT), 440–443
 - basic properties, 5
- Purity standards, hollow cathode poisoning and, 254–255
- Pyrolytic graphite, ion thruster accelerator grid electrodes, 223
- Quasi-neutral plasma:
 - boundary sheaths, 71–73
 - discharge chamber power and energy balance, 126
 - Hall thrusters, dominant power-loss mechanisms, 353–357
 - ion thruster plasma generator design, 95–100
 - radiofrequency (rf) ion thrusters, 152–158
- Radial confinement, microwave ion thrusters, 168–171
- Radial magnetic field thruster:
 - basic properties, 329
 - direct-current-discharge plasma generators, 101–107
 - ionization length and scaling, 335–337
- Radial plasma potential profile, hollow cathodes, keeper electrode wear and life, 308–309
- Radial velocity, primary beam expansion plume models, 402–407
- Radiation emissions, microwave ion thrusters, 165–171

- Radio-frequency Ion Thruster Assembly (RITA), flight ion thrusters, 434–440
- Radiofrequency (rf) ion thrusters (RIT):
 - basic properties, 148–158
 - flight ion thrusters, 437–440
- Randolph's formula, primary beam
 - expansion plume models, 405–407
- Reaction rate coefficient:
 - Hall thruster ionization length and scaling, 334–337
 - ion thruster plasma generator design, 96–100
 - particle collisions, 57–60
 - ring-cusp ion thruster models, neutral ionization/excitation, 118–120
- Recycling behavior, ion thruster design, 137–141
- Refractory metals, hollow cathodes, thermionic electron emission, 251–255
- Remote sensor unit (RSU), plume emissions, 396–398
- Resistivity, hollow cathode:
 - insert region plasma, 259–270
 - plume-region plasma, 290–292
- Resistojets, basic properties, 4
- Retarding potential analyzer (RPA) data,
 - plume emissions, 399–400
 - secondary-ion generation, 410
- Richardson coefficients, thermionic electron emission, hollow cathodes, 252–255
- Richardson-Dushman equation, thermionic electron emission, hollow cathodes, 251–255
- Ring-cusp thrusters, discharge chamber stability, 136–137
- Rocket equation, electric thrusters, 15–18
- Saddle-point magnetic field, ring-cusp ion thruster models, ion confinement, 115–116
- Samarium cobalt (SmCo) magnets,
 - microwave ion thrusters, 170–171
- Sapphire fiber optic probes, hollow cathode lifetime measurements, 297–298
- Scaling parameters, Hall thruster operation, 334–337
- Schottky effect, thermionic electron emission, hollow cathodes, 251–255
- Screen current-to-beam current ratio,
 - perveance limit, 205–206
- Screen supply, ion thruster plasma generators, 0-D ring-cusp model, 105
- Secondary electron temperature, two-dimensional discharge chamber model, 179–182
- Secondary electron yield:
 - dielectric-wall Hall thruster efficiency, 362–365
 - Hall thrusters, dominant power-loss mechanisms, 348–357
- Secondary ion measurements, plume emissions, 398, 408–410
- Self-heating mechanisms, hollow cathodes, 247–248
 - plume-region plasma, 283–292
- Sheath potentials, Hall thruster
 - performance, dominant power-loss mechanisms, 347–357
- Sheath voltage, hollow cathodes:
 - barium depletion model, 298–302
 - insert region plasma, 260–270
- Single particle motions, plasma physics, 39–43
- Slab geometry, Fick's law, 63–65
- SMART-1 mission, 3
- Solar arrays, plume emissions:
 - plasma interactions with, 415–418
 - spacecraft interactions, 411–418
- Solenoidal thrusters:
 - direct-current-discharge plasma generators, 101–107
 - radiofrequency (rf) ion thrusters, 155–158
- Space-charge-limited current flow, plasma double sheaths, 85–86
- Space charge-limited electron emission, Hall thrusters, dominant power-loss mechanisms, 352–357
- Spacecraft, rocket equation, 15–18
- Spacecraft interactions, plume emissions, 410–418
 - particle momentum, 412–413
 - solar arrays, 415–418
 - sputtering and contamination, 413–415

- Space Experiments with Particle Accelerators (SEPAC), plume plasma optical emission, 419–422
- Space Station Contactor (SSC) cathode:
 - barium depletion model, 301–302
 - lifetime measurements, 297–298
- Space Technology Experiment Satellite (STEX), flight thrusters, 440–443
- Specific impulse (Isp):
 - basic principles, 25–27
- Spot-knocking, ion thruster accelerator grid, molybdenum electrodes, 219–221
- Spot mode, hollow cathode operation, 311–315
- Sputtering yield:
 - Hall thrusters, lifetime analysis, 380–383
 - plume emissions, spacecraft interactions, 413–415
- Standard gas law, electrical thruster density and ingestion, 32–34
- Stationary plasma thrusters (SPTs):
 - classification, 325
 - dielectric-wall efficiency, 361–362
 - flight thrusters, 440–443
 - ionization length and scaling, 336–337
 - lifetime analysis, 380–383
 - performance efficiency, 344–345
 - plume emissions, sputtering and contamination, 414–415
 - plume emissions measurement, 398
 - steady-state equations, 372–376
- Stay-out zones, plume emissions, sputtering and contamination, 413–415
- Steady-state equations:
 - Fick's law and, 64–65
 - hollow cathode:
 - insert region plasma, 268–270
 - orifice region plasma, 272–280
 - plume-region plasma, 284–292
 - hybrid Hall thruster models, 372–376
 - ion current, 366–372
 - plume models, primary beam expansion models, 400–407
- Surface-accommodated ions, plume emissions, spacecraft interactions, 413
- Surface particle analysis, hollow cathodes, barium evaporation, 294–296
- Symbols table, 458–461
- Taylor series, pre-sheath potential, 77–79
- Temperature effects:
 - barium depletion model, 298–302
 - hollow cathodes:
 - bulk material insert life, 302–304
 - thermionic electron emission, 252–255
- Term definitions, 450–451
- Thermal conductivity, fluid plasma energy conservation, 52–54
- Thermal contributions, fluid plasma energy conservation, 53–54
- Thermal expansion, ion thruster accelerator grid, 206–208
- Thermalization, discharge chamber neutral and primary densities, 122–124
- Thermalization times, 479–482
- Thermalized potential, hybrid Hall thruster models, magnetic field transport, 369
- Thermal models, hollow cathodes, 281–283
- Thermionic electron emission, hollow cathodes, 251–255
 - poisoning effects, 304–306
- Three-dimensional models:
 - discharge chambers, 174–182
 - primary electron motion and ionization, 176–182
- Threshold voltage vs. gap measurements, ion thruster accelerator grid electrodes:
 - carbon-carbon electrodes, 222–223
 - molybdenum electrodes, 219–221
 - pyrolytic graphite, 223
- Thrust, basic properties of, 21–24
- Thrust-beam plasma potential, Hall thruster potential and current distributions, 338–341
- Thrust correction factor, 24
- Thruster mass utilization efficiency:
 - basic principles, 27–30
 - specific impulse, 25–27
- Thruster with anode layer (TAL):
 - basic properties, 326–329
 - dielectric-wall Hall thruster comparison with, 364–365
 - dominant power-loss mechanisms, 355–357
 - flight thrusters, 440–443
 - lifetime analysis, 3833

- Thruster with anode layer (TAL) (*cont.*)
 metallic-wall efficiency, 363
 Time dependent function:
 Fick's law, 62–65
 recycling behavior, 138–141
 Total collision frequency, Hall thruster
 operation, 331–333
 Total discharge power, dielectric-wall Hall
 thruster efficiency, 361–362
 Total energy flux, fluid plasma energy
 conservation, 51–54
 Total ion beam current:
 Hall thruster, multiply charged ion
 corrections, 346–347
 ring-cusp ion thruster models, density
 calculations, 119–120
 Total ion density, plume emissions,
 395–396
 Total plasma density, Hall thruster, multiply
 charged ion corrections, 346–347
 Total voltage effect, molybdenum
 electrodes, ion thruster accelerator
 grid, 219–221
 Trajectories, ion thruster accelerator grid,
 optics codes, 200–204
 Transverse electron transport, hybrid Hall
 thruster models, 366–369
 Transverse velocity:
 plasma physics, single particle motions,
 41–43
 ring-cusp ion thruster models, ion
 confinement, 111–116, 113–116
 Traveling-wave tubes (TWT), microwave
 ion thrusters, 170–171
 Trough contours, hollow cathode, plume-
 region plasma, 291–292
 Tungsten matrix, hollow cathodes,
 thermionic electron emission,
 252–255
 Two-dimensional models:
 Hall thrusters, 365–366
 hollow cathode:
 insert region plasma, 268–270
 plume-region plasma, 283–292
 thermal models, 281–283
 hybrid Hall thrusters, steady-state
 equations, 372–376
 ion thruster accelerator grid, electron
 backstreaming, 215–216
 ion thruster discharge chamber, 171–182
 neutral atom model, 172–175
 performance evaluation, 179–182
 primary electron motion and
 ionization, 176–179
 Ultraviolet photon, plume plasma optical
 emission, 420–422
 Under-pervance, ion thruster accelerator
 grid trajectories, 202–204
 Uniform plasma, ion thruster plasma
 generators, 0-D ring-cusp model,
 104–105
 Uniform vertical magnetic field, plasma
 physics, single particle motions,
 41–43
 Upstream reference electron density, ion
 thruster accelerator grid trajectories,
 201–204
 Vacuum applications, hollow cathodes,
 thermionic electron emission,
 252–255
 Vacuum potential, hollow cathode
 operation, 309–315
 Vacuum region, ion thruster accelerator
 grid, electron backstreaming,
 212–216
 Variables table, 451–458
 Velocity volume element, plasma physics,
 45–46
 View-factor model, discharge density,
 172–182
 Vlasov equation, hybrid Hall thruster, ion
 current, 371–372
 Wall-scattering frequency, hybrid Hall
 thruster models, transverse electron
 transport, 368–369
 Wirz-Katz model, discharge chambers,
 180–182
 Work function, thermionic electron
 emission, hollow cathodes, 251–255
 Xenon ionization cross-sections, 471–474
 Xenon Ion Propulsion System (XIPS), 3
 direct-current-discharge plasma
 generators, 102
 ion thrusters, 429–440

- plume plasma optical emission, 419–422
- Xenon ion thrusters, direct-current-
 - discharge plasma generators, 102
- Xenon thrusters, specific impulse, 25–27
- 0-D ring-cusp model:
 - discharge loss, 133
 - discharge stability, 134–137
- electron confinement, 108–110
- ion thruster plasma generators, 102–105
 - limitations, 141–142
- magnetic multipole boundaries, 105–107
- microwave ion thrusters, 165–171
- radiofrequency (rf) ion thrusters,
 - 156–158

