
INDEX

A

Admissible shape functions, 219
 Algebraic Riccati equation, 500
 Atomic force microscope, 7
 Austenite, *see* Austenitic phase
 Austenitic phase, 301
 Austenitic-to-martensitic
 transformation, *see* Transformation
 laws
 single-variant model, 304
 single-variant with stress, 305
 Axial bar, 56

B

Beam, 58
 in bending, 58–60
 clamped-free boundary conditions,
 61
 pinned-pinned boundary conditions,
 61
 strain energy, 64
 mode shapes, 235
 Bending 31 piezoelectric transducers,
 see Piezoelectric bimorph

C

Capacitance, 66
 dynamic, 234
 Capacitor(s)
 electric field in a, 65
 energy stored, 66
 Charge
 bound, 44

Charge feedback, 469
 Compact notation, *see* Voigt notation
 Compliance matrix, 32
 Conducting polymer 349
 Conducting polymer actuator
 voltammogram, 364
 transducer models, 367–369
 free displacement, 367
 blocked force, 367
 Conductivity, 44
 Conductor, 43
 Controllability, 493
 Convolution integral, 94
 Coupling, 2
 Curie Temperature, *see* Piezoelectric
 material, Curie Temperature
 Current, 42
 density, 42
 Cyclic voltammetry, 363

D

Damping matrix
 viscous, 93
 proportional, 265
 modal, 265
 Damping ratio, 94
 Dielectric elastomer, 352
 Dielectric material, 46
 Dipole moment, 44
 Dipole, 44
 Displacement
 vector, 25
 admissible, 32

554 INDEX

Dynamic capacitance, *see* Capacitance, dynamic

E

Eigenvalue, 95
 Elastic modulus, 33
 Electric displacement, 37
 Electric field intensity, *see* Electric field
 Electric field, 37
 Electric flux intensity, *see* Electric displacement
 Electric potential, 54
 Electroactive polymer, 4
 Electrochromic material, 11
 Electronic dipole, *see* Dipole
 Electrostrictive materials
 strain-field relationship, 185
 effective piezoelectric strain coefficient, 187
 constitutive modeling, 192
 harmonic response, 196–198
 Energy
 function, 50
 potential, 51
 kinetic, 81
 Helmholtz free, 208
 Gibbs free, 208
 Elastic Gibbs, 208
 Electric Gibbs, 208
 Energy harvesting, 533
 Enthalpy, 208
 elastic, 208
 electric, 208

F

Fiber optics, 11
 Frequency domain, 101
 Full-state feedback, 492
 Full-wave rectifier, 535

G

Gain matrices, 469
 Generalized coupling coefficient, 114, 263

Generalized state variables, 67
 Generalized velocities, 82

I

Inchworm actuator, 403
 Insulator, 43
 Ion-exchange polymer, *see* Ionomeric materials
 Ionomeric materials, 354
 Ionomeric polymer transducers
 blocked force, 375
 free displacement, 376
 material properties, 377
 Isotropic, 33

K

Kinetic law, 303

L

Leveraged piezoelectric actuator
 mechanical, 388
 frequency, 402
 Linear quadratic regulator, 496
 Loop transfer function
 proportional-derivative controller, 392
 proportional-integral-derivative controller, 397
 piezoelectric amplifier, 526

M

Magnetostrictive material, 11
 Martensite, *see* Martensitic phase
 Martensitic fraction, 302
 Martensitic phase, 301
 Martensitic-to-austenitic transformation, *see* Transformation laws
 Mass matrix, 93
 Mechanical rectifier, 402
 Megapascal, 14
 Modal damping, *see* Damping matrix, modal
 Modal filtering, 239–241
 Modal stiffness, 265
 Modulus matrix, 32

- N**
- Natural frequency
 - undamped, 93
 - Nitinol, 300
- O**
- Observability, 508
 - Operational amplifier, 520
 - Operator notation, 28
 - Output feedback, 468
- P**
- Permittivity
 - of free space, 3
 - relative, 46
 - Piezoelectric transducer
 - 33 operating mode, *see* 33 piezoelectric transducer
 - piezoelectric transducer stack, *see* Piezoelectric stack
 - force sensor, *see* Piezoelectric force sensor
 - motion sensor, *see* Piezoelectric motion sensor
 - 31 operating mode, *see* 31 piezoelectric transducer
 - Piezoelectric bimorph
 - curvature, 168
 - transducer equations, 172–174
 - free displacement, 174
 - blocked force, 174
 - substrate effects, 175–177
 - stiffness matrices, 220
 - coupling matrix, 220
 - capacitance matrix, 220
 - Piezoelectric effect
 - direct, 122–124
 - converse, 122, 124–126
 - Piezoelectric material, 4
 - poling of a, 128
 - Curie temperature, 128
 - coupling coefficient, 133
 - linear constitutive relationships, 137
 - Piezoelectric motion sensor, 159
 - Piezoelectric plates
 - strain operator, 269
 - stiffness matrix, 271
 - coupling matrix, 271
 - capacitance matrix, 272
 - mass matrix, 281
 - Piezoelectric shunts
 - system equations, 420
 - frequency response, 422
 - inductive-resistive, 425
 - multimode, 432
 - adaptive, 443–446
 - Piezoelectric stack
 - free displacement, 151
 - blocked force, 151
 - actuating a linear elastic load, 152–154
 - stiffness match, 153
 - Piezohydraulic actuator, 404
 - Piezoelectric force sensor, 158–159
 - Point charge, 36
 - Polarization, 45
 - Pole-zero interlacing, 259
 - Polymer, 347
 - Positive position feedback, 478–480
 - Power
 - electrical, 512
 - average, 514
 - factor, 518
 - Power amplifiers
 - linear, 524
 - switching and regenerative, 530–533
 - Power factor, *see* Power, factor
 - Power flow, 111, 514
 - Power spectral density, one-sided, 441
 - Proportional-derivative (PD) control, 392
 - Proportional-Integral-Derivative (PID) control, 397
 - Pseudoelastic effect, 299
 - Pseudosusceptibility, 189
- R**
- Residual strain, 299
 - Ritz method, 218
 - Root mean square response, 442

556 INDEX

S

Saturation electric field, 189
 Self-sensing actuation, 483–485
 Shape memory alloy actuator
 free strain recovery, 327
 restrained recovery, 327
 controlled recovery, 329
 electrical activation, 330–332
 Shape memory alloy damper, 453
 parametric study, 460–464
 Shape memory alloy, 4
 Shape memory effect, 299
 Simultaneous sensing and actuator, *see*
 Self-sensing actuation
 Single-crystal piezoceramic, 184
 Smart material system, 1
 Smart material, 1
 Spatial filtering, 235–239
 State estimation, 505
 State variable, 2
 Static equilibrium, 30
 Stiffness matrix, 92
 Strain, 14
 of a solid, 26
 normal, 26
 shear, 26
 percent, 27
 Stress, 14
 of a solid, 27
 admissible, 32
 Stress-induced martensite, 320
 Switched-state absorber, 448–453

T

Temperature-induced martensite, 320
 Thermodynamics
 first law, 206
 second law, 206
 31 piezoelectric transducer
 coupling coefficient, 161

free strain, 161
 blocked stress, 161
 free displacement, 161
 blocked force, 161
 33 piezoelectric transducer
 coupling coefficient, 144
 free strain, 144
 blocked stress, 144
 volumetric energy density, 145
 transducer equations, 147–149
 free displacement, 148
 blocked force, 149
 Transfer function, 101
 Transformation coefficient, 302
 Transformation laws
 single-variant model, 304
 single-variant with stress, 305
 partial transformation, 307
 multivariant model, 322
 Transition temperatures, 301

V

Variants, 301
 Variational motion, 68
 Variational principle
 systems in static equilibrium, 70–72
 dynamic systems, 78–81
 Variational work, *see* Work, variational
 Voigt notation, 28
 Volumetric energy density, 15

W

Work
 mechanical, 48
 electrical, 54
 variational, 70

Z

Zero-flux constraints, 114
 Zero-force constraints, 114