

Index

- Adhesion, 200, 201, 222
AFM, 218
Arrhenius equation, 79
- Bimodal distributions
 branch, 63, 64, 71
 lamellar thickness, 63, 71
 molar mass, 65, 68, 76
- Bis-alkylphenoldisulphide (BAPD), 469
Bis(diisopropyl)-thiophosphoryl disulfide (DIPDIS), 445, 446, 469
- Blown film extrusion, 65
Branch density, 72
Branch distribution, 62–64, 68, 69, 72
Brittle-ductile transition temperature (T_{BT}), 413
Bromobenzene, 466
- Carbon black, 444, 462
Chain slip, 77
Chlorinated penetrant, 466
Chlorinated rubber, 450, 452, 454, 461, 462
Chlorobenzene, 466
Chlorohydrocarbon, 466
Chlorosulfonated polyethylene (SPE), 450, 454, 460
N-(4-Chlorophenyl) acrylamide, 452
N-Chlorothioamides, 445
Cocrystallization, 69
Coefficient of linear thermal expansion (CLTE), 203, 204
Compatibility, 224, 225, 247, 264, 442–443, 449–453, 455, 460, 461, 469
Compatibilization, 509, 519, 523
Compatibilizer, 504, 505, 507–513, 517–519, 522, 523
Compression, 466
Continuous phase, 72, 286–290
COP, 59, 503–505, 507–509, 517–519, 522, 523
Copolymer, 28, 270, 273, 274, 277, 282, 284, 289, 293, 296, 298–300
Covulcanization, 448, 452
Crack, 454, 463, 465, 467
Creep resistance, 68
Cross-linking, 270, 273, 278, 279, 284, 290, 291, 293, 295, 298–301
Cross-linking agent, 421, 431
Crystal, 228, 231, 233, 235, 237, 239, 242, 246, 250, 252, 253, 255, 260–263
Crystallization
 cocrystallization, 69
 kinetics, 511, 515–519, 523
 lamellar thickness, 69, 71, 72
 rate, 510, 515, 518, 519, 522
 slow crystallization, 69
Cyclopolyolefin, 28–29
- Damping factor curve, 78
Deformation, 225, 242, 244–246, 263, 264, 293
Differential scanning calorimetry (DSC), 69–71, 73, 74, 201, 413
Diffusivity, 466
Dimethyl itaconate (DMI), 414
2,5-Dimethyl 2,5-bis(*tert*-butyl peroxy) hexane, 414
Dipole–dipole, 442
Dispersed phase, 455
Dithiocarbamate, 445
DMA, 414, 416
DMI-modified PP, 414
Drawability, 225, 264
Dynamic elastic modulus (E'), 456
Dynamic mechanical properties, 456

- Dynamic mechanical spectroscopy (DMS), 78, 79
- Dynamic mechanical thermal analysis (DMTA), 431, 432
- Dynamic radiation curing, 412, 438
- Dynamic shear moduli (G'), 229, 236
- Dynamic vulcanization (DV), 419, 421, 425, 435
- Elastic properties, 528, 534, 539, 540, 543, 547, 550
- Enthalpy, 442
- Entropy, 442
- EPDM-g-MAH, 450
- Ethylene-1-octene copolymer, 214, 220
- Ethylene- α -olefin copolymers (ECP), 203, 204
- Ethylene-butene copolymer (EBR), 214, 226, 228, 229, 244, 247
- Ethylene-hexene copolymer, 214
- Ethylene-hexene-1 copolymer (EHR), 230, 231, 233, 236, 238, 244-247, 250, 251, 253, 256-258, 260, 262, 264
- Ethylene-propylene copolymer (EPM), 236-241, 247-250, 264, 412
- Ethylene propylene diene monomer (EPDM), 7-11, 15-17, 198, 206, 207-217, 222, 224, 242, 412-438, 441, 469, 530-537, 542, 546-550
- Ethylene-propylene rubber (EPR), 5, 6, 8-11, 14-17, 198-200, 202, 203, 224, 225, 234, 242, 247
- Ethylene vinyl acetate copolymer (EVA), 8, 11, 15, 17
- Extender oil, 207
- Fatigue resistance, 420, 442
- Finite element modeling (FEM), 208, 210, 430
- Flory-Huggins theory, 75
- Flow direction (FD), 204
- Folded-chain lamellae, 219
- Fracture, 415, 419, 420, 424-428, 432
- Fringe-micelle, 219
- FT-IR spectroscopy, 416
- Functionalization, 269, 270, 275, 277, 284, 286, 290, 292, 295, 297, 299, 301, 530, 531, 534, 536, 538, 539, 543, 547, 551
- Gel permeation chromatography (GPC), 201
- Gibb's free energy, 442
- Glass transition temperature (T_g), 229, 231, 234, 236, 239, 241-245, 249-251, 253, 254, 265, 432, 456, 457, 460
- Grafting, 270-301
- Grafting efficiency, 272-274, 277, 279, 284, 286, 287, 294, 297, 299
- Halobutyl rubber, 445
- Heat capacity (C_p), 419
- Heterogeneous slip, 78
- High heat deflection temperature (HDT), 436
- High impact polypropylene (hiPP), 198
- Homogeneous slip, 78
- Hydrogen-bonding, 442
- Hydroxyl functional group, 462
- Immiscible, 225, 231, 233, 238, 241-244, 246-250, 261, 264
- Impact copolymer PP (ICP), 198-202, 221
- Impact PP copolymer (IPC), 198, 199
- Impact strength, 411-413, 420, 421, 430-432, 438, 527, 528, 530, 543, 244, 547-551
- Initiators, 273, 278, 279, 283, 296, 300
- In situ* grafting and dynamic vulcanization (ISGV), 432
- In situ* polymerization, 411
- Interactions, 283, 289-292
- Interfacial adhesion force, 254
- Interlaminar deformation, 77
- Intermolecular chain transfer, 64
- Interphase interaction, 528, 530, 531, 533-535, 537, 543, 544, 547, 550, 551
- Intramolecular branch distribution, 63, 72
- Intramolecular chain transfer, 64
- Ion-dipole, 442
- Isopropyl alcohol, 447
- Itaconate, 414
- Izod impact strength, 412, 413, 420-432
- Lamella, lamellar, lamellae, 226, 231, 233, 237, 238, 241, 244, 246, 248-250, 252, 253, 255, 256, 263
- Lamellar fragmentation, 77

- Lamellar rotation, 77
- LCP
 blends, 501, 509–511, 519, 523
 concentration, 502, 515
 copolymer, 508, 510, 517, 519, 523
 domains, 508, 509, 515, 520
 phase, 502, 504, 510, 515, 523
- Light scattering, 200, 412
- Liquid-liquid phase separation, 68, 72, 74
- Loss modulus (E''), 226, 228, 234, 235, 240
- Lower critical temperature (LCST), 207
- Macroradicals, 272–275, 277, 279, 282–284, 287, 290, 294, 297, 299
- MAH, 432, 434
- MAH-g-EPDM, 452, 469
- Maleic anhydride (MAH), 212, 213, 274–276
- Maleic anhydride grafted PP, 416
- Matrix phase, 455
- MBTS, 452, 462
- Mechanical properties, 198, 199, 203, 211, 221, 411, 512, 414, 417, 421, 502, 506, 507, 523
- Melt extrusion, 411
- Melt flow index (MFI), 287–290, 294, 297, 298, 301
- Melt mixing, 412
- Melt strength, 62, 64–68, 76
- Mesophase, 531, 533, 535
- Metallocene catalyst, 61, 66, 68, 73, 199, 201, 203, 214, 221
- Miscibility, 76, 77, 224, 225, 231, 235, 238, 442
- Molar mass distribution, 61, 62, 65–68
- Molecular weight distribution (MWD), 200, 201, 207
- Monomethyl itaconate (MMI), 414
- Morphology, 77–79, 198, 199, 207, 412, 416–424, 431, 435, 437, 438
- Na-neutralized ionomer, 425
- Natural rubber (NR)/EPDM, 441, 442, 445–469
- Nitrobenzene, 466
- Non-Newtonian liquid, 416
- Notch radius (R), 413
- Nucleation, 510, 516, 517–519, 523
- Olefins, 269, 274, 275, 277, 286, 293, 298
- Optical microscopy, 74, 75, 413
- Organic peroxide, 421
- Oriented crystal fraction (I_{oc}), 215
- Ozone, 442, 444, 463–465
- PA/PO blends, 528–531, 533–535, 543
- PE-g-SBH, 502–505, 508, 509, 517, 519, 521, 522
- Permeability, 466
- Permittivity, 462, 463
- Peroxide, 198, 272, 275, 279, 282, 286, 288, 294–296
- Phase diagram, 63, 72, 74, 75, 207
- Phase dissolution, 448
- Phase separation, 226, 231, 250, 262, 278
- Phenolic resin, 200, 421, 428, 435
- Photocrosslinking, 431
- Photoinitiation, 431
- Polar monomers, 270, 274, 293, 300
- Polyamide, 7, 8, 9
- Polybutadiene rubber (BR), 450, 454
- Polybutene (PB), 5, 6, 9, 17, 225
- Polyethylene
 high density, 5, 17, 225
 linear low density, 5, 8, 9, 225
 low density, 5, 9, 17
 polyethylene/ethylene-propylene rubber, 473
 polyethylene-polyamide, 39, 42, 513, 519, 522
 polyethylene-polypropylene, 74, 270, 292, 294
 polyethylene-polystyrene, 44–48
- Polyethylene naphthalate (PEN), 7, 17
- Polyethylene terephthalate (PET), 7, 17
- Polyheptylene-1, 28
- Polyhexylene-1, 28
- 1,4-Polyisoprene, *cis*-, *trans*, 29
- Polymethyl methacrylate (PMMA), 7, 17
- Polymethylpentene (PMP), 5, 17
- Polyoctanomer (TOR), 445
- trans*-Polyoctene rubber, 450
- Polyoctylene-1, 28
- Polyolefin-polyamide blends, 43, 48
- Polyolefin-polystyrene blends, 43–45
- Polypentene-1, 28
- Polyphenylene ether (PPE), 7, 29

- Polyphenylene ether–polystyrene blends, 29
- Polyphylene oxide (PPO), 7, 17
- Polyphenylene sulphide (PPS), 7, 17
- Polypropylene, (PP), 5, 6, 9, 16, 18, 27, 28, 36, 38–40, 42, 46–48, 224, 235, 411–438
- atactic polypropylene, 256, 265
 - isotactic polypropylene, 6, 224, 265
 - polypropylene–polyamide, 49
 - polypropylene–polystyrene, 47
 - syndiotactic polypropylene, 235, 265
- Poly(propylene-*co*-ethylene), 214
- Polystyrene (PS), 8, 9, 29
- Polyvinyl chloride (PVC), 7, 9, 450
- Position annihilation lifetime spectroscopy (PALS), 215
- Postreactor blend, 201, 221
- Power law equation (Ostwald–de Waele equation), 458
- PP/EPDM, 418–421
- PP-*g*-MAH, 434
- PP-*g*-MAH/Zn-SEPDM, 416
- PP-grafted maleic anhydride (PP-*g*-MAH), 212, 213
- PP(PE)/EOC, 299
- PP(PE)/styrene, 300, 309
- Pressure–volume–temperature (PVT) relationship, 75
- Pro-Am, Pro-hd, 467
- Propylene-dominant component, 214
- Propylene–ethylene block copolymer, 214
- Propylene–ethylene propylene copolymers blends, 38
- Propylene–hexene copolymers blends, 38
- Propylene–poly(butene-1) blends, 47–49
- Proton NMR spectroscopy, 445
- Reactive extrusion, 270, 289, 294
- Rheology, 76, 412, 431, 438
- Rheometric mechanical spectrometry (RMS), 432
- Ruthenium tetraoxide (RuO₄), 199, 226, 227, 232, 234
- SAXS, 73
- Scanning electron microscopy (SEM), 358, 415, 503, 546
- Self-nucleation and annealing (SSA), 72
- Semiflexible LCP, 502, 508, 519, 523
- Shear storage moduli (G'), 229, 265
- Shear thinning, 64–66, 68, 76
- Sheet extrusion, 65
- Silanol (Si-OH), 447
- Silica, 448, 456, 462, 464
- Size exclusion chromatography (SEC), 201
- Small angle light scattering (SALS), 245
- Small angle neutron scattering (SANS), 37, 68, 86, 203
- Solubility parameter, 283, 295, 300, 301
- Solution blending, 411
- Solvent extraction, 68
- Sorptivity, 466
- Spherulite, 231, 238, 239, 244, 248, 250, 255
- Stearic acid, 444
- Stereoblock PP, 214
- Stirling's approximation, 30
- Strain hardening, 78
- Strain-induced crystallization, 218
- Stress–strain curve, 77, 243, 262, 263, 455, 573
- Stress whitening, 243, 244, 245, 247
- Styrene–butadiene rubber (SBR), 198
- Sulfonated EPDM ionomer, 414
- Surface tension, 34–35, 44, 45
- Surface-modified carbon nanofiber (MCNF), 220
- Surfactant, 44, 45
- Swelling, 539, 540, 541, 542
- Talc, 200
- Temperature gradient extraction fractionation (TGEF), 200
- Temperature rising elution fractionation (TREF), 202
- Tensile strength, 68, 211, 212, 220, 397, 412, 423, 428
- Thermal properties, 412
- Thermodynamics, 30, 32, 33
- Thermoplastic elastomers (TPEs), 8, 18, 419
- Thermoplastic interpenetrating polymer network (IPN), 425
- Thermoplastic polyolefin (TPO), 416, 442
- Thermoplastic polyolefin elastomer (TPO), 198, 199

- Thermoplastic vulcanizate (TPV), 8, 18,
198, 207–214, 221, 412, 419–425, 430,
436–438
- Time–temperature master curve, 79
- Transmission electron microscope
(TEM), 37–43, 47, 49, 74, 199,
201–210, 215, 432
- UHMWPE, 5, 9, 10, 18
- ULDPE, 5, 18
- Ultrablend, 455, 456, 460
- Ultrasonic curing, 412, 438
- Ultrasonic irradiation, 418
- Unoriented crystal fraction (I_{uc}), 215
- Upper critical solution temperature
(UCST), 33, 37, 63, 72, 74, 75
- Van der Waals, 443
- WAXS, 73, 208, 215–217, 220
- William–Landel–Ferry (WLF)
equation, 79
- Young’s modulus, 412, 453
- Ziegler–Natta, 60, 61, 63, 64, 68, 69, 77
- Zn-neutralized ionomer, 425
- ZnO, 444

