



INDEX

- 1000-CX, 448, 452
- 1000Base-LX, 448, 451
- 1000Base-SX, 448, 451
- 100Base-FX, 439, 440, 444
- 100Base-T4, 439, 442, 444
- 100Base-TX, 439, 440, 441, 442, 444
 - full-duplex, 442
- 100VG-AnyLAN, 389, 410, 436, 437, 442, 446, 448
- 10Base-2, 413, 416, 417, 752
- 10Base-5, 413, 414, 417
- 10Base-F, 413, 438
- 10Base-FB, 413, 421, 428
- 10Base-FL, 413, 421, 428
- 10Base-T, 117, 413, 420, 421, 427, 428, 437, 438, 441, 752
 - full-duplex, 441
 - ports, 491
- 10G Ethernet, 388, 397, 436, 540, 753, 812
- 10GBase-LX4, 540
- 10GBase-R, 540
- 10GBase-W, 540
- 10GBase-X, 540
- 16-QAM, 289
- 2G mobile cellular
 - networks, 471
- 3Com, 400, 436
- 3G mobile cellular
 - networks, 468, 471, 893
- 4B/5B code 294, 300, 464
- 5-4-3 rule, 416
- 802.11a, 468, 473
- 802.11b, 473
- 802.16 standard, 861
- 802.1p/Q, 568
- 802.2, 409
- 802.3/LLC frame, 408
- 802.3z, 451

A

- AAL, 793
- AAL1, 794
- AAL3/4, 794
- ABM, 808, 812
- ABR, 799
- Abramson, Norman, 389
- Accelerated MPLS
 - switching, 832
- Access:
 - lists, 728
 - methods, 392
 - network, 150, 151, 164
 - point, 328, 468, 474
 - router, 755
 - token, 92
- ACK, 195, 684
 - frame, 476
- ACR, 261, 268
- Active concentrator, 461
- Ad-hoc networks, 474
- Adapter, 30
- Adaptive Load Balancing, 557
- Adaptive routing, 692
- ADC, 292, 293
- Add-Drop Multiplexer, 355
- Add/drop ports, 351, 354
- Address:
 - anycast, 41, 45
 - broadcast, 45
 - hardware, 46
 - MAC, 46
 - multicast, 45, 588
 - numeric, 45
 - symbolic, 45
 - table, 513
 - unicast, 45, 588
- Address Resolution
 - Protocol (ARP), 48, 597
- Address space, 46
 - flat, 46
 - hierarchical, 41, 46

- Addressing, 45
- Administrative unit, 353
- ADSL, 168, 170, 860, 864, 886
- Advanced Encryption Standard (AES), 899, 902
- Aggregate channel, 70
- Aggregate ports, 351, 354
- Aggressive behavior of the port switch, 525
- AH, 901, 907
- All-optical networks, 370
- ALOHA, 91, 389
- Alternative traffic routes, 193
- AM:
 - bands, 322
 - ranges, 259
- America On Line, 170
- American National Standardization Institute, 128
- AMI, 294, 298
- Amplitude modulation, 286, 287
- Amplitude shift keying, 286, 288
- Analog-to-digital converter, 292, 293
- ANSI, 128, 347
- Antenna:
 - isotropic, 320
 - omnidirectional, 320
- API, 113, 114, 900
- APNIC, 593
- AppleTalk, 750, 813, 816
- Application:
 - distributed, 36
 - network, 36
- Application layer, 113, 114, 125
- Application Service Provider, 166, 171
- Application-specific integrated circuit, 490
- Arbitrator, 50, 60, 388, 393
- Arcnet, 10, 14, 18, 397
- ARIN, 593
- ARP, 597, 817
 - cache, 601
 - server, 601
 - table, 596, 597
- ARP record:
 - dynamic, 600
 - static, 600
- ARPANET, 15, 133, 768
- ASCII, 125
- ASIC, 490
- ASK, 286, 288
- ASN.1, 845
- ASP, 166, 171
- Assured Forwarding, 742
- Astrolink, 336
- Asymmetric Digital Subscriber Line, 170, 886
- Asynchronous Balance Mode, 808, 812
- Asynchronous Transfer Mode (ATM), 186, 309, 313, 733, 757, 808, 810, 826, 915
 - traffic classes, 789
- AT&T, 157, 347, 437
- ATM, 21, 28, 80, 119, 136, 277, 309, 313, 583, 753, 779, 808
 - protocol stack, 792
- ATM Adaptation Layer (AAL), 793
- ATM cell: *See also* ATM frame format, 796
- ATM Forum, 128
- ATM frame: *See also* ATM cell
- ATM VPN, 898, 917
- Attachment unit interface (AUI), 413, 414, 440
 - port, 491
- Attenuation to Crosstalk Ratio, 261, 268
- Auditing, 198, 202
- Authentication, 198, 202
 - application-level, 202
 - mutual, 202
- Authorization, 202
- Authorized users, 201

- Autonegotiation, 441
- Automatic Protection
 - Switching, 361
- Autonomous system, 691, 696
- Autopartitioning, 493
- Availability, 191, 192, 198, 201, 206
- Average delay, 184, 188
- Average information rate, 191
- AWG, 367, 374

- B**
- B-ISDN, 787. *See also* Broadband ISDN
- Back hauling, 351
- Back-off timer, 477
- Backbone, 16, 150, 151, 152, 164
- Backbone routers, 753
- Backpressure, 525
- Backward resource management
 - cell, 787, 801
- Bandwidth, 39
- Banyan VINES, 816
- Base station, 328, 468, 471, 474
- Basic NAT, 745
- Basic rate interface (BRI), 877, 880
- Basic service set, 474
- Batch-processing system, 12
- Best effort:
 - delivery, 135
 - service, 72, 79
- BFSK, 480, 485
- BGP, 142, 690, 691, 829, 922
- BGPv4, 690, 697, 710
- Billing Service Provider, 171
- Binary PSK, 286, 289
- Bipolar Alternate Mark
 - Inversion, 294, 298
- Bit robbing, 349
- Bit stuffing, 813
- Blowfish, 905
- Bluetooth, 91, 339, 458, 481
 - ACL channels, 488
 - Audio layer, 485
 - Baseband layer, 484
 - Control layer, 485
 - Link manager, 485
 - Logical Link Control Adaptation
 - Layer, 485
 - Physical radio layer, 484
 - profiles, 484
 - SCO channels, 488
- Bluetooth frame:
 - access code, 486
 - data field, 486
 - frame header, 486
- Bluetooth SIG, 480, 481
- Bluetooth Special Interest Group, 480, 481. *See also* Bluetooth SIG
- BNC, 416
- BOC, 157
- Border gateway protocol, 690, 691
 - version, 4, 710
- Bottlenecks, 182, 191
- BPDU, 549, 551
- BPSK, 286, 289
- Bridge, 98
- Bridge protocol data unit, 549, 551
- Bridge:
 - classical, 518
- BRM cell, 787, 801
- Broadband-ISDN, 787
- Broadcast:
 - address, 45, 400
 - domain, 564
 - radio, 322
 - radio ranges, 259
 - storm, 514
- BSS, 474
- BT, 800
- Buffer overflow, 802
- Buffering, 74
- Buffering time, 84
- Burst Mode, 451
- Burst period, 191

- Burst size, 184, 191
- Burst Tolerance (BT), 800
- Bursty traffic, 15

- C**
- CA Unicenter, 841
- Cable & Wireless, 159, 169
- Cable lines, 258
- Cable modem termination
 - station, 890, 891
- Cable TV, 860
- Call setup, 769
- Capacity, 37, 39
- Card protection, 351, 362
- Carrier frequency, 401
- Carrier of carriers, 157
- Carrier sense, 399, 401
- CATV, 860, 861, 864
 - local loop, 890
- CBR, 787, 789, 799. *See also* Constant Bit Rate
- CCITT, 347, 775, 780
- CCK, 468, 473
- CDMA, 309, 336, 340, 392
- CDMA/CA, access method, 893
- CDME, 905
- CDP, 171
- CDV, 787, 792, 799
- Centronics, 30
- Challenge Handshake Authentication Protocol (CHAP), 808, 815, 816
- Channel, 256
 - digital, 16
 - fiber-optic, 22
- Channel Service Unit, 816
- Channel trunking, 816
- Channelized port, 817
- Checksum, 37, 39, 101, 118, 903
- Chipping rate, 339
- CIR, 190
- Circuit, 256
- Circuit switching, 15, 50, 61, 62, 66
- Circuit-switching network
 - performance, 87
- Cisco, 400, 557, 819, 850
 - access list, 729
 - CLI language, 728
 - IOS, 728
- Classless interdomain routing (CIDR), 582, 638, 651
- Clear-to-send frame, 478
- CLEC, 158
- Client component, 34
- Client-server architecture, 869
- CLNP, 130
- CLR, 787, 791
- CMIP, 845, 850
- CMTS, 890, 891
- Coaxial cable, 256, 259
- Code:
 - 2B1Q, 300
 - 4B/5B, 440
 - 8B/6T, 440
 - AMI, 298
 - EBCDIC, 125
 - Manchester, 117
 - NRZ, 296
 - NRZI, 298
 - violation, 300
 - variable length of, 294, 305
- Code Division Multiple Access, 309, 336, 340
- Coefficient of variation, 189
- Collision, 92, 388, 392, 402
 - avoidance, 468, 471
 - detection, 399, 402, 468, 470
 - detector, 413, 415
 - domain, 413, 422, 564
- COM port, 30
- Commitment Information Rate, 184, 190
- Common bus, 41, 44, 100
- Common Management Information Protocol, 845

- Communication carrier, 809
 - Communication device
 - queue, 210
 - Communication link, 20, 24
 - ideal, 256
 - open wire, 258
 - total length, 42
 - Communication protocol, 108
 - Competitive Local Exchange
 - Carrier, 158
 - Complementary code keying, 468, 473
 - Computer network, 10, 11
 - evolution, 10
 - Concentrator, 44, 91, 95, 418, 490
 - Confidentiality, 201, 206
 - Configuration switching, 497
 - Congestion, 74
 - avoidance methods, 183, 213
 - Connection setup, 68
 - Connection-oriented
 - protocols, 66, 79, 102
 - Connectionless protocols, 102
 - CONP, 130
 - Constant Bit Rate, 211, 418, 490
 - Content Distribution
 - Provider, 166, 171
 - Contention window, 477
 - Controller, 30
 - Convergence Sublayer (CS), 794
 - Convergence time, 691
 - Copper cables, 259
 - Core network, 150, 151
 - Corporate client, 153, 156
 - Corporate network, 23
 - Corporate routers, 755
 - CPE-based VPN, 913
 - CPVPN, 914
 - CR-LDP, 925
 - CRC, 306, 307
 - Cryptographic system, 202
 - CS, 794
 - CSMA/CA, 476
 - CSMA/CD, 401, 413, 419, 436, 437, 450, 477, 512
 - CSPE, 838
 - CSU, 816
 - CTD, 787, 792
 - CTS, 478
 - Customer-provided VPN, 914
 - Cyclic Redundancy Check (CRC), 306, 307
- D**
- DA, 292, 293
 - DAC, 466
 - Daisy-chain connection, 59
 - DAS, 463, 466
 - Data centers, 150, 151
 - Data Circuit Terminating
 - Equipment, 256, 259, 775
 - Data compression, 294, 304
 - dynamic, 304
 - Data Encryption Standard, 899, 902
 - Data flow, 50
 - Data link layer, 113, 114, 117
 - functionality, 117, 118, 119
 - Data network, 22
 - Data network identification
 - codes, 775, 777
 - Data Service Unit, 816
 - Data Terminal Equipment, 150, 256, 260, 775
 - Data-transmission network, 11
 - Datacom network, 10, 11
 - Datagram, 76, 113, 117
 - networks, 186
 - transmission, 76, 77
 - dBase, 36
 - DBMS, 36, 115, 199
 - DCE, 260, 775
 - DCF, 468, 476
 - DCF IFS, 479
 - Demultiplexer, 57, 58

- DEC, 388, 407
 - Decimal packing, 294, 305
 - DECnet, 114, 145, 750, 813, 816
 - Decomposition:
 - hierarchical, 109
 - Decoupling elements, 415
 - Default route, 625
 - Default router, 625
 - Delay of packet delivery, 187
 - Demand Priority, 437, 446
 - Demultiplexing, 674, 675
 - Dense Wave Division
 - Multiplexing, 309, 310, 346, 367
 - Department routers, 756
 - DES, 899, 902
 - Descrambler, 299
 - Designated port, 549, 551
 - Designated switch, 549, 551
 - Destination address, 77
 - Determinate access method, 92
 - Deterministic access, 388, 393
 - Dynamic host configuration protocol (DHCP), 134, 582, 609
 - automatic assignment of static addresses, 610
 - dynamic address distribution, 610
 - lease duration, 610
 - manual mode, 610
 - Differentiated Services, 726, 731
 - Diffie-Hellmann concept, 904
 - DiffServ, 726, 731, 811
 - DIFS, 479
 - Digest function, 902
 - Digital channel, 16
 - Digital Cross-Connect (DXCs), 355
 - Digital Equipment, 128
 - Digital Equipment Corp, 388
 - Digital signature, 198, 202, 899, 903
 - Digital-to-analog converter, 292, 293
 - Dijkstra's iterative algorithm, 706
 - Direct sequence spread
 - spectrum, 336, 339
 - Distance vector algorithms, 693
 - Distributed application, 36
 - Distributed computing concept, 16
 - Distributed coordination
 - function, 468, 476
 - Distribution density, 184, 187
 - Distribution system, 475
 - service, 468, 475
 - DNIC, 775, 777
 - DNS, 134, 582, 585, 605, 676, 678, 721, 816, 912. *See also* Domain Name System
 - fully qualified domain name, 603, 605
 - names, 585
 - relative name, 603, 605
 - reverse lookup zones, 608
 - short name, 603, 605
 - Driver, 30
 - DSAP, 409
 - DSL, 156, 886
 - access multiplexer, 886, 888
 - DSS, 468, 475
 - DSSS, 336, 339, 473
 - DSU, 816
 - DSU/CSU, 816
 - DTE, 260, 775
 - Duplex link, 40
 - DVA, 693
 - DWDM, 125, 280, 311, 346, 367, 756, 757, 808, 809
 - DXC, 355
- E**
- E-2, 347
 - E-3, 347
 - E-mail, 15, 36, 139
 - E.164 standard, 781
 - Edge routers, 755
 - EF, 731
 - EFCI, 796
 - Effective protocol bandwidth, 411, 412

- ENCAPS, 659
 - Encoding, 37
 - potential method, 37
 - pulse method, 37
 - Encryption, 202
 - End System Identifier (ESI), 798
 - Enterprise-wide network, 150, 582
 - EPP, 519
 - EPS, 351, 362
 - Equipment protection
 - switching, 351, 362
 - Ericsson, 481
 - Ericsson, Lars Magnus, 319
 - ESI, 798
 - ESP, 901, 909
 - ESS, 468, 474, 475, 483
 - Ethernet, 10, 14, 18, 20, 21, 24, 28, 60,
 - 100, 117, 118, 119, 136, 299, 388,
 - 412, 413, 414, 420, 421, 428, 437,
 - 440, 525, 550, 583, 751, 808, 826,
 - 868
 - II, 407, 409, 410
 - 10 Mbps, 388, 597
 - 10G, 21, 388
 - DIX, 407, 409, 410
 - Fast, 388
 - fiber-optic, 422
 - Gigabit, 388
 - Limitations, 93
 - packet processor, 519
 - SNAP, 407
 - EtherSwitch, 519
 - EtherType, 409
 - Euro Skyway, 336
 - European Telecommunications
 - Standards Institute
 - (ETSI), 351, 471
 - Event-dependent routing, 691
 - Expedited Forwarding, 742
 - Explicit Congestion Forward Identifier
 - (EFCI), 796
 - Extended Service Set, 468, 474, 475
 - Extensibility, 203
 - Exterior Gateway Protocol
 - (EGP), 690, 691, 697, 710
 - Exterior gateway, 697
 - Extra high frequency, 322
 - Extranet, 913, 915
 - Extremely low frequency (ELF), 322
- F**
- Failure:
 - probability, 192
 - rate, 192
 - Fast EtherChannel, 557
 - Fast Ethernet: 19, 39, 136, 162, 186, 277,
 - 388, 397, 410, 436, 437, 438, 439,
 - 440, 441, 442, 443, 444, 445, 448,
 - 449, 450, 812, 889
 - media independent
 - interface, 436, 440
 - physical coding sublayer, 440
 - physical layer device, 436, 440
 - reconciliation sublayer, 440
 - Fast IGP routing, 925
 - Fast link pulse, 436, 442
 - Fault tolerance, 192
 - FCS, 113, 118, 186
 - FDDI (Fiber Distributed Data
 - Interface), 10, 18, 24, 60, 117, 119,
 - 136, 162, 277, 389, 397, 458, 463,
 - 507, 525, 583, 597, 751, 789
 - dual attachment, 463, 466
 - dual attachment
 - concentrator, 463, 466
 - dual attachment station, 463, 466
 - dual homing, 467
 - fault tolerance, 466
 - optical bypass switches, 467
 - primary ring, 464
 - secondary ring, 463, 464
 - single attachment, 463, 466
 - single attachment concentrator, 463, 466

- single attachment station, 463, 466
- SMT layer, 463, 465
- station management layer, 463, 465
- stations, 466
- thru mode, 463, 464
- wrapping operation, 464
- FDM, 50, 58, 261, 309, 842, 865, 870
- FEC, 468, 469, 483
- FHSS, 336, 337
- Fiber amplifier, 369
- Fiber Channel, 450
- Fiber-optic cable, 256, 259
- FIFO (First In, First Out), 218
- File service, 36
- File Transfer Protocol (FTP), 25, 134, 484, 676, 721, 870
- Filtering, 513
- Firewall, 198, 199
- Flat names, 603
- Flood, 514
 - routing, 691, 692
- Flow attributes, 51
- Flow control, 231
- Flow label, 51
- FLP, 436, 442
- FM bands, 322
- FOIRL, 413, 421
- Forward error correction, 468, 469
- Forward resource management cell, 787, 801
- Forwarding, 119, 513
 - table, 56, 77
- Forwarding Equivalence Class, 821, 834
- Four hubs rule, 419
- Four-level FSK, 289
- Fourier formula, 290
- FQDN, 603, 605
- Fragment, 654
- Frame, 50, 113, 117
 - data field, 118
 - header, 118
- Frame Check Sequence, 113, 118, 186

- Frame Relay, 119, 128, 168, 583, 752, 779, 808, 826, 915
 - data-link layer, 781
- Forum, 780
- physical layer, 781
- VPN, 898, 917
- Frequency division duplex, 309, 314
- Frequency Division Multiplexing (FDM), 50, 58, 261, 309
- Frequency modulation, 286, 287
- Frequency shift keying, 286, 288
- Frequency-hopping spread spectrum, 336, 337
- FRF, 780
- FRM cell, 787, 801
- FSK, 286, 288
- FTAM, 131
- Fully connected topology, 41, 42
- Fundamental frequency, 290

G

- G.703, 817
- Gated software router, 730
- Gateway, 899
- General packet radio service, 891, 893
- GEO, 326, 333
- Geostationary:
 - orbit, 326, 333
 - satellite, 326, 333
- Gigabit EtherChannel, 557
- Gigabit Ethernet, 19, 60, 136, 162, 186, 277, 388, 397, 410, 446, 448, 449, 450, 451, 507, 709, 753, 812, 889
- Gigabit Medium Independent Interface, 540
- Global aggregate unique address, 662
- Global One, 159, 169
- Global positioning system (GPS), 326, 334
- Globalstar, 326, 335
- GPRS, 891, 893

Granularity, 228
 Grosh, Herbert, 14
 Grosch's Law, 10, 14, 16
 GUI, 36

H

Half-duplex link, 40
 Handoff, 329
 Hardware:
 address, 46
 controller, 30
 Hash, 899, 902
 Header, 72, 113, 116
 network-layer, 120
 HELLO interval, 551
 Hewlett-Packard, 437, 850
 Hidden terminal, 470, 478
 Hierarchical
 decomposition, 109
 High-Level Data Link Control
 (HDLC), 118, 778, 811, 877
 frame format, 813
 supervisory frames, 814
 Hold down, 705
 Home PNA, 91
 Hosting Provider, 171
 HP OpenView, 840
 HP Operations center, 841
 Hub, 95, 413, 418, 490
 Huffmann algorithm, 306
 Hypertext Transfer Protocol
 (HTTP), 135, 484, 676, 721, 900

I

IANA, 605
 IBM, 127, 132, 458, 461, 903
 cabling system types, 458, 462
 ICMP, 136, 674, 713, 728, 847. *See also*
 Internet Control Message
 Protocol

 error message format, 718
 echo request, 692
 ICMP messages:
 types, 714
 ICP, 171
 ICQ, 198
 Ideal network, 184
 Identification, 198, 202
 Idle Source, 191, 195
 IDN, 775, 777
 IEEE, 428, 437
 IEEE 802 Committee, 397
 IEEE 802.11, 318, 320, 389, 458,
 469, 471
 IEEE 802.11g, 473
 IEEE 802.15.1, 458, 484
 IEEE 802.16, 891, 892
 IEEE 802.1D, 511
 IEEE 802.1H, 526
 IEEE 802.1Q, 562, 565, 568
 IEEE 802.1w, 555
 IEEE 802.3, 128, 399, 407
 IEEE 802.3ad, 555, 557, 561
 IEEE 802.3ae, 540
 IEEE 802.x, 397
 IETF, 126, 129, 731, 822, 845
 IFS, 476
 IGMP, 136
 IKE, 904
 ILEC, 158
 IN: *See* Intelligent
 Network
 Incumbent Local Exchange
 Carrier, 158
 Individual client, 153, 156
 Infocommunication
 network, 23, 159
 Information flow, 50
 Information rate, 37, 39, 210
 characteristics, 184, 190
 Information service, 139
 Infrared band, 322

- Input:
 - buffer, 74
 - queue, 74
- Instant messaging, 198
- Integrated Services, 726, 731
- Integrated Services Digital
 - Network, 20, 22
- Integrity, 201, 206
- Intel, 128, 388, 407, 557
- Intelligent Network, 23
- Interface, 29
 - inter-module, 108
 - logical, 29
 - peer-to-peer, 112
 - physical, 29
 - service, 109
- Interface card, 30
- Interframe space, 476
- Interior Gateway Protocol
 - (IGP), 690, 691, 832
- Intermediate system to intermediate
 - system, 690, 691
- Internet, 10, 15, 21, 166, 198, 200, 582, 710, 808, 876
- Internet Architecture Board
 - (IAB), 126, 129
- Internet Content Provider, 171
- Internet Control Message
 - Protocol, 136, 674, 713, 728, 847
- Internet Engineering Task Force
 - (IETF), 126, 129
- Internet eXchange, 166, 170
- Internet Group Management
 - Protocol, 136
- Internet Protocol, 135
- Internet Service Provider, 166, 167
- Internet Society (ISOC), 126, 129
- Internetwork, 21, 119, 204
- InterNIC, 605
- Interpacket gap, 399, 402, 439
- Intersymbol
 - interference, 318, 324
- InterXchange Carrier, 153, 158
- Intranet, 21, 913, 915
 - services, 174
- IntServ, 726, 731, 811
- IP, 28, 135, 204, 391, 750, 813, 900
 - internets, 808
 - QoS, 731
 - routers, 726, 808
 - switching, 822
 - telephony, 22, 210
 - WANs, 808
- IP addresses, 585
 - broadcast, 586, 590
 - Class A, 587
 - Class C, 588
 - Class D, 588
 - limited broadcast, 589
 - private, 593
 - undefined, 586, 589, 590
- IP networks:
 - pure, 808
- IP/MPLS, 915
- IPAE, 659
- IPCP, 816
- IPG, 399, 402, 439
- IPSec, 668, 898, 900
 - encryption, 902
- Ipsilon, 821
- IPv4, 692
- IPv4-compatible IPv6
 - addresses, 658, 665
- IPv4-mapped IPv6 address, 665
- IPv6, 45, 618, 692
 - format prefix, 658, 661
 - private addresses, 661
- IPX, 131, 391, 750, 813, 900
- IPX/SPX, 126, 129, 131, 145, 583, 845
- IPXCP, 816
- IRTF, 126, 129
- IS-IS, 690, 691, 694, 821, 833, 836, 922.
 - See also* Intermediate System to Intermediate System

- ISDN, 128, 143, 260, 302, 779, 797, 812, 877, 878, 882. *See also* Integrated Services Digital Network
 - ISM ranges, 318, 325
 - ISO, 113, 114, 128, 144
 - ISO 7498-4, 840
 - ISO 8802.3, 128
 - ISO 8824:1987, 845
 - ISOC, 126, 129
 - ISP, 166, 167
 - ISP network, 204, 732
 - ITU, 128
 - ITU-T, 113, 114, 144, 347, 775
 - ITU-T X.208, 845
 - ITU-T X.700, 840
 - IX, 166, 170
 - IXC, 153, 158
- J**
- Jabber control, 415
 - Jam sequence, 402
 - Jitter, 188
- K**
- Kalpana, 519
- L**
- L2CAP, 485
 - L2VPN, 913, 917
 - Label Distribution Protocol, 821, 824, 833
 - Label stack, 826
 - Label Switch Edge Router, 821, 824
 - Label Switch Router, 821
 - Label Switching Path, 821, 824
 - Label-switching tables, 925
 - Lambda routers, 375
 - LAN, 18, 24, 28
 - extensions, 471
 - switches, 727
 - LAN topologies, 391
 - ring, 391
 - star, 391
 - tree, 391
 - LAP-B, 751, 775, 778, 808, 812
 - LAP-D, 752, 781, 882
 - LAP-F, 751, 808, 812
 - LAP-F, control, 781
 - LAP-F core, 781
 - LAP-M, 808, 812
 - Large-scale integrated circuit, 16
 - Laser diode, 280
 - Layer 2 VPN, 917
 - Layer 3 switch, 757
 - LCAP, 555, 561
 - LCN, 778
 - LCP, 808, 815
 - LDP, 821, 824, 833
 - LEO, 326, 333. *See also* Low Earth Orbit
 - LER, 824
 - Light Emitting Diode (LED), 280
 - Line, 256
 - cable, 258
 - port, 351, 354
 - open wire, 258
 - Link, 256
 - ACL, 483
 - SCO, 483
 - Link aggregation, 555
 - protocol, 555, 561
 - Link Control Protocol, 808, 815
 - Link integrity test, 420
 - Link state algorithm, 694
 - Link state database, 690, 706
 - Link-local addresses, 661
 - Link-state request, 709
 - Link-state update, 709
 - LLC, 388, 391. *See also* Logical Link Control
 - LLC1, 396
 - LLC2, 396

LLC3, 396
 LMDS, 891, 892
 Load balancing, 42, 72, 78, 210
 Local loop:
 universal, 864
 Local multipoint distribution
 service, 891, 892
 Logical channel number, 778
 Logical connections, 76
 Logical link control, 388, 391
 Logical network layout, 91, 93
 Logical network structuring, 96, 98
 Logical segment, 98
 Loopback, 590
 Low Earth Orbit, 326, 333
 LSA, 694. *See also* Link state algorithm
 LSI, 16. *See also* Large-scale integrated circuit
 LSP, 824. *See also* Label Switching Path
 LSR, 821, 822. *See also* Label Switching Route

M

M/M/1 model, 404, 508
 MA, 399, 401
 MAC, 113, 118, 388, 391, 826. *See also*
 Medium Access Control
 MAC address, 46, 119, 399
 grouping, 566
 Mail worms, 198
 Mainframe, 12
 IBM 360, 18
 MAN, 24, 28. *See also* Metropolitan
 Area Network
 Manageability, 204
 Management Information Base, 841
 Manchester code, 117, 299
 Marker, 92
 Mask, 587
 MAU, 458, 461
 Maximum Burst Size (MBS), 787, 791, 800

Maximum delay, 189
 Maximum delay variation, 184, 189
 Maximum network diameter, 405
 MBS, 787, 791, 800. *See also* Maximum
 Burst Size
 MCR, 787, 791
 MD2, 903
 MD4, 903
 MD5, 903
 MDI 436, 443. *See also* Medium
 Dependent Interface
 MDI-X, 443, 492. *See also* Medium
 Dependent Interface with
 Crossover
 port, 443
 Mean Time Between Failures, 191, 192
 Media Access Control, 388, 391
 Medium:
 physical, 256, 258
 shared, 91, 118
 wired, 258
 wireless, 258
 Medium Access Control, 113, 118, 388,
 391, 826
 Medium Dependent Interface, 436, 443
 Medium Dependent Interface with
 Crossover, 443, 492
 Medium Earth orbit, 326, 333
 Medium Independent
 Interface (MII), 436, 440
 MEMS, 367, 375
 MEO, 326, 333. *See also* Medium Earth
 Orbit
 Message, 32, 117, 125
 Message transmission time, 84
 Metcalfe, Robert, 389
 Metric, 52, 549, 703
 Metropolitan Area Network, 21, 24
 MFSK, 286, 289.
 See also Multilevel FSK
 MIB, 841. *See also* Management
 Information Base

- MIB-I, 845, 846
 - MIB-II, 845, 846
 - Micro-electro mechanical
 - systems, 367, 375
 - Microcom, 876
 - Microcomputer LSI-11, 18
 - Microsegmentation, 536
 - Microsoft, 127, 132
 - Microsoft System Management
 - Server, 841
 - Microsoft/IBM, 397
 - Microwave band, 322
 - Minicomputer, 16
 - HP, 18
 - PDP-11, 18
 - Minimum routing table, 633
 - Mixed topology, 41, 45
 - MLPPP, 808, 815
 - MLT-3, 441
 - MMDS, 891, 892
 - MME, 279, 280
 - MNP, 876
 - Mobile access, 468, 471
 - Mobile LANs, 471
 - Modems, 8812, 75
 - Modulation, 38
 - Motorola, 877
 - MP-BGP, 921, 927
 - MPLS, 168, 808, 821. *See also*
 - Multi-Protocol Label
 - Switching
 - header, 825
 - L2VPN, 921
 - L3VPN, 921
 - TE, 821, 832, 834
 - VPN, 821, 832, 917
 - VPN 2L, 920
 - VPN 3L, 920
 - VPN tunnel, 923
 - MS-DOS, 132
 - MS-SPRing, 351, 365
 - MSAU, 458, 461
 - MSP, 351, 363
 - MTBF, 192. *See also* Mean Time
 - Between Failures
 - MTU, 721, 811
 - Multi Link PPP, 808, 815, 816
 - Multi-service network, 22
 - Multi-terminal system, 12
 - Multicast address, 45, 399, 400, 590
 - Multilevel FSK, 286, 289
 - MultiLink Trunking, 557
 - Multipath fading, 324
 - Multiple access, 399, 401
 - Multiplex section protection, 351, 363
 - Multiplex section shared protection
 - ring, 351, 365
 - Multiplexer, 58
 - Multiplexing, 28, 57, 675
 - Multi-Protocol Label Switching, 808
- N**
- Name:
 - flat, 603
 - server, 48
 - NAP, 166, 170. *See also* Network Access
 - Point
 - NAPT, 745, 746. *See also* Network
 - Address Port Translation
 - NAT, 726, 745. *See also* Network
 - Address Translation
 - traditional, 745
 - National Computer Security
 - Center, 128
 - National terminal number, 777
 - NCP, 125, 131, 808, 815
 - NCSC, 128
 - NDIS, 489
 - Near End Cross Talk, 261, 267
 - Negative Acknowledgment, 195
 - NetBEUI, 132, 397
 - NetBIOS, 132, 397, 900
 - NetBIOS/SMB, 129, 145

- NetWare, 408
- Network:
 - circuit-switched, 257
 - computer, 10, 66
 - congestion, 210
 - constituent, 583
 - convergence, 211
 - corporate, 23, 160, 204
 - data-transmission, 11
 - datacom, 11
 - department-level, 162
 - enterprise-wide, 150
 - heterogeneous, 203, 205
 - ideal, 184
 - infocommunication, 23
 - Metropolitan Area, 21
 - multi-service, 22
 - overlay, 16
 - switching, 50, 56
 - telephone, 66, 257
 - topology, 41
 - transmission, 16, 257
 - Wide Area, 14
 - workgroup-level, 162
 - X.25, 15
- Network Access Point, 166, 170
- Network adapter, 91, 92
- Network address, 120, 584
- Network Address Port Translation, 746
- Network Address Translation, 726, 745
- Network application, 36
- Network architecture, 108
- Network control protocol, 808, 815
- Network convergence, 10, 257
- Network File System, 125
- Network interface, 45
- Network Interface Card, 62, 92, 488
- Network layer, 113, 114, 119
- Network layout:
 - logical, 91, 93
 - physical, 91, 93
- Network manageability, 203, 204
- Network Management
 - System, 204, 808, 839
- Network node, 41
- Network number, 582, 584
- Network Operating
 - System, 15, 29, 34
- Network response time, 184, 189
- Network scalability, 182
- Network server, 18
- Network sniffing, 488, 494
- Network technology, 14, 18
- Network topology, 182
 - choosing, 28
 - common bus, 41, 44
 - mixed, 41, 45
 - ring, 41, 42
 - star, 41, 44
 - tree, 44
- Network-to-network
 - interface, 775
- Networks:
 - datagram, 186
 - packet-switched, 186
 - public, 199
 - telecommunication carrier's, 150
- NEXT, 261, 267. *See also* Near End Cross Talk
- NFS, 125. *See also* Network File System
- NIC, 62, 92, 488. *See also* Network Interface Card
- NLSP, 131, 821
- NMS, 204. *See also* Network Management System
- NNI, 775
- Node:
 - transit, 42
 - number, 584
- Nominal protocol rate, 411
- Non Return to Zero with
 - ones Inverted, 294, 298
- Nortel, 557

- Novell, 124, 127, 132, 408
 - Novell 802.3, 407
 - Novell IPX, 816
 - Novell NetWare, 18, 125, 603
 - nrtVBR, 799
 - NRZI, 294, 298, 464
 - Numeric address, 45
 - Nyquist formula, 256
 - Nyquist-Kotelnikov Signal Sampling Theory, 293
 - Nyquist-Kotelnikov Theorem, 293
- O**
- OC-N, 351, 352
 - OFDM, 336, 473
 - Offered load, 37, 39, 184
 - One-way function, 899, 902
 - OPEN LOOK, 128
 - Open Shortest Path First, 136, 690, 691
 - Open specifications, 126, 127
 - Open System, 126
 - Open System Interconnection (OSI), 108, 113, 114
 - model
 - Operating system, 15
 - local, 15
 - network, 15, 29, 34
 - Orbcomm, 336
 - Organizationally unique identifier, 399, 400
 - Orthogonal frequency division, 336
 - Orthogonal frequency division multiplexing, 473
 - OS-400, 510
 - OS/2, 603
 - OSI, 108, 113, 114, 129, 145, 465, 694, 809, 816
 - OSI model, 126, 129, 260, 391, 751
 - layers, 114
 - OSPF, 136, 138, 139, 142, 633, 690, 691, 694, 704, 706, 728, 817, 821, 833, 836, 922
- OUI, 399, 400, 409. *See also* Organizationally Unique Identifier
 - Output queue, 74
 - Overlay network, 16, 809
 - OWE, 899, 902. *See also* One-way function
 - OXC, 375
- P**
- P routers, 924
 - Packet, 50, 72, 113, 117, 120
 - buffering delay, 88
 - Packet assembler–disassembler, 775
 - Packet Delays, 210
 - Packet forwarding methods:
 - connection-oriented, 76
 - connectionless, 76
 - virtual circuit, 76
 - Packet headers
 - additional transmission delay, 88
 - Packet Losses, 210
 - Packet Over SONET, 808, 810
 - Packet switching, 14, 50, 61, 62, 72
 - Packet switching:
 - methods, 23
 - network, 186, 188, 809
 - queue, 210
 - Packet, 72
 - PAD, 775. *See also* Packet assembler–disassembler
 - PAN, 458, 891
 - PAP, 808, 815
 - Parity control, 306, 307
 - Partially connected topologies, 42
 - Passive concentrator, 461
 - Password Authentication Protocol, 808, 815, 816
 - Path MTU Discovery, 668
 - PBX, 150, 152, 159, 885. *See also* Private Branch eXchange

- PCF, 476
- PCF IFS, 479
- PCM, 292
- PCR, 787, 791, 799
- PDA, 91, 480. *See also* Personal Digital Assistants
- PDH, 346, 347, 787, 809. *See also* Plesiochronous digital hierarchy
- PDU, 113, 117, 850. *See also* Protocol Data Unit
- PDV, 450
- PE routers, 924
- Peak Cell Rate (PCR), 799
- Peak information rate, 184, 190, 191
- Penultimate Hop Popping, 831
- Per Hop Behavior, 741
- Permanent virtual circuits, 769
- Personal area networks, 458
- Personal digital assistants, 480
- Phase shift keying, 286, 288
- PHB, 741
- Photonic switches, 367, 375
- PHP, 831
- Physical layer, 113, 114, 117
 - functions, 117
- Physical link, 41, 94
- Physical medium, 256, 258
- Physical network layout, 91, 93
- Piconet, 480, 481
 - master, 481
 - slaves, 480, 481
- PIFS, 479
- Pilot signal, 342
- Ping, 674, 713, 717
- PIP, 659
- PIR, 190
- Plesiochronous digital hierarchy, 346, 347
- PNNI, 788
- Point coordination function, 468, 476
- Point of Presence, 153, 159, 860
- Point-to-multipoint, 156
- Point-to-Point Protocol, 811
- Point-to-point tunneling
 - protocol, 899, 900
- Polling, 471
 - algorithms, 393
- POP, 153, 159, 860
- Port, 29, 674, 675
- Port identifier, 549, 550
- Port numbers:
 - well-known, 676
- POS, 808, 810
- Positive Acknowledgement, 191, 195
- Potential code, 286, 288
- PPP, 118, 136, 808, 811, 815, 826, 866, 868
 - negotiation procedure, 815
- PPTP, 899, 900. *See also* Point-to-point tunneling protocol
- PPVPN, 913, 914
- Preamble, 401, 415
- Presentation layer, 113, 114, 124
- PRI, 877, 880
- Primary rate interface, 877, 880
- Print service, 36
- Priority, 225
- Priority Queuing, 224, 225
- Private Branch Exchange, 22, 150, 152
- Private key, 902
- Private NNI, 788
- Programs:
 - distributed, 36
- Promiscuous mode, 512
- Proprietary standards, 128
- Protected channel technology, 202, 203
- Protocol, 33, 112
 - point to point, 118
- Protocol Data Unit, 113, 117
- Protocol entity, 113
- Protocol set, 108, 113
- Protocol stack, 108, 113
 - OSI, 129
- Protocol suite, 113
- Protocols:
 - connection-oriented, 79

Provider Edge router, 921, 924
 Provider-provisioned VPN, 914
 Proxy-ARP, 867
 PSK, 286, 288
 PSTN, 870
 Public key, 904
 Public networks, 199
 Public switched telephone network, 870
 Pulse Code Modulation, 292, 347
 Punched card, 12
 Pure IP networks, 808
 PVC, 769, 772, 820
 PVV, 427

Q

Q.2931, 770, 820
 Q.921, 781
 Q.931, 882
 Q.933, 769
 QAM, 286, 289, 315. *See also*
 Quadrature Amplitude
 Modulation
 QoS, 23, 180, 182, 707, 808, 810, 819.
 See also Quality of Service
 long-term behavior
 characteristics, 180, 182
 medium-term characteristics, 182
 short-term
 characteristics, 180, 183, 213
 QoS characteristics:
 security, 182
 performance, 182
 reliability, 182
 QPSK, 286, 289. *See also* Quadrature
 PSK
 Quadrature Amplitude
 Modulation, 286, 289, 315
 Quadrature PSK, 286, 289
 Quality characteristics:
 classification, 181
 Quality of Service, 23, 180. *See also* QoS

Queuing:
 negative effects, 210
 Queuing theory, 88, 404

R

Radio band, 322
 Radio Ethernet, 259
 RADSL, 886
 Random access method, 92, 199,
 388, 392
 Random Early Detection, 733
 RARP, 601
 RAS, 36, 861, 866. *See also* Remote
 Access Server
 Rate Adaptive DSL, 886
 Raw 802.3, 407
 RBOC, 157
 RC5, 905
 Real-time traffic, 69, 102
 Receiver, 414
 Receiver window, 686
 RED, 733
 Weighted, 736
 Redirector, 34
 Redundant codes, 294, 300
 Regenerators, 355
 Relative encoding, 294, 305
 Remote access, 861
 Remote access server, 36, 861, 866
 Remote node mode, 861, 867
 Remote office routers, 756
 Repeater, 95, 490
 Request For Comments (RFC), 126, 129
 Request-to-send frame, 478
 Residential access, 468, 471
 Reverse address resolution
 protocol, 601
 Reverse ARP, 601
 RFC, 126, 129, 659. *See also* Request
 For Comments
 RFC 1213, 847

RFC 1490, 782
 RFC 1517–1520, 594
 RFC 1577, 136
 RFC 2858, 927
 RFC 768, 674
 RFC 792, 713
 RFC 854, 868
 Ring topology, 41, 42
 RIP, 131, 136, 139, 142, 633, 690, 691,
 697, 817, 821, 833, 922
 RIP IP, 694, 821
 RIP IPX, 694, 821
 RIP messages, 698
 RIPE, 593
 RIPv1, 697
 RIPv2, 697
 RJ-45, 117, 488, 491
 RMON, 845
 RMON 2, 845
 RMON MIB, 846, 852
 Roberts, Lawrence, 732
 Root port, 549, 550
 Root switch, 549
 Round Trip Time, 190, 674, 688
 Route, 28, 49, 52
 Routed protocol, 123
 Router, 56, 120, 184
 backbone, 753
 functional model, 752
 interface,
 unnumbered, 808, 817
 links advertisements, 706
 Routing, 28, 56
 adaptive, 692
 event-dependent, 691
 flood, 691, 692
 redistributive mode, 695
 static, 692
 Routing advertisements, 693
 Routing Information
 Protocol, 136, 690, 691, 697
 Routing protocol, 113, 123

Routing table, 56, 72, 77, 121, 513, 623
 minimum, 633
 RS-232, 484
 RS-232C, 30, 776
 RS-449, 817
 RSA, asymmetric algorithm, 904
 RSVP, 142, 731
 TE, 838
 RTS frame, 478
 RTT, 190, 674, 688, 717
 rtVBR, 799

S

S/MIME, 900
 SA, 904. *See also* Security
 Association
 SAD, 911. *See also* Security
 Association Database
 SAP, 131
 SAP R3, 171
 SAR, 794, 820
 SAS, 463, 466
 Satellite communications, 326, 331
 Scalability, 24, 182, 203, 204
 Scatternet, 483
 SCP, 152, 153
 SCR, 787, 791, 800
 Scrambler, 298
 Scrambling, 301
 SDH, 125, 157, 346, 352, 458, 787,
 808, 809
 SDH ring, 351, 360
 SDH/SONET, 788, 810
 SDSL, 886
 Secure channel, 899
 Secure Socket Layer (SSL), 125
 Security association, 899, 904
 Security association database, 911
 Security gateways, 899, 906
 Security incidents, 199
 Security policy database, 911

- Security tools:
 - computer, 198, 199
 - network, 198, 199
- Segment, 113, 117, 549
 - logical, 98
- Segmentation And Reassembly (SAR), 794
- Self-healing networks, 361
- Server:
 - file, 36
 - component, 34
- Service:
 - availability, 180
 - control points, 151, 152
 - E-mail, 36
 - file, 36
 - interface, 109
 - print, 36
 - provider, 155, 181
 - remote access, 36
- Service Level Agreement, 180, 183, 213, 820
- Services:
 - network, 29, 36
- Session layer, 113, 114, 124
- Sessions, 76
- Set-up packet, 81
- Setup request blocking, 68
- SHA, 903
- Shannon, Claude, 902
- Shannon formula, 256
- Shared channel, 60
- Shared media, 60, 91, 118
- Shielded twisted pair, 256, 259
- Short IFS, 479
- Signal propagation time, 72, 84
- Signaling protocol, 349, 769
- Signaling system, 7, 870, 873
- Simple Mail Transfer Protocol (SMTP), 135
- Simple Network Management Protocol, 808, 845
- Simplex link, 37, 40
- SIP, 659
- SIR, 190
- Site-local addresses, 662
- SLA, 183, 191, 213, 820
- Sliding window, 191, 195, 808, 814
 - algorithm, 195, 684
- SLIP, 136, 811
- Slot size, 477
- Slot time, 403
- Slotted ALOHA, 392
- Slow links, 195
- SMB, 125, 132
- SMS, 839
- SMTP, 135
- SNA, 114, 128, 145, 782, 900
- SNAP, 410
- SNC-P, 351, 364
- SNMP, 143, 808, 845, 869
- SNMPv2, 845
- SNMPv3, 845
- Socket, 674
- Software router, 757
- SONET, 351. *See also* Synchronous optical NET
- SONET/SDH, 753, 757, 797
- Source Routing, 668, 692
- Spanning tree, 553
 - algorithm, 548, 549
 - protocol, 549
- SPD, 911
- Split horizon, 705
- Spread spectrum methods, 469
- SPX, 124, 131
- SS7, 870, 873. *See also* Signaling system
- SSAP, 409
- SSCOP, 797
- SSL, 898
- STA, 518, 548, 549, 708. *See also* Spanning Tree
- Stack:
 - TCP/IP, 126, 133
- Standard access list, 728

Standards:
 international, 126, 128
 national, 126, 128
 proprietary, 128
 Start of frame byte, 401
 Static routing, 692
 Statistic encoding, 305
 Statistical methods, 186
 Statistical TDM, 309, 313
 STDM, 309, 313
 STM-16/64, 709
 STM-N, 351, 352
 Store-and-forward technique, 66, 74
 STP, 256, 259, 282
 STP Type 1, 458, 462
 Structuring:
 logical, 96, 98
 STS-N, 351, 352
 Subchannel, 69
 Subnet, 21
 Subnetting, 592, 638, 651
 Subnetwork connection
 protection, 351, 364
 Sun, 128
 SunNet Manager, 841
 Supernetting, 592, 651
 Sustained information rate, 184, 190
 SVC, 769
 Switch, 55, 100, 184
 nonblocking, 524
 performance, 100
 Switch identifier, 550
 Switched virtual circuits, 769
 Switching, 28, 49, 55
 fabric, 74
 hub, 100
 table, 55, 72, 77, 121
 Symbol suppression, 294, 305
 Symbolic address, 45
 Symmetric cryptographic system, 902
 Symmetric DSL, 886
 Synchronization, 37, 38

Synchronous Digital Hierarchy, 125,
 346, 352
 Synchronous optical NET, 351
 SynOptics, 436
 System:
 batch-processing, 12
 distributed, 11
 multi-terminal, 12
 time-sharing, 13
 System Management System
 (SMS), 839, 841

T

T-carrier systems, 346, 347
 T-connector, 416
 T1, 816
 T2, 347
 Tag switching, 821, 822
 TCP, 124, 135, 137, 667, 674, 728, 847
 ports, 676
 segment format, 679
 TCP/IP, 108, 114, 119, 129, 145, 166,
 204, 397, 484, 582, 821, 845
 types of addresses,
 TCP/UDP port number, 48
 TDM, 50, 58, 261, 309, 311, 809, 870
 TE, 808, 836
 tunnels, 834
 Technology:
 Bluetooth, 91
 network, 14, 18
 packet switching, 14
 Telecommunication carrier, 150, 153
 Teledesic, 336
 Telephone line:
 analog, 38
 Telepolling, 23
 Telnet, 135, 676, 721, 868, 869
 Terminal access mode, 861, 868
 Terminal Multiplexer, 355
 TFTP, 676, 721

- Throughput, 37, 39
 - Time division duplex, 314
 - Time Division Multiplexing (TDM), 50, 58, 261, 309, 311, 388
 - Time to Live, 554
 - Token Bucket algorithm, 733, 734
 - Token passing, 393
 - Token Ring, 10, 14, 18, 20, 21, 24, 60, 117, 119, 136, 162, 299, 389, 458, 525, 550, 583, 597, 751
 - active monitor, 459
 - early token release, 460
 - multistation access unit, 458, 461
 - token-holding time, 460
 - Token Ring 16 Mbps, 460
 - Token Ring 4 Mbps, 459
 - Token-holding interval, 393
 - Topological database, 706
 - Topologies, 41
 - partially connected, 42
 - fully connected, 41, 42
 - typical, 93
 - Traceroute, 674, 719
 - Tracert, 719
 - Traffic:
 - aggregates, 228
 - bursty, 15, 189
 - Engineering, 210
 - filtering, 727
 - localization, 97
 - pulsation coefficient, 71, 72
 - real-time, 23, 102
 - real-world, 210
 - Trailer, 72, 116
 - Transceiver, 413, 414
 - Transit node, 42
 - Transmission:
 - connection-oriented, 76
 - connectionless, 76
 - Transmission Control Protocol, 135
 - Transmission media:
 - shared, 389
 - Transmission network, 16, 809
 - Transmitter, 414
 - Transparent bridge algorithm, 511
 - Transport layer, 114, 123, 124
 - Transport service, 139
 - Tree topology, 44
 - Trellis codes, 290
 - Tributary ports, 351, 354
 - Tributary unit, 351, 353
 - Triggered updates, 705
 - Triple DES, 905
 - Truncated binary exponential back-off algorithm, 403, 477
 - Trunk, 555
 - TTL, 554, 633, 692, 717, 739
 - TUBA, 659
 - Twisted pair:
 - shielded, 256, 259
 - unshielded, 256, 259
- ## U
- U.S. Department of Defence, 15, 850
 - UBR, 799
 - UDP, 124, 135, 137, 667, 674, 702, 728, 847
 - datagram, 679
 - packet, 674, 677
 - ports, 676
 - socket, 679
 - UNI, 775, 813. *See also* User-to-Network Interface
 - Unicast, 399, 400
 - address, 45
 - messaging, 22
 - Universal local loop, 864
 - UNIX, 120, 127, 510, 630, 633, 719, 730, 757, 869
 - Unshielded twisted pair (UTP), 256, 259, 418
 - Unspecified Bit Rate (UBR), 787, 792
 - User Datagram Protocol, 135
 - User-to-network interface, 775
 - Utilization coefficient, 216, 219

UTP, 282, 418. *See also* Unshielded twisted pair
 Type 3, 458, 462
 Type 6, 458, 462

V

V.21, 875
 V.34, 875, 887
 V.34+, 875
 V.35, 816
 V.42bis, 306
 V.90, 887
 V.92, 876
 Variable Bit Rate (VBR), 212, 787, 789, 789
 VCI, 770, 796
 VDSL, 886
 Very high-speed DSL, 886
 Very small aperture terminal, 326, 333
 Virtual channel, 76
 Virtual channel identifier, 769, 770
 Virtual circuit, 76, 80, 102, 119
 Virtual LAN, 519, 548
 Virtual path identifier, 796
 Virtual Private Network, 156, 198, 200
 Visible light band, 322
 VLAN, 548, 563, 758, 839, 898
 Voice over IP (VoIP), 10
 VPI, 796. *See also* Virtual Path Identifier
 VPN, 155, 156, 198, 200, 898, 913
 VSAT, 333
 Vulnerabilities, 198

W

WAN, 14, 15, 20, 24, 28, 808
 WAN link, 21, 779
 Wave Division Multiplexing, 309
 Wave routers, 367, 375
 WDM, 309, 310, 540. *See also* Wave Division Multiplexing
 Weighted Fair Queuing, 229
 Weighted queuing, 224, 228

Weighted RED, 736
 WEP, 468, 480. *See also* Wired Equivalent Privacy
 WFQ, 229. *See also* Weighted Fair Queuing
 Wide Area Network, 14
 Window size, 195
 Windows, 120, 125, 757
 2000, 633, 719
 XP, 489
 Wired (guided) medium, 258
 Wired Equivalent Privacy, 468, 480
 Wired OR scheme, 44
 Wireless (unguided) medium, 258
 Wireless LANs, 891
 external noise, 468
 Wireless link, 318, 320
 Wireless local loop (WLL), 318, 322, 891, 892, 318, 322, 891, 892
 World Wide Web, 21
 WorldCom, 169
 WRED, 736
 WWW, 139, 676, 870. *See also* World Wide Web

X

X.121 CCITT Recommendation, 777
 X.21, 775, 777
 X.21bis, 777
 X.25, 15, 80, 81, 128, 136, 137, 168, 583, 751, 768, 779, 782, 812, 842, 868, 882, 915
 data link layer, 778
 network layer, 778
 physical layer, 777
 X.400, 131
 X.500, 131, 912
 xDSL, 886
 Xerox, 128, 388, 407, 414
 XGMII, 540