

# Index

- Access control
  - closed access, 198
  - hybrid access, 199
  - open access, 198
- Access control triggers
  - data transmission service, 195
  - location area update, 195
- Access methods, 277
  - CSG, 147, 153, 279
  - hybrid, 147, 284
  - open, 118, 147, 281
- Access networks, 39
- Access Point Management System, 49
- Adjacent Channel
  - Interference Rejection (ACIR), 156
  - Leakage Ratio (ACLR), 156
  - Power Ratio (ACPR), 156
  - Selectivity, 156
- Aggressor, 150
- Allocation
  - frequency, 248
  - power, 245
- Allowed CSG list, 193
- Allowed IMSI list, 192
- Analytical model, 106
- Angle of arrival, 165
- Antenna, 120
  - element, 254
  - pattern, 253
- Applications, 287
  - development, 288
  - evolution, 287
- Architecture
  - lu-over-IP, 82
  - lub-over-IP, 82
- Area Spectral Efficiency, 173–174
- AUC, 73
- Authentication, *see* Security
- Automatic, 228
- Autonomous, 228
  
- Badness, 249
- Base station, 117
- BCCH, 239
- Beamforming, 169
- Best SINR, 124
- Bit rate, 128
- Blind Source Separation, 168
- BSC, 72
- BSIC, 239
- BTS, 71
- Burst, 120, 124
  
- Capacity, 130
- Capacity-limited system, 145
- CAPEX, 229
- CDMA, 226, 244
  - modulation, 80
  - processing gain, 81
  - reception, 81
  - signals, 80
- Cell, 118
- Cell handover
  - fingerprint information, 219

- Cell reselection
  - equivalent PLMN, 209
  - virtual neighbour cell list, 215
- Cell selection
  - manual PLMN selection, 204
  - national roaming, 205
- Cell site, 117
- Chip rate, 80, 85
- Clock accuracy, 261
- Closed subscription group ID, 191
- Co-channel, 244
- Co-channel deployment, 130, 154
- Cognitive radio, 237
- Collision, 239
- Concentrator, 41
- Confusion, 239
- Connected home, 288
- Controller, 39
- Coupling loss, 164
- Coverage, 130, 131, 246, 256
- Coverage areas, 148, 155
  - OFDMA, 149
- CQI, 125
- Crystal, 262
- CS domain, 54
- CSG, 118
  
- Dead zone, 147, 154
- Distributed antenna systems, 21
  - active, 25
  - hybrid, 26
  - passive, 21
- Doppler effect, 164
- Driver, 229
  
- EAP, 272
- EIR, 73
- Event
  - unwanted, 247, 256
  - wanted, 247
- Exclusion region, 172
- Experimental evaluation, 130, 253
  
- Fading, 90, 93, 97, 164
- Femtocell Access Point (FAP), 13, 46
- Femtocell ID, 232
  
- Femtocell identifier
  - dedicated frequency, 186
  - hierarchical cell structure, 184
  - PLMN ID, 185
  - PSC/PCI split information, 186
- Femtocells, 33
  - advantages, 34
  - deployment, 34
  - layer, 145
  - penetration, 154
- Femtozone, 288
- FIFO, 124
- Find femtocells
  - neighbour cell list, 189
  - UE autonomous search, 190
- FRESH filters, 167
- FTP, 141
  
- GMSC, 73
- GPRS, 73
  - GGSN, 73
  - SGSN, 73
- GSM, 70, 226
  - AGCH, 77
  - base station subsystem, 71
  - BCCH, 75, 77
  - burst, 75
  - CCCH, 77
  - DCCH, 78
  - FCCH, 77
  - frequency bands, 73–75
  - multiframe, 76
  - network, 70
  - network switching subsystem, 72
  - PCH, 77
  - RACH, 77
  - SACCH, 76, 78
  - SCH, 77
  - SDCCH, 78
  - TCH, 76
  - TDMA frame, 75–76
  
- Handover, 232, 246
- Health issue, 289
- Hidden femtocell, 236
- HLR, 72

- HSDPA, 88–89
- HSPA, 227
- HSUPA, 89–90
  
- IC, *see* Interference cancellation
- IEEE1588, 265
- IMS, 64
- Indoor coverage techniques
  - comparison, 36
- Interference, 126
  - adjacent channel, 176
  - at the FAP, 157
  - at the Macrocell Base Station (MBS), 164
  - co-channel, 165, 175
  - co-layer, 146, 244, 245
    - approaches, 151
    - CDMA, 151–153
    - downlink, 152–154
    - OFDMA, 152–154
    - problems, 146
    - uplink, 151–152
  - cross-layer, 154–161, 166, 244, 245
    - approaches, 157
    - CDMA, 157–161, 170
    - downlink, 159–162
    - OFDMA, 158–159, 160, 161–162
    - problems, 154
    - uplink, 160, 157–159, 170
  - intercarrier, 156
- Interference avoidance, 170–174
  - CDMA, 170–172
  - OFDMA, 172–174
- Interference cancellation, 165–170
  - cyclostationary, 167
  - downlink techniques, 169
  - filter, based on, 166–167
  - multi-user, 167
  - parallel (PIC), 166
  - Single Antenna (SAIC), 170
  - statistics, higher order, 168
  - successive (SIC), 167
  - uplink techniques, 165–169
- Interference-limited system, 145
- Interference-plus-noise, 159
- IPsec, 271
  
- Iu-over-IP, 42, 74
- Iub, 40
- Iub-over-IP, 40, 74
- Iuh, 58, 60
  
- Joint detection, 167
- Joint hopping, 171
  
- Leaky cable, *see* Radiating cable
- Location, 275
- Location area identity, 190
- LTE, 61, 99, 228
  - data rate, 100–101
  - EUTRAN
    - downlink, 100–101
    - uplink, 101–102
  - frame, 99
  - reference symbols, 100
  - resource block, 100
  - slot, 99
- LUT, 108
  
- MAC, 107
- Macrocell, 15
  - layer, 145
- Measurement report, 172, 236, 251
- Measurements, 225, 230, 245
- Media gateway controller, 49
- Message
  - broadcast, 249
  - exchange, 235
- Microcell, 17
- MIMO, 97, 169
- MMSE detector, 167
- MSC, 72
- Multipath channel, 90, 91
  
- Near–far problem, 162, 162–165
- Neighbouring list, 232, 241
- Network listener, 233, 234
- Noise, 128
- Noise rise, 151
- Non-subscribers, 118
- Null steering, 169
  
- OfCom, 166
- OFDM

- OFDM (*continued*)
  - advantages, 95
  - cyclic prefix, 93
  - modulation, 92
  - subcarrier, 92, 93
  - system, 92
- OFDMA, 94, 100, 244
- OPEX, 229
- Optimization, 226, 229
- Optimum combining, 169
- Orthogonality, 130, 244
  - loss, 156
- Oscillator, 262
  - OCXO, 264
  - TCXO, 263
- Outage, 129
  
- PCI, 232, 239
- Peak-to-average-power-ratio, 94
- Performance, 106, 134
- PF, 124
- PHY, 107
- Picocells, 30
  - advantages, 30
  - applications, 32
  - deployment, 31
- Planning, 226
- Plug and play, 232
- Poisson, 140
- Power
  - control, 245
  - pilot, 256
  - transmitted, 245
- Power control, 162
- Power limit
  - at FAP, 161
  - at UEs, 164
- Prediction, Forward Linear (FLP), 166
- Propagation model, 109
- Proportional fair scheduling, 174
- PS domain, 55
  
- RAB, 83, 120, 125
- Radiating cable
  - alternative, 30
  - deployment, 28
- Radio link, 120
- RAN network controller, 48
- Registration, 232
- Repeaters
  - active, 19
  - passive, 18
- Rise-over-thermal, 158
- Round robin scheduling, 174
  
- SC-FDMA, 96, 101
- Scenario, 130
- Scheduling, 124
- Security, 270
  - risks, 270
- Security gateway, 47
- Self-configuration, 225, 228, 230
- Self-healing, 225, 230
- Self-optimization, 225, 228, 230, 252, 256
- Self-organization, 105, 225, 228,  
245–249, 251
- Sensing, 225, 233, 234, 246
- Service, 120, 123
- Signal
  - carrier, 128
  - interference, 128
- Signalling gateway, 49
- SIM, 73
- Simulation
  - computer, 107
  - dynamic, 116, 138
  - link-level, 106, 107
  - static, 116, 117, 121
  - system-level, 106, 108
- Single Antenna IC (SAIC), 165
- SIP, 43
- Slot, 119, 125
- Snapshot, 116, 121
- Source separation, 168
- Spatial processing, 169
- Spectral
  - efficiency, 109
  - occupancy, 159
- Spectrum, 244
  - splitting, 156, 165, 172
  - spread, 79
- Spreading factor, 80, 85

- State Insertion (SI), 167
- Subcarrier, 119
- Subchannel, 119, 248, 249, 251
- Subchannelization, 97
- Subscribers, 118, 232
- Symbol
  - OFDM, 119
- Synchronization, 150, 156, 233
  - backbone, 265
  - cells sensing, 267
  - GPS, 268
  - TV, 268
- Throughput, 129
- Time-hopping, 170
- Timing
  - accuracy, 261
  - requirements, 262
  - synchronization, 264
- Tracking area identity, 190
- Traffic
  - class, 124
  - modelling, 140
- Traffic map, 119, 123
  - indoor, 123
  - outdoor, 123
- Tuning, 225
- Two-layer network, 145
- UMA, 70
- Umbrella macrocell, 145, 166
- UMTS, 78
  - AS, 83
  - channels, 84, 86
    - logical, 85–86
    - physical, 87–88
    - transport, 86–87
  - frame, 85, 85
  - frequency bands, 83
  - NAS, 83
  - network, 81
  - RNC, 82
  - slot, 85
  - UTRAN, 82
- User, 118
  - status, 129
- UTRA, 78
- VLR, 72
- VoIP, 141
- WiFi, 69
- WiMAX, 95–96, 227
  - frame, 97
  - MAC layer, 98–99
  - physical layer, 97–98
  - service types, 98