

Index

Note: Figures and Tables are indicated by *italic page numbers*

- AC powder electroluminescence (ACPEL) 252–4
 - compared with DCPEL 250
 - light emission mechanism 257–61
- AC powder electroluminescent (ACPEL) devices
 - applications 253–4, 267
 - limitations 254, 265–7
 - high operating voltages 266
 - lifetime and luminance degradation 254, 265–6
 - low luminance 266
 - moisture sensitivity 266–7
 - materials 262–5
 - operational characteristics 253, 261–2
 - phosphors used 252, 255
 - structure 255
- accelerating point charge
 - electric field emanating from 2–3
 - magnetic field emanating from 3
- activators (for phosphors) 34, 43, 81, 103, 255, 263, 264
- active matrix OLED (AMOLED) displays 111–12, 124, 125, 126, 127–8, 136
 - manufacturing processes 149–55
- ADS108GE luminescent polymer 177
 - in planar LECs 190, 199, 201
- AllnAsP LEDs
 - color triangle (on CIE diagram) 77
 - properties compared with other light sources 144
- AllnGaN LEDs, properties 208
- AllnGaP LEDs, properties 208, 209
- alkaline earth metal oxo-nitride phosphors 102
- alkaline earth metal silicate phosphors 94–5
- alkaline earth metal silico-nitride phosphors 101
- alkaline earth metal sulfide phosphors 96–7, 234
- alkaline earth metal thiogallate phosphors 97–9
- alternating current . . . *see* AC . . .
- anthracene
 - electroluminescence of 162, 166, 257
 - in OLEDs 114, 118, 120, 121, 162
 - photoluminescence 257
- anti-Stokes shift 32
- artificial atoms (quantum dots) 23, 25
- atomic layer deposition (ALD) process
 - phosphor films in TFEL devices 243–4
 - thin-film encapsulation 154–5
- atomic layer epitaxy (ALE) 243
- Auger electrons 21, 35
- Auger recombination process 31, 35, 56
- avalanche breakdown, in TFEL devices 224, 226
- BaAl₂S₄:Eu phosphor 244, 246
- backlighting applications 228, 262
- band edge emission 31–2
 - improvement in CdS Qdots 51
- band gap 19, 20, 26–7
 - effect of quantum confinement (Qdots) 25, 26–30

- listed for various semiconductors 28, 43, 46, 50, 56, 59
 - see also* energy band diagram
- barium sulfide (BaS) 19
- Barix multilayers, thin-film encapsulation of
 - OLEDs by 154, 155
- BaY₂SiAl₄O₁₂:Ce phosphor 93
- BDOH-PF 179
- BDOH-PF-based LECs 174, 178, 180, 182
- binary oxide dielectrics, properties 235
- bipolar field-emission model 260
 - applied to ZnS:Cu phosphor in ACPEL 258–60
 - experimental evidence 260
- blackbody radiation 2, 12–15
 - Planckian locus in CIE diagram 84, 112, 113
 - spectrum 15
- blinking effect in quantum dots 35, 36
- block copolymers, in LECs 180
- blue LEDs 76, 208, 212
 - wavelength for maximum efficiency 78, 80
- Boltzmann statistics 12
- bulk homojunction LECs 196–201

- Ca₃Sc₂Si₃O₁₂:Ce phosphor 93
- CaAlSiN phosphor 216
- CaAlSiN₃:Eu²⁺ phosphor 101
- cadmium selenide (CdSe) 24, 26, 28
- cadmium selenide (CdSe) quantum dots 56–9
 - bioapplications 59
 - blinking effect 35, 36
 - doped CdSe Qdots 59
 - electroluminescence device using 58
 - optical properties 56–7
 - surface passivation of 57–8
- cadmium sulfide (CdS) 24, 28, 50
- cadmium sulfide (CdS) quantum dots 29, 50–5
 - as bio-imaging probes 53–5
 - doped CdS Qdots 51–2
 - electroluminescence devices using 52–3, 54
 - metal-coated 51
 - optical properties 50–1
- cadmium sulfoselenide (CdS_xSe_{1-x}) 24
- cadmium telluride (CdTe), properties 28, 59
- cadmium telluride (CdTe) quantum dots 59–62
 - bioapplications 61–2
 - in photonic devices 62
 - surface passivation of 59–60
 - type II 60–1
- cathodoluminescence (CL) 2, 20, 21, 22
- cathodoluminescent phosphors 83, 95, 97
- ceramic sheet dielectric electroluminescent devices 225–6, 240
- cerium-activated phosphors 81, 83–93, 94, 234, 234
- chemical vapor deposition (CVD) 42, 154, 244
- chemiluminescence 20
- CIE chromaticity diagram 112, 113
 - blackbody radiation locus 84, 112, 113
 - coordinates, various phosphors 84, 86, 98, 234
 - emitters for white OLED 121
 - LEDs 77
 - Planckian Locus 84, 112, 113
 - tandem white OLEDs + improved color filters 139, 140
 - thiogallate phosphors 98
 - YAG phosphors 84, 86
- color conversion phosphors 75–109
 - activators for 81
 - alkaline earth metal oxo-nitrides 102
 - disadvantages of using LEDs without 76–8
 - excitation wavelengths listed 103
 - metal nitrides 100–1
 - metal oxide based phosphors 83–95
 - metal sulfide based phosphors 95–100
 - problems outstanding 82–3
 - properties required 80
 - requirements 79–80
 - synthesis 83
 - white light generation using 76, 81–2
- color correlation temperature (CCT)
 - lighting applications 112, 146
 - phosphors 83
 - white LEDs 215
- color displays
 - RGBW 4-pixel patterning 127–8
 - tandem OLEDs 136–7
 - white emitter + RGB color filters 123, 124–6
- color rendering 79, 213–14
- color rendering index (CRI) 79
 - improvement using tandem white OLEDs 144–5
 - requirements for various situations 79
 - various OLEDs 144
- color-cathode LCDs 137, 246
- complex oxide dielectrics, properties 236
- computerized tomography (CT), contrast agents 53
- ‘conducting polymers’ 176
- conduction band 19, 20, 227
- conjugated polymers

- electroluminescence from 142, 163–5, 167, 176
 - LECs based on 176
 - OLEDs based on 142–3, 164–5
- contact electroluminescence 256
- copper(I) chloride (CuCl) 24
- Coulombic attraction 27
- Coulombic interaction energy 17, 28, 29–30
- crown ether–alkali metal complexes 182
- crown ethers
 - in backbone of luminescent polymers 179, 180
 - as electrolyte in LECs 182, 188
 - as side groups on luminescent polymers 178
- crystal field splitting 17–18

- DC powder electroluminescence (DCPEL) 249–52
 - compared with ACPEL 250
 - light emission mechanism 251, 252
- DC powder electroluminescent (DCPEL) devices
 - operating mechanism 250–1
 - pulse-wave mode 251
 - structure 250
- defect emission 32–3
- degenerate orbitals
 - doubly degenerate 18
 - five-fold degenerate 18
 - triply degenerate 18
- density of states (DOS) 22, 23
- Destriau cell 252, 253
- Destriau effect 161, 252–3
- dielectrics
 - in ACPEL devices 255
 - in TFEL devices 235, 236
- dipole–dipole energy transfer 15–16
- dipole radiator 5
- direct band gap semiconductor 20
- direct current . . . *see* DC . . .
- display applications
 - OLEDs 112, 122–30, 223
 - TFEL devices 245–7
- dopants (for phosphors) *see* activators
- dynamic bond percolation (DBP) theory 10

- effective mass approximation (EMA)
 - model 27–8
- Einstein coefficients 8–9
- electrical double layer, at LEC
 - electrode–polymer interface 171
- electrochemical doping, in LECs 170, 171
- electroluminescence, first reported 75
- electroluminescence (EL) 2, 20, 21, 21, 161
 - applications 2, 161
 - conjugated polymers 142–3, 163–5
 - first observed 21, 75, 252
 - luminous efficiency 2
 - small organic molecules 114, 162–3
 - see also* powder electroluminescence; thin-film electroluminescence
- electroluminescent (EL) devices
 - advantages in lighting applications 21
 - applications 2, 161, 223
 - compared with other devices 144, 224
 - materials used 223
 - quantum dots used 52–3, 54, 58
- electroluminescent (EL) phosphors 95, 97, 233–4, 257
- electroluminescent (EL) turn-n voltage, listed for various materials 166
- electromagnetic radiation
 - energy released as 3–4, 7
 - selection rules and 7
- electromagnetic spectrum
 - blackbody radiation 15
 - visible light 1
- electron beam lithography 39
- electron spin resonance (ESR) spectroscopy, Mn-doped ZnS Qdots 47
- energy band diagram
 - ACPEL device 259
 - DCPEL device 252
 - semiconductors 20
 - TFEL devices 227
 - see also* band gap
- energy level diagram, ZnS:Cu,Al phosphor 262–3
- etching processes, Qdots manufactured using 39
- europium-activated phosphors 81, 94–5, 96–100, 234, 234
- exciton binding energy 27
 - listed for various semiconductors 28
- exciton Bohr radius 27
- excitons, relaxation processes 30–5
- external quantum efficiency (EQE) 209
 - LECs 178, 188
 - LEDs 77, 209, 210
 - OLEDs 141
- extrinsic luminescence 34

- flash evaporation sources, OLED
 manufacture 152–3
- flexible ACPEL lamps 267
- flexible electroluminescent film 164, 241, 242
- flip–flop bonding of LEDs 210
- fluorescence 31
- fluorescent lighting
 compared with other light sources 144, 219
 requirements for OLEDs in competition 143
- focused ion beam (FIB) technique 39
- Förster resonance energy transfer (FRET) 59, 60
- Fowler–Nordheim equation 259–60
- frozen-junction LECs 171, 183–8
 current/voltage/light intensity characteristics 184
 drawback 187
 EL turn-on response 184–5
 operational stability 185
 photovoltaic response 186–7
 in planar configuration 185–6
 room temperature operation 187–8
- full-color displays
 FTEL 245–7
 LCD 128, 245
 OLED 127–8, 136–7, 156
- full-color electroluminescence
 color-by-blue approach 246–7
 color-by-white approach 245–6
 patterned phosphors used 246
- gadolinium-functionalized quantum dots 52, 54–5, 56
- gallium aluminoarsenide (GaAlAs) LEDs 208
- gallium arsenide (GaAs) 28, 62
- gallium arsenophosphide (GaAsP) LEDs 76
- gallium nitride (GaN) 28, 62
- gallium phosphide (GaP) 20, 28, 62
- germanium, properties 28
- glass substrate thin film dielectric
 electroluminescent devices 224, 225, 235–7
- green LEDs 76, 208
- harmonic perturbation 9–12
- highest occupied molecular orbital (HOMO) 20, 29
- hot-solution decomposition process, Qdots synthesized using 41
- hydrothermal synthesis, of quantum dots 41
- impact-excitation/ionization,
 electroluminescence caused by 161, 162, 233, 257
- incandescent lamps, compared with other light sources 144, 219
- indirect band gap semiconductor 20
- indium antimonide (InSb) 28
- indium arsenide (InAs) 28, 62
- indium gallonitride (InGaN) LEDs 76, 208
 color triangle (on CIE diagram) 77
 luminous efficiency compared with other light sources 77
 properties 208, 209
 with ‘green’ and ‘red’ phosphors 102, 208
- indium nitride (InN) 28, 62
- indium phosphide (InP) 28, 62
- ink paintings, illumination of 220
- inkjet printing, color patterning of OLEDs using 124–5, 142
- internal quantum efficiency (IQE)
 calculations 211
 fluorescent vs phosphorescent emitters in OLEDs 140
 LEDs 210–11
 plot vs emission wavelength 78
 quantum dots 48, 49, 52, 56, 57, 61
- Laporte selection rule 21, 34
- large-area coatings, OLEDs, manufacturing processes 149–55
- large-area displays, OLED-based 124–6
- laser thermal printing, color patterning of OLEDs using 125
- lateral epitaxy on patterned sapphire (LEPS) 209–10
- LCAO-MO model 29–30
- lead selenide (PbSe) quantum dots 63, 63, 64
- lead sulfide (PbS) 24, 28
- LECs *see* polymer light-emitting electrochemical cells
- LED lighting
 applications 219, 220
 characteristic features 217, 218, 220
 energy conservation benefits 221
 future prospects 220–1
- ‘light-emitting battery’, LEC as 174
- light-emitting diodes (LEDs)
 color conversion phosphors 79–83
 alkaline earth metal oxo-nitrides 102
 metal nitrides 100–1
 metal oxide based phosphors 83–95

- metal sulfide based phosphors 95–100
- disadvantages without color conversion phosphors 76–8
- green window problem 78
- history of development 75–6
- inorganic
 - applications 207
 - compared with other devices 143, 144, 183, 224
 - mode of operation 207
 - RGB LEDs approach to white light 76, 81, 208, 212, 213
 - types 211–12
 - see also* organic light-emitting diodes (OLEDs)
- lighting applications
 - comparison of various light sources 144
 - white OLEDs for 112, 143–8
 - performance and cost goals 143–4
- linear combination of atomic orbitals (LCAO) theory 29
 - see also* LCAO-MO model
- liquid crystal display (LCD) TV
 - applications 128, 247
 - color filters 137, 139, 245
- Lossev effect 252
- lowest unoccupied molecular orbital (LUMO) 20, 29
- LS* coupling 17
- luminance
 - ACPEL devices 261
 - LECs 171, 173, 178, 182, 188, 189
 - OLEDs 118, 134, 144
 - quantum dots 58
- luminance efficacy
 - OLEDs 117, 118
 - polymer OLEDs 143
 - tandem OLEDs 133, 134
- luminescence
 - principles 1–18
 - types 2, 20
 - see also* cathodoluminescence; electroluminescence; photoluminescence
- luminescent conjugated polyelectrolytes (LCPEs) 183
- luminescent polymers
 - block copolymers with ion-conductive side groups 180
 - conventional conjugated polymers 142, 176, 177
 - with ion-conductive side groups 176, 178–80
 - in LECs 176–80
 - in OLEDs 142, 164
 - various phosphors (listed) 234
- luminous efficacy/efficiency
 - thiogallate phosphors 99, 100
 - white LEDs 214, 219, 220, 221
 - white OLEDs, compared with other light sources 144
- YAG:Ce phosphors 86–7
 - effect of praseodymium as co-activator 88–90
 - factors affecting 87–8, 92–3
 - (Y_xGd_{1-x})AG:Ce phosphors 91
- magnetic resonance imaging (MRI) properties, quantum dots 52, 54–5, 56
- manganese-activated phosphors 43, 46–7, 227–8, 233, 234
- mechanoluminescence 20
- medical applications, white LEDs 218, 220
- MEH-PPV based LECs
 - blend with PEO + OCA 181–2
 - bulk homojunction LECs 198, 200, 201
 - device characteristics 171, 172, 173
 - factors affecting stability 185–6
 - planar LECs 188, 189, 191, 194–5
- MEH-PPV based LEDs 142–3, 164, 166, 167
- MEH-PPV polymer 177
 - electroluminescence from 142–3, 164–5, 166
 - photoluminescence 191
- metal chalcogenide phosphors 96, 234
- metal nitride based phosphors 100–1, 234
- metal oxide based phosphors 83–95, 234
- metal sulfide based phosphors 95–9, 234
- micro-displays, OLED-based 124, 125
- microemulsion techniques, Qdots synthesized using 40, 49
- molecular beam epitaxy (MBE) 42, 243
- molecular orbital (MO) theory *see* LCAO-MO model
- moving point charge, magnetic field emanating from 1, 2
- multicolor optical coding technique, quantum dots used 56–7, 59
- Na₂Gd₂B₂O₇:Ce³⁺,Tb³⁺ phosphor 94
- nanomaterials 22–3
- nanoparticles, size 23
- nanostructure, categories 22
- nanostructured materials 22–3

- National Television System Committee (NTSC)
 color gamut ratio 135
 listed for white tandem OLEDs 134, 136,
 137
- near-infrared-emitting quantum dots 61
- near-ultraviolet LEDs 207
- phosphors for 95
- properties 208
- in white light generation
 four (OYGB) phosphor approach 215–16
 three (RGB) phosphor approach 208,
 214–15
- nitride phosphors 100–1
- non-radiative relaxation process 34–5
- octyl cyanoacetate (OCA), as additive to
 electrolyte in LECs 181–2
- office lighting requirements 144
- OLEDs *see* organic light-emitting diodes
- oligo(ethylene oxide)
 in backbone of luminescent polymers 179,
 180
 as side groups on luminescent polymers 178,
 179
- on–off bioswitches 59
- operational stability
 LECs 174
 OLEDs 117–19
- organic light-emitting diodes (OLEDs) 111–59
 compared with other light sources 143, 144
 display applications 112, 122–30, 163, 223
 driving voltage of various
 configurations 165, 166
 early developments 111, 163
 electron-transport layer (ETL) in 114, 163
 hole-transport layer (HTL) in 114, 163
 lighting applications 112, 143–8
 manufacturing processes 149–55, 156
 flash evaporation sources 152–3
 thin-film encapsulation 153–5
 vacuum-thermal evaporation using linear
 sources 150–1
 photon emission modes 145–6, 145
 two-layer 113–14, 163
see also white OLEDs
- Ostwald ripening 41
- particle-in-a-box model 27
- passive matrix (PM) displays 111, 228
- patterned phosphors, in full-color EL
 displays 246
- phase transitions
 effects on optical properties of Qdots 26
 factors affecting 26
- phosphor-converted LEDs (pcLEDs) 76, 81–2
- phosphorescence 31
- phosphorescent emitters, OLEDs using 140,
 141, 156
- phosphors
 in ACEP 255
 activators for 34, 43, 81, 103, 255, 263, 264
 color conversion phosphors 75–109
 electroluminescent 233–4, 257
 thin-film growth 242–5
 meaning of term 19
 photoluminescent 79–83, 257
 quenchers 264
 synthesis 83, 96, 97, 99, 263–4
see also color conversion phosphors
- photoluminescence (PL) 2, 20, 21, 21
- photoluminescence quenching, in planar
 LECs 191
- photoluminescent phosphor(s) 79–83, 257
- photovoltaic systems 62
- physical vapor deposition (PVD) 42
- planar LECs 188–201
 benefit of planar configuration 189
 bulk homojunction LECs 196–201
 with millimeter inter-electrode
 spacing 190–5
 multiple 197–9
 with relaxed p-n junction 195–6
 temperature dependence of doping
 propagation speed 193–4
 time-lapse fluorescence imaging studies 192–
 3, 194–5
- plasma-enhanced chemical vapor deposition
 (PECVD) 154
- point charge *see* accelerating point charge;
 moving point charge; stationary point
 charge
- poly(ethylene oxide) (PEO), as electrolyte in
 LECs 180–2
- polyfluorene-based LECs, ‘turn-on’
 characteristics 173, 174
- polyfluorene-based OLEDs 143
- polymer light-emitting diodes (PLEDs) 142–3,
 156, 164–5, 166, 167
 compared with inorganic LEDs 167
 compared with LECs 168, 173, 186
- polymer light-emitting electrochemical cells
 (LECs) 161–205

- background to development 167–8
- compared with inorganic LEDs 183
- compared with polymer LEDs 168, 173
- current/voltage/light intensity
 - characteristics 171–2
- device characteristics 171–5
- doping relaxation in frozen-junction planar LECs 186, 195–6
- drawbacks 173–5, 183, 195
- dynamic-junction compared with frozen-junction LECs 175, 184–5
- early development 168
- EL turn-on voltage 172–3
- electrochemical doping in 170, 188, 192, 201
- electrode–polymer interface in 170–1
- frozen-junction LECs 171, 183–8
- future developments 202
- as ‘light-emitting battery’ 174
- materials
 - luminescent polymers 176–80
 - polymer electrolytes 168, 180–3
- nature of electric current in 171
- operating mechanism 168–71, 190, 192, 201–2
- phase morphology 174, 175, 178, 183
 - see also* frozen-junction LECs; planar LECs
- poly(*p*-phenylene vinylene) (PPV) 177
 - electroluminescence 142, 164, 166
 - see also* MEH-PPV polymer
- powder contact EL device 256, 257
- powder electroluminescence 249–68
 - light emission mechanisms 224, 251, 252, 257–61
 - preparation of phosphors 263–4
 - see also* AC powder electroluminescence; DC powder electroluminescence
- Poynting vector 4
- praseodymium-activated phosphors 88–90
- quantum confinement 25
 - effects on band gap 25, 26–30
- quantum deficit 79
- quantum dots (Qdots) 23–30
 - advantages over organic dyes in
 - bioapplications 23–4, 35, 56–7, 59
 - blinking effect in 35, 36
 - as color converters for LEDs 103–4
 - core/shell Qdots 38, 45, 48, 57–8
 - double-shell nanostructures 58
 - future research 64
 - history 24–5
 - inorganically capped 37–8
 - meaning of term 22
 - non-radiative relaxation process 34–5
 - optical properties and applications
 - 42–63
 - II–VI Qdots 42–62
 - III–V Qdots 62, 63
 - IV–VI Qdots 63, 64
 - organically capped 36–7
 - radiative relaxation processes 30–4
 - structure–properties relationship
 - 25–6
 - surface passivation of 35–8, 45, 47–8, 57–8, 59–60
 - surface-to-volume ratio 25
 - synthesis processes 38–42
 - bottom-up approaches 39–42
 - top-down approaches 38–9
 - use in colored glasses 24
- quantum efficiency *see* external quantum efficiency; internal quantum efficiency
- quantum electrodynamics 9
- quantum mechanics 5–6
- quantum numbers 16
- quantum well–quantum dot (QW–QD) nanostructures 58
- quenchers (of phosphors) 264
- radiation theory 1–4
- radiation-induced sublimation transfer (RIST) process 125–6
- radiative relaxation processes 30–4
 - activator emission 34
 - band edge emission 31–2
 - defect emission 32–3
- reactive ion etching (RIE) 39
- red LEDs 76, 207
- relaxation processes 30–5
 - non-radiative relaxation 34–5
 - radiative relaxation 30–4
- reverse micelle process 40
- reverse micelle technique (for synthesis of quantum dots) 40, 51
- RF magnetron sputtering, phosphor films in TFEL devices 244–5
- RGBW 4-pixel pattern format
 - development of 126–7
 - full-color displays based on 127–8
- roll-to-roll manufacturing, OLED devices 149, 153, 164
- Ryberg energy 28

- Sawyer–Tower method (of plotting charge–voltage relationship in EL devices) 231–2
output trace 232
- scattering layer, OLED efficiency enhanced by 145–6
- Schrödinger equation 16
- selection rules 7–8, 21, 34
- self-healing mechanisms, for thin-film electroluminescent devices 236–7
- ‘semi-conducting polymers’ 176
see also conjugated polymers
- semiconductors
II–VI compounds 28, 42, 263–4
III–V compounds 28, 62
IV–VI compounds 28, 63
properties listed 28
- shadow masking, color patterning using 122–3
- Sialon-type phosphors 102
- silicate garnet phosphors 93
- silicon, properties 28
- simple harmonic radiator 4–5
- Snell’s Law 239
- sol–gel techniques, nanoparticles synthesized using 40
- solar cells 46, 62, 186
- solid-state lighting (SSL)
applications 148, 219–20
energy conservation benefits 221
panels 147–8
manufacture of 149
white OLEDs 112, 143–8
performance and cost goals 143–4
- solvothermal synthesis, alkaline earth metal sulfide phosphors 97
- sphere-supported thin-film electroluminescent (SSTFEL) devices 226, 241, 242
- spherical harmonics 17
- spin–orbit coupling 8, 16
- spin selection rule 21, 34
- spontaneous emission 9, 12, 30
- sputter deposition, phosphor films in TFEL devices 244–5
- SrBa phosphor 216
- $\text{Sr}_x\text{Ca}_{1-x}\text{S}:\text{Eu}$ phosphor 96
- $\text{SrGa}_2\text{S}_4:\text{Eu}^{2+}$ phosphor 97, 234
- $\text{SrS}:\text{Ce},\text{Eu}$ phosphor 234, 245
properties 234
- stationary point charge, electric field emanating from 1, 2
- stimulated emission 9, 34
- Stokes shift 31–2, 79
- street lighting system 218, 219
- strong field scheme (in crystal field theory) 18
- ‘superyellow’ luminescent polymer 177
LEC based on 188
- surface passivation, quantum dots 35–8, 45, 47–8, 57–8, 59–60
- surface states on quantum dots
effects on optical properties 25
factors affecting 33
- tandem OLEDs *see* white OLEDs, tandem
- Tang cell 163
- terbium-activated phosphors 94, 234
- thermoluminescence 20
- thick dielectric electroluminescent (TDEL) devices 224–5, 237–40
in full-color displays 245
- thick top dielectric electroluminescent devices 226, 240–1
- thin film electroluminescence (TFEL) 21, 223–48
light emission mechanism 224
- thin film electroluminescent (TFEL) devices
charge–voltage relation 229–31
method of determining 231–2
equivalent circuit 228–9, 229
self-healing of damaged region 236
structure 224–6, 235–42
theory of operation 226–33
- thin film encapsulation, OLEDs 153–5
- thin film transistor (TFTs), in ACTFEL displays 254
- thiogallate phosphors 97–9
- total internal reflection 145, 146, 239
- triplets, white OLEDs based on 140–2
- tris-(8-hydroxyquinolino)aluminium (Alq), in OLEDs 114, 163
- ultrasound method for Qdot production 41
- ultraviolet irradiation, luminescence quantum efficiency of ZnS Qdots affected by 48
- ultraviolet LEDs 207
phosphors for 79, 82, 94
- ‘upconversion’ 32, 57
- vacuum-thermal evaporation
linear sources, in OLED manufacture 150–1
thin film EL devices prepared using 242–3
- valence band 19, 20, 227
- vanadate garnet phosphors 94

- wallplug efficiency, LEDs 209
- waveguide emission
 in glass substrate EL device 239
 in OLEDs 145, 146
- white LEDs 207–8
 applications 218–20
 costs 219
 design of lighting system 217–18
 luminous efficacy 214, 219, 220, 221
 properties 218
- white light
 generation strategies using LEDs 76, 81–2,
 212–18
 blue LED + one (yellow-orange)
 phosphor 76, 82, 208, 213
 blue LED + two (green + red)
 phosphors 76, 81, 102, 208
 near-UV LED + four (OYGB)
 phosphors 215–16
 near-UV LED + three (RGB)
 phosphors 208, 212, 213, 214–15
 OLEDs 113–22
 three (RGB) LEDs 76, 81, 208, 212, 213
 UV LED + three (RGB) phosphors 82,
 103
- white light-emitting LEDs *see* white LEDs
- white light-emitting OLEDs *see* white OLEDs
- white OLEDs
 display applications 112, 122–30
 color-patterning methods 122–3
 emitter selection method 121–2
 fluorescent and phosphorescent emitters
 in 141
 four-layer 128, 129
 spectrum 129
 large-area displays based on 124–6
 lighting applications 112, 143–8
 low-voltage 128–30
 polymer-based 142–3
 tandem OLEDs
 architecture 131
 fluorescent combined with phosphorescent
 emitters 141–2
 full-color displays using 136–7, 156
 improved color filters for wide color
 gamut 137–9
 optimization of tandem stacks 131–2
 performance 133–5
 scattering layer 146, 147
 spectra 132, 133, 136, 138, 145
 structures for improved color gamut 135–6
- three-layer 112–13, 128, 129
 spectrum 129
- triplet-based 140–2
- two-layer 113–14
 color stability 117, 118, 119
 color stability compared with other colored
 LEDs 120
 half-life data 117–18, 119
 mechanism of operational stability 120–1
 operational stability 117–19
 optimization of white color 114–17
 performance 117–19
 spectra 115, 118, 119
- wurtzite crystal structure 43, 262
 semiconductors 28
- $\text{YCa}_3\text{M}_3\text{B}_4\text{O}_{15}:\text{Eu}^{3+}$ phosphor 94
 $(\text{Y}_{2-x-y}\text{Eu}_x\text{Bi}_y)\text{O}_3$ phosphors 94
- yttrium aluminium garnet (YAG)
 Ce^{3+} -activated phosphor 83–5, 213
 theoretical limit of luminous efficacy 86–8
 $\text{Ce}^{3+}/\text{Pr}^{3+}$ -co-activated phosphor 85–90
- yttrium/gadolinium aluminium garnet, Ce^{3+} -
 activated phosphor 90–2
- zener diodes, in TFEL equivalent circuit 229
- zener emission effect 161, 257
- zero-dimension nanostructures *see* quantum
 dots
- zinc blende crystal structure 43, 262
 semiconductors 28
- zinc oxide (ZnO)
 manganese-doped 44
 properties 28, 43
- zinc oxide (ZnO) quantum dots 43–6
 applications in solar cells 46
 defect states in 33
 doped ZnO Qdots 44–5
 photoluminescence properties 43–4
 quantum efficiency 44
 surface passivation of 45
 synthesis of 40
- zinc selenide (ZnSe), properties 28, 48
- zinc selenide (ZnSe) quantum dots 48–50
 enhancement of luminescence in 49–50
 photoluminescence properties 48–9
- zinc sulfide (ZnS)
 AC EL spectra of various activated powder
 phosphors 264–5
 copper-activated 252, 257, 265
 Cu,Al doped 255, 265

- Cu,Cl doped 258–9, 265
- Cu,I doped 255, 265
- manganese-doped 43, 46–7, 227–8, 233, 234, 257
 - preparation of thin-film phosphors 242–3
- Mn,Cu doped 249–50, 255
- Mn,Cu,Cl doped 255, 265
- properties 28, 46, 262
 - structural modifications 262
 - terbium doped 234
- zinc sulfide (ZnS) quantum dots 46–8
 - doped ZnS Qdots 46–7
 - surface passivation of 47–8
 - UV irradiation effects 48
- zinc sulfoselenide ($\text{ZnS}_{1-x}\text{Se}_x$) 20
 - Cu,Cl doped 255
- zinc telluride (ZnTe) 28