

Index

- actions 58, *see also* Chapter 2
 accidental 58, 59
 favourable 134
 permanent 58, 59, 64, 71, 73, 78, 92, 127, 130, 345, 356, 414
 quasi-permanent 57, 59, 63, 71, 75, 252, 312, 413, 499
 unfavourable 134
 variable 58, 78
accidental design situations 56, 71
adhesive bonding 43
additional properties 14
American plywood 22–24
angle of taper 215, 219, 220
axial compression 69, 148, 150, 163, 299
axial compression and bending 163
axial loading 163, 174, 205, 293, 372, 500
- beams *see* Chapters 4, 6 & 7
 axes 76, 106
 curved 86, 211, 220–222
 glued laminated 86, 364, 205–247
 notched 91, 138
 rectangular 101, 109, 117, 259, 347
 solid section 101, 292
 straight 18, 101, 107, 148
 thin flanged 101, 130, 248–268
 thin webbed 37, 101, 131, 248–268
 trimmer joists 41
bearing length 104, 120, 227, 284
bearing stress 102, 121–122
bending
 deflection 128–129, 223, 261
 stiffness 131–133, 294
 strength, 5, 12, 14, 60, 69, 105, 164, 208, 254
 stress 92, 102, 104, 164, 211, 250, 256, 340
- bolts 90, 305, 372–374, 384
 axially loaded 406
 characteristic yield moment 383, 455
 edge distance 393, 455
 effective number 98, 396, 399, 459, 467
 end distance 393
 spacing rules 391–399
box beams 39, 40, 43, 45, 248, 258, 261
bracing 90, 92, 148, 304, 338–357, 415
brittle failure 390, 394, 454, 461, 466, 485
buckling length 151, 284, 341
buckling strength 108–111, 152–154, 254, 294, 300, 340–344
built-up columns 148, 292–337
 bending stiffness 294
 buckling strength 294, 300
 combined axial loading and moment 311
 connection factor 306
 design criteria 301
 design procedure 291, 299–312
 effective axial stiffness 299, 300
 effect of creep 312
 latticed columns 308
 N-lattice 322
 spaced columns 293, 303–310
 spacer packs 303, 304
 V-lattice 308
- Canadian plywood 22–23
cantilever 97, 109, 110, 126, 129, 260, 261
characteristic embedment strength 89, 383–386
characteristic values 14, 21–38, 58, 153, 207, 209
characteristic values of actions 58
 accidental actions 58
 permanent actions 58
 variable actions 58

- characteristic yield moment 88, 383
- classification of actions 58
- clear span 104
- columns, *see Chapters 5, 6, and 8*
 - axial compression 69, 148, 150, 163, 299
 - axial tension 162, 168
 - built-up 148, 292–337
 - buckling strength 152–154, 294, 300
 - characteristic compressive strength 152, 155, 254, 265, 301, 302
 - combined bending and axial compression, 164–166, 174
 - combined bending and axial tension 168
 - combined stresses 148
 - compression at an angle to the grain 157
 - effective length 150–153, 170, 175
 - glued laminated 148, 153, 206, 232
 - instability factor 153, 155, 164, 301, 303, 307
 - lateral torsional instability 163–168
 - latticed columns 308
 - rectangular section, solid *see Chapter 5*
 - relative slenderness ratio 152, 154–155, 300, 302
 - slenderness ratio 69, 92, 150, 254, 300
 - spaced 293, 303–310
 - strength validation 163
- combination value 59, 63, 71, 92, 413
- combined stresses 148
- compression wood 5
- compressive strength 65, 120, 150, 153, 158, 301
- computer 60, 94, 416, 500
- connections, *see Chapters 10, 11 and 12*
 - alternating forces 399, 466
 - axial loading 372, 375, 403, 500
 - axial withdrawal 388–389, 408, 474, 507
 - bolted 375, 385, 410
 - brittle failure 390, 394, 454, 466, 485
 - combined laterally and axially loaded 408
 - design considerations 375, 452, 483
 - design strength 396, 400, 409, 466, 490
 - dowelled 376, 454
 - effective number of fasteners 91, 396, 400, 412, 484, 496
 - final deformation 413, 414, 416
 - friction effects 388
 - instantaneous slip 410–415, 469
 - lateral stiffness 409, 416, 468, 498, 500
 - member thickness 386–387, 456, 462, 495
 - moment behaviour 487
 - multiple shear planes 401, 465
 - nailed 373, 391, 393–394, 485
 - punched metal plate 67, 372, 395, 400, 467
 - rigidity factors 502
 - rotational stiffness 416, 483, 497–498, 501–502
 - screwed 410, 415
 - secant rotational stiffness 497, 501
 - semi-rigid behaviour 62, 125, 483–527
 - shear planes 377, 382, 401–403, 413, 465, 495
 - split-rings 372, 452, 455, 459, 468, 469
 - toothed-plates 452–459, 468, 469, 484
- conversion of timber 7
- creep 59, 65, 126–127, 251, 259, 312, 413
- critical bending stress 92, 108
- decking 25, 41, 43, 130
- defects in timber 10, 83
- deformation, deflection
 - bending 128, 129, 223, 261
 - cambered 69, 85, 101, 205, 212, 216, 220, 222
 - cantilever 126
 - compression over supports 128
 - creep 59, 65, 126, 127, 251, 259, 312, 413
 - factor 77, 81, 128, 252, 312, 313, 414, 499, 500
 - final 126–127, 176, 125, 312, 375
 - instantaneous 57, 64, 76, 125, 312, 375
 - limiting values 125, 126, 377
 - net final 91, 126
 - out of plane 174, 175
 - shear 128, 176, 216, 223, 259–261, 268, 305
 - shear amplification factor 128, 129
 - slip in joints 131, 292, 410
 - slip modulus 68, 80–82, 294, 313, 410–416, 468
- density 3, 6, 11, 14, 58, 92, 150, 208
- design criteria 55, 129, 301
- design philosophy
 - limit states 50, 52, 56, 57
 - permissible stress 50

538 Index

- design resistance 62, 70
- design values of actions 57, 63, 71, 73
- design values of geometrical data 68
- design working life 52, 54–58
- diaphragms *see Chapter 9*
 - floors and roofs 338, 348
 - racking resistance of walls 351
- Douglas fir plywood 20, 22, 29, 449
- dowels *see Chapter 10*
 - axially loaded 374, 406
 - characteristic yield moment 88, 383
 - edge distance 393, 455
 - effective number 98, 396, 399, 459, 467
 - end distance 393
 - multiple 391, 396, 412
 - spacing rules 391–399
- ductile failure 375, 377, 394, 454
- durability 3, 4, 11, 37, 43, 46, 50, 53–55
- duration of load 64, 91, 101, 251, 312

- effective diameter 383
- effective length 109
 - beam 110–111
 - column 150–153
- end rotation 503
- engineered wood products 1, 43
- equivalent flexural rigidity 130
- equivalent section approach (modular ratio approach) 210, 249, 259, 261
- Euler buckling load 151–153, 175, 342
- European 12, 50
- Eurocode 0 51, 52, 416
- Eurocode 1 50, 51, 53, 93
- Eurocode 3 400, 416
- Eurocode 5 50, 51, 93

- failure modes 164, 377, 388, 401, 403, 406, 410, 465
- fastener *see Chapter 10*
 - axial withdrawal 87, 388–389
 - characteristic yield moment 88, 383
 - dowel-type 61, 372–451
 - effective diameter 89, 383–384
 - effective number 90, 396, 397
 - mechanical 260, 292, 409
 - row 391, 396–397, 399, 458, 467, 484
 - stiffness 375, 396, 409–415

- fibre saturation point 7, 9, 65, 79, 259, 405, 414
- Finnish plywood 22–25
- fire safety and resistance 46–47
- flexural members, *see Chapter 4, see also beams*
- flitched beams 42, 44
- frame analysis 415, 469, 500
- frequent value 59, 63, 92
- fundamental frequency 89, 130, 251

- glued laminated, *see Chapter 6*
 - angle of taper 215, 219, 220
 - apex zone 69, 84, 211, 216, 219, 220
 - bending deflection 223
 - bending strength 208, 209–216
 - bending stress 212–222
 - column 232
 - combined 207, 209, 211, 232
 - criterion for bending stress 221
 - criterion for radial tension stress 221
 - curved beams 86, 211, 220–222
 - design methodology 207
 - finger joints 17–19, 222
 - homogeneous 205, 207, 208
 - horizontally laminated, 84, 207
 - pitched cambered 69, 85, 205, 212, 216, 221–222, 225
 - radial stress 217, 218, 220
 - radial tensile strength 220
 - residual stresses 216
 - shear deflection 216, 223
 - stress class 211
 - tapered members 205
 - vertically laminated members 207
 - volume effects 216, 220
- glulam, *see glued laminated*
- grades 5, 12–14
- grading 5, 11–12
 - machine 12
 - visual 12
- grain 5, 7, 14

- Hankinson equation 385
- Hardwoods 3, 4, 5, 386
- holes
 - pre-drilled 385

- I-beams *see Chapter 7*
imposed loads 51, 59, 93, 470
instantaneous
 deflection 77, 91, 127
 deformation 57, 76, 77, 79, 91, 125, 259
 loading 68, 79
irreversible limit state 136
- Johansen, joint strength equations 377, 388
joints, *see Chapters 10, 11 and 12 see also connections*
 bolted 375, 385, 410
 dowelled 376, 454
 nailed 373, 391, 393–394, 485
 screwed 410, 415
 shear-plate 455, 459, 468–469
 split-ring 372, 452, 455, 459, 468–469
 toothed-plate 452–459, 468, 469, 484
joists 35, 37, 41, 101–102, 250
juvenile wood 2, 6, 7, 11
- knots 4, 11, 12, 150, 162
- laminated strand lumber (LSL) 17, 22
laminated veneer lumber (LVL) 16, 22, 31, 66, 93
lateral bracing *see Chapters 11*
 beam, truss or column systems 345–348
 single members 341–345
lateral instability, of columns 148, 150, 292
lateral stability 254, 338, 345–352
lateral supports, restraint 109, 342
lateral torsional instability, of beams 102, 105, 107, 216
length, *see effective length*
limit states 50, 52, 56, 57
linear elastic analysis 60–62, 68, 312, 343
 first order analysis 60
 second order analysis 60, 151
load duration classes 14, 64, 73, 103
 instantaneous 64, 66
 long-term 64, 66
 medium-term 64, 66
 permanent 64, 66
 short-term 64, 66
load combinations 70, 103, 133
 accidental combinations 66, 67, 73
 characteristic combination 57, 75, 78, 127
 frequent combination 75, 78, 80, 259
 fundamental combinations 66, 68, 71
 quasi-permanent combination 57, 75, 80, 413, 414
- machine grading 12
major axis 105, 107, 163, 169
material properties 1, 14, 63, 67, 155
Mathcad, *see Chapter 3*
mechanical fasteners, *see connections, joints*
medium-term duration loading 64, 66
modification factor for load duration and service class 64, 70, 73, 79, 103, 155
modulus of elasticity 12, 14, 15, 68
 fifth percentile 87, 301
 final mean value 81, 87
 mean 14, 15, 68, 81, 87, 127
moisture content, 1, 3, 7, 9, 10, 11, 16, 64, 65, 79
- nails, nailed joints 306, 310, 372–373, 393, 504
 axially loaded 403–406
 characteristic withdrawal capacity 389, 404, 407
 characteristic yield moment 383–384
 edge distance 391, 392
 effective number 396–399
 end distance 391, 392
 member thickness 386
 minimum penetration 389–390
 pointside withdrawal 389, 404, 405
 pull-through resistance 404
 spacing rules 391–392
non-linear analysis 60–61
 first order analysis 60
 second order analysis 60
notch in a member 115–118
- oriented strand board (O.S.B) 17, 25, 248, 263
- panel shear 24, 90, 257, 350
parallel strand lumber (PSP) 17, 25

540 Index

- partial factors 62, 63, 67, 74, 125
 - for actions 125
 - for material properties 67
- partial factor method 57, 62, 70, 103, 148
- particle boards and fibre composites 35
- permanent actions 58–59, 71–73, 78, 92, 127, 130
- permissible stress 50, 410
- persistent design situations 56, 170
- plate bending stiffness 133
- plywood 20–22
- precamber 231
- pre-drilling 162, 373, 384, 390, 393, 411
- preservative treatment 45–46
- principles of limit state design 55

- Quality management 54, 55, 93
- quasi-permanent value 59, 63, 71, 78, 92, 312, 414, 499

- racking strength 169, 351, 354, 356
- radial stresses 212, 216, 219, 225
- radius of gyration 90, 150, 151
- reaction wood 5
- relative slenderness ratio 92, 105, 152, 155, 300
- reliability 50, 53, 56, 73, 103
- representative values 58, 59, 63, 92
- reversible limit state 75
- robustness 53, 55
- rolling shear 116, 119, 258

- screws, screwed joints 373
 - axially loaded 406
 - characteristic withdrawal capacity 407
 - characteristic yield moment 383–384
 - edge distance 391–392
 - effective diameter 383, 384
 - effective number 396–399
 - end distance 391–392
 - minimum penetration 390
 - spacing rules 391–392
- seasoning 4, 7, 10, 11
- seasoning defects 11
- second moment of area 88, 104, 107
- section sizes 16, 47
- service classes 65
 - service class 1 65
 - service class 2 65
 - service class 3 65
- serviceability limit states 52, 56, 74, 101, 103, 125, 339, 375
 - deformation, deflection 75
 - vibration 74
- shear amplification factor 128, 129
- shear block failure 460, 461, 462
- shear deflection 216, 223, 259, 261, 268
- shear modulus 14, 68, 80, 81, 107, 128, 209, 210
- shear-plate connectors 455, 459
 - edge distance 455
 - effective number 464–465
 - end distance 455
 - spacing rules 455
 - stiffness behaviour 468
 - strength behaviour 459
- sheathing material 91, 170, 354, 356
 - sheathing material factor 91, 356
- size factor 67, 84, 216
- slenderness ratio 69, 92, 150, 254, 300
- slip, in joints 131, 292, 410
- slip modulus 68, 80–81, 410–415
- slope of grain 5, 25
- softwoods 3, 5, 14
- spaced columns, *see Chapter 8*
- species 12–14
- split-ring, and ring connector 452, 455, 459
 - edge distance 455
 - effective number 464–465
 - end distance 455
 - spacing rules 455
 - stiffness behaviour 468
 - strength behaviour 459
- staples 398
 - edge distance 392
 - end distance 392
 - member thickness 386
 - minimum penetration 390
 - spacing rules 392
- steel plates, gusset plates 375, 377, 381, 406, 504
- straightness limits 154
- strength classes 13–15, 113
- strength grading 11–12

- strength properties 12, 15, 55, 85
- strength validation 82, 111, 163, 166
- structural insulated panels (SIP's)
 - 40
- stud walls 169–176
- suspended timber flooring 41
- Swedish plywood 22–24
- system strength factor 85, 87, 91, 106, 171, 211, 254

- tapered beams 211–212, 216–217
- tension members 162
- tension wood 5
- thin webbed beams 39, 249, 251, 263
- thin webbed joists 37, 40, 131
- toothed-plate connectors 452–459
 - edge distance 455
 - effective number 464–465
 - end distance 455
 - spacing rules 455
 - stiffness behaviour 468
 - strength behaviour 459
- torsion of members 123–124
- transformed section 252, 259
- transient design situations 56, 66, 71, 73

- ultimate limit states 52, 56 67
 - equilibrium 70
 - fatigue 70
 - geotechnical 70
 - strength 70
- United Kingdom National Annex 51
 - Nationally Determined Parameter (NDP) 342
 - Non-Contradictory Complimentary Information (NCCI) 51

- variable actions
 - accompanying variable action 71, 78, 88
 - leading variable action 71, 72, 78, 88
- vibration, of residential floors 74, 129–133
 - footfall induced 130
 - high frequency effects 132
 - low frequency effects 130
 - machine enforced 129
 - modal damping ratio 92, 132
 - residential floors 91, 132
 - unit impulse velocity response 91, 132
- visual grading 12
- volume effects 216, 220

- wane 10, 12
- Weibull distribution theory 83