

Index

a

- activated dislocation segments
 - length 95, 96
- activation energy of creep
 - apparent 101
 - in pure metals 6, 7
 - in refractory metals 146, 147, 150
 - in superalloys 101
- activation volume
 - equation 7
- alloys
 - Ir–Nb, Ir–Zr 155
 - Ni–Cr, Ni–Al, Ni–W 55
 - of refractory metals 143, 149, 151, 152, 153
 - W–Re, W–Hf 153
- amplitudes of atomic vibrations
 - in γ' phases of superalloys 102, 103
 - in nickel base solid solutions 54, 55
 - measurements 21–23, 102

c

- creep
 - curve 5, 6
 - dislocation theories 8, 9
 - in refractory alloys 151, 152
 - in refractory metals 143–145, 147–150, 152

- in solid solutions 54
- in superalloys 86, 87, 95, 96, 116–120, 124, 125
 - at higher temperatures 124
 - at lower temperatures 116
 - dislocation splitting 112, 120–122, 129
 - equations 99, 100
 - influence of orientation, temperature and stress 111–120
 - primary stage 118, 119
 - tertiary stage 118
- physical mechanism 43–45, 67, 68
- steady-state stage 51, 77
 - calculation for pure metals 51–53
 - equations 49, 51–53, 95, 96, 100, 137–140
- structural peculiarities 40

d

- deformation map
 - iron 64
 - molybdenum 150
 - nickel 63
 - niobium 145
- density of dislocations
 - differential equation 49–51, 77, 78

- in metals 38
- in superalloys 100, 101
- diffraction electron microscopy
 - 20
- dislocation networks 30–33, 89, 132–135
- dislocations
 - annihilation 49–51
 - coefficients of multiplication 50, 73, 75
 - in γ' phase 90, 92, 94, 97
 - in crept metals 35–38
 - interactions with particles 89–94
 - jogged 35, 36
 - mobile 35, 36
 - partial 112, 160
 - ribbons 120–122
 - screw components 36, 161
 - splitting 121, 129
 - subgrains 35
 - theory 157
- e**
 - evolution of structural parameters
 - in matrix of superalloys 88, 89
 - in metals 25–33
- g**
 - γ/γ' misfit
 - influence of temperature 136
 - γ' phase
 - amplitude of atomic vibrations 102, 103
 - coarsening 104, 105
 - composition 83, 103
 - crystal lattice 84
 - lattice parameter 136
 - rafting 130, 131
 - solubility 85
- h**
 - high-temperature strain rate
 - physical model
 - for metals 43–45, 67, 68
 - for superalloys 95–97
 - shear deformation 124, 125
- i**
 - interaction of dislocations with particles 89–94
- j**
 - jogs in dislocations
 - formation 55, 56
 - in crept metals 36–38
- m**
 - metals
 - copper 27, 28, 30
 - iron 31–35
 - molybdenum 146–151
 - nickel 26, 30, 32, 34–37
 - niobium 144–147
 - vanadium 29, 31
 - misfit 136
- r**
 - rafting 130, 131
 - refractory metals
 - molybdenum 146–151
 - niobium 144–147
 - refractory alloys 149, 151, 152
 - rupture life 86, 87, 114, 115
- s**
 - Schmid factor 112
 - simulation
 - by the system of differential equations 67–71
 - data for metals 71–77
 - of structural parameters evolution 67
 - single crystal superalloys
 - blades 113
 - creep curves 117–120, 123–125
 - influence of orientation on 114–119

- influence of stress on 120
 - influence of temperature on 116–118, 120
 - dislocation mechanisms of strain 119–127, 129
 - properties 115
 - shear strain 125, 126
 - solid solutions
 - Ni-based 55
 - stacking faults
 - energy 57
 - structural parameters
 - average values 30
 - evolution 25–30
 - measurements 17–20
 - structural peculiarities
 - of crept metals 40
 - of superalloys 83, 88
 - sub-boundaries
 - as sources and obstacles for mobile dislocations 34, 35
 - crystallography 55, 56
 - distances between dislocations 31–35, 37, 38
 - stability 58–62
 - superalloys
 - composition 129, 163
 - equations of strain rate 95–100, 137–140
 - physical mechanism of strain 96–98
 - prediction of properties 106–108
 - trends of development 129
- v**
- vacancies
 - energies of formation 46, 52
 - energy of diffusion 46, 47, 52
 - loops and helicoids 39
 - velocity of dislocations
 - with vacancy-absorbing jogs 46, 47
 - with vacancy-producing jogs 46–49, 72, 75
- x**
- X-ray *in situ* studies
 - data 26–31
 - equipment 13, 14
 - technique 15
 - measurement of structure parameters 17–20