

INDEX

Note to the Reader: Throughout this index *italics* page numbers refer to figures; **boldfaced** page numbers refer to primary discussions of the topic.

SYMBOLS AND NUMBERS

- & (ampersand)
 - for background processing, **125–127**, 236, 486
 - to terminate command, 136
- ! (bang), **487, 624**
 - to escape to shell for command execution, **857**
 - for file name generation, 230
 - in ftp, 656
 - to reverse matching in sed, **299**
 - in UUCP addresses, 369
- ! (bang) command, 129
- ! (bang) command (ftp), 391
- ! (NOT) operator (awk), 309, 310
- && (AND) operator, 309
- && operator for branching, **351**
- \ (backslash), **226–227**
 - command (mailx), 755
 - (dash), for grep range, 281
 - (dash), in command syntax, 18
 - " (double quotes), **228–229, 596**
- # command (mailx), 755
- # (pound sign), **807**
 - in awk, 302
 - for C shell script, 203
 - as comment character, **227–228**, 558
 - for root prompt, 58
- / (slash), 26–27, **861**
 - for root symbol, 31–32
- \$ (dollar sign), 213, **591**
 - and double quotes, 225
 - in grep command, 279
 - in v command, 285
 - variable name with, 95–96
- \$ prompt
 - for Bourne shell, 10
 - for Korn shell, 709
- \$ shell variable, 556
- \$? shell variable, 334–335
- #! shell variable (Bourne), 504
- ## shell variable (Bourne), 504
- \$\$ shell variable (Bourne), 504
- \$* shell variable (Bourne), 504
- \$- shell variable (Bourne), 504
- \$? shell variable (Bourne), 504
- #! shell variable (Korn), 714
- ## shell variable (Korn), 714
- \$\$ shell variable (Korn), 714
- \$* shell variable (Korn), 714
- \$? shell variable (Korn), 714
- \$_ shell variable (Korn), 714
- \$(, to scan argument list, 358–359
- \$0 shell variable (Bourne), 504
- \$0 variable (awk), 484
- % prompt (C shell), 10, **799**
- ' (single quote), **861**. *See also* quoting
 - in grep commands, 209
- * (asterisk), 866
 - for file name generation, 230
 - in grep command, 281
 - in v command, 285–286
 - as wildcard, 41, **475–476**
- + (plus) symbol, **806**
- ++ (postincrement) operator, 313
- . (dot) command, **210**
- . (period), **799**
 - and file searches, 42–43
 - in filenames, 26
 - in grep command, 280
 - in v command, 285
 - as vi repeat command, 179
- .. (two periods), for home directory, 35, 103
- : (colon)
 - to indicated Bourne shell script, 203
 - in vi command mode, 187
- : command, 505, **535**
 - for command argument, 345
- : command (C shell), 558
- : command (Korn shell), 716
- ;(semicolon), **853**
 - in case statement, 349

- in multicommand line, 135
- to terminate command, 136
- login, **737**
- < command (vi), 184
- << command (vi), 184
- < (less than) symbol, **728**
- = assignment operator, 95
- == (relational operator), 307–308
- > command (vi), 184
- >> command (vi), 184
- > (greater-than) symbol, 39, **665**
- >> redirection operator, 54
- ? command (ftp), 391
- ? command (Mail), 752
- ? command (mailx), 755
- ? command (telnet), 394, 886
- ? (question mark), 41, **817**
 - for file name generation, 230
 - in ftp, 656
 - for mail command mode prompt, 65
- @ command (C shell), 558
- @(#) (what string), 203
- [] (square brackets), **868**
 - for file name generation, 230
 - in grep command, 281
 - for optional arguments, 18
 - regular expressions with, 286–287
- ^ (caret), **512**
 - in grep command, 279, 281
 - with square brackets ([]), 286–287
 - in v command, 285
- ` (backquote), **486–487**
 - in shell script, **224–226**
- \ (backslash), 487
- || operator, for branching, **351**
- || (OR) operator, 309
- | (vertical bar), for piping, 20
- ~ (tilde), **892**
 - in C shell, 380
 - for empty lines in vi, 169
 - for home directory, 679
- ~ (tilde) escape sequences, **891**
- 4.4BSD Lite, **651**
- ABI (Application Binary Interface), **463**
- aborting command (vi), 161
- absolute mode for chmod command, 112, 527, 528
- absolute path names, **32, 463**
 - displaying, 33
- accent grave, 486
- access modes, 104
- account, **464**
- account command (ftp), 656
- acct command, **464**
- ACK (acknowledgment), **464**
- Acsii command (ftp), 392
- active processes, information about, **811–814**
- active window, **464, 648**
- adb (debugger), **464**
- Address Resolution Protocol (ARP), 385, 883
- admin program (SCCS), 847
- Advanced interactive Executive (AIX), **466**
- AFS (Andrews File System), **465**
- Aho, Alfred, 776
- AIX (Advanced interactive Executive), **466**
- alarm system, sleep command to create, 137
- ali command (MH), 764
- alias command (C shell), **151–153, 466–467**, 558
- alias command (Korn), **466–467**, 716
- alias command (Mail), 752
- alias command (mailx), 755
- aliases
 - listing setup, 152
 - removing, 153, **913**
- allexport option (Korn shell), 713
- alloc command (C shell), **467**, 558
- almanac, 733
- Alt key, 5
 - as Meta key, 608
- alternate command (Mail), 752
- alternate command (mailx), 755
- ambiguous file reference, **467**
- American National Standards Institute (ANSI), **468–469**
- ampersand (&)
 - for background processing, **125–127**, 236, 486
 - to terminate command, 136
- AND (&&) operator, 309
- AND operator (-a), in test command, 339
- Andrews File System (AFS), **465**
- anno command (MH), 764
- anonymous ftp, 391, **467–468**
- anonymous server, **468**

A

- .a filename extension, 638
- a keyword (bc), 492
- abbr command (vi), **189–195**

- ANSI (American National Standards Institute), **468–469**
- ANSI C, **469**
- ansitape command, **469–470**
- a.out file, **470**
- API (application programming interface), **470**
- append command (ed), 623
- append command (ftp), 656
- append mode, in vi editor, 170, 181
- appending, **470**
- output to files, **54–55**
 - text in sed stream editor, **300**
 - vi buffer to file, 172
 - yank, 185
- Application Binary Interface (ABI), **463**
- application interface in X, 425, 426
- application layer (ISO/OSI), 696
- Application layer (TCP/IP), 884
- application programming interface (API), **470**
- apropos command, **471**
- ar command, **471–473**
- archive, **473**
- copying files and directories to, 545–547
 - creating in text form, 855–856
 - tar to work with, **879–880**
- archive libraries, 471–472
- table of contents for, **820**
- arctangent, from bc, 492
- ARGC variable (awk), 312
- ARGC variable (nawk), 484
- argument list, **474**
- arguments, **17–21, 474, 538**
- empty vs. no, 337
 - passing long list to command, **947**
 - testing for, **355–356**
- argv shell variable, **474, 556**
- ARGV variable (awk), 312, 474
- ARGV variable (nawk), 484
- arithmetical values
- awk and, **313–316**
 - sorting by, **245**
- ARP (Address Resolution Protocol), 385, 883
- array, **474**
- splitting string into, 316
- as command, **474–475**
- ascii command (ftp), 393, 657
- ASCII control codes, backslash (\) to generate, 226–227
- ASCII files, 16
- converting between EDCDIC and, 574
 - dd command to convert, 266
 - executable, 236
- ASCII set, 5
- ASCII strings, extracting from binary file, **872**
- ASCII windowing system, starting, **724**
- assembler, command to run, **474–475**
- assignment statement, 214
- asterisk (*), 866
- for file name generation, 230
 - in grep command, 281
 - in v command, 285–286
 - as wildcard, 41, **475–476**
- at command, 138, **476–478**
- redirecting in, 140
- at job queue
- listing contents, **478**
 - removing jobs from, **478–479**
- AT&T, 429
- atan2 command (awk), 314, 482
- atan2 command (nawk), 777
- atq command, **478**
- atrm command, **478–479**
- .au filename extension, 638
- auto keyword (bc), 492
- AUTOEXEC.BAT file (DOS), 91
- autoindent feature (vi), 160
- autoindent (set argument), 192
- autoload (Korn), **479, 716**
- automatic check, overriding, 624
- automounter, **479**
- autoprint (set argument), 192
- autowrite (set argument), 192
- awk, 273, **301–319, 479–485**
- ARGV variable, 474
 - BEGIN and END, **311–313**
 - commands in, 481, 482–484
 - data types in, 312
 - error in, 319
 - F option, **306–308**
 - fields, **303–304**
 - flow control, **316–319**
 - general syntax, 302
 - logical operators, **309–310**
 - and math, **313–316**
 - new awk, **776–779**
 - operators in, 481–482
 - predefined variables, 312
 - printf command, **306**
 - records, **304–306**
 - relational operators, **308–309**

B

- backbones, 367
- background, **485**
- background processing, 124, **486**
 - & (ampersand) for, **125–127**, 236, 486
 - bringing to foreground, 126–127
 - waiting for, 940
- backquote (`), 95, 98, **486–487**
 - in shell script, **224–226**
- backslash (\), **226–227**, 487
- backspace, 223, 265, 564
 - in vi editor, 161
- Backspace key, 8, **487**
 - in vi text-entry mode, 181
- backup, **410–417**
 - cpio command, **414**
 - find command for selective, 260–261
 - frequency, 411
 - incremental, **685**
 - process, **413–417**
 - responsibility for, 412–413
 - strategies, 411
 - tar command for, **879–880**
- backward searches, 283
 - in vi editor, 186
- bang (!), **487, 624**
 - to escape to shell for command execution, **857**
 - for file name generation, 230
 - in ftp, 656
 - to reverse matching in sed, **299**
 - in UUCP addresses, 369
- bang (!) command, 129
- bang (!) command (ftp), 391
- bang path, **487**
- banner command, **487–488**
- banner page, 145, **488**
 - default for printing, 148
- Barber, Stan, 836
- basename, **488**
- basename utility, **488–489**
- bash (Bourne Again shell), 91, **489–490**
 - .bash_logout file, 595
 - .bash_profile file, 595
 - .bashrc file, 595
- Basic Networking Utilities (BNU), 679, 923
- basic regular expressions. *See* regular expressions
- basis, 130
- batch command, 140
- batch queue, **490–491**
- batch utility, **490**
- bbc command (MH), 764
- bc, **491–494**
- BCD (binary coded decimal), **494**
- bdes utility, **494–495**
- bdiff utility, **495–496**
- beautify (set argument), 192
- BEGIN (awk), **311–313**
- bell, 265
- bell command (ftp), 657
- Besel function (bc), 492
- bg command, 127, 486, **496**
- bg command (C shell), 558
- Bg command (Korn), 716
- bgnice option (Korn shell), 713
- bib, **496–498**
- bibliographic databases
 - creating inverted index file for, **685–686**
 - searching, **734–735**
 - searching for specified keyword, **739**
- bibliography file
 - creating troff formatted output from, **827–828**
 - preprocessor to format, **496–498**
- biff utility, **498**
- bin login name, 90
- /bin/passwd file, 84
- /bin subdirectory, 89, **498**
 - in path, 90
- binary command (ftp), 392, 393, 657
- binary files, 16, 89, 236, **499**
 - displaying data and text segment sizes, 861
 - extracting ASCII strings from, **872**
 - mailing, **370–371**
- binary numbers, **499**
- bind, **499**
- BISON, **499**
- bit, **499**
- bitmap program (X), 435
- bitwise operator, **499**
- blank, 144, 170, **499**
- blind courtesy copy, 75, **500**
- block device, **500**
- block special file, 578, 636
- blocks, **500**
 - command to report size, 531
- BNU (Basic Networking Utilities), 679, 923
- body, for mail message, 65
- bookmarks, in vi editor, 187
- Boolean expression, 317
 - test command with, **339–341**

C

- /boot directory, **500**
- booting up, **405–406**
- Borden, Bruce, 77
- Bourne Again shell (bash), **489–490**
 - starting, **821**
- Bourne shell, 90, 200, **500–507**, 856
 - \$ prompt for, 10
 - : command to indicate script for, 323
 - commands, 501, 505–506
 - curly braces ({ }) in, 507
 - dot (.) command, **210**
 - and Korn shell, 709
 - login profile, **92**
 - logout, 13
 - metacharacters in, 501–502
 - predefined variables in, **504–505**
 - quoting in, 503
 - redirecting in, 502–503
 - restricted version, 841
 - scripts for, 201
 - set command options, 506–507
 - special commands, 208
 - starting, **854–855**
 - startup files, 501
 - Zsh as replacement, **963**
- braces ({ }), 507
- brackets ([]). *See* square brackets ([])
- branching, logical operations for, **351**
- break command, 326, 345, **507**
 - for for loop, 357
- break command (awk), 482
- break command (Bourne), 505
- break command (C shell), 558
- Break command (Korn), 716
- break command (nawk), 777
- break (Ctrl-C), **563**
- breaksw command (C shell), **507**, 558
- broadcasting message, to all network users, 843–844
- BSD terminal handler, cbreak mode, **514–515**
- buffers, 8
 - for file changes, 406–407
 - numbered, **788**
 - in vi editor, 185
- bunzip function, 508
- Burrows-Wheeler-Fenwick block-sorting text compression, 508
- burst command (MH), 765
- bye command (ftp), 656
- bzip program, **508**
- c command (vi), 183
- .c filename extension, 638
- c keyword (bc), 492
- C language, 301
 - bitwise operators, 499
 - creating error message file from source code, 769
 - curly braces ({ }) in, 507
 - gcc C compiler, **659–660**
 - lint to check source code, **731**
 - source code formatting, 514
 - standard, 468, **469**
 - X Window library of routines, 953
- C++ language, 301
 - standard, 468
- The C Programming Language*, 702
- C shell, 91, 200, **552–561**, 856. *See also* csh command
 - % prompt for, 10, **799**
 - alias command, **151–153**
 - syntax, 467
 - commands, 558–560
 - curly braces ({ }) in, 507
 - environment variables in, 557–558
 - login profile, **92–93**
 - logout, 13
 - metacharacters, 554
 - quoting in, 555
 - redirecting in, 554–555
 - repeating commands, 624
 - scripts for, 201
 - startup files, 553
 - Tcsh as replacement, 884
 - Zsh as replacement, **963**
- CAE (Common Application Environment), **508**
- cal command, 19, **509**
 - month argument, 20
 - year argument, 20–21
- calculator
 - bc, **491–494**
 - dc command for, **572**
- calendar utility, **509–510**
- calendars, **19**
 - printing, **509**
- call, **510**
- call by reference, **510**
- call by value, **511**
- calling environment, **511**
- cancel command, **156, 511–512**

- canceling, scheduled jobs, 138
- Caps Lock key, and login error, 9
- Car Ret key, 6
- carbon copy, 74
- caret (^), **512**
 - in grep command, 279, 281
 - with square brackets [], 286–287
 - in v command, 285
- carriage return, 223, **512**
- case, **512**
- case command
 - in C shell, 558
 - esac to end, **619**
 - in Korn shell, 716
- case-insensitive, **513**
- case-sensitive, **513**
- case sensitivity, 27
 - of command options, 44
 - in grep searches, **276–278**
 - for password, 9
 - and sort command, 243
 - for user variables, 213
- case statement, **349–351**
- cat command, **45–46, 513–514**, 640
 - to examine /etc/passwd file, 85–86
 - for file creation, **47–48**
- catenate, **514**
- cb utility, **514**
- cbreak mode, **514–515**
- cc (C language compiler), **515–521**
- cc command (vi), 184
- ccat shell script, **521–522**
- cd command, 34, 102, **522**
- cd command (Bourne), 505
- cd command (C shell), 559
- cd command (ftp), 392, 656
- Cd command (Korn), 716
- cd command (mailx), 755
- cd command (Samba), **449**
- CD-ROM, command to eject from drive, 604
- cdc program (SCCS), 847
- CDE (Common Desktop Environment), **522**, 543
- CDPATH shell variable (Bourne), 94, 504, **523**
- cdpath shell variable (C shell), **522**, 556
- CDPATH shell variable (Korn), **523**, 715
- cdup command (ftp), 392, 656
- central printers, **144–145**
- change command, in ed editor, 623
- character-based programs, running in X, 432
- character class, **523**
- character set, converting file between, 683
- character special file, **523**, 578
- characters, 636
 - counting for file, 49–50
 - erasing, 8
 - invisible, **692**
 - quoting, **818**
 - regular, **828**
 - tr command to translate, **264–265**
 - translating between forms, **900–901**
- chdir command (C shell), **523**, 559
- chdir command (Mail), 752
- chdir command (mailx), 755
- checkmail command, **523–524**
- checknr command, **524–525**
- checksum, calculating and printing, **875**
- chflags command, **525**
- chgrp command, 111–112, **526**
- child process, 123
 - waiting for, 126
- chkey command, **526**
- chmod command, 112, 150–151, 323, **527–529**
- chown (change owner id) command, 111, **529**
- chpass command, **530**
- ci program (RCS), 823
- cksum command, **531**
- cleanup daemon, 383
- clear command, **531**
- click command, **531**
- client software in X, 424, **424, 948–949**, 959
 - configuration file for window-related values, 950
 - killing, 436
 - xkill to close connection, 953
- close call, 578
- close command (awk), 482
- close command (ftp), 392, 656
- close command (nawk), 777
- close command (telnet), 394, 886
- cmchk command, **531**
- cmdedit, **531**
- cmdterm, 431, 956
- cmp command, **531–532**
 - for compressed files, 961
- co program (RCS), 823
- cof2elf command, **532–533**
- COFF (common object file format) files, **533**
 - converting to ELF format, 532–533
- col command, **533–534**
- colcrt command, **534–535**

- colon (:)
 - to indicated Bourne shell script, 203
 - in vi command mode, 187
- colon (:) command, 505, **535**
- colon commands in vi, 172
- color chart, displaying, 950
- colrm command, **535**, 640
- column command, **535–536**
- columns
 - creating output from multiple files, 796–797
 - cut command to extract, **567–568**
 - input formatted in, **535–536**
 - listing in, 49
 - printing in, 156
 - removing from text file, **535**
- COLUMNS shell variable (Korn), 715
- comb program (SCCS), 847
- comm command, **536**
- command directories, **537**
- command file, **537**
- command history list, displaying or editing, **630–631**
- command-line, **537–538**
 - command to parse options, **662**
 - parsing, 218
- command-line argument, **538**. *See also* arguments
- command-line editing, **531**
- command mode, 73, 160, 538
 - confirming, 172
 - macros for, 189
 - in vi editor, 167, 932–933
 - vi keystroke for, 161
- command substitution, 224, 228, 487, **538–539**
- command text, 236
- commands, **11–12**
 - arguments, **17–21**
 - in awk, 481, 482–484
 - backslash (\) for long, 227
 - in Bourne shell, 501
 - checking status in UUCP, 382
 - combining, **267–270**
 - displaying information on executed, **723**
 - displaying type, 908
 - embedded, **614**
 - executing remote, **373**, **625**, 928–929
 - multiple on one line, 12
 - online reference manual, 17
 - pipe to pass information between, **805**
 - re-executing the previous, **818–819**
 - script to force failure, 219
 - shell script as, **208–209**
 - storage in history file, 677
 - terminators, 136
- comments, 324, **539**
- Common Application Environment (CAE), **508**
- Common Desktop Environment (CDE), **522**, 543
- common object file format (COFF) files, **533**
- Common Open Software Environment (COSE), **543**
- communications
 - interprocess, **690**
 - printing information, **693–694**
 - two-way, terminal-to-terminal, **878–879**
- communications link, accuracy check on data transmission, 548
- comp command (MH), 765
- compact command, 522, **539**
- comparing
 - directories, **585–586**
 - expressions, 829
 - file revisions, **584–585**
 - file versions, **583–584**
 - files, **531–532**
 - floppy disks, **589**
- comparing files, **531–532**
- compile, **539**
- compiler, **540**
 - cc (C language), **515–521**
 - f77 (Fortran compiler), **654**
 - gcc (C language), **659–660**
- compiler compiler, **540**
 - eyacc (extended yacc), **628**
 - yacc, 540, **960**
- compose mode, 73
 - for e-mail messages, 72
- compress command, **540–541**
- compression
 - bzip program for, **508**
 - compact command for, **539**
 - executable file, 671
 - lossless, **740**
 - lossy, 700, **740**
 - pack command for, **793**
 - uncompressing after, **914**
 - unpack to expand, **918**
 - zcat to uncompress, **961**
 - zmore to view files, 962
- concatenating, 46, **541**
 - cat command for, **513–514**
- condition code, 219
- /config directory, **541**

- configuration, listing information, 681–682
- confirmation, before file deletion, 53
- connect time, quotas for, 13
- connected terminals, 62
- connections, 4
- console, 5
 - virtual, **938**
- constants, in shell scripts, 663
- contents of file, displaying, 45–46
- context of suspended program, 120
- continue command, 326, **542**
- continue command (awk), 482
- continue command (Bourne), 505
- continue command (C shell), 559
- Continue command (Korn), 716
- continue command (nawk), 777
- control characters, 5, **542**
 - inserting in vi editor, 162
 - octal values, 265
- control codes, inserting in macro, 190
- converting, COFF to ELF format, 532–533
- copies, printing multiple, 149
- coprocesses (Korn shell), 719
- copy command, 71, **542–543**
- copy command (ed), 623
- copy command (Mail), 752
- copy command (mailx), 755
- copying
 - directories in UUCP, 375
 - files over network connection, **821–822**
 - floppy disks, **589–590**
 - mcopy command, **456–457**
 - uucp command for, 366–367, **379–382**, **921–922**
- copyleft command, **543**
- core image, command to obtain, 660
- corrupted files, check for, 405
- cos command (awk), 314, 482
- cos command (nawk), 777
- COSE (Common Open Software Environment), **543**
- cosine, from bc, 492
- counting, words, **49–50**
- cp (copy) command, 103, **544–545**
- cpio archive, extracting one file from, **958**
- cpio command, **414**, **545–547**
- cpp command, **547–548**
- CR, 6, 265
- crackers, 87
- CRC (Cyclic Redundancy Check), **548**
- creation mask, **548**, 911–912
- cron command, 132, 139, **548**
- crontab command, 140, **549–550**
- cross-reference table, 569
- crypt command, **87–88**, **550–551**, 640
- cscope utility, **551**
- csh command, **551–552**
- .csh filename extension, 638
- .cshrc file, 465, 553, **561**, 595
 - alias commands in, 152
- csplit utility, **561–562**
- ct utility, **562–563**
- ctags command, **563**
- ctrace command, **563**
- Ctrl-C (break), **563**
- Ctrl-D (^D), **564**
 - for EOF (end-of-file) character, 47
 - to terminate program, 62
- Ctrl-H (backspace), 564
- Ctrl key, 5, 542, **564**
 - in emacs editor, 608
- Ctrl-L (redraw), 564
- Ctrl-Q (restart), 564
- Ctrl-\ (quit), **563**
- Ctrl-R, 564
- Ctrl-S (pause), 564
- Ctrl-U, 564
- Ctrl-W, 565
- Ctrl-X, 565
- Ctrl-Z, 565
- cu command, 373, **565–567**
- curly braces ({ }), 507
- current directory, 90, **594**, 946
 - changing, **522**, **523**
 - command to list, **587**
 - listing contents, 43
- courses, **567**
- cursor movement, in vi editor, **173–175**, 178–179, 933–934
- cursors, 7
 - controlling location, 567
 - in emacs editor, 609
 - in xterm window, 433
- cut-and-paste, **568–569**
 - in vi editor, **184–186**
- cut command, **253–254**, **567–568**, 640
- cut, selected text, **568**
- cwd shell variable, 556
- cxref command, **569**
- Cyclic Redundancy Check (CRC), **548**
- cylinders on floppy disks, 454

D

- daemons, 124, 132, 382, **569–570**
- DARPA (Defense Advanced Research Projects Agency), 570
- dash (-)
 - in command syntax, 18, 44
 - for grep range, 281
- Data Encryption Standard (DES), 494–495, **576**
- data-link layer (ISO/OSI), 696
- data segment, 121
- data types, in awk, 312
- database applications, 387
- date
 - formatting in awk, 315–316
 - Julian, **701**
 - scheduling jobs to run on specific, 477
- date command, 11, **570–572**
- Davidsen, Bill, 855
- dbx (debugger), **572**
 - .dbxinit file, 572
- dc command, **572**
- dd command, **266, 573–574**
- DDI (Device Driver Interface), **574**
- DDRM (Device Driver Interface/Driver Kernel Interface Reference Manual), **575**
- dead.letter file, 75
- debugger
 - adb, **464**
 - dbx, **572**
 - gdb (debugger), **660–661**
 - sdb, **849**
- debugging
 - ctrace command for, **563**
 - shell script, **207–208, 362**
- decimal numbers, sorting, 245
- decryption, 614
- default: command (C shell), 559
- default shell, 89
- defaults, **10, 575**
 - for nice number, 133
 - permissions, **110–111**
 - printers, 154
 - for printing, 147
 - system administrator and, 65
 - text editor, 631
- Defense Advanced Research Projects Agency (DARPA), 570
- define keyword (bc), 492
- del command (Samba), **449**
- delete command
 - in ed editor, 623
 - for e-mail messages, 71
 - repeating in vi, 179
- delete command (awk), 482
- delete command (ftp), 656
- delete command (Mail), 752
- delete command (mailx), 755
- delete command (nawk), 777
- deleting
 - characters, 8
 - directories, **35**
 - e-mail messages, **70–72**
 - e-mail messages when quitting, 66–67
 - empty directory, **835–836**
 - file from archive file, 473
 - files, **52–54, 834–835**
 - line of input, 564, 565
 - old jobs in UUCP, 383
 - in sed stream editor, **299–300**
 - text in vi editor, **181–183**
 - words, 565
- delimiter, 223, **575**
- delta, 847
- delta program (SCCS), 847
- deroff command, **575–576**
- des command, **576**
- DES (Data Encryption Standard), 494–495, **576**
- descriptor table, **576**
- DeskSet, 437
- Desktop System (OpenServer), 790
- destination file, for cp (copy) command, 103
- destructive yank, 185
- detached processing, 486
- /dev directory, 409, **576–577, 869**
- /dev/lp0, 145
- /dev/null file, 346
- /dev/tty, 145
- devconfig file, 577
- “device busy” message, 410
- device-dependent, **577**
- device driver calls, **578**
- Device Driver Interface (DDI), **574**
- Device Driver Interface/Driver Kernel Interface Reference Manual (DDRM), **575**
- device drivers, 146, **577**
 - directory for, **576–577**
- device file, **578**
- device filename, 578
- device-independent, 578

- device-independent troff, **590**
- device interrupt, 120
- device number, 578
 - major, **757**
 - minor, **766**
 - variable to set, 839
- df command, **579–580**
- DFS (Distributed File System), **580**
- dfspace script, **580**
- /dgn directory, **580**
- dial-up connection
 - system interface setup to, 907
 - tip command to login, **897–898**
- diction command, **580–581**
- dictionary
 - comparing file contents to, **865–866**
 - finding words in system, **738–739**
 - running against password file, 87
- dictionary sort, 244
- diff command, 296, **581–583**, 797
 - for compressed files, 961
- diff3 command, **583–584**
- diffmk command, **584–585**
- dig command, 390, **585**
- dir command (ftp), 392, 656
- dir command (Samba), **449**
- dircmp command, **585–586**
- directories, 16, **24–31**, **586**
 - changing in Samba, **449**
 - changing working, **522**, **523**
 - for commands, **537**
 - comparing contents, **585–586**
 - copying in UUCP, 375
 - copying to archive files, 545–547
 - creating, **767**
 - deleting, **35**
 - deleting empty, **835–836**
 - empty, 29
 - file organization suggestion, 102
 - home, 33–34
 - listing contents, **40–45**, **746–747**
 - moving to parent, 35
 - mtools to manipulate, 456–458
 - NFS exporting for sharing, 386
 - ownership of, **104**
 - parent, **794**
 - paths, **28–29**
 - permissions, **105–106**, 107, 635
 - report on disk space use by, 599
 - root, **31–35**, **839**, 869
 - and script troubleshooting, 207
 - shell variable for, 225
 - standard, **869**
 - swapping in stack, **817**
 - trees and hierarchies, **27–31**
 - working, 33–34
- “directory: does not exist” message, 35
- directory (set argument), 193
- dirname command, **586–587**
- dirs command (C shell), 559, **587**
- dis command, **587**
- disable command, **588**
- disassembler, 587, **589**
- discard command (mailx), 755
- disconnect command (ftp), 656
- disk block number, from grep command, 278
- disk drives, device number, 757
- disk I/O, and program swapping, 119
- disk image copy, of floppy disk, 456
- disk space
 - report on free, **579–580**
 - use report for directory, 599
- diskcmp command, **589**
- diskcp command, **589–590**
- display command (telnet), 886
- dist command (MH), 765
- distributed file-sharing system, 782
- ditroff command, **590**
- dividing files into smaller segments, 561–562
- DNS (Domain Name System), 389
 - query of name servers, 585
- do command, **590**
- Do command (awk), 482
- Do command (Korn), 716
- Do command (nawk), 777
- document instance, **590**
- document type definition (DTD), **597**
- documents, report on writing style, **873–874**
- dollar sign (\$), 213, **591**. *See also* \$ (dollar sign)
- domain, **591**
 - domain address, **591**
 - vs. UUCP address, **389–390**
 - domain information proper, 585
 - domain member list, **591**
 - domain name, **592**
 - domain name server, **592**
 - Domain Name System (DNS), 389
 - domainname command, **592**

done command, 325, **592**

DOS (disk operating system), **592–593**

- access to files on Unix server. *See* Samba
- AUTOEXEC.BAT file, 91
- converting text file to Unix, **597**
- converting Unix text files to, **958**
- hierarchical file structure, 28
- Unix system file manipulation in, **452–453**

doscat command, 593

doscp command, 593

dosdir command, 593

dosemu program, 593, **594**

dosformat command, 593

dosls command, 593

dosmkdir command, 593

dosrm command, 593

dosrmdir command, 593

dot (.), **594, 799**

dot (.) command, **210, 594**

dot dot, **594**

dot file, **594–595**

dot requests, **595**

double-line spacing

- from pr command, 51, 157
- in sed stream editor, 299

double quotes ("), **228–229, 596**. *See also* quotation marks

dp command (Mail), 752

dp command (mailx), 755

dpost command, **596–597**

dt command (Mail), 752

dt command (mailx), 755

DTD (document type definition), **597**

dtoc command, **597**

dtype command, **597–599**

du command, **599**

Duff, Tom, 821

dumb terminals, 5

dump command, 413–414

dump of file, **788–789**

duplex, **600**

duplicates, suppressing in sorted lists, 246–247

E

e command, **600**

e keyword (bc), 492

e protocol, **617**

eb (error bells), **600**

EBCDIC (Extended Binary Coded Decimal Interchange Code), **600**

- dd command to convert, 266

echo, 5, 8, **600**

echo area, **602**

echo command, 96, 221, **222–223, 600–601**

echo command (Bourne), 505

echo command (C shell), 559

Echo command (Korn), 716

echo command (mailx), 755

echo shell variable, 556

echoing, **602**

ed editor, **602**

- starting within mail, 74

EDCDIC file format, converting between ASCII and, 574

edit, **603**

edit command (Mail), 752

edit command (mailx), 755

editing buffer, saving in vi, 171

EDITOR shell variable (Korn), 715

Effective User Identifier (euid), **621**

egrep command, **289–292, 603**

- regular expressions, 294
- regular expressions in descending precedence, 292
- summary, 293

eject command, **603–604**

electronic mail. *See* e-mail messages

electronic mail service, 11

ELF (Executable and Link Format) files, **533, 604**

- converting COFF to, 532–533
- manipulating comments sections, 761–762

elif command, **348–349, 604**

.elm file, 595

elm (mail program), 77, **604, 749**

else command, **605**

- in awk, 317

emacs editor, 77, **605–613, 749**

- cursor, 609
- editing commands, 610–612
- help for, 609
- key combinations, 608–609
- killed text, 610
- major and minor modes, 606–608
- mark, 610
- point, 609
- region, 610

.emacs file, 595

emacs option (Korn shell), 713

- e-mail, **613**. *See also* e-mail messages
- e-mail address, **613**
 - displaying, **753**
- e-mail messages, **57, 940–941**
 - appending to database, **662**
 - broadcasting to all network users, **843–844**
 - command to manage, **662–663**
 - controlling receipt during vi session, **166**
 - deleting when quitting, **66–67**
 - display options, **69**
 - displaying current, **66**
 - encryption, **955**
 - headers, **67–68**
 - to indicate completed printing, **149**
 - indicator for current, **68**
 - MIME for binary elements, **766**
 - more filter to control display, **66**
 - notification of arrival, **498, 786, 948**
 - for notification of file arrival, **381**
 - open to receiving, **59**
 - printing, **67**
 - reading from another source, **72**
 - report on status, **523–524**
 - responding to, **73–74**
 - retaining when exiting, **66**
 - saving and deleting, **70–72**
 - searches for regular expressions in, **868**
 - selecting, **68–70**
 - sending, **72–75**
 - sending to multiple users, **73**
 - sendmail as transport agent, **853**
 - smtp as transport agent, **862**
 - standard for distribution systems, **952**
 - summary of messages waiting delivery, **753**
 - vacation command to respond, **929–930**
- e-mail programs. *See also* mail
 - elm, **604**
 - MH message handling system, **764–765**
- embedded command, **614**
- empty directory, **29**
 - removing, **835–836**
- empty string, **333**
- emulation software, **5**
- enable command, **614**
- .enc filename extension, **638**
- encryption, **614**
 - bdes utility for, **494–495**
 - crypt command for, **550–551**
 - makekey utility for, **758**
 - of password, **795**
 - rot13, **839–840**
- encryption key, **88**
 - chkey command to change, **526**
- end command (C shell), **559, 614**
- END, in awk, **311–313**
- end-of-file (EOF) character, **564, 615**
 - for /dev/null file, **346**
 - environment variables to ignore, **684**
 - and read cancel exit status, **343**
- end-of-file (EOF) message, **30**
- end-of-text (ETX) character, **715**
- end-of-transmission (EOT), **615**
- endif command (C shell), **559, 615**
- endless loops, **326–328**
- endsw command, **615**
- Enter key, **6, 9, 615**
- env command, **211, 615–616**
- ENV environment variable, **616**
- ENV shell variable (Korn), **715**
- ENVIRON variable (gawk), **485**
- environment, **511, 616**
- environment file, **616**
- environment variables, **65, 210–211, 616–617**. *See also* shell variables
 - assigning value, **854**
 - in boot up, **235**
 - in C shell, **557–558**
 - displaying, **211**
 - displaying or changing, **615–616**
 - null value vs. unset, **214**
 - removing, **919**
- EOF (end-of-file) character, **615**
 - Ctrl-D (^D) for, **47**
- EOF (end-of-file) message, **30**
- EOT (end-of-transmission), **615**
- epoch, **617**
- eqn preprocessor, **617–618**
 - removing formatting from file, **575–576**
- equations, formatting text containing, **779**
- erasing. *See* deleting
- erexit option (Korn shell), **713**
- \$ERRNO shell variable (Korn), **714**
- error handling, **346–349, 618–619**
- error message file, creating from C source code, **769**
- error messages. *See* messages
 - sending to standard error, **347**
- errorbells (set argument), **193**
- errors, standard, **55**
- esac command, **349, 619**

- Esac command (Korn), 716
- Esc key, in macro, 191
- escape, **619**
- escape character, **619**
- escape commands, **619**
- Escape key, 265
 - as Meta key, 609
- escape sequences, **620**
 - for echo, 222–223
 - removing from file, 575–576
- escaped character, **619**
- /etc/cshrc file, 92
- /etc/default/lpd file, 148
- /etc directory, 84, 402, 869
 - files and directories in, **620–621**
- /etc/dump command, 413–414
- /etc/haltsys command, 407
- /etc/initab file, 234
- /etc/passwd file, **84–88**, 234–235, 307
 - cat command to examine, 85–86
 - password encryption in, 86–87
- /etc/profile file, 92
- /etc/restor command, 413–414
- /etc/shutdown command, 407–408
- /etc/termcap file, 162–163
- ETX (end-of-text) character, **615**
- eid (Effective User Identifier), **621**
- eval command, **621**
- eval command (Bourne), 505
- eval command (C shell), 559
- Eval command (Korn), 716
- ex command (mail), 66
- ex command (Mail), 752
- ex command (mailx), 755
- ex command mode, **187–188**
- ex editor, 160, **621–623**
 - commands, 623
 - line addressing in, 622
- ex Escape mode, in vi editor, 167–168
- ex mode commands (vi), **188–196**
 - abbr command, **189–195**
- ex mode, for vi editor, 166
- exa-, **623**
- exabyte, **624**
- exclamation point (!), **624**. *See also* ! (bang)
- exec command, **624**
- exec command (Bourne), 505, 624
- exec command (C shell), 559, 624
- Exec command (Korn), 716
- exec system call, 123
- Executable and Link Format (ELF) files, **533**
- executable file, 236
 - compressing and uncompressing, **670**
 - default name, 470
- “execute permission denied” message, 205
- execute permissions, 104, 108, 527, **624–625**, 635, 800
 - for directories, 105
 - owner, group and public, 107
 - for script file, 323
 - testing for, 338
- executing remote commands, **625**
- EXINIT environment variable, 191, 557
- exit command, 219, 327, 346, **625**
- exit command (awk), 482
- exit command (Bourne), 505
- exit command (C shell), 559
- Exit command (Korn), 716
- exit command (mail), 66
- exit command (Mail), 752
- exit command (mailx), 755
- exit command (nawk), 777
- exit command (Samba), **449**
- exit statement, 319
- exit status, 219, 325, **625**
 - of last executed command, 335
 - of read command, 343
 - test command to return, 329
- exit to shell, signal generated on, 327
- exit value, return by command, 215
- exiting, vi editor, 173
- exp command (awk), 482
- exp command (nawk), 777
- exp operation (awk), 314
- expand command, **625–626**
- explain program, **626**
- export command, 99, **626**
- export command (Bourne), 505
- export command (Korn), 716
- /export directory, **626**
- exportfs command, **626**
- exporting, shell variables, **216–218**
- expr command, 362–363, **626–628**
- expressions. *See* regular expressions
- .excrc file, 166, **195**, 595, **628**
 - abbreviations in, 189
 - macros in, 191
- exstr command, **628**
- ext2fs (Second Extended Filesystem), **628**
- Extended Binary Coded Decimal Inter-change Code (EBCDIC), **600**

extracting
 files from archives, 880
 from tar backup, 416
 yacc (extended yacc), **628**

F

.f filename extension, 638
 .F filename extension, 638
 f (finger) command, 629
 f protocol, **651**
 f77 (Fortran compiler), **654**
 face command, **629**
 FACE (Framed Access Command Environment), **629**
 factor command, **630**
 false, **630**
 FAQ (frequently asked questions), **630**
 fault tolerance, RAID (redundant array of inexpensive disks) for, **819–820**
 fc command, **630–631**
 FCEDIT environment variable, **631**
 FCEDIT shell variable (Korn), 715
 fd (file descriptor), for open files, 347
 FDDI (Fiber Distributed Data Interface), standard, 469
 fdformat command, **631–632**
 fg command, 126–127, 486, **632**
 fg command (C shell), 559
 Fg command (Korn), 716
 fgrep command, **288–289, 632**
 regular expressions, 294
 summary, 293
 fi command, **632**
 Fi command (Korn), 716
 Fiber Distributed Data Interface (FDDI), standard, 469
 field separators, **684**
 in awk, 306, 311
 fields
 in awk, **303–304**
 removing from file, **253–254**
 for uniq command, 249–250
 for who command response, 60
 FIFO file, **633, 636**
 creating, 767
 ignore variable, 556, **633**
 file allocation tables, and mtools, 452
 file attributes, **634**
 mattrib to change, 456
 file command, **84–87, 633–634**
 file command (Mail), 752
 file command (mailx), 755

file commands, **634**
 file creation mask, **548, 911–912**
 file descriptor (fd), for open files, 347
 file extension in DOS, 26
 file flags, command to change, **525**
 file formats
 converting, **573–574**
 ELF (Executable and Link Format) files, **604**
 file locking, **635**
 “file not found” message, 17, 28, 206
 file server, **636**
 file size, 30
 file transfer. *See also* ftp command
 to remote system, 928–929
 file types, **636**
 command to determine, 84–85
 on Internet, **689–690**
 filec environment variable, **636**
 Filec shell variable, 556
 filename completion, **638**
 filename expansion, **638**
 filename extension, **638–639**
 disabling, 785
 types on Internet, 689–690
 filename generation, 230–231, 475, **639**
 “filename: not found” message, 28
 filename substitution, 475, **639, 663**
 FILENAME variable (awk), 312, 484
 filenames, 16, **26–27, 637**
 changing, 774–775
 characters to avoid, 637
 DOS vs. Unix, 593
 duplicates, 29–30
 extracting from path statement, 488–489
 as ls argument, 40–41
 for output redirection, 39
 files, **16–17**
 adding to archive file, 473
 ambiguous reference, **467**
 appending output to, **54–55**
 bdiff utility to compare, **495–496**
 buffers for changes, 406–407
 cat command to create, **47–48**
 changing modification and access time for, **898–900**
 combining content of multiple in columns, 255–257
 comparing, **531–532, 849–850**
 comparing 3 versions, **583–584**
 comparing revisions, **584–585**

- compressing, **540–541**
- copying, 544–545
- copying and converting, **573–574**
- copying to archive files, 545–547
- deleting in Samba, **449**
- displaying, **674**
- displaying contents, 45–46
- displaying contents of packed, **799**
- displaying is specified format, 675–676
- distribution over networks, **386–387**
- dump of, **788–789**
- encrypting, 87–88
- find to search for, **257–263**
- finding by searching database, 736
- forcing overwrite in vi, 171
- grep to search contents, 274
- hierarchical structure, 27, **676–677**
- invisible, **692**
- linking, 31
- listing, 40
- mtools to manipulate, 456–458
- open, **789**
- ordinary, **792**
- orphaned, **792**
- overwriting, 30, 54
- ownership of, **104**
- permissions, **104–105, 635**
- printing multiple, 147–148
- removing, **834–835**
- renaming and moving, **774–775**
- restoring, 914
- rm to erase, **52–54**
- and sed output, 296
- separating into smaller pieces, 561–562
- shell manipulation within vi, 188
- sort command for multiple, **246**
- splitting, **252–253**
- suggestions for directory organization, 102
- testing, **338–339**
- tracking multiple revisions of, **846–847**
- filesystem, **409–410, 639**
 - remote, **830–831**
 - root, **839**
- filesystem check command, **653**
- filesystem data block, fragment of, **651**
- filter command, **640**
- filters, 20, 50
 - for pipelines, 52
 - for printers, 147
 - scripts for, 201
- find command, **257–263, 640–643**
 - cpio option, 261
 - exec option, 260
 - logical operations, 259
 - perm option, 261–262
 - primary expressions, 262–263
 - type option, 261
- finger command, **643–645**
 - and .plan file, 806
- finger entry, **645**
- firewall, **645**
- fixed strings, fgrep to search for, **288–289**
- flat files, 30–31
- flex, **645**
- floppy disks
 - for backup medium, 412
 - backup to, 415
 - command to eject from drive, 603–604
 - comparing, **589**
 - copying, **589–590**
 - determining type, 597–599
 - formatting, **631–632, 650**
 - splitting files when backing up, 414
- floppy drives
 - configuration file properties for, 454–455
 - drive parameters for mtools, **453–458**
- floppyd command (mtools), **455–456**
- flow control, 202. *See also* if command
 - awk, **316–319**
 - branching with && and ||, **351**
 - case statement, **349–351**
 - elif command, **348–349**
 - if command, **683–684**
 - for loop, **356–360**
 - of script
 - exit status for, 219
 - switch command, 560, 610, **876**
 - until loop, **328–329**
 - while loop, **324–329**
- /flush command (IRC), 694
- flushing pending file I/O, 407
- fmlr command, **646**
- FMLI (Forms and Menu Language Interpreter), **646**
- fmt command, 640, **646–647**
- fntmsg command, **647–648**
- FNR variable (awk), 312, 484
- focus, **648**
- fold command, **648**
- folder command (Mail), 752
- folder command (mailx), 755

- folder command (MH), 765
 - folder environment variable, 71
 - folders. *See* directories
 - folders command (Mail), 752
 - folders command (mailx), 755
 - folders command (MH), 765
 - followup command (mailx), 755
 - Followup command (mailx), 755
 - fonts
 - creating files, 890
 - listing available, 953
 - xfd to display, **951**
 - for command (awk), 482
 - For command (Korn), 716
 - for command (nawk), 777
 - for keyword, **649**
 - for keyword (bc), 491
 - for loop, **356–360**
 - foreach command (C shell), 559, **649**
 - end to terminate, 614
 - foreground, 125, **649**
 - bringing background job to, 486, 632
 - foreground processing, **649**
 - fork system call, 123–124, **650**
 - format command, **650**
 - formatting
 - floppy disks, **631–632, 650**
 - with pr command, **156–157**
 - text files, 50, **780–781**
 - formfeed, 223, 265, **650**
 - Forms and Menu Language Interpreter (FMLI), **646**
 - Fortran language
 - filter for translating file, 651
 - splitting source code into routines, **654**
 - standard, 468
 - forw command (MH), 765
 - forward quotes, 95
 - forward searches, 283
 - in vi editor, 186
 - forwarding mail, in UUCP, 371–372
 - for.while, in awk, 318–319
 - 4.4BSD Lite, **651**
 - Fox, Brian, 489
 - FPATH environment variable, **651**
 - FPATH shell variable (Korn), 715
 - fpr filter, **651**
 - fragment, **651**
 - fragmentation, **651–652**
 - Framed Access Command Environment (FACE), **629**
 - free blocks, **652**
 - free disk space, report on, **579–580**
 - Free Software Foundation (FSF), 605, 612, **654**
 - BISON, 499
 - file compression utilities, **670–672**
 - General Public License, 543
 - GNU Project, 489
 - Hurd project, **681**
 - FreeBSD, **652**
 - freeware, **652**
 - frequently asked questions (FAQ), **630**
 - from command, **653**
 - from command (Mail), 752
 - from command (mailx), 756
 - frontware, 434
 - FS variable (awk), 311, 312, 484
 - fsck command, 405, 410, **653, 740**
 - fsplit command, **654**
 - fstat command, **654**
 - ftp
 - anonymous, 391, **467–468**
 - file transfer with, **390–393**
 - ftp command, **654–657**
 - FTP (File Transfer Protocol), **658**
 - configuration information file for, 780
 - ftpd daemon, 569
 - full duplex, 600
 - full-screen editor, 658
 - function, call to, 510
 - function command (awk), 482
 - Function command (Korn), 716
 - Function command (nawk), 778
 - fvwm, **658**
-
- G
- g (global) command, 283
 - G (global) command, 284
 - G protocol, **664**
 - g++ shell script, **658**
 - gadgets, **658**
 - Gaines, Stockton, 77
 - gateway, 367
 - gawk command, 479, **659**
 - gcc C compiler, **659–660**
 - gcore command, **660**
 - gdb (debugger), **660–661**
 - GDS (Global Directory Service), **661**
 - gencat command, **662**
 - General Sherman, 185
 - geographical domains, 389

get command (ftp), 392, 393, 656
 get command (Samba), **450**
 get program (SCCS), 847
 getline command (awk), 483
 getline command (nawk), 778
 getoptcv command, **662**
 getopts command, **662**
 getopts command (Bourne), 505
 getopts command (Korn), 716
 gettxt command, **662–663**
 getty command, in boot up, 234
 Ghostview, **663**
 Gid, chpass to change, 530
 .gif filename extension, 638, 690
 .gl filename extension, 638
 glob command (C shell), 559, **663**
 global command, in ed editor, 623
 global commands, **283–284**
 inverse, **284–287**
 Global Directory Service (GDS), **661**
 global login profile, 91
 in Bourne shell, 92
 global variables, 217, **663**
 globbing, **663**
 gmacs option (Korn shell), 713
 GNU, **663–664**
 GNU C compiler preprocessor, 547
 goodpw command (SCO UNIX), 84
 .gopherrc file, 595
 goto command (C shell), 559, **664**
 gprof tool, **664**
 grace period, for shutdown, 408
 graph command, **664–665**
 graphical desktop, 437
 Graphical User Interface (GUI), 6, 200–201, 422. *See also* X Windows systems
 Open Desktop, **789**
 grave accent. *See* backquote
 greater-than (<) symbol, 39, **665**
 Greer, Ken, 884
 grep command, 209, 273, **274–278**, 640, **665–667**
 -b option, **278**
 -c option to count matching lines, **277**
 case-sensitive searches, **276–278**
 for compressed files, 962
 -e option, **278**
 egrep command, **289–292**
 family summary, **292–294**
 fgrep command, **288–289**
 -h option for multiple files, **277**

 -l option, **278**
 -n option, **276–277**
 quoting search pattern, **275**
 regular expressions, **278–288**, 294
 regular expressions in descending precedence, 292
 -s option, **278**
 -v option, **277–278**
 -w (word) option, **275**
 grodvi command, 668
 groff command, **667–668**
 refer command for, **827–828**
 grog command, 668
 grops command, 668
 grotty command, 668
 group, **669**
 group command (mailx), 756
 group ID, **669**, 761
 group permissions, 107
 viewing, 108–109
 groups
 changing, **111–112**
 changing file association, **526**
 find command to select files belonging to, 261
 membership, 104–105
 groups command, **669**
 groupware, **669**
 gsub command (awk), 483
 gsub command (nawk), 778
 GUI (Graphical User Interface), 6, 200–201, 422. *See also* X Window systems
 Open Desktop, **789**
 gunzip command, 670, 671
 gwm (window manager), **670**
 .gz filename extension, 638, 690
 recompressing .Z files to, 962
 gzexe command, **670**
 gzip, **670–672**
 gzip files, 961–962

H

.h filename extension, 638
 hacking, 200
 half-duplex, 600
 haltsys command, 407
 hanpug signal, 327
 hard copy, 143
 hard drives
 fragmentation, **651–652**

- fscck command to check and repair problems, **653**
 - incremental backup, **685**
 - hard link, **672**, 735, 736
 - hard-wired, **673**
 - Hardpaths shell variable, 556
 - hardware interrupt, **672**
 - hardwired connection, 4
 - hash command (Bourne), 506, **673**
 - hash command (ftp), 392, 657
 - Hash command (Korn), 716
 - hash symbol (#). *See* # (pound sign)
 - hash table, **673**
 - rebuilding, **829**
 - removing internal, 915
 - hashing, **673**
 - hashstat command (C shell), 559, **673**
 - hd command, **674**
 - head command, **250–251**, 269, 640, **675**
 - header file, 684
 - headers
 - for e-mail messages, 65, **67–68**
 - skipping, 70
 - as pr default, 50
 - headers command (Mail), 752
 - headers command (mailx), 756
 - heads on floppy disks, 454
 - hello command, **675**
 - help command (ftp), 391, 656
 - /help command (IRC), 694
 - help command (Mail), 752
 - help command (mailx), 756
 - help command (Samba), **450**
 - help, for mail program, 65–66
 - help program (SCCS), 847
 - Hewlett-Packard 2640 terminal series, 680
 - hexdump command, **675–676**
 - hidden characters, **676**
 - hidden files, 594
 - hierarchical file structure, 27, **676–677**
 - leaf in, **725**
 - high-level backups, 411
 - histchars environment variable, **677**
 - Histchars shell variable, 556
 - HISTFILE shell variable (Korn), 715
 - history, **677**
 - history command (C shell), 559, **677–678**
 - History command (Korn), 716
 - .history file, 595, **678**
 - history shell variable, 556
 - HISTORY shell variable (Korn), 715
 - HISTSIZE environment variable, **678**, 718
 - hold command (Mail), 752
 - hold command (mailx), 756
 - home, **678**
 - home directory, 33–34, 38, 101, 465, **678**, **678–679**, 869
 - changing, 616
 - chpass to change, 530
 - .login, 92
 - moving to, 102
 - .profile file, 92
 - returning to, 34
 - HOME environment variable, 557
 - home page, **679**
 - HOME shell variable, 94, 211, 556, **678**
 - HOME shell variable (Bourne), 504
 - HOME shell variable (Korn), 715
 - HoneyDanBer UUCP, **679**, 923
 - Honeyman, Peter, 679, 923
 - Horton, Mark, 567
 - host, **679**
 - host command, 390
 - host computer, summary of system status, **841–842**
 - Host-to-host Transport layer (TCP/IP), 884
 - hostid, **679**
 - hostname, **679**
 - hp command, **680**
 - HP-UX, **680**
 - hpterm, 431, 956
 - HQX filename extension, 690
 - HTML (Hypertext Markup Language), **680**
 - HTTP (Hypertext Transfer Protocol), **680–681**
 - Huffman coding, 539
 - Hurd project, **681**
 - hwconfig command, **681–682**
 - hypermedia, **682**
 - hypertext, 395, **682**
 - Hypertext Markup Language (HTML), **680**
 - Hypertext Transfer Protocol (HTTP), **680–681**
 - hyphen (-)
 - in command syntax, 18, 44
 - for grep range, 281
 - HZ environment variable, 212
-
- |
- i-node table, **688**
 - i-nodes, **30**, **687–688**
 - i-number, **691**

- I/O devices, file-like interface for, 145–146
- ibase keyword (bc), 492
- ICMP (Internet Control Message Protocol), 385, 883
- icon in X, 428
- iconv command, **683**
- id command, **683**
- ident program (RCS), 823
- if command, 344–346, **683–684**
 - alternative to, **351**
 - fi to terminate, **632**
 - then keyword, **890**
- if command (awk), 317, 483
- if command (C shell), 559
- if command (Korn), 716
- if command (nawk), 778
- if keyword (bc), 491
- IFS shell variable, 94, 211, 214, **684**
- IFS shell variable (Bourne), 504
- IFS shell variable (Korn), 715
- ignore command, 70
- ignore command (Mail), 752
- ignore command (mailx), 756
- ignorecase (set argument), 193
- IGNORECASE variable (gawk), 485
- ignoreeof environment variable, **684**
- ignoreeof option (Korn shell), 713
- Ignoreeof shell variable, 556
- image copy, **684**
- image in Unix, 121, 122
- images, JPEG file compression, **700–701**
- imake, 684
- in-line input, 55
- in statement, in for loop, 357
- inactive window, **684**
- inc command (MH), 765
- include file, **684**
- inclusive OR, 309–310
- incremental backup, 411, **685**
- incremental search, **685**
- indent command, **685**
- indenting, 299
 - when printing, 157
- index command (awk), 483
- index command (nawk), 778
- index, permuted, **801**
 - creating, **816–817**
- indxib command, **685–686**
- inetd daemon, 569
- info command, **686**
- InfoExplorer, 686
- information node, 687
- inheritance, **686**
- init level, for shutdown, 408
- init process, 124, **686–687**
 - in boot up, 234
- initialization file, **687**
 - for X, 430
- initialization string, **687**
- input, 5
 - buffer for, 8
 - erasing line, 564, 565
 - redirecting, 40, **50–51**
 - typing errors, **8**
- input mode, in vi editor, 932–933
- input/output streams, 295
- input stream, 295
- insert command
 - in ed editor, 623
 - repeating in vi, 179
- Insert key, 5
- insert mode, in vi editor, 167, 170, 181
- inserting, text in sed stream editor, **300**
- installing, UUCP network software, 367–368
- Institute of Electrical and Electronics Engineers, 806
- int command (awk), 483
- int command (nawk), 778
- int operation (awk), 314
- integer command, **688**
- Integer command (Korn), 716
- integers
 - comparing, **337–338**
 - remainder after division, **769**
- Intel-based PCs
 - Linux for, 731
 - NetBSD for, **779**
 - Solaris for, **863**
- intelligent terminals, 5
- interactive, **688**
- interactive global command, 284
- Interactive UNIX, **688**
- interface definition, for character device, 523
- internal command, 508
- International Organization for Standardization (ISO), 468, **695**
- International Organization for Standardization/Open System Interconnection model, **696**
- Internet, **388–396, 688**
 - anonymous ftp access, 467–468
 - file transfer with ftp, **390–393**

file types, **689–690**
 Internet Relay Chat (IRC), **395–396**
 telnet to connect to remote computer,
394–395
 URL (Uniform Resource Locator), **920**
 USENET, **396**
 what it is, **388**
 World Wide Web, **395**
 for X System files, 437

internet, **688**
 Internet address, **689**
 Internet Control Message Protocol (ICMP), 385, 883
 Internet layer (TCP/IP), 884
 Internet Packet Exchange (IPX), **694**
 Internet Protocol (IP), **692**
 Internet Relay Chat (IRC), **395–396, 694–695**
 internetwork, 688
 interpreter, **690**
 interprocess communications, **690**
 printing information, **693–694**
 interrupt handler, **691**
 interrupting program, 563
 interrupting program, in endless loop, 326–327
 interrupts, **672, 691**
 for peripherals, 120–121
 inverse global commands, **284–287**
 invert command, **691–692**
 invisible character, **692**
 invisible file, **692**
 ioctl call, 578
 IP address, command to provide, **787**
 IP (Internet Protocol), **692**
 address, 389
 ipcrm command, **692**
 ipcs command, **693–694**
 IPX (Internet Packet Exchange), **694**
 IRC (Internet Relay Chat), **395–396, 694–695**
 ismpx command, **695**
 ISO (International Organization for
 Standardization), 468, **695**
 ISO/OSI model, **696**
 isochronous, **696**

J

J (join) command, in vi editor, 181
 j keyword (bc), 492
 Java, **697**
 job control, **697–698**
 job number, **698**

jobs, **697**
 at job queue, **478–479**
 scheduling, 549–550
 jobs command, **698**
 to list running jobs, 486
 jobs command (C shell), 559
 Jobs command (Korn), 716
 Jobs, Steve, 422
 joe (editor), **698**
 join command, **699**
 /join command (IRC), 695
 jot command, **699–700**
 jove editor, **700**
 Joy, Bill, 552, 621
 JPEG filename extension, 690, **700–701**
 .jpg filename extension, 638, 690
 jsh, **701**
 jterm command, **701**
 jukebox, **701**
 Julian date, **701**
 jwin command, **701**

K

K&R, **702**
 kdestroy command, **702**
 kdump command, **702–703**
 Kerberos, **703**
 ksrvtgt utility, **720**
 login after ticket expiration, **707–708**
 register command for, **828**
 Kerberos tickets, 703
 destroying, 702
 listing current, **708**
 kernel, 119, **704**
 boot program to load, 405
 rebuilding, **826**
 kernel address space, **704**
 kernel description file, **704**
 kernel process tracing, 720–721
 kernel trace information, displaying, **702–703**
 Kernighan, Brian, 702, 776
 key binding, **704**
 keyboard, **5–6**
 click control, 531
 Ctrl key, **564**
 Enter key, **9**
 file creation from input, 47
 mapping for vi editor, 161–162
 stdin to reference, 38

keylogin, **704**
 keylogout, **704**
 keys, for sort command, 240
 keyword, **704–705**
 keyword lookup, in online manual pages, 471
 keyword option (Korn shell), 713
 kill character, **706**
 kill command, **127–129, 705–706**
 kill command (C shell), 559
 Kill command (Korn), 717
 kill file, **707**
 kill ring, in emacs editor, 610
 kill signal, **707**
 killall command, 129
 killer signal, 327
 kinit command, **707–708**
 klist command, **708**
 Knuth, Donald, 889
 Korn, David, 708
 Korn shell, 89, 91, **708–719**, 856
 alias command syntax, 466–467
 arrays and arithmetic expressions, 719
 Bourne shell scripts in, 201
 command history, 718–719
 commands, 709–710, 716–718
 coprocesses, 719
 filename metacharacters, 710
 options, 712–713
 quoting in, 712
 redirecting in, 710–712
 rksh, **833**
 shell variables, 713–715
 startup files, 709
 kpasswd command, 795
 ksh command, **719–720**. *See also* Korn shell
 .kshrc file, 465, 709, **720**
 ksrvtgt utility, **720**
 ktrace command, **720–721**

L

l, 721
 l filename extension, 690
 l keyword (bc), 492
 lam command, **721–722**
 Lampport, Leslie, 723
 LAN (local area network), **722**. *See also* local area network (LAN)
 LANG shell variable (Korn), 715
 laser printer, formatting text file for, 905

last command, **722–723**
 “last in last out” data management, 729
 lastcomm command, **723**
 LATEX, **723–724**
 layers command, **724**
 LBX (low-bandwidth X), **724**
 lc command, **48–49**
 lcd command (ftp), 392, 656
 lcd command (Samba), **450**
 ld (link editor), **725**
 library file maintenance for, 472
 LDAP (Lightweight Directory Access Protocol), 952
 ldd utility, **725**
 Lea, Ian, 893
 leader, of spawned processes, 129
 leaf, **725**
 learn command, **725**
 leave command, **725–726**
 /leave command (IRC), 695
 Lempel-Ziv (LZ) algorithm, 672, 740, **748**
 length command (awk), 483
 length command (nawk), 778
 length function (awk), 309
 length keyword (bc), 492
 less command, 640, **726–727**
 less than (>) symbol, **728**
 Let command (Korn), 717, **728**
 lex command, **728**
 lexical analysis, **728**
 /lib directory, **728**
 library, **728**
 library function, **729**
 Lightweight Directory Access Protocol (LDAP), 952
 LILO, **729**
 limit command (C shell), 559, **729**
 Lincoln, 185
 line command, **730**
 line editor, **730**
 line erase character, 706
 line numbers
 adding to text file, **783–785**
 from pr command, 157
 line of text
 counting for file, 49–50
 deleting, 8
 line printers, 144, **730**
 creating file for output to, **787**
 linefeed, **730**
 LINENO shell variable, **730**
 \$LINENO shell variable (Korn), 714

lines

- counting, 941–942
- extracting common from sorted files, 699
- reversing in file, 832
- LINES shell variable (Korn), 715
- link, **730–731**
- link editor, 725, **731**
- lint, **731**
- Linux, **731–733**
 - minimum RAM, 119
 - steps to rebuild kernel, 826
- Linux Journal*, 733
- Linux loader, 729
- /list command (IRC), 695
- list command (mailx), 756
- list (set argument), 193
- listserv, **733–734**
- listusers command, **734**
- lkbib command, **734–735**
- ln (link) command, 31, **735–736**
- local area network (LAN), **722**
 - displaying status of systems on, **842–843**
 - displaying users logged on, 844
 - users logged on, **843**
- local printers, **144–145**, 156
 - printing to, **744**
- local systems, host status of, 842
- local variables, 216, 217, **736**
- locate command, **736**
- lock command, **736**
- lockd daemon, 569
- locking files, **635**
- log command (nawk), 778
- log operation (awk), 314
- logger command, **736**
- logging in, 6, **7–8**, **737**
 - changing entry, **830**
 - checking for mail when, 64
 - errors, **9**
 - greetings, **10–11**
 - report on last, **722–723**
 - as root, 58
 - X Window systems, **430**
- logging off, **12–13**, **737**
- logical operators, in awk, **309–310**
- login, **737**
 - remote, **831**
 - root, **839**
- login command (C shell), 559
- login command, in boot up, 234
- .login file, 202, 465, 553, 595, **737**
- login group, assigning user to, 418
- “Login incorrect” message, 9
- login name, **737**
 - displaying, 683, 944
 - process owner from ps command, 131
- login profile, **91–93**
 - Bourne shell, **92**
 - in C shell, **92–93**
 - chpass to change, 530
 - personal, **93–99**
- login: prompt, 7, 8
- login shell, **737**
- logname command, **738**
- LOGNAME environment variable, 557
- logon, 8. *See also* user name
 - command to list, 18
 - grep command to check for, 286
- logout command, **738**
- .logout file, 553, 595, **738**
- logs, for security, 403
- long filename, **738**
- look command, 640, **738–739**
- lookbib command, **739**
- loops
 - debugging, 362
 - endless, **326–328**
- lorderr utility, **739**
- lossless compression, **740**
- lossy compression, 700, **740**
- /lost+found directory, **740**
- low-bandwidth X (LBX), **724**
- low-level backups, 411
- lowercase
 - for logon, 8
 - translating to uppercase, 900
- LP daemon, 145
- lp (line print) command, 144, **147–153**, **740–741**
 - i (inquire) option, **155**
 - immediate copies of files in, 153
- lpd daemon, 569
- lpq command, **741–742**
- lpr command, 67, **742–743**
- lprint command, **156**, **744**
- lprm command, **744**
- lprprof command, **744**
- lpstat command, **154–155**, **745–746**
 - for print request id, 155
- lpctest command, **746**
- ls command, **40–45**, **746–747**

online manual pages for, 43
 and permissions, 105
 wildcards for, **41–43**

ls command (ftp), 656

ls command (Samba), **450**

ls-lR.Z filename extension, 689

ls-ltR.Z filename extension, 689

Lynx, **748**

Lyrinx, and /etc/termcap, 163

LZ (Lempel-Ziv) algorithm, **748**

M

m (mark) command (vi), 187

m4 (macro language preprocessor), **764**

Mach operating system, **748**

machid command, **748**

Macintosh interface, 425

macros, 151, 189

- assignments to avoid, 189–190
- mm, **769**
- ms, **773**
- removing during session, 191
- removing from file, 575–576
- troff, **906**

magic (set argument), 193

magnetic tapes

- command to read and write to, 469–470
- copying and verifying, **882**
- manipulating, 773–774

mail, **748–750**

mail alias file, recreating database for, 780

Mail command, 73, 749, **751–753**

mail command, 58, 64, **750**

- ? for command mode prompt, 65
- escape character for command entry, 74
- help for, 65–66
- leaving, **66–67**
- mail, 73
- summary, 75–77

mail command (Mail), 752

mail command (mailx), 756

Mail command (mailx), 756

MAIL environment variable, 557

mail headers, printing, 653

MAIL shell variable, 94

mail shell variable, 556

MAIL shell variable (Bourne), 504

MAIL shell variable (Korn), 715

mail transport agents, 77

- mail user agents, 77
- mailalias command, **753**
- MAILCHECK shell variable, 94, 214
- MAILCHECK shell variable (Bourne), 504
- MAILCHECK shell variable (Korn), 715
- mailing list, 733–734
- MAILPATH shell variable (Korn), 715
- mailq command, **753**
- mail.rc file, **753**
- .mailrc file, **372–373**, 595, **754**
- mailserv, 733
- mailx command, 77, 749, **754–756**
 - escape commands, **619**
- mailx.rc file, **757**
- maintenance mode, 405
- major device number, **757**, 839
- major mode, **757**
- majordomo, 733
- make utility, **757**
- makefile file, **757–758**
- makekey utility, **758**
- man command, **43–45**, **758–759**
 - options for customizing and printing, 45
 - syntax in, 44–45
- man- command, 17
- man macros, 906
- man pages, **759–760**
 - X interface to, **954**
- managing processes, **760–761**
- manuscript macros, **769**
- map, **761**
- map command, **189–192**
- map! command, **189–192**
- mapping
 - files to i-nodes, 30
 - remote, **831**
- mark command (MH), 765
- mark, in emacs editor, 610
- markdirs option (Korn shell), 713
- marking text, in vi editor, 187
- mask, **761**
- mass-storage device, unmounting removable, 410
- master map, **761**
- match command (awk), 483
- match command (nawk), 778
- math, awk and, **313–316**
- mathematical symbols, formatting text containing, 779
- mattribcommand (mtools), **456**
- mbox command (Mail), 752
- mbox command (mailx), 756
- mbox file, 67, **761**

- mcatcommand (mtools), **456**
- modcommand (mtools), **456**
- mcopyscommand (mtools), **456**
- mcs command, **761–762**
- md command (Samba), **451**
- mdelcommand (mtools), **457**
- mdeltreecommand (mtools), **457**
- mdircommand (mtools), **457–458**
- mducommand (mtools), **458**
- me macros, **762**, 906
- measurement units, converting, **916**
- memory
 - stack, **868**
 - status of blocks, 647
 - in terminal, 5
 - virtual, **938–939**
- menu, **762**
 - code for, 352–353
 - quit variable in, 341–342
 - read command, **342–343**
 - shell script to create, **322–363**
 - user response to prompt, 344–346
 - in xterm window, 434
- Merge, **459**, 593
- merge, **762**
- merge command, **763**
- merge program (RCS), 823
- mesg command, 59, **763**
- mesg (set argument), 193
- message of the day (motd), 11, 93
- messages
 - “device busy”, 410
 - “directory: does not exist”, 35
 - EOF (end-of-file), 30
 - “execute permission denied”, 205
 - “filename: not found”, 17, 28, 206
 - “Login incorrect”, 9
 - “Mismatch - password unchanged”, 83
 - “not found”, 12
 - permission denied, 60–61
 - “remote access to path/file denied”, 375
 - shutdown warning for users, 408
 - suppressing from grep command, **278**
 - “Using open mode”, 163
 - You have mail, 64
- Meta key, **764**
 - in emacs editor, 608–609
- metacharacters, 95, 218, **226–233**, **763**
 - # (pound sign) for comments, **227–228**
 - backslash (\), **226–227**
 - in Bourne shell, 501–502
 - in C shell, 554
 - " (double quotes), **228–229**
 - in grep command, 279
 - in Korn shell, 710
 - quoting, 333, **818**
 - sequences, **229–232**
 - summary, 232–233
- metafile, **764**
- mformatcommand (mtools), **458**
- mget command (ftp), 392, 657
- MH message handling system, 77, 749, **764–765**
- mhl command (MH), 765
- mhmail command (MH), 765
- mhn command (MH), 765
- mhook command (MH), 765
- mhparam command (MH), 765
- mhpath command (MH), 765
- MIME (Multipurpose Internet Mail Extensions), **766**
- minibuffer, **766**
- minor device number, **766**, 839
- minor mode, **766**
- “Mismatch - password unchanged” message, 83
- mkdep command, **766**
- mkdir command, 34, 103, **767**
- mkdir command (ftp), 656
- mkfifo command, **767**
- mkfs command, 409
- mklocale command, **768**
- mkmsgs command, **768**
- mknod command, **768**
- mksrt command, **769**
- .mm filename extension, 638
- mm macros, **769**, 906
- mmdcommand (mtools), **458**
- mmovecommand (mtools), **458**
- /mnt directory, **769**
- mode, **769**
- mode argument for chmod command, 112
- /mode command (IRC), 695
- mode line, **769**
- modem connection, 4
 - hanging up, 13
 - utility for, 562–563
- modules, 363
- modulo, **769**
- monitor. *See also* screen display
- monitor option (Korn shell), 713
- Montoulli, Lou, 748
- MORE environment variable, **771**

more filter, 19–20, 640, **769–770**
 for mail message display, 66

Mosaic browser, 395

motd (message of the day), 11, 93

Motif window manager (mwm), 428–429, 436, **771, 776**

mount, **771**

mount command, **771–772**

mount point, **772**

mounting filesystem, 409, **772**
 manual, 410

mouse cursor, in xterm window, 433

move command, in ed editor, 623

moving, files, 774–775

MPEG filename extension, 690

.mpg filename extension, 638, 690

mput command (ftp), 392, 657

mrencommand (mtools), **458**
 .ms filename extension, 639

ms macros, **773**, 906

mscreen command, **772**

mset command, **772**

/msg command (IRC), 695

msgchk command (MH), 765

msgs command, **773**

msh command (MH), 765

mt utility, **773–774**

mtools, 442, **452–453**
 drive parameters for, **453–458**
 floppyd command, **455–456**
 mattrib, **456**
 mcat, **456**
 mcd, **456**
 mcopy, **456**
 mdel, **457**
 mdeltree, **457**
 mdir, **457–458**
 mdu, **458**
 mformat, **458**
 mmd, **458**
 mmove, **458**
 mren, **458**
 mtype, **458**
 running, **455–458**

mtypecommand (mtools), **458**

multicommand line, **134–136**

Multiplan, and /etc/termcap, 163

multiprocessor system, 118

multiprogramming operating systems, **118–120**

multitasking, **120–121**

multiuser environment, 118
 security for, 7

multiuser mode, 405, **406**

mush (mail user's shell), 749, **774**

mv command, **377, 774–775**

mview macros, 906

mwm (Motif window manager), **776**

mymenu file, 322

N

NAK (negative acknowledgment), **776**

name generation, 226

named daemon, 569

named pipe, **776**, 805

names
 for printers, 146
 of shell, **90–91**

nawk, 479, **776–779**

negative numbers, sorting, 245

neqn, **779**

Net News software, 396

NetBIOS connectivity, 444

NetBSD, **779**
 .netrc file, 595, **780**

Network Access layer (TCP/IP), 884

network connections
 copying files over, **821–822**
 sockets for, **863**
 testing, 804–805

network filesystem (NFS), **386**

Network Information Service (NIS) domain, **783**
 setting or displaying name, 592

network layer (ISO/OSI), 696

networking reference model, 696

networks, **384–388**
 client-server computing, **387–388**
 file distribution over, **386–387**
 NIS (Network Information Service), **387**
 TCP/IP and Ethernet, **385–386**

new accounts, **417–418**

newalias command, **780**

newform command, **780–781**

newgrp command, **781**

newgrp command (Bourne), 506

Newgrp command (Korn), 717

newline, 47, 223, 265, **781**
 from echo command, 222
 in quoted string, 97

to terminate command, 136
 in vi editor, 161

news command, **781–782**

newsgroups, for Linux, 732–733

.newsrsrc file, 595, 893

newsreader, **396**

- kill file, **707**
- readnews, **825**
- rn, **836–838**
- tin, **893–897**
- trn, **902–905**
- xrn to interface, 955

next command (awk), 483

next command (Mail), 752

next command (mailx), 756

next command (MH), 765

next command (nawk), 778

NeXT operating system, 748

NF variable (awk), 312, 484

NFS (network filesystem), **386, 782–783**

nfsd daemon, 570

nice command, **133–134, 783**

nice command (C shell), 559

/nick command (IRC), 695

NIS (Network Information Service), **387, 783**

- password changes, **960**

nl command, 640, **783–785**

nm command, **785**

nmbd (Samba), **444–445**

nn (newsreader), 396

Nobeeep shell variable, 556

noclobber environment variable, **785**

noclobber option (Korn shell), 713

Noclobber shell variable, 556

node, **785**

node name (UUCP), 368

noexec option (Korn shell), 713

noglob environment variable, **785**

noglob option (Korn shell), 713

Noglob shell variable, 556

Nohup command (Korn), 717

nohup (no hangup), 128, 560, **785–786**

- killing, 129

nolog option (Korn shell), 713

nomagic, **786**

nonomatch environment variable, **786**

Nonomatch shell variable, 556

nonprintable characters

- displaying, 939

- and sort command, **244**
- unvis to convert, **919**

“not found” message, 12

NOT (!) operator

- in awk, 309, 310
- in test command, 339, 342

NOT option, in find command, 259

notify command, **786**

notify command (C shell), 560

Notify shell variable, 557

nounset option (Korn shell), 713

novice environment variable, **787**

novice mode for vi editor, 165

- turning off and on, 166

Nowitz, David, 679, 923

NR variable (awk), 306, 312, 484

nroff, **787**

- error check for input file, 524–525
- macros, **762, 773**
- output display on screen, 533–534
- removing dot requests from file, 575–576
- vs. troff, 905

nslookup command, 390, **787**

null, **787**

null argument, **788**

null character, **788**

null device, 577, **788**

null path, 211

null string, 333, **788**

null value, 214

number (set argument), 193

numbered buffer, **788**

.o filename extension, 639

O

o (over), 62

obase keyword (bc), 492

object file, profile data of, 811

object files, 540

- displaying data and text segment sizes, 861
- listing dependencies for group, **739**

object-oriented programming, inheritance, **686**

oclock program, 949

octal notation, 223

- for chmod command argument, 112–113
- for control characters, 265

od command, **788–789**

offline, 4

offsets, when printing, 157

OFMT variable (awk), 312, 484
 OFS character, 305
 OFS variable (awk), 312, 484
 Oikarinen, Jarkko, 694
 \$OLDPWD shell variable (Korn), 714
 olwm (Open Look window manager), 427–429, 789
 onintr keyword, **789**
 online, 4
 online manual pages. *See* man command
 displaying, **758–759**
 keyword lookup in, 471
 open call, 578
 open command (ftp), 392, 656
 open command (telnet), 394, 886
 Open Desktop, **789**
 open files, **789**
 identifying and reporting on, 654
 Open Look window manager (olwm), 428–429, 436, 789, **790**
 open new line, in vi editor, 181
 open system, **791**
 OpenGL (Open Graphics Library), **789**
 opening file, 38
 OpenServer, **790**
 openwin command, **791**
 OpenWindows window manager, **791**
 operating system, shutting down, **860**
Operating System System Administrator's Guide, 400
 operators
 in awk, 481–482
 in bc, 493
 /opt directory, **791**, 869
 OPTARG environment variable, **792**
 \$OPTARG shell variable (Korn), 714
 OPTIND environment variable, **792**
 \$OPTIND shell variable (Korn), 714
 options for commands, 17
 OR (| |) operator, 309
 OR operator (-o), in test command, 339
 OR option, in find command, 259
Orange Book guidelines, 403
 ordinary files, 636, **792**
 orphan process, **792**
 orphaned file, **792**
 ORS variable (awk), 312, 484
 OSF/1, 748, **792**
 OSx, **792**
 output, 5
 appending to files, **54–55**
 redirecting, **39–40**, **46–47**

output stream, 295
 overwriting files, 30, 54
 owner permissions, 107
 viewing, 108–109
 ownership of file, 16, **104**
 changing, **111–112**, **529**
 in home directory, 465

P

pack command, **793**
 packed files, displaying contents, **799**
 packet internet groper (ping), **804–805**
 packf command (MH), 765
 page, **793**
 page length, setting for printing, 149
 pager utility, less command as, **726–727**
 pages in virtual memory, 939
 pagesize command, **793**
 parallel port, 145
 parallel processing, pipelining in, 806
 parameter, **793**. *See also* variables
 parameter substitution, 228, **793**
 parent directory, **794**
 listing contents, 43
 moving to, 35
 parent directory (..), 103
 parent process, 125, 124, **794**
 parent shell, 236
 parentheses to control precedence, 290–291
 parsing command line, 218
 passive system, UUCP link as, 368
 passwd command, 82, **794–795**
 password, 8, **795**
 case sensitivity for, 9
 changing, **82–84**
 changing NIS, **960**
 choosing, **13**
 chpass to change, 530
 for crypt command, 550
 encryption, **795**
 encryption in /etc/passwd file, 86–87
 good and bad, **83–84**
 minimum length, 84
 for new accounts, 417
 for root, 402
 password file, **796**
 paste command, **255–257**, 640, **796–797**
 patch command, **797–798**

- path database, to route mail, 372
- path environment variable, 851
- PATH environment variable, 207, 211, 214, 558, **798**, 851
 - working directory in, 323
- path names
 - absolute, **463**
 - including in alias, 466
- PATH shell variable, 94
- path shell variable, 557, **798**
- PATH! shell variable, 93
- PATH shell variable (Bourne), 504
- PATH shell variable (Korn), 715
- pathname, **798–799**
 - relative, **829**
- pathname extension, 475, **799**
- paths, **28–29**, **89–90**
 - absolute names, **32**
 - to environment file when starting shell, 616
 - extracting directory name from, **586–587**
 - extracting filename from, 488–489
 - for find command, 258
 - specifying for function definitions, 651
- pattern, in awk, 481
- pattern matching, **799**
- pattern space for sed, 851
- pause, 343, 564
 - code in menu for, 353
 - in scrolling display, 19
- PC (personal computer), 5
 - X server to run, 426
- pcat command, **799**
- percent sign (%) prompt, 10, **799**
- period (.), **799**
 - and file searches, 42–43
 - in filenames, 26
 - in grep command, 280
 - in v command, 285
 - as vi repeat command, 179
- peripherals, interrupts for, 120–121
- perl (Practical Extraction and Report Language), **800**
- permission bits, **800**
- permission denied message, 60–61
- permissions, 16, **103–111**, 338, **635**
 - access modes, **107–110**
 - changing, **112–114**, **527–529**
 - creation mask for, 548
 - defaults, **110–111**
 - directories, **105–106**
 - and executable scripts, 205–206
 - files, **104–105**
 - finding files with specific, 261–262
 - script files, 111
 - in UUCP, 374
 - viewing, 108–110
- permuted index, **801**
 - creating, **816–817**
- personal login profile, 92, **93–99**
- personal mail resource file, 372
- personal shell variables, 94
- personalizing Unix
 - login profile, **91–93**
 - password, **82–88**
 - personal login profile, **93–99**
 - shell, **88–91**
- peta-, **801**
- petabyte, **801**
- pfbttops command, **801**
- pg command, 640, **801–803**
- phone number, utility to dial, 562–563
- physical layer (ISO/OSI), 696
- physical links, 735
- physical option (Korn shell), 713
- pic, **803–804**
- pick command (MH), 765
- pico, **804**
- PID (process ID), **804**
- pid (process identifier), 122
 - of parent process, 131
 - ps (process status) command to find, 131
- Pine (mail program), 749
- .pinerc file, 595
- ping (packet internet groper), **804–805**
- pipe, 123, 269, **805**
 - command output into grep, 274
 - and split command, 253
- pipe command (mailx), 756
- pipelines, **20**, **805**
 - redirecting vs., **51–52**
- pipelining, **806**
- Placeway, Paul, 884
- .plan file, 595, **806**
- pling (!), **487**. *See also* ! (bang)
- plot command, **806**
- plus (+) symbol, **806**
- point, in emacs editor, 609
- Point-to-Point protocol (PPP), **808**, 883
- popd command (C shell), 560, **806**

- port, for printer, 145
- positional parameters, 150, 270, **354–362**
 - set to assign values, 360–362
 - in shell script, **220–221**
- POSIX (portable operating system interface), **806**
- postincrement (++) operator, 313
- PostScript files
 - translating font file into ASCII, 801
 - viewing in X Window system, **663**
- PostScript printing, translating troff-formatted files for, 596
- pound sign (#), **807**
- PPID environment variable, **808**
- \$PPID shell variable (Korn), 714
- PPP (Point-to-Point protocol), **808**, 883
- pppd daemon, 570
- pr command, 50–51, **156–157**, 640, **808–809**
- Practical Extraction and Report Language (perl), **800**
- precedence, **809**
 - in awk, 310
 - in egrep command, **290–292**
 - for test operations, 340–341
- predefined variables. *See also* shell variables
- prepending, 67
- presentation layer (ISO/OSI), 696
- preserve command (Mail), 752
- preserve command (mailx), 756
- prev command (MH), 765
- print command, **809–810**
 - in ed editor, 623
- print command (awk), 483
- Print command (Korn), 717
- print command (Mail), 752
- Print command (Mail), 752
- print command (mailx), 756
- Print command (mailx), 756
- print command (nawk), 778
- print command (Samba), **451**
- print request id, 147
- print spooler, 125
 - removing jobs from, **744**
- printenv command, 617, **810**
- printer ports, 144
- printers
 - advancing paper, 650
 - central and local, **144–145**
 - device number, 757
 - displaying queue status, **741–742**
 - enabling, 614
 - port for, 145
 - testing, 146
 - turning off temporarily, 588
- printf command, **810**
- printf command (awk), **306**, 483
- printf command (nawk), 778
- printing, 143
 - in awk, 304–305
 - c copy option, **153**
 - canceling, **156**
 - canceling request, **511–512**
 - changing requests, **155**
 - e-mail messages, **67**
 - to local printers, **744**
 - man command options for, 45
 - messages from shell scripts, **647–648**
 - multiple files, 147–148
 - sending text files to print queue for, 742
 - sequential or random data, 699–700
 - smbd for Windows users, **442–443**
 - specific e-mail message, 68–69
 - symbol table, **785**
- “printing on the screen”, 50
- printout, banner page in, **488**
- priorities
 - nice command to lower, 133–134, **783**
 - for print request, 150
- private (symmetrical) key schemes, 614
- privileged account, **810**
- privileged option (Korn shell), 713
- /proc directory, 810
- procedure, in awk, 481
- process IDs (PID), 760, **804**
 - of shell, 215
 - terminating, **705–706**
- process in Unix, 121
 - biography, **122–123**
 - information about active, **811–814**
 - parent, 123, 124, **794**
 - priority of, **783**
 - spawning by, 123–124
 - suspending, **861**
- process paths, 234
- process status, **811**
- processes
 - managing, **760–761**
 - scheduling, **138–140**, **476–478**
- prof command, **811**
- profile data
 - of object file, 811
 - of program, **744**

.profile file, 92, 191, 202, 210, 465, 595, **811**
 viewing, **98–99**

program
 interrupting, 563
 quit signal for, 563

program code, 16. *See also* binary files

programming languages. *See also* awk; C language
 Java, **697**
 perl, **800**
 shell, **858**
 standards, 468

programs, 121
 multiple in memory, 119
 profile data of, **744**

.project file, 595

prompt, 7, **811**
 ? for mail command mode, 65
 for information, 10–11
 in Samba, 448
 shell, 10, **858**

prompt command (ftp), 392, 657

prompter command (MH), 765

protected option (Korn shell), 713

protocol stack, 696

protocols
 AFS (Andrews File System), **465**
 e, **617**
 f protocol, **651**
 FTP (File Transfer Protocol), **658**
 G protocol, **664**
 HTTP (Hypertext Transfer Protocol),
680–681
 IP (Internet Protocol), **692**
 LBX (low-bandwidth X), **724**
 LDAP (Lightweight Directory Access
 Protocol), 952
 Point-to-Point protocol (PPP), **808**
 RFS (Remote File System), **833**
 SMTP (Simple Mail Transfer Protocol), **862**
 SPX (Sequenced Packet Exchange), **868**
 TCP/IP (Transmission Control
 Protocol/Internet Protocol), **385–386, 883**
 TCP (Transmission Control Protocol), **883**
 x protocol, **954**
 Zmodem file transfer protocol, **844–846**

prs program (SCCS), 847

.ps filename extension, 393, 639, 690

ps (process status) command, 128, **130–133,**
811–814

PS1 shell variable, 94, 95, 214, **814**

PS1 shell variable (Bourne), 504
 PS1 shell variable (Korn), 715
 PS2 shell variable, 94, 97, 214, **814**
 PS2 shell variable (Bourne), 504
 PS2 shell variable (Korn), 715
 PS3 shell variable (Korn), 715, **814**
 PS4 shell variable (Korn), 715, **814**
 pseudocode, 326
 pstat command, **815–816**
 ptx command, **816–817**
 PUBDIR directory, 374
 moving files from, 377
 uuto command to send files to, 376

public (asymmetrical) key schemes, 614

public permissions, 105, 107
 viewing, 108–109

pushd command (C shell), 560, **817**

put command (ftp), 392, 393, 657

put command (Samba), **451**

Pwd command (Bourne), 506

pwd command (ftp), 392, 656

Pwd command (Korn), 717

PWD environment variable, 558

pwd (print working directory) command, **33–34,**
38, 817

\$PWD shell variable (Korn), 714

Q

/query command (IRC), 695

question mark (?), 41, **817**
 for file name generation, 230
 in ftp, 656
 for mail command mode prompt, 65

queue. *See also* at job queue
 batch, **490–491**

queue command (Samba), **451**

quit command (ed), 623

quit command (ftp), 391, 656

quit command (mail), 66–67

quit command (Mail), 752

quit command (mailx), 756

quit command (Samba), **449**

quit command (telnet), 394, 886

quit (Ctrl-), **563**

quota command, **817–818**

quotation marks, 222, **223–226**
 for date in awk, 315
 double quote, **596**
 double quote and backquotes, 225

forward vs. backward, 95
 for sed edit command, 296
 quote, **818**

quoting, **818**
 in Bourne shell, 503
 in C shell, 555
 for echo, 331
 for find command file arguments, 258
 grep search pattern, **275**
 in Korn shell, 712
 and metacharacters, 333
 parentheses for text, 341
 single quote ('), **861**

R

r command, **818–819**

R command (Korn), 717

r command (vi), 183

R command (vi), 183

-r (recursive) option, for rm command, 53

RAID (redundant array of inexpensive disks),
819–820

Rakitzis, Byron, 821

RAM (Random Access Memory), 119

Ramey, Chet, 489

rand command (awk), 314, 483

rand command (nawk), 778

Rand operation (awk), 314

random access, 16

Random Access Memory (RAM), 119

random command, **820**

RANDOM environment variable, **820**

\$RANDOM shell variable (Korn), 714

ranlib command, **820**

RARP (Reverse Address Resolution Protocol), 385, 883
 raw, **820**

raw device, **820**

raw mode, **820**

rbash command, **821**

.rc file, **821**

rc shell, **821**

rcp command, **821–822**

.rcrc file, 595

rcs program (RCS), 823

RCS (Revision Control System), **822–823**

rcslean program (RCS), 823

rcsdiff program (RCS), 823

rcsfreeze program (RCS), 823

rcsmerge program (RCS), 823

rcvstore command (MH), 765

rd command (Samba), **451**

rdist utility, **823–824**

read call, 578

read command, **342–343, 825**

in ed editor, 623

read command (Bourne), 506

read command (Korn), 717

read-only filesystem, **825**

“read-only” version of vi editor, 164

read permission, 104, 108, 527, 635, 800

for directories, 105

owner, group and public, 107

testing for, 338

read protected file, 106

reading e-mail messages, from another source, **72**

readnews, **825**

readonly command, **825**

Readonly command (Bourne), 506

Readonly command (Korn), 717

rebuilding kernel, **826**

receive directory, 374

record locking, 635

records, in awk, 302, **304–306**

recurring jobs, scheduling, 140

red command, **827**

redirecting, **827**

in Bourne shell, 502–503

in C shell, 554–555

in at command, 140

input, 40, **50–51**

input to shell scripts, **204–205**

in Korn shell, 710–712

output, **39–40**

for pasting, 257

vs. pipelines, **51–52**

to save sort command results, 241–242

to send mail, 74

Redman, Brian D., 679, 923

redundant array of inexpensive disks (RAID),
819–820

refer command, **827–828**

refile command (MH), 765

regcmp command, **828**

region, in emacs editor, 610

register command, **828**

regular character, **828**

regular expressions, 160, **278–288, 828–829**

with [], 286–287

in awk, 302, 305

- for egrep command, 289
- for grep and egrep in descending precedence, 292
- in sed stream editor, 298
- tagged, **287–288**
- regular files, 636
- rehash command (C shell), 560, **829**
- relational operators, **829**
 - in awk, **308–309**
- relative mode, for chmod command, 113
- relative pathname, **829**
- relogin, **830**
- remapping keyboard, 5
- “remote access to path/file denied” message, 375
- remote command, **830**
- remote commands, executing, **625**
- remote connections, 4, **565–567**
 - ftp for file transfer, **654–657**
 - logging in, 833–834
 - running commands on, 830
 - sending file, 927
 - shell to execute single command on, **840–841**
 - telnet command for, **394–395**
 - tip command to login, **897–898**
- Remote File System (RFS), **833**
- remote filesystem, **830–831**
- remote login, **831**
- remote mapping, **831**
- Remote Procedure Call (RPC) protocol, 387, **840**
- remote system, executing commands on, **373**
- removable mass-storage device, unmounting, 410, **913**
- removing. *See* deleting
- remsh command, 841
- repeat command, **831**
 - period (.) as in vi, 179
- repeat command (C shell), 560
- repeating search in vi editor, 186
- repl command (MH), 765
- reply command (Mail), 752
- Reply command (Mail), 752
- reply command (mailx), 756
- Reply command (mailx), 756
- \$REPLY shell variable (Korn), 714
- report (set argument), 193
- report threshold, 165
- Request for Comments (RFC), **832**
- Request for Discussion (RFD), **833**
- reset command, **831**
- reset string, **831**
- resolver, **831**
- resource, **832**
- resource allocation, in multiprogramming operating systems, 118
- resource sharing, **832**
 - uux command for, 373
- resources, automounting, 479
- respond command (Mail), 753
- respond command (mailx), 756
- responding to e-mail message, 73–74
- restor command, 413–414
- restoring files, from tar backup, 416
- Retain command (Mail), 753
- return code, 219
- return command, **832**
- return command (awk), 483
- return command (Bourne), 506
- Return command (Korn), 717
- return command (nawk), 778
- Return key, 6, 615
 - Ctrl-M for, 190
- return keyword (bc), 492
- return value, 325, 625
- rev command, 640, **832**
- Reverse Address Resolution Protocol (RARP), 385, 883
- reverse polish notation, 572
- reverse slash. *See* backslash (\)
- Revision Control System (RCS), **822–823**
- RFC (Request for Comments), **832**
- RFD (Request for Discussion), **833**
- RFS (Remote File System), **833**
- .rhosts file, **833**
- ripple test, to standard output, **746**
- Ritchie, Dennis, 702, 917
- rksh (Korn shell), **833**
- RLENGTH variable (awk), 484
- rlog program (RCS), 823
- rlogin command, **833–834**
- rm command, **52–54, 834–835**
- rmail, **835**
- rmb command, **835**
- rmidel program (SCCS), 847
- rmdir command (ftp), 656
- rmdir (remove directory) command, **35, 835–836**
- rmf command (MH), 765
- rmm command (MH), 765
- rn (newsreader), 396, **836–838**
- robust program, 337
- roffs, **839**
- Romine, John, 77
- root, **839**. *See also* superuser

root account, 810
 root directory, **31–35**, **839**, 869
 root filesystem, 409, **839**
 root login, **839**
 root login name, 402
 capabilities, 402–403
 logging in, 58, 404
 rootdev variable, **839**
 Rose, Marshall, 77
 rot13, **839–840**
 RPC (Remote Procedure Call) protocol, 387, **840**
 rpcgen, **840**
 RS (record separator) variable, 304
 RS variable (awk), 312, 484
 rsh command, **840–841**
 Rsh command, **841**
 RSTART variable (awk), 484
 rstat command, **841–842**
 run levels, 234, 405
 for shutdown, 408
 rup command, **842**
 ruptime command, **842–843**
 rusers command, **843**
 rwall command, **843–844**
 rwho command, **844**
 RZSZ tools, **844–846**

S

s command (vi), 184
 S command (vi), 184
 .s filename extension, 639
 s keyword (bc), 492
 s (substitute) command, **282–283**
 sact program (SCCS), 847
 Samba, **442–451**
 cd command, **449**
 del command, **449**
 dir command, **449**
 exit command, **449**
 get command, **450**
 help command, **450**
 lcd command, **450**
 ls command, **450**
 md command, **451**
 nmbd, **444–445**
 print command, **451**
 put command, **451**
 queue command, **451**
 quit command, **449**
 rd command, **451**
 running, **448–451**
 setmode command, **451**
 smbclient, **445–448**
 smb.conf file, **443**
 smbd, **442–443**
 swat program, **443**
 Santa Cruz Operation (SCO), **848**
 sash (standalone shell), **846**
 save, **846**
 save command (Mail), 753
 save command (mailx), 756
 savehist environment variable, **846**
 savehist shell variable, 557
 Saveignore command (Mail), 753
 Saveretain command (Mail), 753
 saving, e-mail messages, **70–72**
 /sbin directory, **846**, 869
 scale keyword (bc), 492
 scan command (MH), 765
 SCCS (Source Code Control System), **846–847**
 sccsdiff program (SCCS), 847
 sched process, 124
 scheduled jobs, 549–550
 at command for, **138–140**, **476–478**
 scientific calculator. *See also* bc
 SCO (Santa Cruz Operation), **848**
 SCO OpenServer, **848**
 SCO UNIX, **848**
 C compiler options, 517–521
 goodpw command, 84
 Merge, **459**
 minimum RAM, 119
 sysadmsh (system administration shell), 85
 text-only screen, 6
 VisionFS, **459**
 SCOadmin tools, **848**
 scoterm, 431, 956
 screen display, **6**
 command to clear, 531
 pause in scrolling, 19
 pausing output, 564
 redrawing, 564
 restarting output, 564
 stdout to reference, 38
 troubleshooting garbled, 163
 screen redraw, 170
 screen refresh, 170
 script command, **849**

- script files, **848**. *See also* shell script
 - permissions, 111
- scroll bars, for xterm window, 433
- scroll (set argument), 193
- scrolling display
 - pause in, 19
 - in vi editor, 161
- SCSI (Small Computer System Interface), standard, 468
- sdb (symbolic debugger), **849**
- sdiff command, **849–850**
- search path, **850–851**
- search permissions, for directories, 105
- searches. *See also* find command; grep command
 - incremental, **685**
 - for patterns in files, **665–667**
- searching text, in vi editor, **186–187**
- Second Extended Filesystem (ext2fs), **628**
- secondary prompt, 97
- SECONDS environment variable, **851**
- \$SECONDS shell variable (Korn), 714
- section coding scheme, 44
- sectors on floppy disks, 454–455
- security, 7, 307. *See also* password
 - firewall, **645**
 - Kerberos, **703**
 - logs for, 403
 - Orange Book* guidelines, 403
 - remote mapping, **831**
 - UUCP network software, **374–384**
- sed stream editor, 273, **295, 851–852**
 - ! (bang) to reverse matching, **299**
 - appending and inserting text, **300**
 - d (delete) function, **299–300**
 - edit_command, **297–301**
 - f (file) option, 296–297
 - g (global) option, 297
 - p function, **301**
 - q (quit) option, 297
 - regular expressions in, 298
 - s (substitute) function, **298–299**
 - syntax, **295–301**
 - y function, **300**
- Select command (Korn), 717
- select statement (Korn), **853**
- selecting e-mail messages, **68–70**
- semicolon (;), **853**
 - in case statement, 349
 - in multicommand line, 135
 - to terminate command, 136
- send command (MH), 765
- sendbug command, **853**
- sending, e-mail messages, **72–75**
- sendmail environment variable, 371
- sendmail program, **853**
 - definition in vi, 171
- Sequenced Packet Exchange (SPX), **868**
- Serial Line Internet Protocol (SLIP), 883
- serial port, 145
- server, anonymous, **468**
- Server Message Block (SMB) protocol, 442
- server software in X, **423, 424, 955, 959**
 - benchmark program to test, **950–951**
- session layer (ISO/OSI), 696
- set command, 191, **192–194, 207–208, 360–362, 854**
 - to display shell variables, 217
- set command (Bourne), 506
 - options, 506–507
- set command (C shell), 560
- Set command (Korn), 717
- set command (Mail), 753
- set command (mailx), 756
- set command (telnet), 395, 886
- set ignorecase ex command, in vi editor, 186
- /set novice off command (IRC), 695
- set uid bit, **854**
- setenv command, 560, 617, **854**
- setmode command (Samba), **451**
- SGML (Standard Generalized Markup Language), document instance, 590
- sh command, **854–855**
 - .sh filename extension, 90, 639
- SHACCT shell variable, 94, 505
- shadow password file, 87
- Shapiro, Norman, 77
- shar (archiver), **855–856**
 - .shar filename extension, 639, 690
- shared objects, utility to list, 725
- shar.Z filename extension, 690
- shell, **856–857**
 - choosing, **88–91**
 - chpass to change, 530
 - launching new temporarily, 552
 - names of, **90–91**
 - as process, **124–125**
 - temporary escape to, 129
 - terminating, 236
 - using within vi, **188**

- shell command (Mail), 753
- shell command (mailx), 756
- shell command, ~! to execute, 75
- SHELL environment variable, 212, 558, **857**
- shell escape, **857**
- shell function, **857**
- shell option, **857**
- shell out, **857**
- shell program, **857–858**
- shell programming language, **858**
- shell prompt, 10, **858**
- shell script, 95, **201–210**, 537, 857, **858**. *See also*
 - .login file; .profile file
 - arithmetic tools, **362–363**
 - backquote (`) in, **224–226**
 - basic steps, 207
 - as command, **208–209**
 - creation basics, **202–204**
 - debugging, **207–208**, 362
 - execute permissions for, 323
 - executing directly, **205–206**
 - to force command failure, 219
 - how they work, **218–223**
 - menu creation, **322–363**
 - for multiple commands, 270
 - naming, **204**
 - positional parameters, **220–221**
 - for printing, **150–151**
 - printing messages from, **647–648**
 - redirecting input to, **204–205**
 - scheduling from, 140
 - while command in, **329–342**
 - white space in, 323
 - for X resources, 430
- shell (set argument), 193
- shell shell variable, 557
- SHELL shell variable (Bourne), 505
- SHELL shell variable (Korn), 715
- shell variables, **93–97**, **210–218**, 617, **858**. *See also*
 - environment variables
 - in Bourne shell, **504–505**
 - in C shell, 556–557
 - echo to display contents, 96
 - evaluating, **621**
 - exporting, **216–218**, **626**
 - in Korn shell, 713–715
 - personal, 94
 - set command to display, 217
 - setting and unsetting, **214–215**
 - setting automatically by shell, 214–215
 - shells, 200
 - shelltool, 956
 - shift command, 220–221
 - shift command (Bourne), 506
 - shift command (C shell), 560
 - shift command (Korn), 717
 - Shift key, 5
 - shift keyword, **859**
 - shiftwidth (set argument), 193
 - shl command, **859**
 - show command (MH), 765
 - showmatch (set argument), 193
 - showmode, in vedit, 165, 166
 - showmode (set argument), 193
 - shutdown, **406–408**, **859**
 - sync command to prepare for, **876**
 - shutdown command, 407–408, **859–860**
 - shutting down system, **860**
 - signal, **860**
 - between processes, 327
 - .signature file, 595
 - Simple Mail Transfer Protocol (SMTP), 57, 385, **862**, 883
 - Simple Network Management Protocol (SNMP), 385, 883
 - simultaneous peripheral operation online (spool), 144, **867**
 - sin command (awk), 483
 - sin command (nawk), 778
 - sin operation (awk), 314
 - sine, from bc, 492
 - single quote ('), **861**
 - in grep commands, 209
 - single-user mode, 405, **406**
 - single-user state, **861**
 - SIT filename extension, 690
 - size command, **861**
 - Size command (Mail), 753
 - size command (mailx), 756
 - slash (/), 26–27, **861**
 - for root symbol, 31–32
 - sleep, **861**
 - sleep command, **137**, **862**
 - sleeping state, 123
 - SLIP (Serial Line Internet Protocol), 883
 - slocal command (MH), 765
 - smail program, **862**
 - SMB (Server Message Block) protocol, 442
 - smbclient (Samba), **445–448**
 - smb.conf file (Samba), **443**

- smbd (Samba), **442–443**
- smit program, **862**
- SMP (symmetrical multiprocessing), 118
- SMTP (Simple Mail Transfer Protocol), 57, 385, **862**, 883
- SNMP (Simple Network Management Protocol), 385, 883
- sockets, 636, **863**
- soelim command, **863**
- soft links, 735, **863**
- software, displaying configuration information, **875–876**
- Solaris, **863**
- Solaris source code debugger (dbx), **572**
- sort, **864**
- sort command, **240–250**, 268, 640, **864–865**
 - d option, **244**
 - f option, **243–244**
 - foreign language variations, **242–243**
 - i option, **244**
 - for multiple files, **246**
 - n option, **245**
 - o (output) option, 241–242
 - redirecting to save results, 241–242
 - u option, **246–247**
- sorted files, finding common lines in, 536
- sortm command (MH), 765
- Source Code Control System (SCCS), **846–847**
- source code, maintaining file dependencies, **757**
- source command, **865**
 - in ed editor, 623
- source command (C shell), 560
- source command (mailx), 756
- source file, for cp (copy) command, 103
- spaces. *See also* white space
 - as argument separator, 223
 - converting tab character to, **625–626**
- spawned processes, leader of, 129
- special characters. *See also* metacharacters
 - restricting in vedit, 165
- special file, 578
- special users, 403–404
- spell command, 640, **865–866**
- splat, **866**
- spline command, **866–867**
- split command, **252–253**, **867**
- split command (awk), 316, 483
- split command (nawk), 779
- /spool directory, **868**, 869
- spool (simultaneous peripheral operation online), 144, **867**
- spooler, 125, 144–145, **868**
 - displaying status information for lp, **745–746**
 - removing print jobs from, **744**
- sprintf command (awk), 483
- Printf command (nawk), 779
- SPX (Sequenced Packet Exchange), **868**
- SQL (Structured Query Language), 387–388
- sqrt command (nawk), 779
- sqrt keyword (bc), 492
- sqrt operation (awk), 314
- square brackets ([]), **868**
 - for file name generation, 230
 - in grep command, 281
 - for optional arguments, 18
 - regular expressions with, 286–287
- srand command (awk), 484
- srand command (nawk), 779
- srand operation (awk), 314
- srchtxt command, **868**
- stack, 121, **868**
- Stallman, Richard, 605, 654
- /stand directory, 869
- standard directories, **869**
- standard error, 55, **870**
 - redirecting, 827
 - sending error messages to, 347
- standard files, 347
- standard input, 38–39, **870**
 - assigning to variables, 825
 - reading line from, 730
 - redirecting, 827
 - sorting, 240
- standard output, **38–39**, **870**
 - echo to write to, **600–601**
 - redirecting, 827
 - reporting system information to, **913**
 - ripple test to, **746**
 - testing for running under layers software, 695
- standards, 468
- start bit, **870**
- start-up shell, 235–236
- startup files, **870**
 - for Bourne shell, 501
 - for C shell, 553
 - for Korn shell, 709
- .startxr file, 430
- state, **870–871**
- status command (ftp), 392, 657
- status command (telnet), 395, 886
- status command (vi), 170

- status environment variable, **871**
- status message, displaying in vi, 170
- status shell variable, 557
- stderr, 55. *See also* standard error and streams, 295
- stdin, **38–39**. *See also* standard input and streams, 295
- stdout, **38–39**. *See also* standard output redirecting output from, 46 and streams, 295
- stop bit, **871**
- stop command (C shell), 560, **871**
- storage allocation blocks, **500**
- stream, sed to edit, **851–852**
- string options, 192
- strings, **872**
 - empty, 333
 - extracting from C language source code, **628**
 - splitting into array, 316
- strip command, **872**
- struct command, **872**
- Structured Query Language (SQL), 387–388
- stty command, 97, **97–98, 872–873**
 - to change interrupt key, 326
- style command, **873–874**
- su command, 404, **874**
- sub command (awk), 484
- sub command (nawk), 779
- subdirectories, 28, **874**. *See also* directories listing, 40
- subject, for e-mail messages, 72
- subprocesses, 234
- subroutine, call to, 510
- SUBSEP variable (awk), 485
- subshell, 205, 206, **875**
 - exporting variables for, 216
- substitute command, in ed editor, 623
- substr command (awk), 484
- substr command (nawk), 779
- sum command, **875**
- summary, of printer service, 155
- Sun Microsystem, 429
- Sun workstation, Meta key, 608
- Sun Yellow Pages, 387
- super-block, 408
- supercomputer, **875**
- superuser, 58, 810, **875**
 - for backup operation, 412–413
 - becoming, **404**
 - messages from, 59
 - process priority increase by, 134
 - for system administration, **402–405**
- suspend command (C shell), 560
- suspended programs, 565
 - context of, 120
 - swapping, 119
- swap spaces, 409
- swapper, 124
- swapping suspended programs, 119
- swat program (Samba), **443**
- swconfig command, **875–876**
- switch command, 560, **876**
 - end to terminate, 614
- switch options, 192
- switches for commands, 17
- symbol cross-reference, **551**
- symbol table, printing, **785**
- symbolic links, 636, 735
- symbolic mode, for chmod command, 113, 527, 528–529
- symmetrical multiprocessing (SMP), 118
- sync command, **876**
- synonyms, explain to look up, **626**
- syntax, 17, **876**
- syntax error, **877**
- /sys directory, **877**
- sysadmsh (system administration shell), 85, 400, 418, **877**
- syslog system log module, shell command interface to, 736
- system administration, **400–401**
 - backup, **410–417**. *See also* backup booting up, **405–406**
 - filesystems, **409–410**
 - new accounts, **417–418**
 - required tasks, 401–402
 - shutdown, **406–408**
 - smit program for, **862**
 - superuser access for, **402–405**
- system administrator, 7, 400, **877**
 - overriding msg n user setting, 63
 - and security, 8
- System Administrator's Reference Guide*, 400
- system calls, 121
 - truss command to trace, **906**
- system command (awk), 484
- system command (nawk), 779
- system console, 5
- system diagnostics, 580
- system mailbox, 64

system messages, reading, 773

system resources

displaying or setting limits, **729**

limiting, 910–911

system time, 892

T

tab character, 223, 265

as argument separator, 223

converting to spaces, **625–626**

table of contents, for archive libraries, **820**

tables, formatting, **881–882**

tabs command, **877**

tagged regular expressions, **287–288**

tail command, **251–252**, 640, **877–878**

talk command, **878–879**

tape drives

for backup medium, 412

device number, 757

Tar archive, **881**

tar command, **414–417**, **879–880**

display options, 416

.tar filename extension, 393, 639, 689

.tar.gz filename extension, 393

.tar.Z filename extension, 393, 689

tasks, 120

Tauber, Dan, *The Complete Linux Kit*, 732

Taylor, Dave, 77, 604

tbl, **881–882**

output display on screen, 533–534

removing formatting from file, 575–576

/tcb directory, **882**

tcop command, **882**

TCP/IP (Transmission Control Protocol/Internet

Protocol), **385–386**, **883**

architecture, **884**

TCP (Transmission Control Protocol), **883**

Tcsh, **884**

.tcshrc file, 595

tee command, 135–136, 136, **885**

tee program, **884**

telecommunications, 366

teletypewriter (TTY), 144

telnet command, **394–395**, 425, **885–886**

tn3270, **898**

temporary files, directory for, **898**

term, **887**

TERM environment variable, 558

term-info database, displaying information from, **900**

term (set argument), 193

TERM shell variable, 94, 163, 164

term shell variable, 557

TERM shell variable (Bourne), 505

TERM shell variable (Korn), 715

termcap, **887**

TERMCAP environment variable, 558

terminal emulator, 427

Terminal window, opening, 6

terminals, **4–5**

command to list name, 18

connected, 62

device number, 757

enabling, 614

files for managing, 577

Hewlett-Packard 2640 series, 680

locking, **736**, **953**

multiple login screens, 772

output to, 143

pathname of device file, 908

prompt for type, 10–11

sending message to, 675

stty to set options, **97–98**

system interface setup to, 907

turning off temporarily, 588

vi editor and type, 163

virtual, **939**

in X Windows, **426–427**

xterm to emulate, **956–957**

terminating, shell, 236

terminfo directory, 887

terminfo file, 146, 169

terse (set argument), 194

test command, **329–342**, **887–889**

with Boolean expressions, **339–341**

to compare two strings, 332

Test command (Bourne), 506

test command (Korn), 717

testing

for arguments, **355–356**

empty variables, **333–337**

files, **338–339**

numbers, **337–338**

.tex filename extension, 639

TEX (typesetting language), **889–890**

text-based approach, 6

text cursor, in xterm window, 433

text editor

to compose letter, 74

default, 631

- ed editor, **602**
- edit, **603**
- emacs editor, **605–613**
- ex editor, **621–623**
- joe (editor), **698**
- jove, **700**
- pico, **804**
- vedit, **930**
- vi editor, **931–938**
- text-entry macros, 189
- text-entry mode, 160
 - in vi editor, 167, **180–181**
- text files, 16
 - adding line numbers to, **783–785**
 - breaking long lines in, **648**
 - converting DOS to Unix, **597**
 - converting Unix to DOS, **958**
 - displaying differences, **581–583**
 - displaying last lines of, **877–878**
 - displaying screen at a time, **801–803**
 - dividing, **867**
 - fmt command for formatting, **646–647**
 - formatting, **780–781, 808–809**
 - printing beginning, **675**
 - removing blank lines from, **835**
 - removing duplicate lines from sorted, **915–916**
 - sending to print queue, 742
 - sorting, **864–865**
 - troff to format, **905–906**
 - updating to later version, **797–798**
- text, print command to display, **809–810**
- text segment, 121–122
- text streams, 295
- text window, accessing, 6
- tfmtodit command, **890**
- tftp command, **890**
- then keyword, **890**
- Thompson, Ken, 199, 917
- thrashing, 119
- threads, 120, **891**
- TIF filename extension, 690
- tilde (~), **892**
 - in C shell, 380
 - for empty lines in vi, 169
 - for home directory, 679
- tilde (~) escape sequences, **891**
 - in mailx command, 77
- time command, **892**
- time command (C shell), 560
 - time command (Korn), 717
 - time-of-last-access, for file list order, 49
 - time-of-last-data-modification, for file list order, 49
 - time, scheduling jobs to run at specific, 476–477
 - time shell variable, 557
 - time slice, 118
 - TIMEOUT shell variable, **892**
 - times command, **892**
 - Times command (Bourne), 506
 - times command (Korn), 717
 - tin (newsreader), 396, **893–897**
 - tip command, 373, **897–898**
 - TMOU shell variable, 715, **898**
 - /tmp directory, 869, **898**
 - tn3270, **898**
 - to-do list, calendar utility for, **509–510**
 - tolower command (awk), 484
 - tolower command (nawk), 779
 - toolkit, 431
 - top command, for e-mail messages, 69
 - Top command (Mail), 753
 - top command (mailx), 756
 - top-level domains, 389
 - Torvalds, Linus, 731
 - touch command, **898–900**
 - touch command (mailx), 756
 - toupper command (awk), 484
 - toupper command (nawk), 779
 - tput command, **900**
 - tr (translate) command, **264–265, 267–268, 640, 900–901**
 - trace mode, 362
 - trackall option (Korn shell), 713
 - tracks on floppy disks, 454
 - trailer, as pr default, 50
 - translate command, **901**
 - Transmission Control Protocol (TCP), **883**
 - transmission speeds, 366
 - transparent file sharing, 386
 - transport layer (ISO/OSI), 696
 - trap command, **326–328, 902**
 - trap command (Bourne), 506
 - Trap command (Korn), 717
 - trapdoor syndrome, 403
 - “trash can” system file, 346
 - trivial ftp, 890
 - trn (newsreader), 396, **902–905**
 - troff
 - device-independent, **590**
 - eqn preprocessor, **617–618**

- macros, **762, 773, 906**
- pic preprocessor for, **803–804**
- translating files for PostScript printing, 596
- troff command, **905–906**
- troff dot requests, removing from file, 575–576
- troff input file, error check for, 524–525
- Trojan Horses, 374
- troubleshooting
 - garbled screens, 163
 - gcore to obtain core image, 660
 - hard drive problems, **653**
 - truss command to trace system calls, **906**
- true command, **906**
- truss command, **906**
- truth table, 340–341
- tset command, 98, **907**
- tty command, **908**
- TTY (teletypewriter), 144
- Twm (Tab Window manager), **908**
- .txt filename extension, 639, 690
- type command, **908**
- type command (Bourne), 506
- type command (Korn), 717
- type command (Mail), 753
- Type command (Mail), 753
- type command (mailx), 756
- Type command (mailx), 756
- typescript file, 849
- typeset command (Korn), 717, **908–909**
- typesetting
 - formatting text file for, **905–906**
 - TEX for, **889–890**
- TZ environment variable, 212

U

- u (undo) command (vi), 179
 - after deleting, 182
- UDP (User Datagram Protocol), 385, 883
- uid, chpass to change, 530
- ul command, **909–910**
- ulimit command (Bourne), 506
- ulimit command (Korn), 717, **910–911**
- umask command, 93, 99, 111, **911–912**
- umask command (Bourne), 506
- umask command (C shell), 560
- umask command (Korn), 717
- umask value, 912
- umount command, 410, **913**
- unab command, 189

- unalias command, 153, **913**
- unalias command (C shell), 560
- unalias command (Korn), 717
- Unalias command (Mail), 753
- uname command, **913**
- unbuffered device, 820
- uncompact command, **914**
- uncompress command, **914**
- undelete command (Mail), 753
- undelete command (mailx), 756
- undeleting e-mail messages, 71–72
- underlining, translating for display, 909–910
- unexpand command, **914–915**
- unget program (SCCS), 847
- unhash command, 560, **915**
- Uniform Resource Locator (URL), **920**
- uniq command, **247–250**, 268–269, 640, **915–916**
 - fields for, 249–250
 - options, 248
- units command, **916**
- Unix, **917–918**. *See also* personalizing Unix; system administration
 - booting up, **405–406**
 - bootup steps, 234
 - check for mail at login, 64
 - date used for beginning of time in, 617
 - developers, 917–918
 - displaying length of time running, **919–920**
 - file types in, **636**
 - kernel, **704**
 - origins, 199
 - security features, 7
 - system manual divisions, 759–760
 - system usage statistics, **940**
 - XENIX, **951**
- Unix prerequisites, **4–6**
 - keyboard, **5–6**
 - screen display, **6**
 - terminals, **4–5**
- unlimit command, 560, **918**
- unmap command, 191
- unnamed buffer, in vi editor, 185
- unpack command, **918**
- unread command (Mail), 753
- unreferenced file, 792
- unset command, 214, 334, **918–919**
- unset command (Bourne), 506
- unset command (C shell), 560
- unset command (Korn), 717
- Unset command (Mail), 753

unset command (mailx), 756
unset command (telnet), 886
unsetenv command, 560, 617, **919**
until command (Korn), 717
until loop, **328–329, 919**
unvis command, **919**
update process, 132
uppercase, translating to lowercase, 900
uptime command, **919–920**
urgent messages, from root, 63
URL (Uniform Resource Locator), **920**
USENET, **396**. *See also* newsreader
USENIX Association, 737
user command (ftp), 392, 656
User Datagram Protocol (UDP), 385, 883
user-defined variables, 311
 placing standard input in, 342
USER environment variable, 558
user filesystem, 409
user ID, 761
user id
 access using another, 404, **874**
 euid (Effective User Identifier), **621**
 login name and, 86
user name, 8
 command to list, 18
user shell variable, 557
user time, 892
user variables, 212–213
users
 adding new, **465**
 authenticating for server drive access, **455–456**
 changing database information, **530**
 checking for online, 59–60
 displaying disk usage and limits, 817–818
 displaying login name and ID, 683
 find command to select files belonging to, 261
 information about, 796
 information about logged on, **643–645**
 limiting use of crontab, 550
 listing group memberships, 669
 listing in /etc/passwd, 85
 message warning about shutdown for, 408
users command, **920**
“Using open mode” message, 163
/usr directory, 869, **920–921**
.uu filename extension, 639
uucico utility, 924
uucp command, 366–367, **379–382, 921–922, 924**
 syntax, 381

UUCP job id, 383
UUCP network software, **366–373**
 address syntax, 369
 address vs. Internet domain address,
 389–390
 configuration, **922–924**
 forwarding mail, 371–372
 HoneyDanBer UUCP, **679**
 installing, 367–368
 job tracking, **383–384**
 mailing binary files, **370–371**
 .mailrc file, **372–373**
 making contact, **367–368**
 security, **374–384**
 uucp command, **379–382**
 uulog command, **382**
 uname command, **369–370**
 uustat command, **382**
 uuto command, 370
uucp user name, 374
uucpd daemon, 570
uudecode command, 370–371, **924**
uue filename extension, 690
uencode command, 370–371, **924–925**
uue.z filename extension, 690
uuglist command, 924, **925**
uulog command, **382, 384, 925**
uumail program, 372
uname command, **369–370, 924, 925**
uupick command, **375–379, 377, 924, 925–926**
uucq command, 924, **926–927**
uusemail command, 924, **927**
uustat command, **382, 383, 924, 927–928**
uuto command, 370, **375–379, 924, 928**
 vs. uucp command, 379
uux command, 373, 924, **928–929**

V

v command, 284–285
V command, 284–285
vacation command, **929–930**
val program (SCCS), 847
/var directory, 869, **930**
variable identifier, 93
variable substitution, 793
variables. *See also* environment variables; shell variables
 assigning standard input words to, 825
 assigning value to, 330

- defining within shell, 334
- displaying value, 331
- global, 217, **663**
- local, 216, 217, **736**
- removing, 918–919
- setting, **854**
- to store test results, 356
- testing empty, **333–337**
- unset command for, 334
- user, 212–213
- user-defined, 311
- vedit, 164. *See also* vi editor
- vedit command, **930**
- verbose mode, 207–208
- verbose option (Korn shell), 713
- verbose shell variable, 557
- version command (mailx), 756
- vertical bar (|), for piping, 20
- vertical tab, 223
- vgrind command, **931**
- vi editor, 159–160, **931–938**
 - autoindent feature, 160
 - changing text, **183–184**
 - command mode and input mode, 932–933
 - cursor movement, **173–175**, 178–179
 - editing commands, 934–936
 - entering and leaving, **195–196**
 - exiting, 173
 - forcing file overwrite in, 171
 - keyboard mapping for, 161–162
 - learning curve, 177, 178
 - local variables, **938**
 - mode-switching maneuvers, **168–169**
 - moving around in, 933–934
 - operational mode, **166–168**
 - pattern searching, 936–937
 - preliminaries, **160–164**
 - saving editing buffer, 171
 - screen-control commands, **179–180**
 - searching text, **186–187**
 - starting within mail, 74
 - text creation with, **169–175**
 - text deletion, **181–183**
 - text entry, **170–173**
 - text-entry mode, **180–181**
 - unassigned printing keys, 189–190
 - using shell within, **188**
 - vedit, 164
 - view editor, 164
 - yanking and putting text, **184–186**
- vi option (Korn shell), 713
- view command, **938**
- view editor, 164. *See also* vi editor
- view mode, **938**
- viraw option (Korn shell), 713
- virtual console, **938**
- virtual memory, **938–939**
 - statistics on, 939
- virtual terminal, 431, **939**
- viruses, 374
- vis command, 939
- VisionFS, **459**
- visual command (Mail), 753
- visual command (mailx), 756
- VISUAL shell variable (Korn), 715, **939**
- Visual Systems Management (VSM), 466
- vmh command (MH), 765
- vmstat command, **939**
- vnews (news reader), 396
- VSM (Visual Systems Management), 466

W

- w command, **940**
- wait command, **126–127, 940**
- wait command (Bourne), 506
- Wait command (C shell), 560
- wait command (Korn), 717
- wait for child process, 124
- Wall, Larry, 800, 836
- wall (write all) command, 63, **940–941**
- warn (set argument), 194
- wc filter, command output combined by, 135
- wc (word count) command, 49–50, 122, 640, **941–942**
- Weinberger, Peter, 776
- what command, 203
- what program (SCCS), 847
- what string (@(#)), 203
- whatis command, **942**
- whatnow command (MH), 765
- whence command (Korn), 718, **942**
- whereis command, **942–943**
- which command, **943**
- while command, 326, **943**
 - in scripts, **324–342**
 - test for, 329–330
- while command (awk), 318, 482, 484
- while command (C shell), 560
- while command (Korn), 718

while command (nawk), 779
 “while forever” loop, null command for, 345
 while keyword (bc), 491
The White Book, 702
 white space, 499
 replacing with tabs and spaces, 914–915
 in scripts, 323
 and variable assignment, 330
 when testing strings, 332
 who command, 12, **17–19**, 59–60, **943–944**
 grep command for output of, 286
 /who command (IRC), 695
 whoami command, 944
 whodo command, **945**
 whois command, 390, **945**
 /whois command (IRC), 695
 whom command (MH), 765
 widget, 431, **945**
 widget library, **945**
 wildcards, **945**. *See also* metacharacters
 for ls command, **41–43**
 window
 active, **464**
 with focus, **648**
 inactive, **684**
 window command, **945–946**
 window manager in X, 426, 426, 427–429
 window (set argument), 194
 windowed applications, 646
 Windows (Microsoft), 425, 459
 access to files on Unix server. *See* Samba
 wksch, **946**. *See also* Korn shell
 words
 counting, **49–50**, **941–942**
 counting in expression, 361
 deleting, 565
 finding in system dictionary, **738–739**
 for for loop, 358
 in vi editor, 174
 wordy text, evaluating, **580–581**
 working directory, 33–34, 946. *See also* current directory
 World Wide Web
 home page, **679**
 Lynx browser, **748**
 worms, 374
 wrapmargin (set argument), 194
 wrapscan (set argument), 194
 write call, 578

write command, 58, **946**
 appropriate use, 63
 in ed editor, 623
 write command (Mail), 753
 write command (mailx), 756
 write login command, **59–64**
 write permissions, 104, 108, 527, 635, 800, **946**
 for directories, 105
 owner, group and public, 107
 for restoring backups, 416
 and rm command, 53
 testing for, 338
 write protected file, 106, 108
 writeany (set argument), 194

X

x command in mail command, 66
 x command (Mail), 752
 x command (mailx), 755
 X Consortium, 423
 X Protocol, **425**
 x protocol, **954**
 X server, **955**. *See also* server software in X
 X Window systems, 6, **958–959**
 benchmark program, **947**
 benchmark program to test server, **950–951**
 benefits, **427**
 client software, **424**, **424**, **434–436**
 communications link, **424–425**
 components, **425–426**, 426
 future of, **436–437**
 introduction, **422–427**
 logging in, **430**
 Motif, **771**
 Motif window manager (mwm), 428–429
 obtaining files on Internet, 437
 Open Look window manager (olwm),
 428–429
 vs. other windowing systems, **425**
 requirements, **429–436**
 resources, **430–431**
 server software, 424
 standard, 469
 standard development, 436
 starting, **791**
 terminals, **426–427**
 Twm (Tab Window manager), **908**

user configuration settings, **955–956**
 version number, 437
 X11R5 (X Window specification), **951**
 X11R6 (X Window specification), **951**
 X.400 standard, **952**
 X.500 standard, **952**
 xargs command, **947**
 xbench program, **947**
 xbiff program (X), 435, 436, **948**
 xcalc program (X), 435, **948**
 xcalendar program (X), 435
 xclock program (X), 435–436, **949**
 xcolors program (X), 435, **950**
 .Xdefaults configuration file, **950**
 xdm (X Display Manager), 430, **950**
 xdos program, 593
 xdpr program (X), 435, 950
 XENIX, **951**
 Xerox Corporation, Palo Alto Research
 Center, 422
 xfd program (X), 435, **951**
 xfontsel program (X), 435
 XFree86, **952**
 xinit program, 430, **952**
 .xinitrc file, 430, 595, **952**, 956
 xit command (Mail), 752
 xit command (mailx), 755
 xkill program (X), 435, 436, **953**
 xlax program, **953**
 xlib library, **953**
 xllperf program (X), **950–951**
 xload program (X), 435
 xlock program (X), **953**
 xlsfonts program (X), 435, **953–954**
 xman program (X), 435, **954**
 xrdp program (X), **954–955**
 xrefresh program (X), 435
 xrn (X Window newsreader interface), 955
 xsend utilities, **955**
 .xsession file, 430, 595
 xset program (X), 435, **955–956**
 xsetroot program (X), 435, **956**
 Xstone, 947
 xstr command, **956**

xterm command, **431–434, 956–957**
 command line options, 432–433
 xtod command, **958**
 xtrace option (Korn shell), 713
 xtract command, **958**
 xwd program (X), 435, **958**
 xwud program (X), 435
 .xx filename extension, 639

Y

Y2K problem, 701
 yacc compiler compiler, 540, **960**
 yanking and putting text, vi editor, **184–186**
 Yellow Pages, 783
 yes command, **960**
 You have mail message, 64
 yppasswd command, **960**
 yyfix command, **960**

Z

z command (mailx), 756
 z command (telnet), 886
 .Z filename extension, 393, 639, 689
 recompressing to gzip format, 962
 .z filename extension, 639, 689, 793
 zcat command, 670, **961**
 zcmp command, **961**
 zdiff command, **961**
 zforce command, **961–962**
 zgrep command, **962**
 .zip filename extension, 393, 689
 .zlogin file, 595
 .zlogout file, 595
 Zmodem file transfer protocol, tools to implement,
844–846
 zmore command, **962**
 znew command, **962–963**
 .zprofile file, 595
 Zsh, **963**
 .zshenv file, 595
 .zshrc file, 595