

INDEX

- (MLME)-SCAN, 212
- 16-bit quadrature amplitude modulation (QAM-16), 590
- 3GPP, 290
- 3PHP, 246,248,250
- 3rd Generation Partnership Project, 290
- 64-bit quadrature amplitude modulation (QAM-64), 591
- 802.11a/b/g, 241
- 802.15.4-compliant network, 392

- AA batteries, 390, 392, 410, 440, 444
- AAL, 481
- AAL-1, 481
- AAL-2, 481
- AAL-5, 481
- AAS, 489, 494
- AC, 13–15, 76, 192
- Acceptor, 130–131
- Access categories (AC), 13–15, 76, 192
- Access code, 110–111, 113–114, 118–119, 123
- Access point (AP), 4–8, 11–13, 16, 20, 22, 30–31, 33, 35–40, 42–44, 48–58, 60–61, 65, 68–69, 72, 94, 108, 139, 141–142, 153–154, 156, 159–161, 240, 416–417, 444, 480, 512, 555, 557, 585
- Access slots, 193
- ACI, 169
- ACK, 10–12, 15, 24, 82–83, 86–87, 91–93, 95–96, 98–100, 143, 147, 157, 194–195, 198–204, 206–209, 212, 215, 218, 220–221, 223–224, 229, 242–248, 252, 254–257, 304–305, 308, 325–330, 332, 335–336, 340, 354–357, 382–383, 394, 398, 406–407, 429, 447–451, 453–455, 460, 462–463, 499, 512
- Acknowledgment (ACK), 10–12, 15, 24, 82–83, 86–87, 91–93, 95–96, 98–100, 110, 113–114, 131, 143, 147, 157, 161, 163, 194–195, 198–204, 206–209, 212, 215, 218, 220–221, 223–224, 229, 242–248, 252, 254–257, 304–305, 308, 313, 325–330, 332, 335–337, 339–340, 342–347, 354–357, 382–383, 391–392, 394, 397–398, 400, 406–407, 426, 429, 440–441, 446–451, 453–455, 460, 462–463, 499, 512, 568
- Acknowledgment request (ARQ), 95, 110, 113–114, 137, 147, 343–346, 494, 512
- Acknowledgment request notification (ARQN), 113
- AckWaitDuration, 336
- ACL, 108, 111–113, 115, 117–120, 125, 127–128, 137–138, 140, 143–144, 147–148, 153, 157, 164, 333
- Acquisition overhead, 306, 309–310, 316
- Active list, 596
- Active member address (AM_ADDR), 113, 120, 122–124
- Adaptive antennas, 588
- Adaptive coding, 439
- Adaptive frequency hopping (AFH), 19, 140–141, 155–156, 161–164, 166–167, 179, 181–183
- Adaptive modulation and coding (AMC), 515, 523–524, 536, 588
- Adaptive Parameter Tuning, 82, 93–94
- ADD, 22, 95, 116, 122–123, 160, 162, 176, 242, 264–265, 373, 416, 440–441, 451, 504
- Additive white Gaussian noise, 159, 265
- Address assignment, 420–423
- Address mode, 418–419
- Admission control, 241, 498, 509, 515–516, 518–528, 530, 532, 534, 536–538, 540, 542, 544, 546–548, 550, 610
- ADSL, 512
- Advanced encryption standard, 8, 217, 393
- AES, 8, 217, 231–233, 393
- AES algorithm, 232, 393
- AFH, 19, 140, 155–156, 161–164, 166–167, 179, 181–183
- Agent Operation, 50–51
- Aggregate request, 502–503, 593
- Aggregate Signature, 561, 572, 574
- AIMD algorithm, 363
- All-QPSK loading, 289

- AM_ADDR, 113, 120, 122–124
 AME, 416–417
 Announce, 197, 201, 203, 208, 229–230, 355, 452
 Announce commands, 203, 208, 230
 AP, 4–8, 11–13, 16, 20, 22, 30–31, 33, 35–40, 42–44, 48–55, 57–58, 60–61, 68, 72, 94, 139, 141–142, 153–154, 156, 160–161
 APDU, 417
 API, 56, 58, 60, 393
 APS, 5–6, 8, 30–38, 41–43, 49, 51–53, 55–58, 60–61, 68, 141, 219–220
 Arbitrary interframe space (AIFS), 13–15
 ARQ, 114, 137, 147, 494, 512
 Arrival Probability Matrix, 534
 Association, 7–8, 30, 51, 55, 57–58, 61, 168, 192, 195, 197–198, 203, 211, 215, 219, 228–229, 241, 261, 323, 325, 336, 338, 341–344, 353, 420, 443–444, 447–448, 483
 Association commands, 192, 198
 Association request, 8, 51, 55, 215, 229–230, 341–343
 Association response, 229, 341–343
 Asymmetric link, 152
 Asynchronous, 4, 108–109, 111, 113–115, 137, 153, 161, 198, 201, 207–208, 212, 219–220, 241, 333, 445–446, 448–449, 452, 479, 592
 Asynchronous connectionless (ACL) communication, 108, 111–113, 115, 117–120, 125, 127–128, 137–138, 140, 143–144, 147–148, 153, 157, 164, 333
 Asynchronous data allocation, 220
 Asynchronous power save, 219
 ATM, 479, 481, 488, 592
 ATM CS, 481
 ATP, 219–220
 Attachment gateway (AG), 111, 418, 420, 426–427, 432, 489, 534
 Auction-Based Mechanisms, 66
 Authentication block, 234
 Authentication data, 231–235
 Authentication, authorization, and accounting (AAA) architecture, 557
 Automated clearing house (ACH), 572
 Autonomous organizations, 65
 AUX, 127
 Average BER, 274, 277–279, 283–286
 Average end-to-end queueing delay, 538
 Average PEP, 278–279
 AWGN, 159, 169–173, 176, 178–179, 182, 265, 278
 AWMA, 136, 139, 141–142, 144, 149, 156–159, 183
 Backhaul network, 488, 516, 522
 Backoff interframe space, 247
 Backoff period, 9, 330–332, 352, 374, 392, 394–397, 400, 402, 404–405, 407–410, 483
 Bandwidth request management packets, 592
 Bandwidth Reservation, 591
 BANs, 352
 Bargaining game, 526, 528–529, 531, 540, 542–544, 550
 BaseSuperframeDuration, 338, 395–396, 442
 Base station, 76–77, 385, 475, 493, 498, 512, 515, 523, 528, 532–536, 555–556, 562, 585, 587, 600
 Base station (BS), 76–77, 385, 475, 477, 479, 482, 484–486, 488–494, 496, 498–502, 504, 507–512, 515–518, 523–529, 532–538, 540–541, 543–548, 550, 555–556, 562, 585, 587–602, 609
 Basic service set (BSS), 4–7, 12–13, 16, 153, 475, 516, 524–525, 527, 532, 535–537, 540, 544, 548, 555
 Bayesian game, 72
 BCS, 156, 183
 BcstID, 219
 BD_ADDR, 116, 118, 120, 123–125
 BE, 4–24, 28–39, 44, 46, 48–52, 54–55, 57–58, 60–61, 65–67, 69–75, 77–79, 81, 83–89, 91–97, 99–101, 107–109, 111–121, 123–144, 147–149, 151–173, 176–177, 179, 182, 189–191, 193–232, 234–236, 241, 243–244, 247–255, 257–258, 262–266, 268–269, 271, 273–282, 284–285, 287, 289–292, 294, 299–309, 311–314, 316, 321, 323–327, 329–336, 338–347, 350–352, 354–356, 358, 360–365, 367, 369, 373–377, 379–386, 389–394, 396–397, 399–400, 402–409, 415, 417–427, 429–433, 435–441, 443–453, 459, 461–462, 466–468, 470–471, 475–477, 479–492, 494–496, 498–502, 504, 507–508, 510–512, 516, 518–523, 525–529, 531–537, 540–542, 547–548, 550, 555–564, 566–576, 578–582, 586–589, 591–593, 595–596, 598–599, 602, 607
 Beacon, 11–13, 15, 18, 94, 120, 138, 141–142, 144, 157–158, 192–204, 206–209, 211–215, 218–227, 229–230, 232–233, 241, 251, 254, 303–304, 309, 313, 323–328, 330, 333, 335–339, 341–342, 344–345, 350–357, 361, 365, 373–374, 376–378, 380, 382, 384, 389–392, 394–402, 407, 412, 441–444, 446–449, 451, 453–456, 458, 463, 468
 Beacon integrity protection, 226–227

- Beacon interval, 138, 141–142, 221–226, 338, 352, 365, 395, 397, 402, 442–444, 446, 448, 453, 456
- Beacon order, 338, 353
- Beacon time token, 230, 232
- Beacon-enabled mode, 353, 390–391, 441
- Beacon-scheduling, 443
- Beacon-to-beacon, 138
- BER, 82, 88, 90–91, 134, 140, 159, 161, 169–170, 262, 274, 276–280, 283–287, 291–293, 512
- Bernoulli scheduling, 402
- Best Effort Service (BES), 593–594, 596–599, 601–609
- BI, 84, 235, 353, 395–396, 402, 453, 532, 535, 573
- BIAS, 155, 163–164, 167, 183
- BICM, 261, 263, 267, 271–272, 290, 295
- Bidimensional process, 84
- Bidirectional management connection, 591
- BIFS, 199–201, 247–248
- Bilinear pairing, 561
- Binary exponential backoff (BEB), 9, 55, 90, 483, 592
- Binary integer linear programming, 528
- Binary phase shift keying (BPSK), 22, 323, 350, 395, 524, 536
- Binary pulse position modulation, 300
- Bit error rate, 82, 134, 140, 159, 252, 262, 347, 512
- Bit error rate (BER), 82, 88, 90–91, 134, 140, 159, 161, 169–170, 252, 262, 274, 276–280, 283–287, 291–293, 347, 512
- Bit-interleaved coded modulation, 261
- Blind Signature, 558–560
- Block acknowledgement (BA), 15, 272, 290
- Block cipher encryption, 234–235
- Block cipher key, 233, 235
- Bluetooth, 17, 19, 28, 38–44, 48, 53–54, 105, 107–108, 110–111, 113, 116–119, 121, 123, 126–129, 132–134, 151–170, 172–174, 176, 178–183, 191–192, 236, 240–241, 349
- Bluetooth WPAN standard, 110
- BMAC, 445
- BO, 189, 217, 338, 353, 356–357, 364–366, 395–396, 410, 446
- Boolean expression, 420
- Bottom-up, 421
- BR, 488
- Bridge switching, 397
- Broadcast, 11, 120, 123, 125–126, 192, 201, 211, 224, 228, 246, 304–305, 313, 336, 377, 385, 391, 419, 423, 426–427, 429, 436–438, 490, 499, 504, 506, 574, 589, 591–592
- BSD, 128
- BS DL Scheduler, 594–595
- BSID, 196–197, 512
- BS Periodic Grant Generator, 595
- BS UL Scheduler, 594–595
- BS UL-MAP Generator, 595
- BSN, 327, 336
- BT, 134, 158, 441, 446–448, 452, 456–457, 464–471
- BTC, 494
- Buffer Management, 517
- Built-in, 441
- Bursty traffic, 588
- Burst acknowledgment request (BurstAckReq), 95–96
- Business-to-business (B2B), 558
- BW, 497–498, 500, 502–506, 508–512, 593–599, 609
- BWA, 475, 477–479, 495, 497, 512, 586
- CAC, 113–114, 116, 120, 123, 509
- CAP, 192–194, 198–204, 206, 208, 214–216, 219–221, 241, 243, 245, 248, 323–325, 332, 335, 338, 341, 347, 353–356, 362, 364–365, 369, 395, 442
- Carrier sense multiple access, 136, 153, 193, 300
- CBC, 231, 234–236
- CBC-MAC, 234–236
- CBR, 500, 512, 592, 600
- CBR traffic, 600
- CC, 287, 291, 294
- CCA, 16, 200, 331–332, 399–400, 404–405, 411, 453–455, 457, 460, 463
- CCADetectTime, 247
- CCAP, 156, 159–161, 183
- CCB, 289–292, 294
- CCK, 20, 23, 136–137
- CCM, 232–233
- CCM nonce frame format, 232
- CCM security cryptographic algorithm, 232
- CDMA, 20, 261, 347, 512, 517, 556
- Cellular networks, 30, 65, 556, 585
- Certificate authority (CA), 4, 9, 20, 54, 70–71, 83, 95, 136, 193, 199, 239, 241, 245, 323–327, 330–332, 350–351, 353–355, 376, 389–391, 394, 396–397, 399, 440, 442–443, 451, 454–455, 466, 557, 562
- Certificate revocation list (CRL), 563, 570
- CFP, 11–13, 15, 193–194, 323–325, 330, 346, 352–356, 369, 395, 442

- CHANNEL ACCESS, 10, 12, 70, 82–83, 87, 93–96, 98–99, 113, 189–190, 192, 194, 196, 198–208, 210, 212, 214, 216, 224, 241, 324, 330–331, 351, 356, 391, 440, 483
- Channel impulse response, 264–265, 267–268
- Channel management, 588
- Channel scanning, 227
- Channel status request, 209, 230
- Channel status response, 209
- Channel time allocation, 193, 195, 198, 202–203, 208, 219–220, 241, 344
- CI, 54, 78, 379, 401, 487, 564
- CID, 128, 132, 480, 483–485, 487–489, 492, 498, 503, 508, 512, 591, 593
- Cipher blockchaining, 231
- Cipher keys, 218
- CIR, 159, 265–266
- Circuit-switched connection, 112
- Clearance procedure, 572
- Clear-channel assessment (CCA), 16, 200, 247, 331–332, 399–400, 404–405, 411, 453–455, 457, 460, 463
- Clear-channel assessment detect time, 247
- CLKN, 116
- Cloning transmission, 227
- Cluster tree routing, 385
- Clustered UWB wireless PAN, 313
- CM1, 267–271, 280–287, 291–295
- Cochannel interference, 27, 29, 31, 33–36, 38, 43, 45–46, 50, 54, 151–153, 155
- Code division multiple access (CDMA), 20, 261, 347, 382, 512, 517, 556
- Coexistence mechanisms, 135–136, 138–140, 149, 151, 155, 161
- Coin fraud attack, 559, 573
- Collision avoidance, 4, 70, 83, 136, 153, 156, 193, 239, 323, 350, 376, 389, 398, 401, 440
- Collision probability, 39, 82–84, 88, 93–95, 248–250, 374, 466
- Command frame, 193, 195, 203, 227, 241, 243, 246, 250, 321, 327–328, 330, 332, 335–337, 340–346, 418, 420–421, 433, 441, 444–445, 448–449, 451, 463, 465, 468
- Command integrity, 218, 226–227, 232
- Command integrity protection, 226
- Common part sublayer (CPS), 241, 416, 444, 480–481, 485, 488, 512, 588, 591
- Communication channels, 109, 111, 128
- Complementary code keying (CCK), 20, 23, 136–137
- Confirm, 130–131, 139, 144
- Connection blocking probability, 533, 537, 544–548
- Connection ID (CID), 128, 132, 480, 483–485, 487–489, 492, 498, 502–503, 508, 512, 591, 593
- Connectivity matrix, 424–425, 427, 429
- Constant bit rate (CBR), 500, 512, 588, 592, 600
- Constant-bit-rate service, 482
- Consuming credit, 568
- Contamination, 69
- Contention access, 192–193, 208, 220, 241, 246, 248, 250, 323, 353, 442
- Contention access period, 192–193, 208, 220, 241, 323, 353, 442
- Contention period, 11, 97, 241
- Contention slots, 592–593
- Contention window (CW), 9–10, 13–14, 70–71, 82–87, 93–95, 203, 330–332, 351–354, 356–357, 360, 369, 483, 592
- Contention-free, 4, 9, 11–12, 193, 201, 243, 323, 352, 374, 386, 395
- Contention-free period (CFP), 11–13, 15, 193–194, 201, 323–325, 330, 346, 352–356, 369, 395, 442
- Continued wake beacon, 220
- Convolutional code, 264, 271, 275–276, 281, 286–289, 292–294
- Cooperative medium access scheme, 522
- Coordinated multihop scheduling (CMS), 523
- Coordinator, 4, 12, 32, 189, 192, 241, 322, 324–327, 335–336, 338, 341–345, 350, 353–358, 361–365, 374, 385, 389, 391–394, 396–397, 400, 404–405, 429–430, 435, 442–444, 447–448, 593–594
- Counter block, 235
- CP, 11–12, 15, 275
- CPS, 241, 480–481, 485, 488, 512, 588, 591
- CRC, 114–115, 127, 332, 337, 486–487, 499–500
- Cryptographic hash function, 393
- CS, 19, 349, 480–483, 487, 499, 588
- CSMA, 4, 9, 20, 54, 70–71, 83, 95, 136, 193, 199, 216, 239, 241, 245, 300, 323–327, 330–332, 350–351, 353–355, 376, 389–391, 394, 396–399, 440, 442–443, 451, 454–455, 466
- CSMA/CA, 4, 9, 20, 54, 70–71, 83, 95, 136, 199, 239, 241, 245, 323–327, 330–332, 350–351, 353–355, 389–391, 394, 396–397, 399, 440, 442–443, 451, 454–455, 466
- CT, 207
- CTA, 193, 195–196, 199, 201–210, 212–216, 219, 224–226, 241–244, 246, 251–254, 256–257
- CTA IE, 196

- CTA REQ, 207, 242, 253
 CTAP, 198–201, 204, 206, 208, 216, 241,
 251–252
 CTC, 494
 CTM, 207
 CTR, 231–233
 CTR mode encryption algorithm, 233
 CTRq, 201, 203–204, 206–208, 213–214,
 224–225, 229–230, 235, 242, 244, 254
 CTS, 10–11, 82–83, 85, 87, 91, 96, 98–100, 374,
 451–453, 463
 CurrentTimeToken, 227
 Cut-and-choose algorithm, 560
 CW, 9–10, 13–14, 82, 84–87, 93–95, 330–332,
 351–354, 356–357, 369
- DA, 70, 292, 417
 DAMA, 490–492, 502, 512, 589
 Data authentication, 231–232, 234
 Data authentication mechanisms, 231
 Data collision, 356
 Data control transmission, 591
 Data encryption, 217–218, 226, 232–233, 333,
 392
 Data encryption generation, 232–233
 Data-driven, 429
 Data frame, 5–7, 9–11, 13, 16, 24, 83, 86,
 90–91, 93, 95, 97–98, 100, 143, 195–196, 219,
 227–230, 233, 241, 245, 251–252, 327–328,
 332–333, 335, 338–340, 346, 351–352,
 354–357, 360–361, 391, 417–420, 426–427,
 429, 437–438, 444–445, 447–450, 452–454,
 458–463, 466, 468–469
 Data-high, 114, 148
 Data integrity, 73, 113, 127–128, 131, 218,
 226–227, 232
 Data integrity code generation, 218, 232
 Data link layer, 109, 389, 478
 Data-medium, 113, 148
 Data packet, 110, 112–114, 120, 129–132, 157,
 163, 179, 304, 328, 382–383, 391, 399, 407,
 427, 429, 480, 501–502, 518, 524, 593
 Data payload protection key, 233
 Data request, 326, 341, 344, 354–355, 357, 391,
 503
 Data stream, 19, 23, 115, 198, 201, 207, 216,
 220, 224–225, 242, 244
 Data-voice (DV), 113, 147
 DCF, 4, 8–15, 81–85, 87, 91, 93–97, 99–101,
 136, 522
 D-coin, 559, 561–563, 567–568, 570–574, 578,
 580–581
 D-coin batch verification, 572
- DCT, 156, 167–176, 178–183
 Decryption, 231, 235, 574–575
 Dedicated inquiry access code (DIAC), 119,
 123
 DeficitCounter, 596
 Deficit fair priority queue, 595, 603, 605, 607
 Degree of connectivity, 379
 Delay lower limit (DLL), 86, 88
 Delayed acknowledgment, 243
 Delivery latency, 384
 Denoted U-coin, 558
 Des-Mode, 211, 213
 Dest_DEV, 245, 248
 DestID, 196, 203, 208, 213, 219, 231–232
 DEV, 190, 192, 195–232, 236, 241–242,
 244–249, 251–257, 325–327, 330–333,
 336–346, 447–451
 DEV PHY, 200
 Device management entity, 211, 227, 416
 Device synchronized power save, 219
 DEVID, 197, 202, 213, 218, 220–221, 224, 228,
 230–231, 252
 DEV-to-DEV, 198
 DFNS, 156, 159, 183
 DFPQ, 596–597, 605, 609–610
 DHCP, 591
 Differentiated Services (DiffServ) IP network,
 527
 Digital signal processing (DSP), 23
 Digital subscriber lines (DSL), 477, 494–495,
 555, 587
 Digital telephony, 479
 Direct sequence (DS), 6, 17–20, 240, 299–300,
 408
 Directional antenna, 20, 522
 Direct-link protocol (DLP), 13, 15–16
 Direct-sequence spread spectrum (DSSS), 4,
 16–20, 23, 136–137, 148, 153, 323
 Disassociation request, 215, 229–230
 Discrete random probability distribution, 392
 Distributed coordination function (DCF), 4,
 8–15, 81–85, 87, 91, 93–97, 99–101, 136,
 239, 522
 Distributed-constraint optimization problems
 (DCOPs), 55
 Distributed Security Management, 581
 DistributeKey request command, 228
 Distribution system (DS), 6–8, 17–20, 240,
 299–300, 408
 DIUC, 507, 512
 DL, 489, 494, 507–508, 512, 589, 594–595, 597,
 610
 DL-MAP, 507–508, 512, 589, 595

- Dly ACK, 194–195, 255
- DME, 211, 227, 229, 339, 416–417
- Domain agents (DAs), 70
- Downlink channel, 492, 589, 594
- Downlink channel descriptor message (DCD), 490, 589
- Downlink map (DL-MAP), 507–508, 512, 589, 595
- DS, 6, 17–20, 240, 299–300, 408
- DSC, 485, 500, 512
- DSL, 477, 494–495, 555, 587
- DSR, 74, 246
- DSSS, 4, 16–20, 23, 136–137, 148, 153, 323
- Dst, 249, 428
- DS-UWB, 240, 300
- DUT, 126
- DV, 113, 147
- Dynamic channel service and selectio, 192
- Dynamic CTA, 201–202, 204
- Dynamic source routing (DSR), 74, 246
- Dynamic topology, 189

- Earliest deadline first, 242
- E-cash/e-voting system, 560
- EC, 487–488
- ECC-UAB, 574–579
- ECDSA signature, 561, 578
- ECMA, 261
- EDF, 242
- Effective CTA rate, 251, 254, 256
- EK, 487
- ElementID, 196–197
- Embedding Hm (M), 37, 41–42, 53, 57, 84, 109, 126, 140, 152–153, 155–156, 166, 171–172, 189, 191, 232–235, 239, 242, 252, 255–256, 272, 290, 304, 309, 311, 337, 358, 362, 365, 397, 399, 401, 406–408, 423, 525, 537, 568, 571, 579, 585
- Encryption, 8, 33, 123, 125–126, 195, 217–218, 226–227, 231–235, 333, 392–393, 487–489, 571, 574–575, 578, 588
- Encryption data, 233
- Encryption key, 123, 125, 232–233, 235, 487
- Encryption key stream, 235
- End-to-end, 384, 426, 508, 518, 521, 523, 526–527, 532–533, 535–538, 540–541, 548, 550
- End-to-end transmission rate, 540–541
- Enhanced CAP, 243
- Enhanced distributed-channel access (EDCA), 12–15
- Enhanced Interaccess point protocol (IAPP), 557
- Enhanced SRPT, 242
- Error-free reception, 193
- ErtPS, 501–502, 508
- ESRPT, 242
- ETSI, 16, 19, 586
- European Radio-communications Office (ERO), 16
- European Telecommunications Standards Institute (ETSI), 16, 19, 586
- Evolutionary Scheme, 75
- Exchange-Based Mechanisms, 66
- ExpDate, 565–566
- Extended SCO (eSCO), 112
- Extended service set (ESS), 6–7, 555
- Extreme non-LOS multipath channel, 267

- FACTA, 242
- Fair-SRPT, 242
- Fast frequencyhopping (FFH), 109–110
- FC, 57, 417
- FCC, 16–17, 19, 153, 162, 165, 240, 261, 289, 291, 299
- FCFS, 352, 355
- FCS, 193–194, 230, 327–329, 333–334, 337–340
- FDD, 476, 492–494, 504, 507, 589
- FEC, 21, 114–115, 123, 140, 143, 147–149, 494, 588
- Federal communications commission, 16, 153, 240, 261, 299
- Feedback-assisted CTA, 242
- Fedora Core 4, 576
- FFH, 109–110
- FFT, 20–21, 23, 264–266, 268
- FHS, 113, 115, 118–120
- FHSS, 16, 18–19, 136–137, 152
- FIFO, 115, 358
- File transport protocol (FTP), 163, 512, 592, 600
- First in first out (FIFO), 115, 358
- Fixed point-to-multipoint BWA, 586
- Flexible channel bandwidth allocation, 588
- Forward error correction (FEC), 21, 114–115, 123, 140, 143, 147–149, 494, 588
- Four separate channel models, 267
- Fourier transform (FFT), 20–21, 23, 264–266, 268
- Fragmentation control field, 232
- Frame check sequence, 193, 230, 328, 334, 337–338, 340, 410
- Frame Concatenation, 82, 89, 93, 95, 97, 99–100
- Frame control field, 334, 418
- Frame control format, 194

- FRAME FORMAT, 99, 189–190, 192–198, 200, 202, 204, 206, 208, 210, 212, 214, 232–233, 242, 321, 333–335, 337–340, 417–420
 Frame header, 233, 252
 Frame Piggyback, 82, 93
 Frame relay, 479
 Frame Type Field, 194
 Frequency band, 17–19, 22–24, 28, 110–111, 133, 135–136, 139, 141–146, 151, 153, 155, 161, 164, 191, 240, 261, 264–265, 289, 299, 323, 374, 395, 475–476, 478–479, 492, 494–495, 519–520, 524, 536
 Frequency division duplexing (FDD), 476, 492–494, 504, 507, 589
 Frequency division multiple access (FDMA), 18, 515, 588
 Frequency hop synchronization (FHS), 113, 115, 118–120
 Frequency hopping, 4, 19, 40, 111, 140–141, 155, 161–162, 261, 270–271, 299
 Frequency hopping (FH), 4, 17–20, 40, 111, 116–117, 137–138, 140–141, 155, 161–162, 261, 270–271, 299
 Frequency-hopping spread spectrum (FHSS), 16, 18–19, 136–137, 152
 Frequency-Nulling Scheme, 156, 159
 Freshness protection, 226–227, 392
 FTP, 163, 512, 592, 600
 Full-duplex SSs, 492

 Game theory, 523
 Game-Theoretic Forwarding, 75
 Game-Theoretic Strategies, 67
 Gaussian, 41, 134, 152, 159, 263, 265–266, 269, 272–273, 278, 301
 GC, 421, 430–437
 GCUD, 433–436
 GDIS, 436
 General inquiry access code (GIAC), 118–119, 121, 123
 Generalized processor sharing (GPS), 190–191, 523, 607
 Generic QoS architecture, 593, 595, 597
 Geometric distribution, 83, 404, 407
 GFSK, 134, 152, 169
 GIAC, 118–119, 121, 123
 Global network controller (GNC), 32
 GM, 430–438
 GP, 358–359, 397, 407, 410
 3GPP, 288
 GPS, 190–191, 523, 607
 Grant Generator, 594–595
 Grant per connection (GPC), 591–593, 595, 599, 601, 603–610
 Grant per SS (GPSS), 591–593, 595, 598–599, 602–603, 605, 607, 609–610
 Granting bandwidth (BW), 497–498, 500, 502–506, 508–512, 589, 593–599, 609
 Grid topology, 380
 GS, 441, 446, 451–452, 463–466, 468–471, 563
 GSM (Global System for Mobile Communications), 6, 556
 GTS, 192, 194–195, 201, 325, 341, 344, 346–347, 352–353, 355–356, 361–369, 395, 442
 GTS hit, 361–364
 GTS miss, 361–363
 GTS scheduling algorithm, 364
 Guaranteed time slot transmission, 419
 Guard band, 142, 536

 Half-duplex SSs, 493, 589
 Hamming code, 114
 Handoff Latency, 51–53, 55, 57, 578
 Hash function, 393, 563
 HCF controlled-channel access (HCCA), 12–13, 15
 HCI, 129
 Header error check (HEC), 110, 113–115, 140
 High definition TV (HDTV), 82
 High rate WPAN, 192, 349
 High-quality voice, 113
 HiperMAN standard, 586
 HMAC, 393
 Hop selection mechanism, 162
 Hop-by-hop, 426
 Hopping rates, 137
 Hops2Nb, 420, 426
 HR-WPAN, 192, 207, 216–218, 227, 231, 233, 236
 HT, 373–374, 376–377, 487, 512
 Hungarian method, 520
 HV, 144
 Hybrid coordination function (HCF), 9, 12, 101

 IAC, 113, 116, 119, 123
 ID, 113, 115, 119, 124, 131–132, 196–197, 203–204, 221, 245, 247, 334–336, 338–346, 375, 377–378, 417–419, 436, 487, 489, 493, 524–525, 533, 536, 564, 566, 575, 591
 Idle listening, 440–441, 447, 452, 470
 IE, 36–39, 45–48, 196–197, 212, 220–222, 224, 245, 247–248, 592
 IEEE, 1, 3–24, 27–28, 31, 33, 39–40, 42–44, 50, 54–55, 57–58, 65–66, 68–70, 72, 74, 76–79,

- IEEE (*Continued*)
- 81–88, 90–101, 105, 107–116, 118, 120, 122–124, 126, 128, 130, 132–149, 151, 153–154, 187, 189, 191–192, 195, 198, 216–220, 222, 224, 226–228, 230–234, 236, 239–242, 244, 246, 248, 250, 252, 254, 256, 258, 261–262, 267, 295, 300, 319, 321–324, 326, 328, 330–332, 334, 336–338, 340–342, 344, 346–347, 349–370, 373–374, 383, 389–390, 392, 395, 415–416, 418, 420, 422, 424, 426, 428, 430, 432, 434, 436, 439–448, 450, 452, 454–458, 460, 462, 464, 466, 468, 470–471, 473, 475–486, 488–490, 492–497, 512, 515–516, 522–525, 533, 550, 555, 568, 574–578, 581, 585–594, 609–610
 - IEEE 801.15.1, 236
 - IEEE 801.15.1 piconet, 236
 - IEEE 802.11, 1, 3–24, 27–28, 31, 33, 39–40, 42–44, 50, 54–55, 57–58, 65–66, 68–70, 72, 74, 76–79, 81–88, 90–101, 135–138, 140–141, 144–145, 147–149, 151, 153–154, 239, 241, 352, 439–440, 477, 522, 555, 585
 - IEEE 802.15, 28, 105, 107–116, 118, 120, 122–124, 126, 128, 130, 132–149, 187, 189, 191–192, 195, 198, 216–220, 222, 224, 226–228, 230–234, 236, 239–242, 244, 246, 248, 250, 252, 254, 256, 258, 261–262, 267, 295, 300, 319, 321–324, 326, 328, 330–332, 334, 336–338, 340–342, 344, 346–347, 349–370, 373–374, 383, 389–390, 392, 395, 415–416, 418, 420, 422, 424, 426, 428, 430, 432, 434, 436, 439–448, 450, 452, 454–458, 460, 462, 464, 466, 468, 470–471, 477
 - IEEE 802.15.1, 105, 107–116, 118, 120, 122–124, 126, 128, 130, 132–138, 140–141, 143–149, 240–241, 349
 - IEEE 802.15.3, 187, 189, 191–192, 195, 198, 216–220, 222, 224, 226–228, 230–234, 236, 239–242, 244, 246, 248, 250, 252, 254, 256, 258, 267, 300, 349, 415
 - IEEE 802.15.3 piconets, 239–240, 242, 244, 246, 248, 250, 252, 254, 256, 258
 - IEEE 802.15.3 WPAN, 189, 217, 240–241, 250, 258
 - IEEE 802.15.3a channel model, 267
 - IEEE 802.15.3a UWB channel model, 267
 - IEEE 802.15.4, 28, 319, 321–324, 326, 328, 330–332, 334, 336–338, 340–342, 344, 346–347, 349–370, 374, 383, 389–390, 392, 395, 416, 439–448, 450, 452, 454–458, 460, 462, 464, 466, 468, 470–471
 - IEEE 802.15.4 MAC Protocol, 365
 - IEEE 802.15.5, 373, 415–416, 418, 420, 422, 424, 426, 428, 430, 432, 434, 436
 - IEEE 802.16, 473, 475–482, 484–486, 488–490, 492–497, 515–516, 522–525, 533, 550, 555, 585–594, 609–610
 - IEEE 802.16–based backhaul topology, 522
 - IEEE 802.16 broadband wireless access standard, 585
 - IEEE 802.16 mesh networks, 522
 - IEEE 802.16 standard, 475–479, 481, 485–486, 495–496, 523–525, 586–587, 589, 591, 593, 609
 - IEEE 802.16.1, 475, 479
 - IEEE 802.16.2, 475
 - IEEE 802.16.3, 476
 - IEEE 802.16a, 475, 495, 515, 524, 555, 586
 - IEEE 802.16e standard, 587
 - IEEE 802.2, 416
 - IEEE 802.3, 81, 482
 - IEEE standards, 483, 586
 - IFS, 198–199
 - Imm-ACK, 195, 199–200, 202, 204, 206–207, 209, 215, 218, 224, 229, 243, 245–248, 252, 255–257
 - Impersonation Attack, 567, 574
 - Incentive-compatible MAC (ICMAC), 72
 - Incremental request, 502–503
 - Indication, 130–131, 140, 306, 416–417, 444, 486
 - Industrial, scientific, and medical (ISM), 17, 19, 28, 40, 109, 111, 133, 151–153, 323, 349, 391–392, 394, 396–397, 410
 - Information elements (IEs), 233, 500, 503, 590
 - Inquiry access code (IAC), 113, 116, 118–119, 123
 - Inquiry response, 116–117, 119, 121
 - Inquiry scan, 116–117, 119
 - Integrity code, 218, 227, 231–232, 234–235, 392
 - Intercarrier interference (ICI), 21
 - Interdomain interference, 46
 - Interdomain WLAN, 41
 - Interference-aware routing mechanism, 522
 - Interferer power, 159
 - Interframe spaces, 251
 - International Organization for Standardization (ISO), 109–110
 - International Telecommunications Union (ITU), 17, 38, 332
 - Internet, 5, 7–8, 70–71, 81, 97, 239, 476–479, 482, 493–497, 512–513, 516–517, 524–525, 532–533, 537, 547, 555–558, 561–562, 564, 567, 585

- Internet service providers (WISPs), 70–71, 556–559, 561–563, 570, 574
- Intersymbol interference (ISI), 21
- Intrapiconet route optimization, 250–251, 253, 255, 257
- Intrusion detection systems (IDSs), 69
- Inverse fast Fourier transform (IFFT), 23, 264, 268
- IP, 8, 482–484, 487–488, 491, 497, 512, 527
- ISM, 17, 19, 28, 40, 109, 111, 133, 151–153, 323, 349, 391–392, 394, 396–397, 410
- ISOAFH, 167
- ISP, 477, 479, 492–493, 496
- ITU-T, 332
- IWF, 488

- JREP, 432–433, 435–436
- JREQ, 431–433, 435–436

- Key encryption operation, 218, 232
- Key establishment(s), 13, 19, 34, 38–40, 43, 48–49, 52, 54–55, 57–59, 70–72, 75, 84–85, 89, 97, 107–113, 115–118, 120–121, 123–126, 128–129, 132, 136–137, 149, 155–156, 161, 166–168, 170, 178, 191, 197, 200, 208–209, 212–213, 215, 217, 226, 228, 247, 249–250, 253, 261, 273, 289, 294, 299, 302–305, 307, 310–316, 327, 342–344, 347, 358, 363, 366–368, 374–375, 377, 380, 383–386, 389, 392–393, 401–403, 409, 412, 422–423, 429–430, 435–437, 443, 446, 450–451, 453, 455–467, 469–470, 482–483, 488, 490, 493, 501, 509–512, 536, 539–541, 543, 545, 557, 559–560, 562–564, 566–567, 569–571, 573–575, 581–582, 585–586, 588, 591, 594, 601, 604, 606, 608
- Key exchange, 389–390, 393, 398, 404, 409–412, 588
- Key exchange mechanism, 389
- KeyInfoLength, 229
- Key management, 193, 390, 392
- Key predistribution, 568
- Key request command, 228, 233
- Key selection, 228, 230
- Key stream, 231, 235
- Key stream generation, 231
- Key transport(s), 13, 19, 34, 38–40, 43, 48–49, 52, 54–55, 57–59, 70–72, 75, 84–85, 89, 97, 107–113, 115–118, 120–121, 123–126, 128–129, 132, 136–137, 149, 155–156, 161, 166–168, 170, 178, 191, 197, 200, 208–209, 212–213, 215, 217, 226–228, 247, 249–250, 253, 261, 273, 289, 294, 299, 302–305, 307, 310–316, 327, 342–344, 347, 358, 363, 366–368, 374–375, 377, 380, 383–386, 374–375, 377, 380, 383–386, 392, 401–403, 409, 412, 422–423, 429–430, 435–437, 443, 446, 450–451, 453, 455–467, 469–470, 482–483, 488, 490, 493, 501, 509–512, 536, 539–541, 543, 545, 557, 559–560, 562–564, 566–567, 569–571, 573–575, 581–582, 585–586, 588, 591, 594, 601, 604, 606, 608
- L2CAP, 108, 110, 114, 126–132
- LAN, 6, 27–28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 108–109, 111, 151–152, 154, 156, 158, 160, 162, 164, 166, 168, 170, 172, 174, 176, 178, 180, 182, 477, 487–488, 585
- LAP, 113, 121–123
- Laplace–Stieltjes transform, 402
- LastValidTimeToken, 227, 230
- LBT, 9, 40, 156, 166–167, 183
- LC, 114–115, 124, 275–277, 279–280, 405–406
- Least significant bit (LSB), 113, 122, 132
- Least-squares error, 265
- L-length field, 231
- Line of sight (LOS), 20, 22, 267, 478, 512, 586, 588
- Linear feedback shift register (LFSR), 114–115
- Linear programming-based branch-and-bound algorithm, 528
- Line-of-sight, 267, 494, 515, 537, 586
- Line-of-sight communication, 515, 537
- Link control (LC), 108–110, 114–117, 124, 126–127, 129, 131, 144, 241, 275–277, 279–280, 405–406, 416, 589
- Link manager, 108, 110, 114, 129, 139, 144, 160
- Link manager protocol (LMP), 108, 110, 124–128, 133, 161, 163, 166
- Link optimization ratio, 254–256
- Link Quality, 51, 53–54, 57–58, 89, 92, 250, 257, 424
- Link quality rate, 51, 53–54
- Link state, 251, 375, 421, 423–424, 426–427
- Listen-before-talk (LBT), 9, 40, 156, 166–167, 183
- LLC (link layer control), 76, 109–110, 241, 416
- Local area network (LAN), 3, 6, 27–28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 65, 81, 108–109, 111, 135, 151–152, 154, 156, 158, 160, 162, 164, 166, 168, 170, 172, 174, 176, 178, 180, 182, 239, 299, 439, 477, 487–488, 523, 585
- Local network controller (LNC), 32–37, 41
- Local user accounting profile (LUAP), 559, 563, 567–571

- Local voting strategy, 559
- Localized authentication, 557, 559, 574–575, 578
- Location Privacy Protection, 574
- Log-domain BCJR AU2 algorithm, 288
- Logical link control (LLC), 76, 108–110, 126–127, 129, 131, 241, 416
- Logical link control and adaptation protocol (L2CAP), 108, 110, 114, 126–132
- Logical link sublayer, 588
- LOR, 254–257
- LOS, 20, 22, 267, 586, 588
- Low probability of intercept (LPI), 18
- Low rate WPAN (LR-WPAN), 28, 321, 389, 395, 415–416
- Lower address part (LAP), 113, 121–123
- LP, 130–131, 441, 446, 448–450, 457–471
- LPA, 441, 446, 449–451, 460–463, 465–470
- LPAS, 441, 446, 450, 462–463, 465–466, 468–471
- LREP, 434–435
- LREQ, 434–435
- LSB, 113, 122, 132
- LSE, 265–266, 273, 281, 283, 286–287, 295
- LST, 402–403, 407–408, 423–424

- M authentication field, 231
- MAC, 3–9, 11–16, 24, 43, 54–55, 70–72, 75, 81, 83, 87, 91–92, 95–96, 98–101, 108–110, 123, 127, 134, 136, 138–139, 144–145, 147, 153, 156–157, 164, 167–168, 192–195, 197, 199, 210, 216–218, 226–227, 231, 234–236, 239–252, 254, 257, 321–323, 326–330, 332–345, 347, 349–350, 356–361, 363, 365, 367, 369, 373–374, 376, 382–383, 386, 390–395, 399, 409, 415–417, 419, 426, 429, 436–441, 444–446, 448–449, 451–454, 464, 466, 468, 475–481, 483–490, 492–497, 499–500, 502, 504, 507–508, 512, 522, 524, 586–588, 591, 595, 598, 609
- MAC address, 6, 252
- MAC command frames, 246, 330, 336–337
- MAC CPS, 480–481, 485, 488, 512
- MAC frame, 7–9, 83, 95, 192–195, 197, 218, 227, 252, 257, 333–335, 339, 392, 436, 487, 489
- MAC frame payload, 252
- MAC header, 24, 92, 100, 194, 231, 242, 247, 250–251, 328, 337, 341, 343–345, 358, 486–487, 489, 499–500
- MAC layer management entity, 210, 226, 327, 416
- MAC protocol, 4–5, 7, 9, 11–13, 15, 87, 91, 96, 98, 101, 108, 147, 241, 254, 328, 365, 382–383, 394, 439, 444, 446, 448, 476–477, 507–508, 522, 591
- MAC protocol data unit (MPDU), 7–11, 96, 147, 327–329
- MAC service data unit, 8, 242, 327, 480
- MacAssociationPermit, 338
- MacBeaconOrder, 395–396, 446
- MacCoordExtendedAddress, 339–341, 344
- MacDSN, 336, 339–340
- MacRxOnWhenIdle, 445
- MacSuperframeOrder, 395–396, 446
- MAN, 477, 555–556, 558, 579, 585–586
- Management channel time allocation, 202–203, 220
- Management information base (MIB), 109, 491–492
- Management payload protection key, 232
- Mandatory QoS parameters, 593
- Markov point, 403–404
- Master–slave paradigm, 109
- MaxDrift, 205
- MaxFrameResponseTime, 354, 391
- Maximum traffic, 243, 500
- Maximum traffic burst, 500
- MaxKeyChangeDuration, 228
- MaxTimeTokenChange, 230
- Maximum latency, 500–502
- Maximum sustainable interference, 302
- Maximum throughput (MT), 82, 86–87, 243, 526, 609
- Maximumratio combining, 267
- Max-min fair allocation, 595–596, 603, 605, 607, 609
- MaxMulticastJoinAttempts, 433
- MB-OFDM, 240, 248, 254, 261–268, 270–272, 274–276, 278–284, 286–290, 292–295, 299–300
- MB-OFDM–based wireless PANs, 300
- MB-OFDM UWB PHY, 248
- MB-OFDM UWB system, 261–262, 264, 266, 268, 270, 272, 274, 276, 278, 280, 282, 284, 286, 288, 290, 292, 294
- MB-OFDMPHY layer, 254
- MBS scheme, 356
- MBS + EWMA scheme, 358, 360
- MCPS SAP, 416–417
- McstID, 219
- MCTA, 193, 202–204, 220, 242–243
- MDMS, 167
- Mean value, 309, 404, 407

- Medium access control (MAC), 3–16, 18, 20, 22, 24, 43, 54–55, 70–72, 75, 81, 83, 87, 91–92, 95–96, 98–101, 107–110, 112, 114, 116, 118, 120, 122–124, 126–128, 130, 132, 134, 136, 138–139, 144–145, 147, 153, 156–157, 164, 167–168, 192–195, 197, 199, 210, 216–218, 226–227, 231, 234–236, 239–252, 254, 257, 321–324, 326–330, 332–347, 349–350, 356–361, 363, 365, 367, 369, 373–374, 376, 382–383, 386, 390–395, 399–400, 409–410, 415–417, 419, 426, 429, 436–441, 444–446, 448–449, 451–454, 464, 466, 468, 475–490, 492–497, 499–500, 502, 504, 507–508, 512, 522, 524, 586–588, 591, 595, 598, 609
- Medium access control layer, 400, 410
- Membership updates, 228–229
- Mesh access points (MAPs), 484, 507, 555–557, 559, 561–564, 569–570, 573, 578, 594
- MESH-DATA, 416, 418, 430
- Mesh data service, 417
- Mesh gateway, 517, 555–556, 562
- Mesh layer payload, 419–420
- Mesh management service, 417
- Mesh routers, 516–521, 540, 547
- Mesh sublayer frame formats, 418–419
- MeshMaxProbeInterval, 429
- MeshTTLOfHello, 423–425, 427, 429
- Message block, 234
- META, 49, 156–157, 159, 165, 183
- Metropolitan area network (MAN), 475, 477–478, 513, 555–556, 558, 579, 585–586, 590
- Metropolitan-area WMN, 555, 563, 581
- MFR, 327–329, 333–334, 337–340
- M/G/1/K queuing model, 401
- MHR, 327–329, 333–334, 337–346
- MHSME, 416–418
- MHSME SAP, 416–418
- MI, 77, 91, 134, 290
- MIB, 109, 491–492
- Micropayment, 567
- MIFS, 199, 206, 208
- Minimum meansquare error, 266
- MinCAPLength, 364
- Ministry of Internal Communications (MIC), 16
- MLME, 210, 226–229, 327, 416, 444–447
- (MLME)-SCAN, 210, 226–229, 327, 416, 444–447
- MLMESTART, 211
- MMaxLostBeacon, 202, 204–205
- MMCTAAssocPeriod, 203
- MMSE, 266
- Mobile user (MU), 28, 557–559, 562–564, 566–576, 581, 585, 587, 590
- Modified CCB algorithm, 292
- Moment-generating function, 404
- Monte Carlo simulation, 173, 182, 280, 291
- Most significant bit (MSB), 113, 117, 122, 356, 358
- Moving Pictures Experts Group (MPEG), 82, 242
- MPDU, 7–11, 96, 147, 327–329
- MPIB, 383
- M/M/c AUI queuing model, 242
- MR, 435
- MRC, 264, 267
- MRR, 499, 501, 512
- MSC, 131
- MSDU, 8–12, 14–15, 242, 327–329, 333, 489
- MSE, 142, 158
- MSI, 56–58, 302–305, 307–315
- MSI-based scheme, 303, 309, 311–313
- MSR, 499–502, 512
- MT, 82, 86–87, 243
- MTR, 437
- MTS, 194
- MTT, 437–438
- MTU, 129, 132
- Multiagent system (MAS), 27, 29, 48–49, 51, 53, 55, 57–59, 61
- Multiband orthogonal frequency division multiplexing, 240, 299
- Multicast, 241, 415, 419–420, 429–438, 482, 484, 504, 506, 591–592
- Multicast polling, 504, 506
- Multicast routing, 415, 420, 429
- Multicluster sensor network, 389
- Multidomain WLAN, 30–33, 35, 41
- Multihop, 65, 72–78, 244, 246, 251–253, 257, 315, 350, 374, 439, 443–445, 452, 464, 469, 471, 515–517, 521–524, 556, 569
- Multihop ad hoc/sensor networks, 521
- Multihop diversity, 522
- Multihop relay networking, 522
- Multihop wireless communication, 516
- Multi-input multi-output (MIMO), 16, 23–24, 588
- Multiple access time division multiple access (DAMA-TDMA), 589
- Multiple Bluetooth piconets, 151, 154, 156, 169, 179, 182
- Multiple-input multiple-output (MIMO), 16, 23–24, 588
- Multirate support, 192, 250

- Multiuser diversity, 520, 526
- Multi-WISP wireless MAN, 558
- Musical instrument digital interface (MIDI), 108
- Mutual interference, 136, 154

- Nakagami-m channel model, 525
- Nash equilibrium, 67, 71–72, 75, 78, 523
- NB, 265–266, 330–332, 375
- NBT, 441, 446–448, 454–459, 464–470
- NC, 268, 277–278, 360–361, 408–409, 429–438
- Neighbor list, 375, 424–425, 428–429
- Neighbor MAPs (nMAPs), 559, 567–570, 573
- Network allocation vector (NAV), 9–10, 12, 91
- Network capacity, 78, 82–83, 85, 87–88, 91, 93, 95, 97, 99–100, 147, 314
- Network lifetime, 390, 406
- Network Protocol Stack, 588
- Network topology, 138, 322, 325, 361, 366, 376, 379, 381, 390, 420, 423, 524, 587
- New key SECID selection, 230
- NLOS, 494, 512, 586, 589
- No-ACK, 194, 206, 208–209, 243, 252
- Node sleep control, 389
- No-FEC, 494
- Noise power, 159, 169
- Nonce field, 231
- Non-beacon-enabled mode, 353, 441
- Noncollaborative coexistence mechanism, 135, 140
- Non-GM, 430, 432–434, 436, 438
- Non-line-of-sight communication, 515, 537
- Non-PNC DEV, 197
- Non-QoS, 497
- Non-Real-Time Polling Service (nrtPS), 498, 501, 508, 512, 592, 594–599, 601–609
- Non-real-time variable-bit-rate service, 482
- NrtPS, 498, 501, 508, 512, 592, 594–599, 601–609

- OBT, 40, 467
- OFDM, 4, 16–17, 20–23, 240, 248, 261–272, 274, 276–280, 282–284, 286, 288–290, 292–295, 299–300, 515, 522–523, 526, 586, 588–589
- OFDM bit loading, 262, 272, 288
- OFDMA-based wireless infrastructure, 516, 519
- OFDM-based UWB systems, 267
- OFDM-based UWB transmission, 271
- OffTR, 430–438
- OGS, 467–468
- OLA, 155, 164–165, 167, 183

- OLP, 467
- OLPA, 467
- OLPAS, 467–468
- ONBT, 467
- OnTR, 430–437
- Open systems interconnection (OSI), 109–110
- OPNET, 72, 510
- Optimal Subchannel Allocation, 527–528, 540, 550
- Optimized resource reservation, 543–544
- Orthogonal frequency division multiplexing (OFDM), 4, 16–17, 20–23, 240, 248, 261–272, 274, 276–280, 282–284, 286, 288–290, 292–295, 299–300, 515, 522–523, 526, 586, 588–589
- Outage BER, 274, 276–278, 283–286
- Outage rate, 277, 282, 287, 291–293
- Overcharge attack, 559, 573–574
- Overcharge Attack, 559, 573–574
- Overgrazing, 69
- Overhead, 15, 24, 33, 43, 66–67, 74, 82–83, 85–87, 92–93, 95–100, 128, 162, 168, 242–243, 251, 253, 255, 258, 282, 291, 300, 302, 305–306, 309–311, 316, 321, 350, 358, 380–381, 386, 389, 404, 426, 438, 441, 448–450, 453–454, 456, 458–460, 464, 467, 471, 499–502, 527, 561, 580–581

- Packet CS, 481–482
- Packet scheduling, 140, 148–149, 155
- Pairwise error probability, 274–276
- Pairwise master key (PMK), 568, 570–572, 574, 578
- PAN, 3, 27, 65, 81, 107, 135, 151, 189, 217, 239, 261, 299–305, 309, 312–313, 321–322, 324–325, 327, 329–331, 334–339, 341–346, 349, 355, 357, 361–365, 373, 383, 385, 389, 391, 393–395, 397, 415, 417–419, 436, 439, 443–444, 447, 475, 477, 497, 515, 555, 585
- Parameterized QoS, 498
- Pareto distribution, 43–44
- Pareto optimality, 531–532, 541–542
- Partially Blind Signature, 558–560
- Partially blind signature-based e-cash, 558
- Payload, 85–87, 96–98, 110–111, 113–115, 124, 126, 129, 131, 147, 149, 190, 193–194, 196, 228, 232–233, 246, 251–257, 264, 300, 323, 327–329, 333–334, 336–341, 396, 417–420, 446, 449, 481, 483–484, 486–490, 499, 588
- Payload protection, 190, 193, 228, 232–233
- Payload protection key, 190, 232–233
- Payload size threshold, 253
- Payment-Based Mechanisms, 66

- Payments deposit, 573
- PC, 4–5, 11–12, 108, 189–191, 325, 539
- PCF interframe space (PIFS), 11–12, 15
- PCM, 123, 126
- PDAs, 107–108, 217
- PDU, 124–125, 481, 483, 486–487, 489, 499–500, 512, 525–528, 532–539, 541, 547–548, 550
- PDU Dropping Probability, 526–527, 532–533, 535, 537–539, 547, 550
- Peer discovery, 192, 240, 244–250, 257
- Peer to peer, 193, 198, 322, 327
- Peer-to-peer connection, 189, 198, 230–231, 244, 249, 305
- Peer-to-peer management key, 230–231
- Peer-to-peer network, 229, 325
- PEP, 274, 276, 278–279
- Per-flow buffering approach, 518
- Per-flow queuing approach, 518
- Per-packet authorization, 144
- Personal computers, 107, 217
- Personal operating space (POS), 107–110, 113, 439
- PHS, 481, 483–485
- PHSF, 484–485
- PHSI, 483–485
- PHSM, 484
- PHSS, 484–485
- PHSV, 484
- PHY layer, 8, 108, 134, 136, 138, 240, 244, 250–252, 254, 257, 321, 323, 327–330, 334, 347, 416, 476–480, 483, 490–495, 588–589
- PHY layer convergence procedure (PLCP), 8, 16, 139, 144
- PHY/MAC headers, 251
- Physical (PHY) 3–6, 8–10, 12, 14–24, 30, 33, 43, 49–50, 81–82, 87, 100, 107–108, 110–112, 114, 116, 118, 120, 122, 124, 126, 128, 130, 132, 134, 136, 138–144, 151, 153, 157–160, 165, 183, 193, 197, 200, 203, 205, 211, 222, 226, 240, 244, 248, 250–252, 257, 261, 321–324, 326–330, 332, 334, 336, 338, 340, 342, 344, 346–347, 349, 358, 373, 380, 395, 410, 415–416, 439, 475–480, 482–484, 486, 488, 490–496, 499, 508, 522, 524, 558, 586–589, 609
- Physical (PHY) layer, 3, 8, 16, 43, 81, 108, 110, 134, 136, 138–139, 144, 193, 200, 203, 205, 211, 226, 240, 244, 248, 250–252, 257, 321, 323, 327–330, 334, 347, 349, 358, 373, 395, 415–416, 475–480, 483–484, 490–496, 586–589, 609
- Physical layer, 3–4, 6, 8–10, 12, 14, 16–24, 107–108, 110–112, 114, 116, 118, 120, 122, 124, 126, 128, 130, 132, 136, 140, 157, 159–160, 261, 321–324, 326, 328, 330, 332, 334, 336, 338, 340, 342, 344, 346, 410, 439, 475–476, 478, 480, 482, 484, 486, 488, 490, 492, 494, 508, 522, 524, 588
- Physical medium dependent (PMD), 16
- Physical medium-dependent sublayer, 588
- Physical synchronization signal, 143
- PIB, 335, 444–446
- Piconet, 40, 44, 54, 109, 111, 113–116, 120–121, 123, 125, 137–138, 147–149, 152–154, 156, 160–161, 163, 169–173, 175–176, 179–182, 189–198, 200–222, 224, 226–233, 236, 240–241, 243–252, 254–255, 257–258
- Piconet controller, 189, 217
- Piconet coordinator, 241
- Piconet coverage ratio, 249
- Piconet group data key, 227–232
- PICONET OPERATION, 189–190, 192, 194, 196, 198, 200, 202, 204, 206, 208–216, 231
- Piconet service, 229
- Piconet synchronized power save, 219
- Piggyback request, 499, 502, 504
- PKC-LA, 574–578
- PKI, 557, 559, 562, 581
- PKI architecture, 562
- PM, 93, 97–98, 120, 123, 176, 178–179, 213, 217, 219–221, 223–224, 230, 505
- PM CTRq, 213, 224
- PM mode change, 220–221, 223, 230
- PMP, 489, 494, 512
- PN, 19, 159
- PNC, 189–225, 227–231, 241–249, 251–257, 443, 447
- PNC DEVID, 197
- PNC-DEV management entity, 227, 230–231
- PNC handover, 197–198, 212–213, 218, 228, 230
- PNC handover information, 212, 230
- PNC handover response, 212–213, 230
- PNC information commands, 230, 248
- PNC information request, 209, 212, 230, 245–247
- PNC-capable DEV, 211, 214
- PNC-DEV management key, 227, 230–231
- PNCID, 202–203, 208, 229
- PNID, 213
- Poaching, 69
- Point coordination function (PCF), 4, 9, 11–12, 136

- Point-to-multipoint, 20, 125, 153, 480, 489, 493, 504, 515, 586
- Point-to-point, 20, 111, 125, 153, 482
- Poisson, 177, 309, 366, 402, 534, 536
- Poisson process, 309, 402, 536
- Poisson stream, 366
- Polling, 4, 12, 15, 116, 120, 137, 352, 482, 500–502, 504–506, 512, 590, 592
- Poll-me bit, 592
- POS, 107–110, 113
- Power control, 30, 55, 125, 133, 155–156, 165–167, 183, 243, 302
- Power management, 75, 121, 192, 195, 198, 209, 217–226, 228, 230, 232, 234, 390–391
- Power save, 202, 219–220, 241
- Power-saving (PS), 5, 24, 85, 170–173, 178, 202, 204, 212, 219–224, 226, 230, 236, 439–442, 444–454, 456, 458, 460, 462, 464–466, 468, 470–471
- Power-saving algorithms, 439–440, 442, 444, 446–452, 454, 456, 458, 460, 462, 464, 466, 468, 470–471
- PPDU, 327–329
- PPM, 116, 134, 301
- PPP, 482
- Predictive authentication, 557
- Preencryption data, 233
- Prekey distributions, 557
- Primary collision, 373–376, 386
- Prioritized QoS, 498
- PRNG, 200, 204
- Probability density function (PDF), 268–269, 272, 282, 402–403, 576
- Probability distribution, 51, 55, 350, 352, 392, 402–404, 407
- Probability distribution function, 402–403
- Probability generating function, 402
- Probe request, 209, 229–230, 245, 247–248
- Probe response, 229–230, 245, 247–248
- Protocol, 4–5, 7–9, 11–13, 15, 20, 22, 24, 33, 57, 69–72, 74, 76, 81–83, 87, 89, 91, 93, 95–98, 100, 108, 110, 115, 118, 124–132, 146–147, 153, 160–161, 163, 168, 189, 191–192, 194, 218, 239, 241, 243–245, 247, 249, 252, 254, 300, 322, 327–328, 365, 370, 382, 392–394, 397, 410, 417–418, 429–430, 433, 438–439, 441, 443–445, 448, 451, 476–477, 479–482, 485–487, 489, 492–495, 500, 504, 507–508, 512–513, 522, 524, 556–557, 565–567, 570, 575, 586, 588, 591–592, 600
- Protocol data units (PDUs), 96, 124, 147, 417, 481, 483, 486, 493, 504, 508, 524–525, 532–537, 539, 541, 543, 545, 548
- Protocol Version Field, 194
- PS, 5, 85, 170–173, 178, 202, 204, 212, 219–224, 226, 230, 236
- PS set information request, 222–223, 230
- Pseudocode, 277, 279–280, 420, 426–428
- Pseudorandom hopping scheme, 111
- Pseudorandom noise (PN), 19, 159
- PSM, 132
- PSTN, 477, 479, 492–493, 496
- PT, 57, 164–165
- PTA, 136, 139–140, 144–145, 149
- Pth, 253
- Public key, 393, 557, 560, 562–563, 566–567, 570–571, 574–578, 580–581
- Public key infrastructure (PKI), 557, 559, 562, 581
- Public key certificate, 557, 563, 567, 570, 574
- Pulse-based TH-UWB wireless PAN, 300
- Pulse-based UWB wireless PANs, 300
- PVC, 488
- QAM, 20, 22, 289, 491, 588–589
- QCT, 176
- QoS, 4, 9, 11–12, 15, 24, 71, 76, 81, 100–101, 125–127, 131–132, 149, 192–193, 201–202, 239–242, 257, 299, 303, 306, 312, 349, 476, 479–483, 490, 494, 496–502, 504–512, 515, 518–523, 525–527, 530, 533, 535, 547–548, 550, 586, 590–591, 593–595, 597–599, 605, 609–610
- QoS architectural component, 593–594
- QoS guarantees, 240–241, 257, 598–599, 605, 610
- QoS management framework, 522
- QoS scheduling architecture, 593, 609
- QoS signaling mechanism, 591
- QoS-supporting basic service set (QBSS), 12–13, 15
- QPSK, 22, 263, 271–272, 275–276, 289, 292, 323, 350, 395, 491, 524, 588
- Quadrature phase shift keying (QPSK), 21–22, 263, 271–272, 275–276, 289, 292, 323, 350, 395, 491, 524, 588
- Quantum, 596–597
- Quaternary phase shift keying, 263
- Queue Throughput, 518, 536
- Queueing analytical model, 516, 532–533, 535
- QUEUEING ANALYTICAL MODEL, 516, 532–533, 535

- Queueing delay, 359–360, 518, 526–527, 532–533, 537–539, 550
- Queueing delay, 55
- RA code, 271, 281, 288, 293
- RA decoder, 288
- RA-ACK, 242, 244
- Radio frequency, 16, 28, 43, 107, 264, 397, 589
- Radio interference, 110–111, 136
- Radio resource management, 24, 27, 29, 31, 516, 519, 522–526, 550
- Radio technology, 107
- RADIUS, 42–43, 139–140, 249, 255–256, 494, 537, 581
- RAND, 123–125
- Rate matrix, 252, 530
- Rate-adaptive acknowledgment, 242
- Rayleigh fading channel, 269, 271, 280–281, 295, 537
- Real-Time Polling Service (rtPS), 498, 501, 508–512, 592, 594–599, 601–609
- Real-time variable bit rate, 588
- ReasonCode, 228
- Receive signal strength indicator, 252
- Receiving code, 301, 304–305
- Reciprocity-Based Mechanisms, 67
- REG-RSP, 485, 492
- Relay Traffic, 517–518
- Remote scan request, 230
- Remote scan response, 230
- Repeat-accumulate codes, 293, 295
- Repeater service, 192, 195
- Request (REQ), 10, 72, 82, 95, 110, 113–114, 120, 125–126, 130–132, 137, 139, 144–146, 157, 192, 195, 197–199, 201–204, 206–216, 220–224, 226, 228–230, 233, 242, 245–248, 254, 303–308, 313, 326–327, 332, 335–336, 341–346, 354–355, 357, 362–365, 374, 386, 391, 397, 399, 416–418, 421, 423, 425–427, 430–431, 434, 436, 444–448, 451, 453, 482–483, 485–490, 494, 497–506, 510, 512, 525, 532, 557, 561–562, 564–565, 571–572, 574–575, 590–598
- Request/Transmission policy, 499–502
- Request-to-send/clear-to-send (RTS/CTS), 10, 82–83, 85, 87, 96, 98–99, 374
- Reservation header (RSH), 91
- Residual interference, 141
- Resource allocation, 31, 33–37, 49, 55, 58, 299–300, 302–308, 310, 312, 314, 316–317, 517–518, 520, 522–523, 525, 528
- Resource management, 24, 27–61, 101, 516, 519, 522–526, 550
- Resource Reservation Threshold, 529, 540, 544, 547
- Response (RSP), 8, 11, 13, 113, 115–119, 121, 124–126, 130–132, 146, 152, 161, 207, 209, 212–213, 222–223, 229–231, 233, 245–248, 254, 264–268, 341–343, 354–355, 417, 444, 453, 485–486, 492, 498–499, 509, 512, 590
- Retransmission interframe space, 248
- RFD, 322, 341–342, 345, 350
- RIFS, 199, 248
- RM, 10, 130, 145–146, 157, 192, 223, 252–254, 263, 286, 394, 416–417, 444, 500
- RNG-RSP, 485, 492
- Roaming broker (RB), 528, 557, 559, 561–563, 570, 572–574, 578–582
- Robust security network (RSN), 8
- Route request, 246
- Route response, 246
- Route selection, 519, 521, 525–527, 529, 531–532, 547–548
- RREP, 246
- RREQ, 246, 248
- RREQ broadcasting, 248
- RRES, 246
- RSA signature, 561
- RSA-UAB, 574, 576–579, 581
- RSSI, 125, 133, 140, 148, 166, 252
- RtPS, 498, 501, 508–512, 592, 594–599, 601–609
- RTS, 10–11, 82–83, 85, 87, 89, 91, 96, 98–100, 374, 451–453, 463, 465–466
- RX, 453, 476, 479, 494
- SA, 417, 563
- SAP, 416–418, 444, 480–481, 483, 490, 512
- SAS-UAB, 574, 576–581
- Scalability, 29, 48, 494, 518, 557, 559
- Scatternet, 109, 120, 159–160
- SCO, 108, 111–113, 115, 117–120, 126–128, 137–140, 143–149, 153, 157–158, 164
- SCT, 156, 167, 169–170, 173–176, 179–183
- SCTA, 251, 253–254, 257
- SDU, 481, 483–484, 489, 493, 500, 503
- SEC, 194–195, 211, 213, 218, 227–228
- SECID, 194, 228–230, 233
- Secondary collision, 373–374, 376, 386
- Secure 802.15.3 piconet, 231, 233, 235
- Secure beacon frame, 230
- Secure beacon integrity code generation, 218, 232
- Secure command integrity code generation, 218, 232
- Secure frame counter, 231–233
- Secure frame generation, 228–229

- Secure frame reception, 228, 230
- Secure piconet, 227–228
- Security, 3, 8, 32–33, 71, 74, 115, 123–124, 126, 192–195, 197–198, 213–215, 217–218, 220–222, 224, 226–234, 321, 323–324, 332–333, 335, 339–346, 357, 389–390, 392–393, 416, 419, 478, 494, 496, 556–560, 563, 566–567, 570, 572–574, 581–582, 588, 590
- Security commands, 198, 215
- Security Implementation, 232, 494
- Security information command, 228
- Security mechanisms, 8, 217–218, 226, 323, 390
- Security membership, 217, 226
- Security-enabled transmission, 419
- Sequence (SEQN), 4, 10, 17–19, 40, 54, 91, 95, 99, 110–111, 113, 116–121, 124–125, 130–131, 133, 141, 152–153, 155–156, 159–160, 162–163, 168, 193–194, 209, 212–213, 223, 230–231, 234, 243, 245–248, 299, 327–329, 333–334, 336–340, 395, 410, 419, 437, 439, 443, 449–450, 457, 459–460, 466, 484, 490, 595
- Service coverage extension, 517
- Service set identifier (SSID), 570
- Service-level agreement (SLA), 32, 48, 557
- Service-specific convergence sublayer (CS), 19, 349, 480–483, 487, 499, 588
- Serving MAP (sMAP), 557, 559, 567–570, 575
- Short Digital Signature, 561
- Short interframe space (SIFS), 10–13, 15, 83, 86, 95–96, 98, 143, 199–201, 205–208, 245, 247–248
- Shortest digital signature, 561
- Shortest path algorithms, 251
- Shortest remaining processing time, 242
- Short-term gain, 69
- SIFS, 10–13, 15, 83, 86, 95–96, 98, 143, 199–201, 205–208, 245, 247–248
- SIG, 108, 133, 570–572, 578
- Sigmoid utility function, 529
- Signaling propagation latency, 557
- Signal-to-interference-plus-noise ratio, 301
- Signal-to-noise ratio (SNR), 82, 89–92, 100, 148, 159, 169–170, 173, 176, 179, 183, 273, 281–283, 286, 288–289, 524–525, 527–528, 536–537, 539–540, 542–543, 588
- Simple network management protocol (SNMP), 33, 591
- SKKE, 389–390, 392–394, 397–401, 403, 405
- Slot allocation, 309, 588, 590, 592, 598, 601–603
- Slot pool, 383
- Slot priority, 145–146
- Slow-hopping WLAN devices, 138
- SMAC, 401, 445
- SNAP, 241
- SO, 5, 8–10, 18–21, 28, 30, 34, 42, 51, 55, 66, 69–72, 74, 79, 85, 89, 97–98, 108–111, 121, 128, 135, 137, 140, 143, 145, 147, 156, 160–161, 163–166, 168–169, 171, 191, 197, 202, 211–212, 214, 217, 225, 228, 234, 242–243, 245, 253–254, 258, 281, 302–303, 306–307, 313, 334, 337–338, 353–354, 357, 363–364, 366, 375, 380, 386, 394–396, 406, 410, 418, 423, 425, 429–432, 435, 437, 444, 446, 452, 466, 485, 494, 502, 504, 508, 510–511, 520–521, 524, 526, 528–529, 541, 557–558, 564, 574, 578, 597–600
- SOHO, 480, 495, 587
- SPAs, 251
- Special interest group (SIG), 108, 133, 570–572, 578
- Spectral efficiency, 520–521
- SPS, 202, 220–223, 230
- SPS configuration response, 223, 230
- Src, 248–249
- Src_DEV, 248
- SrcID, 196, 202–203, 208, 213, 219, 231–232
- SRPT, 242
- SS, 17, 401, 479, 482, 484–490, 492–494, 498–502, 504–505, 507–512, 524, 537, 587, 589–595, 598–601, 603, 607, 610
- SS BW Request Generator, 593
- SS Coordinator, 343, 593–594
- SS UL Data Classifier, 593
- SSCS, 416
- ST, 164–165, 401
- STA, 4–5, 39, 154, 156
- Star network topology, 361
- Stand-alone request, 502
- State Space, 534–535
- STC, 489, 494
- Stealing, 69
- Storage consumption, 578–580
- Strategy to Effect Optimal Utilization (EOU), 50–51, 55
- Stravation avoidance mechanism, 356, 361
- Subchannel allocation, 515–516, 518–522, 524–532, 534, 536, 538–544, 546, 548, 550
- Subchannel allocation algorithms, 526, 528, 539
- Subnetwork access protocol, 241
- Subscriber station (SS), 17, 401, 479, 482, 484–490, 492–494, 498–502, 504–505,

- 507–512, 515, 523–524, 537, 587, 589–595, 598–601, 603, 607, 610
- Superframe, 11–12, 192–193, 195, 198–206, 208–209, 213–215, 219–221, 225–227, 229, 231–233, 241–244, 251–252, 323–325, 328, 332, 334, 337–339, 346, 351–357, 362, 364–365, 374, 391, 394–397, 399, 404, 410, 442–444, 446–448
- Superframe order, 338, 353
- Superframe structure, 195, 198–199, 242–243, 323–325, 334, 353–354, 374, 442
- Symmetric cryptography, 226, 231–232
- Symmetric cryptographic operations, 218
- Symmetric encryption, 231
- Symmetric-key security operations, 218, 231
- SYNC, 110, 113, 398, 451–453, 463, 466–467
- Synchronous, 66, 108–109, 111–115, 137, 153, 202, 220, 445, 447, 451, 464, 468, 471
- Synchronous connection-oriented (SCO) communication, 108, 111–113, 115, 117–120, 126–128, 137–140, 143–149, 153, 157–158, 164
- Synchronous power save, 202, 219–220

- Tainting, 69
- Tandem queueing model, 527, 550
- Target beacon transmission time (TBTT), 11–13, 138, 141–142
- TargetID, 224
- Target MAP (tMAP), 559, 569–572, 575
- TBTT, 11–13, 138, 141–142
- TC, 85, 291, 294, 512, 588
- TCM, 494
- TCP/IP, 488, 512
- TCS, 127–128
- TCT, 176
- TDD, 111, 120–121, 152, 476, 485, 490–494, 504, 507, 513, 589–590
- TDLS, 375
- TDM, 36–37, 476, 479, 494, 513
- TDMA, 138, 152, 157, 193–194, 201, 203, 205, 216, 241, 251, 347, 374–376, 386, 490–492, 494, 513, 517, 589
- Temporal unfairness, 98
- TH, 57, 243, 276, 279, 299–301, 351–352, 356–357, 364–365, 447
- The algorithm of Chow, Cioffi, and Bingham, 289
- The heuristic (iterative) algorithm, 288, 350, 406, 526, 528–530, 539–540, 550
- The logical link control, 108–109, 241
- The optimal algorithm, 526, 529, 539–540

- Third-party handshake protocol, 244–245, 247, 249
- Threshold, 43–44, 57, 76, 90–92, 95–97, 99–100, 147, 161, 165, 253, 271, 280–281, 312–313, 365, 397–398, 401, 410, 412, 526–530, 532, 540–544, 547, 559, 582
- Throughput, 15, 18, 20, 22–23, 30, 35–37, 43, 45, 51, 53–55, 67, 70–72, 81–82, 85–90, 92–101, 140, 147, 149, 151, 153–161, 163, 165–167, 170, 173, 175, 179–183, 242–243, 250–251, 255, 282, 299, 310–316, 350, 352, 373–374, 491, 494, 500–501, 511, 517–518, 520, 522, 526–527, 536, 550, 600–609
- Throughput enhancement, 517
- Throughput upper limit (TUL), 86–87
- TH-UWB, 243, 300–301
- TH-UWB wireless PAN, 300–301
- TICER, 445, 448–449
- Time division duplex (TDD), 111–112, 120–121, 152, 476, 485, 490–494, 504, 507, 513, 589–590
- Time division multiple access, 138, 152, 193, 241, 347, 374, 490, 513, 517, 589
- Time hopping, 299
- Timehopping UWB, 243
- Time token, 218, 227, 229–232
- Time unit, 19, 132, 206–208, 254, 353, 394
- Timeout period, 219
- Timer-driven, 429
- Time-sensitive communication, 112
- TL, 143, 426, 429–430, 435, 527–529, 531
- Tolerated jitter, 500–501
- Top-down, 422
- Traffic load, 4, 33–35, 38, 41, 43–44, 51, 55, 82–83, 85, 87, 94–95, 145, 158, 176, 179, 242, 312, 351, 353–354, 356, 358–361, 365, 376, 526, 532, 536, 547–548
- Traffic Source, 518, 534
- Traffic priority, 500–502
- Transition Matrix, 534–535
- Transmission control protocol (TCP), 76, 89, 93, 95, 97, 243–244, 487–488, 512, 600
- Transmission latency, 51, 53–54, 374
- Transmission opportunity (TXOP), 12–15
- Transmission options, 418–419, 430, 437
- Transmission radius, 537
- Transmission Rate Distribution, 533
- Transmission rate matrix, 530
- Transmit power change, 231
- Transmitter control, 192
- Travel incognito, 557
- TrgrtID, 229

- Truncated binary exponential backoff mechanism, 592
- Truncated global positioning system (TGPS) scheduling scheme, 523
- Truncated Poisson, 534, 536
- Trusted central authority (TCA), 71
- Trusted third party (TTP), 557–559, 561–564, 566–567
- TST, 375
- TTL, 423–424, 426–427, 429
- TTP, 557–559, 561–564, 566–567
- TU, 254
- Turbo codes, 288–289, 291–295
- Two-hop-relay network, 523
- Two-state Markov traffic model, 44
- TX, 50, 92, 139, 144–146, 198, 453, 476, 479, 490, 493–494
- TxOptions, 418, 426

- UAB, 559, 562–563, 567–568, 572–582
- UAP, 121–123
- UDP, 76, 243, 591, 600
- UGS, 498, 500–501, 508, 510, 513, 592, 594–599, 601–609
- UL, 489, 494, 503–504, 506–509, 513, 589, 591–598, 600, 610
- UL-MAP, 503–504, 506–508, 513, 589, 591–593, 595
- Ultra-wideband, 240, 261, 299
- Ultra-wideband wireless PANs, 299
- UMTS, 6, 513
- Unicast, 374, 377, 415, 420, 426, 429, 431–432, 437–438, 454–455, 457, 484, 501–502, 504–505, 591–593
- Unicast polling, 504–505
- UnitBackoffPeriod, 330, 353, 357, 383, 395
- Universal authentication and billing architecture, 555–556, 558–572, 574, 576, 578, 580
- Unlicensed ultra-wideband, 240
- Unsolicited Grant Service (UGS), 498, 500–501, 508, 510, 513, 592, 594–599, 601–609
- Up-down, 420, 426–427
- Uplink map (UL-MAP), 498, 503–504, 506–508, 513, 589, 591–593, 595
- Uplink subframe structure, 590
- Uplink transmission, 358, 391, 493, 501, 536, 589, 595, 600
- U.S. Federal Communications Commission, 261, 299
- User asynchronous (UA), 114
- User datagram protocol, 76, 243, 591, 600
- User isochronous (UI), 114, 277, 280
- User synchronous (US), 46, 89, 92, 114, 157, 168, 171, 337, 376, 381, 392, 400, 403
- Utilization Modeling and Optimization (UMO), 33, 50–52, 55–56
- UWB CM1 channel, 283–286
- UWB wireless PAN, 299–305, 312–313, 316
- UWB wireless PANs, 299–300, 302, 305, 316
- UWB-based 802.15.3 WPAN, 243
- UWB-based PHY layer, 240

- Value assignment, 60–61
- VBR-MCTA, 243
- VBR stream, 243
- VC, 481
- Vendor-specific commands, 215
- Voice traffic, 112, 143, 164
- Voice over Internet protocol (VoIP), 97, 497, 500–501, 513, 556
- VoIP, 97, 497, 500–501, 513, 556
- V-OLA, 164–165
- Voltage, 392, 410, 439
- Voltage scaling, 439
- VP, 481

- WA, 449–451, 460–462, 466, 468
- Water-filling algorithm, 529
- Wake beacon, 219–226
- Wake beacon interval, 221–226
- Weighted fair priority queuing, 595, 597
- Weighted fair queuing, 595, 597
- WFPQ, 597, 602–603, 605, 609–610
- WFQ, 597–598, 605, 607, 609
- WG, 4, 139, 141–146, 475, 477, 496
- Whitewashing action, 67
- WiFi, 8, 68, 239, 374, 385, 477, 494–495, 585–587
- WiFi HotSpot interconnection, 586
- WiMAX, 477, 496–500, 502–513, 515–516, 522–524, 526–527, 556, 562, 585–588, 590, 592, 594–596, 598, 600, 602, 604, 606, 608
- WiMAX Forum, 477, 496, 586, 590
- WiMAX Forum Network Working Group (NWG), 590
- WiMedia Alliance, , 261
- Wired equivalent privacy (WEP), 8
- Wireless ad hoc and sensor network, 393
- Wireless connectivity, 108, 239, 349
- Wireless Internet service providers (WISPs), 70–71, 556–559, 561–563, 570, 574
- Wireless local area network (WLAN), 3–4, 17, 20, 27–37, 39, 41–45, 47–57, 59, 65, 68–72, 77, 81–82, 109–110, 135–144, 149, 151–159,

- 161, 163–169, 179, 181–183, 239, 299, 439–440, 477, 523, 585
- Wireless MAN, 3, 27, 65, 81, 107, 135, 151, 189, 217, 239, 261, 299, 321, 349, 373, 389, 415, 439, 473, 475, 497, 515, 555–558, 560, 562, 564, 566, 568, 570, 572, 574, 576, 578–582, 585–586
- Wireless MAN-OFDM, 515
- Wireless mesh topology, 373, 415
- Wireless media system (WMS), 522
- Wireless mesh networks (WMNs), 515–516, 519, 522, 550, 555
- Wireless metropolitan-area networks, 555
- Wireless networks, 4, 6, 8, 28, 30, 65–79, 83, 91, 136, 138, 151, 153, 191, 217, 376, 439, 493, 523–524, 556
- Wireless PAN, 3, 27, 65, 81, 107, 135, 151, 187, 189, 217–218, 220, 222, 224, 226, 228, 230, 232, 234, 239, 261, 299–305, 309, 312–313, 316, 319, 321, 349, 373, 389, 395, 415, 439, 475, 497, 515, 555, 585
- Wireless PANs, 3, 27, 65, 81, 107, 135, 151, 189–236, 239, 261, 299–317, 321, 349, 389, 415, 439, 475, 497, 515, 555, 585
- Wireless personal area networks (WPANs), 27–29, 31, 35–36, 38–39, 42, 44–46, 48, 50, 107–109, 111, 134–135, 139, 141–146, 189, 217, 236, 239–240, 243–244, 250, 261, 299, 321, 349–350, 352, 354, 356, 358, 360–362, 364, 366, 368
- Wireless sensor networks, 29, 321, 349, 386, 389, 393, 415, 439–440, 442, 444, 446, 448, 450, 452, 454, 456, 458, 460, 462, 464, 466, 468, 470
- Wireless USB, 261
- WirelessMAN, 478, 513, 515
- WiseMAC, 445
- WLAN, 3–4, 17, 20, 27–37, 39, 41–45, 47–57, 59, 65, 68–72, 77, 81–82, 109–110, 135–144, 149, 151–159, 161, 163–169, 179, 181–183, 239, 439–440, 477, 523
- WLAN TBTT, 141–142
- WLL, 475, 479
- WMAN, 476–478, 495–496
- WPAN, 28–29, 31, 33, 35–36, 38–39, 41, 43–48, 50, 107–111, 135–144, 151, 158, 189, 191–192, 199, 207, 216–218, 227, 231, 233, 236, 240–241, 244, 252, 257–258, 321, 349–350, 352, 362, 364, 366, 389, 395, 415–416, 418, 420, 422, 424, 426, 428, 430, 432, 434, 436, 477
- WPAN MAC, 199
- WPAN mesh network, 415–416, 418, 420, 422, 424, 426, 428, 430, 432, 434, 436
- WPANs, 27–29, 31, 35–36, 38–39, 42, 44–46, 48, 50, 107–109, 111, 134, 189, 217, 236, 239–240, 243–244, 250, 261, 321, 349, 361
- WPAN SCO link, 139–140
- WR, 448–451, 457, 459–462, 466, 532, 541
- XMAC, 445
- XOR, 122–123, 231, 263
- ZigBee, 347, 373, 389, 392–393, 443
- ZigBee Alliance, 393
- ZigBee protocol, 392
- ZP, 264–265, 563

