

Index

- 3GPP, 27, 58, 61, 81, 82, 83, 89
- 802.11i, 27, 234
- 802.1X, 235, 236, 237, 238

- Abort-Session-Request/Answer, 75, 77
- Access-Accept, 28, 29, 30, 31, 33, 34, 35, 37, 39, 40, 41, 42, 45, 46, 47, 48, 49, 50, 51, 52, 55, 77, 230, 231, 233, 237, 238
- Access-Challenge, 29, 30, 31, 34, 35, 38, 41, 45, 46, 77
- Access Controller (AC), 177, 178, 179, 180, 181, 182, 183, 184, 185, 186
- Access-List (ACL), 236, 237
- Access Network, 214
- Access Point (AP), 176, 177, 181, 182
- Access-Reject, 28, 29, 30, 31, 34, 35, 36, 45, 46, 47, 51, 77)
- Access-Request, 28, 29, 30, 31, 34, 35, 36, 38, 39, 46, 50, 51, 55, 77, 230, 233
- Access-Resource and Admission Control Function (A-RACF), 86, 87, 88, 89
- Accounting-Auth-Method, 78
- Accounting-Input-Octets, 78
- Accounting-Input-Packets, 78
- Accounting-Off, 31, 38
- Accounting-On, 31, 38
- Accounting-Output-Octets, 78
- Accounting-Output-Packets, 78
- Accounting-Realtime-Required, 76
- Accounting-Record-Type, 76, 78
- Accounting-Request (RADIUS), 29, 30, 31, 38, 47, 48, 50, 51, 52, 53, 55, 231
- Accounting-Request/Answer (Diameter), 68, 75, 77
- Accounting-Response (RADIUS), 29, 31, 35, 47
- Accounting start, 31, 38, 47, 48, 50

- Accounting stop, 31, 47, 48, 50
- Acct-Interim-Interval, 48
- Acct-Multi-Session-Id, 48
- Acct-NAS-Traffic-Rule, 54
- Acct-Session-Id, 49
- Acct-Status-Type, 31, 47, 48, 57
- Acct-Termination-Cause, 48
- Application function (AF), 85, 86, 87, 89
- Application identifier, 72
- Application server (AS), 85
- Audit events, 117
- Authentication methods, 108
- Automation, 15
- Autonomous WLAN architecture, 178

- Bandwidth-Profile-Id, 55
- Basic Service Set (BSS), 177
- BEEP, 106, 108, 109, 114, 153
- BGP, 4, 9, 211
- Border Gateway Function (BGF), 83, 86, 87, 88, 89

- Callback-Number, 40
- Call session control function (CSCF), 85
- Candidate datastore, 118, 144, 171
- Capabilities-Exchange-Request/Answer, 74
- Capability, 116, 118, 162
- Captive portal, 227, 228, 230, 232, 233
- Centralized WLAN architecture, 178
- Change-of-Authorization, 41, 49, 52
- CHAP-Algorithm, 77
- CHAP-Auth, 77
- CHAP-Ident, 77
- CHAP-Password, 32
- CHAP-Response, 77
- Chillispot, 228

- CIM, 106
- Cisco-AVPair, 233, 237
- Cisco-SSG-Account-Info, 233, 234
- Cisco-SSG-Command-Code, 234
- Cisco-SSG-Control-Info, 234
- Cisco-SSG-Service-Info, 233, 234
- Class, 23, 103, 220
- Client-Type, 92, 204
- C-Num, 95
- CoA, 49, 55
- CoA-ACK, 49, 50
- CoA-NAK, 49, 51
- Command code, 72
- Command flags, 71
- Configuration data, 117
- Configuration events, 117
- Containment node, 130
- Content layer, 115
- Content match node, 130
- COPS, 91, 106
 - messages, 95, 97
- COPS-PR, 101
- Core IMS, 85
- Credit control, 38, 48, 49, 55, 58, 67, 81, 82
- Credit-Control-Request/Answer, 82
- CTP, 182

- Datastores, 118
- DEN, 106
- Destination-Host, 68, 69
- Destination-Realm, 66, 68, 69, 70
- Device-Watchdog-Request/Answer, 74
- Diameter agent, 66, 74, 75
- Diameter client, 65, 66, 68, 69, 70, 72
- Diameter connection, 67
- Diameter proxy agent, 66
- Diameter redirect agent, 67
- Diameter relay agent, 66
- Diameter server, 65, 66, 68, 69, 70, 75, 76, 89
- Diameter session, 67
- Diameter translation agent, 67, 72
- DiffServ, 190, 192
- Disconnect-ACK, 49
- Disconnect-NAK, 49
- Disconnect-Peer-Request/Answer, 74
- Disconnect-Request, 49, 23
- Disconnect-Response, 233
- Distance vector, 6, 7
- Distributed WLAN architecture, 178
- Distribution System (DS), 177

- DSCP, 190
- DTLS, 183, 184, 185

- EAP, 28, 31, 44, 45, 46, 47, 57
- EAP Failure, 45, 47
- EAP-Message, 44, 45, 46
- EAPoL, 28, 237
- EAP Request, 45, 46
- EAP Response, 45, 46
- EAP Success, 45, 46
- EGP, 5
- Egress-Bandwidth, 55
- Egress-VLANID, 52
- End-to-End Identifier, 72
- Enterprise code, 33, 42, 43
- EPD, 102
- ETSI/TISPAN, 61, 81, 82, 83, 85, 89
- EVENT Record, 76
- Extended Service Set (ESS), 177
- Extensible Markup Language, 110

- Fault events, 117
- FIB, 4, 201
- Filter, 129, 130, 135, 152, 165
- Filter-Id, 33, 40, 41, 42, 43, 44, 52, 53, 54, 55, 80, 237
- Felting, 129
- Framed-Compression, 40
- Framed-IP-Address, 33, 39, 40, 49
- Framed-IP-Netmask, 33, 40
- Framed-MTU, 40
- Framed-Protocol, 39
- Framed-Route, 40
- Framed-Routing, 40

- Heartbeat events, 117
- Hop-by-Hop Identifier, 72
- HTML, 111

- Idle-Timeout, 40
- IETF, 106, 107, 115
- IGP, 4, 5
- IMS, 58, 59, 61, 82, 83, 85, 86
- Ingress-Bandwidth, 54
- Ingress-Filters, 52
- Inheritance, 220
- interface e4, 88
- interface Gq, 89, 90
- interface Ia, 89
- interface Ra, 89

- interface Re, 89
- interface Rq, 89
- Interim accounting update, 47
- INTERIM records, 76
- Interim-Update, 31, 37, 38, 48
- Internet Architecture Board, 106
- IP, 3, 199, 211
 - filter rule, 52
 - sphere forum, 242
- Keep-alive, 36
- Label, 11
- LDAP, 214
- Link state, 6, 7
- Local MAC, 178, 179, 180, 181, 183
- LPDP, 92, 201
- LWAPP, 176, 182, 183
- Maintenance events, 117
- Managed device, 105, 114, 115, 116
- Managed entity, 114
- Management application, 114, 116, 117
- Message length, 71
- Message types, 30
- Message-Authenticator, 45, 46
- Metric, 4, 205
 - events, 117
- MIB, 106
- MOBILEIP, 62
- Model, 215
- MPLS, 10, 105, 199, 211
- Namespace, 111
 - selection, 130
- NAS-Filter-Rule (Diameter), 77, 78, 79, 81
- NAS-Filter-Rule (RADIUS), 52, 53, 54
- NAS-IP-Address, 32
- NAS-Port, 32
- NASREQ, 61, 62, 67, 69, 76, 77, 78, 81, 82, 90
- NAS-Traffic-Rule, 54
- Negative response, 135
- NETCONF, 105, 106
 - client, 105
 - data, 117
 - device, 163
- NETMOD, 116, 173
- Network, 4, 214
 - providers, 106
- Network access identifier, 32, 56, 57
- Network Address Identifier (NAI), 63, 69
- Network attachment subsystem (NASS), 83, 85, 86, 88
- NGN, 61, 82, 83, 85, 89
- Notification, 108, 117, 135, 149
- One way RPC, 120
- Operations and Management Area, 106
- Operations Layer, 115
- Origin-State-Id, 76
- Outsourcing mode, 100
- PCEP, 94
- PDP, 22, 92, 101, 201
- Peer table, 68
- PEP, 23, 92, 101, 201
- PIB, 106, 23, 206
- Policy, 14, 19, 193, 199, 213
- Port-Limit, 40
- Positive response, 135
- PRC, 23, 103
- PRI, 23, 103
- PRID, 23, 203
- Provider network, 214
- Provisioning mode, 101
- Proxy CSCF (P-CSCF), 85, 86, 89
- Pull Mode, 49, 50
- Push Mode, 49
- QoS, 189
- QoS-Filter-Rule, 77, 78, 79, 80, 81
- RADIUS authenticator field, 29, 30, 31, 32, 44, 45, 46, 49
- RADIUS client, 28, 31, 32, 33, 35, 36, 37, 38, 39, 41, 45, 46, 47, 49, 50, 51, 56
- RADIUS exchanges, 34
- RADIUS identifier field, 29, 31, 36
- RADIUS length field, 29, 34
- RADIUS message code field, 29, 31, 33, 34
- RADIUS Retransmission Rules, 36
- RADIUS server, 27, 30, 34, 35, 36, 37, 38, 39, 41, 42, 45, 46, 47, 50, 51, 52, 56, 57
- RAP, 107
- Realm-based routing table, 68
- Re-Auth-Request/Answer, 75, 77, 81
- Remote MAC, 178, 179
- Reply-message, 41
- REQ, 97, 202

- Resource and admission control subsystem (RACS), 84, 85, 86, 87, 88, 89
- Resource Control Enforcement Function (RCEF), 86, 87, 88, 89
- Retrieval mechanisms, 107
- RIB, 4, 201
- RFC, 106
- ROAMOPS, 62
- Rollback capability, 108
- Router, 3
- RPC, 115
 - layer, 115
- RPT, 97, 203
- Rule, 19, 197, 214
- Running datastore, 118

- Selection node, 130
- Self-Organizing Networks, 248
- Service, 14
 - providers, 106
- Service-based Policy Decision Function (SPDF), 86, 87, 88, 89
- Service selection gateway (SSG), 228, 229, 230, 231, 232, 233, 234
- Service-Type, 39, 50, 51, 57
- Session, 116, 118, 142
- Session initiation protocol (SIP), 67, 82, 85, 86
- Session-Termination-Request/Answer, 75, 77
- SLAPP, 182, 183
- SLS, 192, 196, 213
- S-Num, 102
- SOA, 242
- SOAP, 109
- SON, 248
- Split MAC, 178, 179, 180, 181, 183
- SSH, 109
- SSS, 242
- START record, 76
- Startup datastore, 118
- State data, 117
- STOP record, 76
- S-Type, 102
- Subscriber edge services manager (SESM), 228, 229, 230, 231, 232, 233, 234
- Subtree filtering, 129

- TEQUILA, 196
- Termination-Action, 40
- Traffic engineering, 191, 199
- Transfer functions, 83
- Transport layer, 114
- Tunneling, 78
- Two way RPC, 120

- URN, 118
- User-Name, 32, 49
- User-Password, 32
- User-Priority-Table, 52

- Vendor-Specific Attribute (VSA), 32, 33, 35, 40, 41, 42, 43, 52, 54, 56, 80
- Version field, 71
- VLAN-Name, 52
- VoIP, 105
- VPN, 105

- WICOP, 182
- Wi-Fi, 175, 182, 227, 228, 233, 234, 235, 238
- Wireless Termination Point (WTP), 177, 178, 179, 180, 181, 182, 183, 184, 185, 186
- WLAN, 175, 176, 177, 178, 179, 180, 181, 182, 183, 186
- WPA/WPA2, 234, 238

- XML attributes, 110
- XML comment, 111
- XMLCONF, 108
- XML document, 110
- XML tag, 110

- <close-session>, 116, 135, 142
- <commit>, 135, 148, 149, 167
- <copy-config>, 115, 131, 138
- <delete-config>, 115, 131, 137
- <discard-changes>, 135, 149
- <edit-config>, 131, 139, 140
- <get>, 115, 117, 131
- <get-config>, 117, 135, 136
- <kill-session>, 116, 135, 143
- <lock>, 131, 144, 145
- <notification>, 135, 150, 171
- <ok>, 123, 124, 125
- <rpc>, 115
- <rpc-error>, 122, 124
- <rpc-reply>, 115, 122
- <subscribe-notification>, 135, 171
- <unlock>, 135, 145
- <validate>, 135, 146, 164