
INDEX

KEY: *T* refers to tables. *F* refers to figures.

A

Abbreviations, 476–478

Activity, coefficient:

definition, 24

rules, 451–452

tables, 453–455

Aircraft:

aluminum alloys in, 395

Boeing 777, 395

fretting corrosion, 182

hot corrosion, 229–230

microbiologically influenced corrosion,
388–389

stress-corrosion cracking, 395

titanium, 425

Aluminum, **383–398**

anodic protection,

anodizing, 287–288, 296

atmospheric corrosion, 194*T*, 383, 391

cathodic protection of, 252, 260, 261, 384,
395

chlorinated solvents, corrosion in, 389–391

inhibitors for, 390

mechanism of, 390–391

water, effect of, 390*F*

coatings, 280–281

corrosion characteristics, 384–392

by microbiological constituents in fuel,
388–389

galvanic coupling of, 392–393

nitric acid, corrosion rates in, 392

oxide coatings on, 287–288, 383, 386

painting of, 296

passivity of, 83, 383, 384, 386, 388

soil corrosion, 208

steam, corrosion in, 384

vapor degreasing of, 293

waters, corrosion in, 384–386

pH, effect of, 387

pitting, 98, 99

Aluminum alloys, **393–395**

anodes in impressed current cathodic
protection, 259

clad, 384, 395

compositions, 385*T*

exfoliation of, 394

intergranular corrosion, Al–Cu alloys,
393–394

sacrificial anodes, 254–255

stress-corrosion cracking, 384, 394–395

Amorphous alloys, 335

Amphoteric metals, 12, 47, 79, 245, 260, 279,
446

Anion, definition, 13

Anode:

definition, 11–13

materials, for cathodic protection, 258–260

sacrificial, 144, 251, 252, 254–257, 263, 354,
370, 378

Anode–cathode area ratio, 56, 67–69, 71–75,
123, 132, 208–210

magnesium, galvanic corrosion of, 402

tantalum, 442

Anodic protection, **263–264**

by alloying, 90–92

of aluminum, 264, 386

theory of, 90–92

Anodizing:

aluminum, 287–288, 296

magnesium, 403

Atmospheric corrosion, **191–204**

avoiding, 201–202

- comparison with seawater and soils, 195*T*
- corrosion product films, protection by, 192–195
- corrosion rates, steels, 193*F*
 - alloying, effect of, 202*T*
 - various metals, 194*T*
- critical humidity, 199–200
- factors influencing, 195–200
- gases in atmosphere, effect of, 197–199
 - sulfur dioxide content of air, 197–198
- moisture, effect of, 199–200
- particulate matter, effect of, 196–197
- time of wetness, 199
- types of atmospheres, 192
- Automobiles, 4, 196, 295
 - aluminum alloys in, 394–395
 - body panels:
 - electrogalvanizing, 270
 - painting, 295
 - phosphate coating, 287
 - engines, 3
 - Ford, 404
 - fretting corrosion, 182
 - Honda, 395
 - lead in, 447
 - magnesium in, 399, 404
 - nickel coatings, 272
 - mufflers, 2, 280
 - painting, 295
 - stainless steels in, 341
 - Volkswagen, 399
- B**
- Backfill, for cathodic protection, 255, 259
- Bacteria, 4, 118–120, 206–207, 279, 298, 309, 367, 388–389
- Blister, 66
- Blister cracking, 170–172
- Boiler corrosion, **323–330**
 - alkali addition, effect of, 327–328
 - embrittlement detector, 324–325
 - inhibitors for, 328
 - mechanisms of, 328–330
 - oxygen, dissolved, effect of, 329
 - oxygen scavengers, 318–319, 330
- Boiler water, treatment of, 326–328
 - alkali addition, 327–328
 - carbon dioxide removal, 326–327
 - inhibitor addition, 328
 - oxygen removal, 326
 - phosphate addition, 328
- Brasses, **371–378**
 - naval, red, yellow, 371–372
 - see also* Copper–zinc alloys
- Bridges, 2
 - cathodic protection for, 253
 - steel reinforcements in, 144
 - failure by stress-corrosion cracking, 153, 169–170
 - painting, 290
 - weathering steels for, 201
- Bronzes, 13, 252, 270, 371–372
- C**
- Cadmium, 70–71, 168, 178, 184, 198, 231, 264, 271, 274, 276–277, 288, 314, 392–393,
 - toxic properties of, 277, 392–393
- Catalytic properties and passivity, 108–109
 - hydrogen overpotential, relation to, 65
- Cathode, definition, 11–13
- Cathodic protection, **251–267**
 - anode materials for, 258–260
 - backfill, use of, 255, 259
 - coatings, combined use with, 255–257
 - criteria of protection, 260–263
 - doubtful, 262
 - potential measurements, 260–262
 - current, magnitude required, 77–79, 257–258
 - economics of, 263
 - history of, 252–253
 - how applied, 253–254
 - overprotection, effect of, 259–260
 - pitting, used to avoid, 261–262, 354
 - potential decay along pipeline, 257
 - derivation of formula for, 467–469
 - steel reinforcements in concrete, 144, 253
 - stress-corrosion cracking, to avoid:
 - in aluminum alloys, 384, 395
 - in brasses, 378
 - in stainless steels, 360
 - in steel, 155–156, 162
 - in titanium alloys,
 - theory of, 77–79
- Cation, definition, 13
- Caustic embrittlement, 152
- Cavitation-erosion, **130–131**
 - in diesel engine liner, 131*F*
- Cells:
 - Daniell, 54–55
 - galvanic, 11–12, 22, 26, 54, 68, 84, 115, 143, 157, 197, 207, 254, 280, 343, 369
 - local-action, 10–11, 68, 142, 261
 - passive–active, 96, 280, 352
 - reference, 34–37
 - calomel, 35–36
 - copper–copper sulfate, 36–37
 - silver–silver chloride, 36–37

- types, in corrosion reactions, 13–15
 - concentration, 13–14
 - differential aeration, 13–15, 28–30, 164, 197, 298–299, 329, 353, 370, 371, 384, 388, 430
 - differential temperature, 14–15
 - dissimilar electrode, 13
- Cement, Portland, as cause of corrosion:
 - of aluminum, 388, 391
 - of lead, 446
 - as protective coating for steel, 286
 - steel reinforcements, failure of, 143–145
 - galvanic effects of, 144
- Chromates, *see* Passivators
- Chromium–iron alloys:
 - critical composition for passivity, 100–101
 - critical current densities for passivity, 101*F*
 - oxidation, elevated temperatures, 232–235
 - effect of yttrium, 234–235
 - maximum temperatures in air, 235*T*
 - potentials of, in 4% NaCl, 101*F*
 - Flade, 88*F*
 - see also* Stainless steels
- Chromium–nickel alloys:
 - commercial alloys, composition, 413*T*
 - corrosion characteristics, 411–417
 - critical composition for passivity, 102
 - intergranular corrosion, 415
 - oxidation, elevated temperatures, 226*T*, 236–237
- Clean Air Act, 191, 198, 289, 295
- Coatings:
 - compliant, 289
 - inorganic, **285–288**
 - chemical conversion, 286–288
 - chromate, 288
 - oxide, 287–288
 - phosphate, 286–287
 - as preparation for painting, 295–296
 - Portland cement, 286
 - vitreous enamel, 285–286
 - metallic, **269–283**
 - aluminum, 280–281
 - application, methods of, 269–271
 - cadmium, 276–277
 - chromium, 279–280
 - classification, 271–272
 - lead, 274
 - nickel, 272–274
 - electroless, 273–274
 - fogging of, 273
 - thickness of, 272–273
 - tin, 277–279
 - zinc, 274–276
 - atmospheric corrosion, 198
 - seawater corrosion, 275
 - soil corrosion, 208
 - polarity reversal in hot waters, 276
 - see also* Steel, galvanized
- organic, **289–301**
 - cathodic protection, combined use with, 255–257
 - filiform corrosion, 296–299
 - pigments, inhibiting, 291–292
 - plastic, 299–300
 - prime coat, 291–292, 294, 295, 296, 299, requirements for, 291–292
 - rules for applying, 295
 - surface preparation, 293–295
 - effect on life, 295*T*
- Cobalt and cobalt alloys, **419–423**
 - cavitation-erosion, 420, 423
 - compositions, 422*T*
 - corrosion characteristics, 419–423
 - fretting corrosion, 420, 423
- Cold working, effect on corrosion:
 - iron and steel, 149–150
 - nickel, 150
 - pure iron, 150*F*
- Complexes, chemical, effect on Emf, 30–32
- Concrete, 143–145, 253, 388, 391
- Condenser tube alloys, 378–379
- Conversion factors:
 - corrosion rates, 474–475*T*
 - to current densities, 475*T*
- Copper, **367–381**
 - atmospheric corrosion, 194*T*, 195*T*, 197–199
 - blue staining, caused by, 321, 369
 - corrosion characteristics, 367–371
 - deposit attack, 370
 - hydrogen, reaction with, 231–232
 - impingement attack, 17, 368–372, 379, 411
 - inhibitor for tarnish of, 314
 - oxidation, high temperature, 230–232
 - pitting of, 369–370, 371, 378
 - seawater corrosion, 195*T*,
 - soil corrosion, 195*T*, 208, 209*T*
 - stress-corrosion cracking, 371, 374
 - waters, corrosion by, 369–371
- Copper–nickel alloys, for condenser tubes, 378–379
 - see also* Nickel alloys, copper–nickel,
- Copper–zinc alloys, **371–378**
 - dezincification, 17, 252, 334, 371–374
 - effect of Zn content, 372*F*
 - mechanism of, 334, 374
 - impingement attack, effect of Zn content, 372*F*

- stress-corrosion cracking, 374–378
 effect of applied potential, 377*F*
 effect of Zn content, 372*F*
 mercurous nitrate test, 376
 prevention, 378
- Corrosion:
 alloying, effect of, 333–335
 cost, 2–5
 current and corrosion rate, 56, 475*T*
 importance of, 2–5
 direct and indirect losses, 2–5
 products, protective, in atmospheric corrosion, 192–195
 rates, calculation of, from polarization data, 71–73, 456–461
 classification for handling chemical media, 16
 control of, anodic, cathodic, 68–69
 derivation of formula for, 456–461
 polarization, influence on, 68–71
 scientist and engineer, 1–2
 tendency and free energy, 21–22
 types, 15–18
- Corrosion-erosion, definition of, 17
- Corrosion fatigue, **173–180**
 appearance of, 174 (Photo)
 definition, 18, 173–174
 effect of oxygen, moisture, 175
 mechanism of, 179–180
 minimum corrosion rate for, 178*T*
 prevention, 178–179
 strength, values of, 177*T*
- Crazing, 286
- Crevice corrosion, 14, 29, 99, 117, 173, 342, 350–351, 352–354, 361, 412, 416–417, 429–430, 432
- Critical pitting potential, 97–99, 160, 264, 351–354, 384–386, 421, 429, 437
- Critical pitting temperature, 99–100, 351–352
- Crystal face, effect on corrosion, 13, 149
 effect on oxidation, 230–231, 232
- Current density:
 critical for passivity, 85–86, 90, 117, 242, 411
 for Cr–Fe alloys, 101*F*
 for Ni–Cu alloys, 104*F*
 exchange, 61
 limiting, 58–60
 passive, 85
 for Ni–Cu alloys, 104*F*
- D**
- Deactivation of water:
 definition, 317
 by hydrazine, 318–319
 by ion-exchange resins, 326
 by sodium sulfite, 318, 326
- Dealloying, 17, 118, 172, 372–374
- Deaeration of water, 178, 317–319, 326, 402, 414
 definition, 319
 oxygen concentration, maximum allowable for steel systems, 320*T*
- Depolarization:
 in acids, 124–125
 by oxygen, 72, 116, 122, 124, 131–133, 139, 262, 458
- Deposit attack, 370
- Dezincification:
 Cu–Zn alloys, 334, 371–374
 definition, 17
 mechanism, 374
- Diesel engines, 130, 215, 322,
- E**
- Electrochemical equivalent, 10
- Electrochemical impedance spectroscopy, 75–77
- Electrochemical mechanism:
 of corrosion, 9–18, 22, 70–71, 143
 for corrosion of iron and steel, 115–116
 of passivation, 89
 of pitting, 96, 351–353
 of stress-corrosion cracking, 157–158, 190, 377
- Electrode:
 copper–copper sulfate, 36–37
 hydrogen, 24–25
 oxygen, 28–30
 reference, 34–38
 standard or normal hydrogen, 24–25
- Electron configuration theory, 102–108
- Emf:
 calculation of, 25–28
 relation to Gibbs free energy, 22
 Series, definition of, 30
 Table, 31*T*
- Endurance limit, 18, 141
- Environmental Protection Agency (EPA), 191, 196, 369, 447
- Exfoliation, 394
- F**
- Faraday, value of, 22
- Faraday's law, 9–11, 56, 85, 178, 244, 259,
- Fatigue, affected by air, moisture, 175
 limit, definition of, 18, 173
 strength, definition of, 173
see also Corrosion fatigue

Filiform corrosion, 279, **296–299**

photos, 297
theory of, 298–299

Films, oxide:

isolation of, 94
passive, oxidizing properties, 93–94
thickness of:
on aluminum, 383
on iron, 93–94

Flade potential:

aluminum, 383
definition, 86
chromium, 279
chromium–iron alloys, 88*F*
iron, 47, 84–89, 93–94, 112
nickel, 410
nickel–copper alloys, 106
nickel–molybdenum alloys, 412
tantalum, 441
titanium, 426

Fogging, 16, 273, 411

Fouling, marine:

Cu²⁺ concentration to prevent, 103–105, 252, 369
of Cu–Ni alloys, 103–105, 104*F*
of stainless steel, 351

Fracture mechanics, 162–166

Fretting corrosion, **180–184**

aircraft, 182
automobiles, 182
cobalt alloys, 420, 423
definition, 17, 180–181
equation for weight loss, 183
derivation of, 471–474
factors causing, of steel
mechanism, 182–184
nuclear reactors, 182
prevention, 184
railroad car wheels, 182

Fugacity, 24

Furnace windings, 236, 237

G

Galvanic coupling:

of aluminum, 391–393
in aerated media, 127
in deaerated media, 127–129
of different steels, 141–142
in soils, 206
effects of, at elevated temperatures, 227–228
hydrogen cracking of stainless steels, caused by, 357
hydrogen embrittlement of Ta, caused by, iron–gold, 306

in natural waters and soils, 141–142
and passivity of stainless steels, 361

Galvanic Series:

definition, 32
in seawater, 33*T*

Galvanized steel, *see* Steel, galvanized

Glass, cavitation–erosion, 130

coatings, 256, 285–286
electroless nickel coatings on, 274
stress-sorption cracking, 160

Glass electrode, 25

Glassy alloys, 335

Gmd, conversion factors of mm/y,
474–475

definition, 16

Gold, 17, 22, 109, 227, 232, 269–270, 286, 334,
372–374,

coatings, electrical contacts, 182
coupled to iron, 306
fatigue, 175

Graphitic corrosion, 138, 142, 206

Gun barrels, protecting, 287

H

Humidity:

critical in atmospheric corrosion, 196,
199–201
and filiform corrosion, 298
and growth of bacteria, 120
and stress-corrosion cracking, 165, 376

Hydrogen:

cracking, 65–66, **166–172**
and cadmium coatings, 276
and cathodic protection, 252, 259, 267
of cobalt alloys, 421–423
mechanism, 167–170
metal flaws, effect of, 170–172
of stainless steels, 354–361
of steel, 166–172
of steel reinforcements in concrete,
145
disease, in copper, 231–232
in silver, 203
electrode, 24–25, 25*F*
standard, 25
embrittlement, 54, 158, 166–169
of aluminum alloys, 395
and cathodic protection, 259
of magnesium alloys, 402
caused by microbiologically influenced
corrosion, 118
caused by pickling inhibitors, 312
of Ta,
of ultra-high-strength steels, 357

overpotential, 60–61, 62*T*, **63–66**, 70, 80–81, 90, 116, 123, 125–129, 139, 143, 149–150, 267, 278–279, 310, 402, 412, 448
standard scale, definition of, 25

I

Impingement attack:

of condenser alloys, 379
of copper, 368–370
of copper–tin alloys, 371
of copper–zinc alloys, 371–372
definition, 16–17
photo, 368

Inhibition efficiency, definition, 311

Inhibitors, 2, 3, **303–316**

for aluminum, 384, 390, 392
classification, 303
for corrosion fatigue, 178–179
and critical pitting potential, 97
definition, 303
for diesel-engine cylinder liners, 130
for engine cooling systems, 323
evaluation of, 73
in foods, 278
for industrial waters, 318
 boiler waters, 152, 328
 cooling waters, 322–323
for iron and steel, 130, 133, 143
for lead, 447
mechanism of, 304–308
nontoxic, 323
oxygen, as inhibitor in acids, 125
in phosphate coatings, 287
pickling, 310–313
 applications of, 294, 312–313
 concentration, effect of, 312*F*
 hydrogen embrittlement, caused by, 312
pigments for paints, 291–292
slushing compounds, 313
sodium:
 benzoate, 306, 384
 borate, 133, 306, 322
 polyphosphate, 306–307, 323
 silicate, 133
for soil corrosion, 206
for stainless steels, 157, 361
 pitting corrosion, 350–351
for stress-corrosion cracking, of brass, 376, 378
 of steel, 152–156, 157
 of stainless steels, 157
 of titanium alloys, 157, 430–431
for tarnishing of copper, 314
toxicity, 303–304, 309

in vapor degreasing aluminum, 293
vapor phase, 201
see also Passivators

Insulation, stress-corrosion cracking
 associated with, 355, 375

Intergranular corrosion:

in copper–zinc alloys, 156, 378
definition, 17–18
in aluminum alloys, 252, 384, 394, 395
in high purity aluminum, 384
in lead alloys, 448
in nickel-base chromium alloys, 415, 416
in stainless steels, 252, 343–350, 358
in titanium, 430–431
in zirconium, 437

Ion implantation, 270

Ionization constant of water, various
 temperatures, 28*T*

ipy, conversion factors to mdd, 474–475
definition, 16

IR drop, 56–57, 63, 68, 73, 74, 88, 262–263, 456

 calculation of, in electrolytes, 58
 as cause of polarization, 61–63

Iron, **115–148**

acids:

 citric, rates in, 71*T*, 139*T*

 dissolved oxygen:

 effect of, 124–125

 inhibition by, 125–127

 HCl + NaCl, rates in, 139*T*

 velocity, effect of, 125–127

anaerobic bacteria, effect of, 118–120

anodic protection, 90, 263–264

atmospheric corrosion, 191–204

cast,

 coupled to steel, 142

 graphitic corrosion, 138, 142, 206

 soil corrosion, 138, 206

 water pipe, 286

 in water, 138

composition, effects of, 138–142

heat treatment, effect of, 142–143

hydrogen cracking, 166–172

 delay time and H₂ content, 168*F*

metallurgical factors, effect of, 138–143

oxidation, elevated temperatures:

 in oxygen, 232–234

 in steam, 323–326

 effect of pH, 327*F*

oxygen, dissolved, effect of, 116–118

pH, effect of, 120–123

salts, dissolved, effect of, 131–138

seawater, rates in, 124*T*, 195*T*

soil corrosion, **205–213**
 stress, effect of cold work, 149–150
 stress-corrosion cracking, **151–156**
 effect of:
 alkalies, 151–152
 carbon monoxide–carbon dioxide, 153
 cold work, 153–155
 illuminating gas (HCN), 153
 liquid ammonia, 153
 nitrates, 151–155
 silicates, 152
 temperature, effect of in aqueous media, 120
 velocity, effect of:
 in acids, 125–127
 in natural waters, 129–130
 wrought, 123, 124*T*, 138, 206, 209*T*
see also Steel

K

Knife-line attack, 348

L

Lead, **445–449**
 and air quality, 191
 atmospheric corrosion, 192, 194*T*, 198
 cathodic protection of, 251, 260, 261, 262*T*,
 chemical conversion coatings on, 286
 coatings of, on steel, 179, 184, 271, 274
 in copper alloys, 372
 corrosion characteristics, 445–448
 of Pb-acid battery grids, 447–448
 in differential temperature cells, 15
 fatigue cracks in, 174
 hydrogen overpotential of, 62*T*, 65
 oxidation, 231
 in paints, 290, 291–292, 295*T*, 296
 passivation of, 84, 92, 127
 polarization of, 68
 soil corrosion, 207, 208, 209*T*,
 stray current corrosion, 242, 244*T*, 245
 toxic properties of, 4, 393
 in water, 137, 317, 321,
 woods, corroded by, 446
 Lead and Copper Rule, EPA, 369, 447
 Liquid-metal embrittlement, 158, 160, 165
 Local-action cells, 10–11, 68, 142, 261
 current, 10, 259, 266
 Luggin capillary, 56, 57*F*

M

Magnesium, 399–406
 alloy compositions, 403*T*
 coatings on, 403–404

corrosion characteristics:
 alloys, 400–403, 404–404
 pure magnesium, 399–400
 as sacrificial anode, 254–255
 efficiency of, 255
 for hot water tanks, 256*F*
 stress-corrosion cracking, 402–403
 tolerance limit, definition of, 400
 for iron, 401*F*
 univalent ion, 259
 mdd, conversion factors to ipy, 474–475
 definition of, 16
 Molybdenum, 84, 96, 108, 184, 229, 237, 341–
 342, 344, 348, 350, 351, 353, 409*T*,
 412, 415–417, 421

N

Nernst equation, derivation of, 22–24

Nickel, 408–411

atmospheric corrosion, 194*T*, 198–201
 corrosion characteristics, 408–411
 Flade potential, 410
 oxidation, elevated temperatures, 216–217,
 236–237, 410
 alloyed with Cr, 226*T*, 234*F*, 236–237
 intergranular, 236–237, 410
 Nickel alloys, **411–417**
 compositions, 413*T*
 critical pitting potential, 98*T*
 irradiation-assisted stress-corrosion
 cracking, 172
 nickel–chromium, 236–237, 411–412
 nickel–chromium–iron, 236, 414–415
 in pressurized water reactors, 414–415
 nickel–copper, 414
 atmospheric corrosion, 194*T*
 cupro-nickel, 103, 378–379, 411
 corrosion fatigue, 177*T*
 in condenser tubes, 378–379
 corrosion in 3% NaCl, 103*F*
 critical current densities, in 1*N* H₂SO₄, *F*
 fouling of, in seawater, 105
 passive current densities, 104*F*
 passivity, 103–108
 pitting, in seawater, 104*F*
 stress-corrosion cracking, 379
 nickel–molybdenum, 412, 415–416
 behavior in acids,
 Nitrites, *see* Passivators
 Nuclear reactors, 172–173, 182, 348, 437

O

Overpotential:
 definition, 60

- hydrogen, 60–61, **63–66**
 factors affecting, 63–66
 mechanism of, 64–65
 values of, 62*T*
 metal deposition and dissolution, 61
 values of, 62*T*
 oxygen, 61
 values of, 44*T*
- Overvoltage,
 definition, 60
- Oxidation, 215–240
 catastrophic, hot ash, 229
 of copper, 230–232
 equations expressing rate, 220–223
 galvanic effects, 227–228
 initial, thin film, 216–218
 internal, 231
 iron and iron alloys, 232–233
 iron–chromium alloys, 235–236
 life test, ASTM, 233–234
 nickel and nickel alloys, 236–237
 coupled to Pt in borax, 227–228
 reactive element effect, 215, 234–237
 Wagner theory, 223–224
 Zn alloyed with Al, Li, 227*T*
- Oxidation-resistant alloys, 234–237
 Reactive element effect, 234–235
- Oxides, properties, **224–227**
p-, *n*-type, 224–225
- P**
- Paints, **289–291**
 applying, **295–296**
see also Coatings, organic
- Parting, definition, 17, 334
- Passivators, **303–310**
 applications, 308–310
 chromates, 303–310
 for cooling waters, 322–323
 toxicity, 304, 322–323
 critical concentrations of chlorides and sulfates, 310*T*
 effect on steel, various temperatures and Cl⁻ concentrations, 308*T*
 nontoxic alternatives, 323
 critical concentration, 305
 definition, 303
 examples of, 88
 oxygen as, 125, 306
 sodium, benzoate, 306, 384
 borate, 133, 306, 322
 nitrite, 303–306, 309–310
 corrosion of steel, effect of concentration, 309*T*
 critical concentrations of chlorides and sulfates, 310*T*
 polyphosphate, 306–307, 323
 combined with chromates, 309
 for treatment of municipal waters, 321
 disposal, 322
 silicate, 133, 152, 306
 for treatment of potable waters, 321–322
 theory of, 88–90, 304–308
 toxicity, 303–304
see also Inhibitors
- Passivity, **83–113**
 of alloys, **100–108**
 critical compositions, 100–102
 breakdown of, 89, 90, 94, 96
 catalytic properties, relation to, 108–109
 cathodic polarization, effect of, 108
 chlorides, action of, 96–100
 definitions, 84
 film thickness:
 on aluminum, 383
 on iron, 93–96
 of iron:
 in nitric acid, 89–90
 in sulfuric acid, 84–87
 theories of, 92–96
 adsorption, 92–94, 96, 99, 102, 108
 electron configuration, 102, 108–109
 oxide-film, 92, 96, 102
- Patina, on copper, 198–199
- pH:
 aluminum, effect of, 387–388
 definition, 28
 iron, effect of, 120–123
 measurement, 28
 values for water at various temperatures, 28*T*
 zinc, effect of, 274–275
- Pilling and Bedworth rule, 6, 219–220
- Pipelines, 2, 4
 cathodic protection of, 211, 253–255, 257–263, 467–470
 microbiologically influenced corrosion of, 120
 hydrogen-induced cracking of, 140, 170
 inhibitors, 309
 pitting of, 210
 soil corrosion of, 205, 206
 stray-current corrosion of, 241–244, 247
 stress-corrosion cracking of, 153, 210–211, 300
- Pitting:
 in aluminum, 384–386
 in condenser alloys, 378–379

- in copper, 369–370
 - critical potential for, 97–99
 - critical temperature for, 99–100
 - definition, 16
 - elongated, 352, 353*F*
 - factor, 16
 - in stainless steels, 350–354
 - theory of, 96–99, 351–353
 - Plastics, coatings, used for, 299–300
 - tetrafluoroethylene, 184, 300
 - Polarization:
 - causes of, 58–63
 - activation, 60–61
 - concentration, 58–60
 - IR drop, 61–63
 - corrosion rates:
 - anode–cathode areas:
 - effect of, 73–75
 - calculation of, 71–73
 - relation to, 68–71
 - definition, 54
 - galvanostatic, for iron, 86*F*
 - how measured, 56–58
 - potentiostatic, for iron, 85*F*
 - Potential:
 - calculation of, 22–28
 - corrosion, 54
 - definition, 56
 - measurement, 66
 - critical:
 - for pitting, 97–99
 - for stress-corrosion cracking, 158–162, 355–358
 - decay along pipeline:
 - derivation of formula, 467–469
 - formula, 257
 - definition, 24–26
 - drop along soil surface by current entering pipe, 245, 469–470
 - Flade, chromium, value for, 279
 - chromium–iron alloys, 88*F*
 - definition, 86
 - iron, value for, 86
 - as calculated, 93, 112
 - in chromates, 88–89
 - nickel, value for, 410
 - passivity, relation to stability of, 87
 - pH, dependence on, 86–87
 - hydrogen, normal, 25
 - standard, 25
 - liquid-junction, 33–34
 - characteristic values, 34*T*
 - sign of, 25–28
 - standard, 31*T*, 476*T*
 - definition, 24
 - standard hydrogen, definition, 25
 - Potentiometer, 22, 26, 66
 - Potentiostat, 66–67, 85, 263
 - Potentiostatic polarization, 85, 97, 105, 242
 - Pourbaix diagrams, 43–51
 - aluminum, 47–48, 383
 - basis of, 43–44
 - copper, 367–368
 - iron, 45–47
 - lead, 445–446
 - limitations, 49
 - magnesium, 48–49, 400
 - nickel, 408–410
 - tantalum, 441–442
 - titanium, 419–420
 - water, 44–45
 - zirconium, 435–436
- R**
- Radiation damage, **172–173**
 - Reaction limit, 334
 - values, gold alloys, 334*T*
 - Reactive element effect, 215, 234–237
 - Resistivity:
 - IR drop in electrolytes, 58, 61–63
 - in soil, 206–207
 - measurement, 246
 - formula for, derivation of, 470–471
 - Ring-worm corrosion, 143
 - Risk, 5, 7–8
 - Rust:
 - composition, 116
 - definition, 1
 - iron, effect on corrosion of, 14, 15*F*, protection by, in atmospheric corrosion, 192–195, 201
- S**
- Saturation index:
 - alteration of, by water treatment, 136, 321
 - calculation of, 134–136, 417*F*
 - derivation of equation for, 461–463
 - effect of temperature, 136
 - limitations of, 137–138
 - and municipal waters, treatment of, 321–322
 - Schikorr reaction, 325
 - Season cracking, 334–335
 - Seawater:
 - aluminum in, 280, 386, 392
 - galvanic coupling, 393
 - cathodic protection in, 254–256, 258*T*, 261, 272,
 - coal-tar coatings, 291

- copper–aluminum alloys in, 371
 - copper–nickel alloys in, 378–379
 - copper–zinc alloys in, 372
 - corrosion of aircraft over, 229
 - copper in, 195*T*, 369–370,
 - corrosion in, 11, 14
 - corrosion rate of steel in, 16
 - corrosion rate of magnesium in, 19
 - galvanic coupling in, 127
 - galvanic series in, 32, 33*F*
 - IR drop in, 58
 - iron in, 118
 - lead in, 446, 448
 - lead alloys for cathodic protection, 446
 - magnesium in, 400, 405
 - stress-corrosion cracking, 402
 - microbiologically influenced corrosion in, 118–119
 - nickel in, 410, 411
 - nickel–chromium alloys in, 412,
 - nickel–chromium–iron alloy in, 414
 - nickel–chromium–molybdenum alloys in, 412, 416–417
 - nickel–copper alloys in, 103, 104*F*, 408*T*, 411, 414
 - stainless steel in, 208, 341, 344, 350–351, 352, 353*F*, 354, 357, 360, 362
 - steel in, 123, 124*T*, 131–132, 138, 195*T*,
 - boiler corrosion, 324, 329
 - cavitation–erosion, 130
 - corrosion fatigue, 175, 178
 - deaeration, 317
 - effect of carbon content, 139
 - effect of chromium, 141, 208
 - effect of flow velocity, 129, 130*F*
 - effect of nickel, 141
 - paints for, 292
 - Portland cement coatings on, 286
 - and stray current corrosion, 244
 - titanium in, 98, 426, 429–430, 432
 - titanium alloys in, 431
 - zinc in, 195*T*, 274–275
 - zirconium in, 437
- Sensitization:
- aluminum alloys, 384, 393–394
 - stainless steels, 156, 172, 343–347, 350, 351, 359–361
- Silver, 15, 16, 17, 32, 61, 179, 184, 197, 216, 223–224, 227–228, 231, 232, 264, 269, 271, 334, 361, 400–402, 410, 447
- Slushing compounds, 313
- Soils, corrosion in, 205–213
- avoiding, 211
 - in cinders, 208
 - depth of burial, effect on, 207
 - factors affecting, 206–207
 - pitting, 208–210
 - rates, 195*T*, 209*T*
 - resistivity measurements, 207, 246
 - stress-corrosion cracking, 210–211
- Stainless steels, **335–365**
- anodic protection of, 90–91, 263–264
 - classes and types of, 337–343
 - cold work, 343
 - compositions, 338–340*T*
 - corrosion resistance, general, 361–362
 - crevice corrosion, 350–351
 - avoiding, 354
 - definition, 100, 335
 - galvanic coupling, 357, 361
 - heat treatment, for optimum corrosion resistance, 342–343
 - sensitizing, 343
 - austenitic, 343–345, 344*F*
 - ferritic, 349
 - history, 336–337
 - hydrogen cracking, 167, 170, 357
 - avoiding, 361
 - 18–8, cold worked, 357
 - galvanic coupling, as cause of, 167, 357
 - intergranular corrosion, **343–350**
 - austenitic types, 343–349
 - avoiding, 347–348
 - effect of carbon and nitrogen, 346*F*
 - knife-line attack, 348
 - of nonsensitized alloys, 348–349
 - theory of, 345–347
 - ferritic types, 349–350
 - theory of, 350
 - passivity, effect of alloyed Cu, Pt, Pd, 90
 - pitting, 350–354
 - avoiding, 354
 - critical potential, 97–99
 - critical temperature, 99–100
 - inhibiting against, 350–351
 - theory of, 351–353
 - soils, corrosion in, 208
 - stress-corrosion cracking, hydrogen cracking, **354–361**
 - austenitic:
 - avoiding, 360–361
 - critical potential in MgCl₂, 360
 - damaging ions, 354–355
 - in polythionic acids, 359–360
 - metallurgical factors, 357–359
 - nickel, effect of, 358*F*
 - nitrogen, carbon, effect of, 358, 359*F*
 - oxygen dissolved, effect of, 355, 356*F*

- ferritic and martensitic, 354, 356–357, 361
 - weld decay, 344, 345*F*
- Steam:
 - condenser corrosion, 327
 - corrosion:
 - of aluminum in, 386
 - of iron in, 323–326
 - of zirconium in, 437–438
 - return-line corrosion, 327, 328
- Steel:
 - atmospheric corrosion, 193*F*, 194*T*, 195*T*, 202*T*
 - Bessemer, oxygen-furnace, 138
 - carbon content, effect on corrosion, in 3% NaCl, 124*T*
 - in hydrochloric acid, 151
 - in seawater, 139
 - cold rolling, effect of, 149–150
 - composition, effects of, 138–141
 - corrosion fatigue, 173–180
 - fretting corrosion, 180–184
 - galvanic coupling, effects of, 141–142
 - galvanized, 274–276
 - corrosion of:
 - atmospheric, 198, 274, 275*T*
 - in soils, 206, 208, 209*T*
 - first patent, 252
 - painting of, 296
 - pitting of, in hot water, 276
 - heat treatment, effect on corrosion, in water, 124*T*
 - in acids, 143
 - low alloy, 138–142, 206
 - atmospheric corrosion, 193*F*, 194*T*, 201
 - copper-bearing, 124*T*, 140–141, 206
 - atmospheric corrosion, 193*F*, 202*T*
 - corrosion in aqueous media, 123, 138–142
 - corrosion fatigue, 177*T*
 - oxide coatings on, formation of, 287
 - pickling of, 294
 - reinforcements in concrete, 143–145
 - cathodic protection, 144, 253
 - soils, corrosion in, 206, 207, 208, 209*T*, 210
 - stress-corrosion cracking in, 210–211
 - stainless, *see* Stainless steels
 - weathering, 201
 - see also* Iron
 - Stepwise cracking, 140, 166
 - Stern–Geary equation, 72–73
 - derivation of, 456–458
 - general corrosion, 458–461
 - Stray-current corrosion, **241–249**
 - avoiding, 246–247
 - damage by, ac vs. dc, 241–242
 - to amphoteric metals, 245
 - quantitative values, 244
 - detection of, 245
 - pipe, inside of, 243–244
 - sources of, 242–244
 - Stress, residual, 149
 - in brass, 376
 - and corrosion fatigue, 177
 - and hydrogen-induced cracking, 170
 - in magnesium alloys, 402–403
 - in stainless steels, 357
 - and stress-corrosion cracking of steel, 151, 155, 156*T*
 - in zirconium alloys, 437
 - Stress-corrosion:
 - of aluminum alloys, 394–395
 - of bridge cable, 153
 - of copper–zinc alloys, 162, 163*F*, 374–379
 - critical crack depth, 165–166
 - definition, 18
 - initiation of, critical potentials for, 161–162
 - of iron and steel, 151–156
 - of magnesium alloys, 402–404
 - mechanisms, **156–166**
 - of pipelines, 210–211
 - rate of crack growth, 162–166
 - of stainless steels, 354–361
 - surface flaws, effect of, 166, 431
 - of titanium alloys, 431
 - Stress intensity factor, 164–166, 171–172
 - Stress-sorption cracking, 158–161, 395
 - Subscale formation, 231
 - Sulfidation, 18, 226, 230, 237, 409*T*
 - Sulfide stress cracking, 166–167, 421
 - effect of surface flaws, 171–172
- T**
- Tafel equation, 61, 64, 71, 457, 459
- Tantalum, **441–443**
 - as alloying element, 155
 - corrosion characteristics, 436, 441–443
 - galvanic effect, 227, 228*F*
 - and glass coatings, 286
 - hydrogen embrittlement, avoiding, 441–442
 - passivity, 96, 441–442
- Telluric currents, 241
- Terne plate, 274
- Thermal spraying, 270
- Tin:
 - atmospheric corrosion, 194*T*
 - coatings, 277–279

- complexes, effect on corrosion, 30–32
corrosion characteristics, 279
- Titanium, 425–434
alloy compositions, 428
corrosion characteristics, 425–432, 436
 in alkali–hydrogen peroxide solution, 427
Flade potential, 426
hydrochloric acid, corrosion rates in
 inhibited, 427–429, 428*F*
 effect of alloyed Pt or Pd, 428*F*
nitric acid, fuming, reaction with, 427
pitting and crevice corrosion, 429–430
 in bromides, iodides, 429–430
 pitting potentials in chlorides at elevated
 temperatures, 430*F*
seawater, resistance to, 429–430
stress-corrosion cracking of alloys, 431
 cathodic protection against, 431
 inhibiting ions for, 431
- Transition metals:
 catalytic properties, 108–109
 overpotential for deposition or dissolution,
 61
 passive properties, 93
- Transpassivity, definition, 92
- Tungsten, 96, 220, 221, 412, 421,
- V**
- Valves, corrosion of, 142
- Vanadium, as cause of catastrophic oxidation,
 229
- W**
- Wagner:
 definition of passivity, 84
 theory of oxidation, 223–224
 and Traud experiment, 70
- Wash primer, 296
- Water, treatment of, **317–332**
 boiler, 323–328
 cooling, 322–323
 hot-water heating systems, 321–322
 municipal supplies, 321–322
- Welds:
 knife-line attack, 348
 weld decay, 345 (Photo)
 definition, 344
- Y**
- Yttrium, 215, 234–235, 236–237, 271
- Z**
- Zinc:
 atmospheric corrosion, 194*T*, 195*T*, 198, 199
 chromate coatings on, 288
 coatings on steel, 208, 274–276. *see also*
 Steel, galvanized
 electrogalvanizing, 270
 oxidation of, in O₂, 227*T*
 painting of, 296
 pH, effect of, 275*F*
 -rich paints, 292, 296
 seawater corrosion, 195*T*, 275
 soil corrosion, 195*T*, 207, 208, 209*T*, 211
- Zirconium, **435–440**
 corrosion characteristics, 435–439
 pitting in chlorides, critical potentials for,
 437
 Pourbaix diagram, 436
 radiation, effect on, 173
 steam, behavior in, 437–438, 439*F*
 effect of alloyed tin, 438
 stress-corrosion cracking, 437
 transition point, 436, 438, 439*F*
 water, high temperature, corrosion by,
 437–439