

Index

- accelerating gas, 2
 - helium, 84
 - nitrogen, 84
- acceleration of powder particles, 3 ff
- adiabatic shear instability, 17 ff
 - adiabatic shear band thicknesses, 32 ff
 - jet formation, 44
 - jetting, 79
 - vortexes, 40
- Arrhenius' law, 91
- average single pass thickness, 85
- bonding mechanisms, 16 ff
 - adhesion, 131
 - adiabatic welding, 137
 - boadiabatic bonding, 149
 - bonding area structure, 137
 - bonding surface area, 137
 - bonding types, 137
 - fraction of bonded atoms, 132
 - friction welding, 137
 - interparticle bonding, 149
 - liquid phase sintering, 137
 - macroscopic bonding strength, 137
 - mechanical interlocking, 40
 - reaction bonding, 44
 - relative strength of the bond, 132
 - solid-state bonding, 171
- build-up parameter, 87
- coating, 4 ff
 - Al–Zn-based sacrificial coatings, 207
 - composite coatings, 135
 - composite coatings for mechanical components, 186
 - decorative coatings, 184
 - dielectric coatings, 184
 - electrically conductive coatings, 183
 - friction coatings, 183
 - Ni-based composite coatings, 201
 - thermally sprayed coatings, 4 ff
 - thick coatings, 4 ff
 - thin coatings, 4 ff
 - wear resistant, low-friction coatings, 183
- Cold gas dynamic spray (GDS), 1
 - cold spray gun, 73
 - heat chamber, 73
 - pick-up device, 74
 - powder flow rate sensor, 73
- collision, 88
 - collisions with particles, 101
 - particle-wall collisions, 101
- compression, 142
 - diametrical compression, 142

- diametrical compression of notched samples, 142
- uniaxial compression, 142
- computational fluid dynamics, 100
- corrosion protection, 184 ff
- de Laval nozzle, 1
 - nozzle geometry, 102
- deformation, 14 ff
 - critical strain, 20
 - deformation behavior, 160
 - flattening, 16
 - flow localization processes, 18
 - material softening, 18
 - severe deformation, 16 ff
 - shear localization, 17
 - strain rate, 19
 - strain-hardening, 18
 - temperature sensitivity of flow stress, 19
- deposition efficiencies, 2 ff
- diffusion constants, 96
- drag coefficient, 100
- drag force, 106
- DYMET gun, 81
- elastic modulus, 144
 - effect of porosity on elastic constants, 148
 - ultrasonic velocity, 144
- electric arc spraying, 5
- energy balance equation, 49
- explosive cladding, 9
- failure criterion, 165
- friction coefficient, 193
- friction of the particles, 100
- Gas Flow, 98
- grit blasting, 171
- Hall–Petch equation, 163
- Hashin–Shtrikman (H–S) model, 148
- high-pressure GDS system, 68
 - kinetic spray system, 68
- impact, 11 ff
 - contact time, 31
 - deformation
 - elastic, 14 ff
 - particle impact mechanism, 14 ff
 - erosion, 12
 - heat generation due to impact, 96
 - impact interactions, 11 ff
 - interaction of a single particle, 11 ff
 - rebound, 12
- impingement, 42
- interface, 32
- interparticle contact, 44, 137
- isentropic gas flow model, 91, 103
- Johnson–Cook model, 23
- kinetic energy, 3
- MCA model, 150
- mechanical properties, 142 ff
 - adhesion tests, 142 ff
 - flow stress, 160
 - fracture toughness, 142 ff
 - structural strength, 142 ff
- metal–matrix composites (MMC), 135
 - Al metal–matrix composites, 138
 - Al/Al₂O₃ coating composites, 156 ff
 - hybrid–particulate composites, 138
 - matrix elements, 138
 - Ni–TiC composite, 157

- particulate-reinforced MMCs, 140
- microforging process, 94
- microstructure formation, 37
 - defect generation, 37
 - dislocation density, 20
 - elongated dislocation cell formation, 51
 - randomly distributed dislocations, 51
 - recrystallized microstructure, 51
- microstructure of LPGDS composites, 153
- minimal contact area (MCA) model
 - minimum contact area, 153
- Normal Shock Region, 121
- particle, 16
 - agglomerates, 42
 - cluster formations, 93
 - clustering, 93
 - concentration
 - particle volume concentration, 75
 - density, 2
 - dynamic, 98
 - fracture of grains, 54
 - fragmentation, 54
 - mass flow rate, 86
 - morphology, 2
 - particle distortion, 54
 - particle size, 2
 - particle strains, 30
 - velocity, 1 ff
 - critical particle velocity, 1 ff
 - radial particle velocity, 116
 - rebound velocity, 14
- particle concentration, 87
- Particle-laden jet, 96 ff
 - Free Jet, 116
- particle-to-gas mass flow ratio, 87
- particle/substrate interface, 23
- penetrators, 42
- portable GDS system, 65
 - portable GDS SST machine, 78
- postprocessing operations, 167
- powder feeding rate, 81 ff
- powder feeding system, 70
 - axial injection, 66
 - dispensing hoppers, 70
 - fluidized bed hoppers, 70
 - high-pressure powder delivery system, 68
 - powder metering device, 71
 - powder passage, 69
 - vibratory powder feed systems, 70
- powder jet composition, 83
- powder jet incidence angle α , 83
- powder metallurgy (PM), 167
- processing of smart components, 210
- rapid prototyping, 7
- repair applications, 185
 - car body shape repair, 198
 - Cast iron G2500 gear box repair, 196
 - casting die components repair, 196
 - casting repair, 195
 - on-line repairs of stamping dies, 186
- rule of mixture, 147
- shock compression of the powder layer, 11
- shock energy, 52
- shock-wave consolidation, 52
 - consolidation, 54
 - interparticle sliding, 54
 - powder densification, 54

- rearrangement of grains (particles), 54
- shock consolidation model, 156
- shock-wave layer, 93
- shock-wave powder compaction, 37
 - defect energy, 39
 - fracture energy, 39
 - friction energy, 39
 - interparticle friction, 37
 - mechanical alloying reactions, 89
 - microkinetic energy, 37, 38 ff
 - plastic deformation energy, 38 ff
 - some chemical reaction, 39
- soldering priming, 183
- solid phase concentrations, 87
- solid-state welding, 9
 - solid-state diffusion reactions, 12
- stagnation pressure, 111
- stagnation temperature, 120
- stand-off distance, 83
- strengthening GDS composites, 158
- stress–strain curve, 25 ff
 - flow stress, 55
 - static yield stress, 26
 - strain rate sensitivity, 25 ff
 - strain-rate hardening, 26
 - the strain localization parameter, 26
 - the work hardening, 26
 - thermal sensitivity, 25 ff
 - thermal softening, 26
 - thermal softening parameter, 25 ff
- structure parameters, 140
 - composite density ρ , 166
 - interparticle distance, 141
 - mean free interparticle distance, 166
 - porosity, 141
 - reinforcement particle clustering, 147
 - spatial arrangement of the particles, 141
 - volume fraction of adiabatic shear bands, 166
 - volume fraction of bridges, 166
 - volume fraction of particles, 141
- subsonic Mach number, 126
- thermal dissipation, 183
- thermal spraying methods, 5
 - flame spraying, 5
 - plasma spraying, 5
 - velocity air-fuel (HVAF), 5
- toughening mechanisms, 165
 - crack bridging, 165
 - crack tip shielding, 165
 - crack–tip interaction, 165
- tribology tests, 187
- up capacity, 113
- volume fraction of adiabatic shear bands, 50
- wear behavior, 189
- yield Function, 55