INDEX

- absorbing capacitance 429
- AC-breakers 37
- AC fluctuation components 147
 - active power 147, 169, 177
 - DC-bus voltage 169
 - electromagnetic torque 158, 177
 - grid harmonic current 168
 - reactive power 147, 169, 177
- AC source 314
- activation time 367
- ambient temperature 267, 396
- angular frequency 68
 - electrical 68
 - grid 107
 - induced EMF voltage 68
 - mechanical 68
 - PLL 103
 - rotor 69, 74
 - slip 69, 95
 - stator 69
 - synchronous 74, 94
- angular speed 68, 89, 105
 - dq reference frame 89
 - grid 114, 124, 129
 - harmonic 167, 191
 - mechanical 68
 - PLL 105
 - rotating 6
 - wind turbine 28
- auto-reclosing 55
- average loss 388
- bandwidth, *see* control bandwidth
- block diagram 119
 - calculate power loss 390
- capacitor current control 271, 282
- current control 199, 249
- DC voltage outer loop 252
- grid voltage disturbance 151
- GSC control system 250
- harmonics control loop 225
- power-control mode 119
- speed-control mode 126
- bode diagram 111–113, 121, 188–189
- bonding wire 392
- breaker resistance 367
- caged motor (CM) 418
 - Inertia Emulation Mode 419
 - Speed-Control Mode 419
 - Torque-Control Mode 419
- capacitor current 250, 268, 270, 273
 - control 280, 282
 - phase 270
 - second-order component 270
- carrier ratio 388
- ceramic-based substrates 392
- Clarke transformation 78
 - inverse 79
- Coffin–Manson lifetime models 407
- collector-emitter voltage, IGBT 445
- communication 440
 - baud rate 440
 - CAN 440
 - serial port 440
- complex plane 77, 450
- conduction loss 387, 390
 - freewheeling diode 388
 - IGBT 388
- conduction time 388

Advanced Control of Doubly Fed Induction Generator for Wind Power Systems, First Edition.

Dehong Xu, Frede Blaabjerg, Wenjie Chen, and Nan Zhu.

© 2018 by The Institute of Electrical and Electronics Engineers, Inc. Published 2018 by John Wiley & Sons, Inc.

454 INDEX

- constraint functions 47
 - absolute power constraint 47
 - delta power constraint 47
 - ramp rate constraint 47
- control
 - active power control 47
 - dc capacitor current control 278
 - dc voltage fluctuation control 266
 - demagnetizing current control 349
 - feedforward control 359
 - feedforward transient compensation control 349
 - flux linkage tracking control 349, 356
 - FRT strategy 348
 - Inertial control 50
 - multiple-loop control 167
 - pitch control 28
 - power converter 31
 - DFIG 32
 - PMSG 32
 - SCIG 33
 - reactive power control 49
 - resonant control 195
 - stator current balancing control 262
 - thermal-oriented reactive power control 411
 - vector control 99
- control bandwidth 145, 249
- control circuit
 - analogy signals 424
 - contactor driver 425, 429
 - DSP controller 425, 428
 - grid emulator 431
 - GSC 424
 - IGBT drivers 425, 428
 - sampling circuit 424, 428
- control diagram. *See also* control scheme
 - DFIG 7, 119, 126, 131
 - GSC 113
 - recurring fault ride through 55, 379
- controllable range 349, 355, 361
- controller
 - adaptive resonant controller 196
 - bandwidth 162–163
 - gain 171
 - parameters 162, 182, 188, 223, 228, 263
 - PI 28, 167
 - resonant controller 195
- controller design
 - grid side converter 99
 - multiple-loop control 182, 188
 - PI 111
 - resonant 223
 - rotor side converter 99, 121, 133
- control limitations
 - capacitor current 255
 - DC voltage 256
 - GSC 250
 - RSC 249–250
 - vector control 307
- control loop
 - active power 107
 - capacitor current 278
 - fifth harmonic suppression 173
 - GSC current 107
 - harmonics 200
 - inner current loop 125
 - pitch 28
 - reactive power loop 125
 - RSC current 263
 - vector control 152
- control model
 - GSC 109
 - RSC
 - power-control mode 119
 - speed-control mode 126
 - starting mode 131
- control performance
 - capacitor current control 292
 - harmonics control 215
 - phase compensation 228
 - recurring grid fault ride through 379
 - vector control 114
- control scheme 32, 271
 - capacitor current control 271
 - demagnetizing current control 350
 - feedforward control 360
 - flux linkage tracking control 356
 - grid emulator 434
 - grid side converter 107
 - GSC 107
 - harmonic voltage disturbance 171
 - test bench 423
 - recurring grid fault ride through 379
 - RSC
 - current multiple-loop control 172, 178

- power-control mode 115
- speed-control mode 125
- starting mode 130
- test bench 426
- control software 440
 - auxiliary 440
 - debugging 440
 - display 440
 - Modbus protocol 440
- control target
 - current multiple-loop control 168
 - feedforward control 360
 - GSC 101
 - recurring grid fault ride through 375
 - RSC
 - harmonic voltage disturbance 176
 - power-control mode 114
 - speed-control mode 124
 - starting mode 128
- converter 85
 - ABB, ACS800-67 269
 - abc model 85
 - AC–DC converters 85
 - active power 90
 - back-to-back converters 14, 210
 - dq model 89, 91
 - equivalent circuits 85, 89
 - per-unit system 94
 - PWM modulator 93
 - reactive power 90
- cooling method 396
 - forced air cooling 394
 - liquid cooling 394
- crossover frequency 111–112, 121, 133, 152–153, 164, 170, 183
- crowbar model 310
- crowbar resistance 430
- current multiple-loop control
 - control effect 175, 179
 - control scheme 172, 178
 - control target 168, 176
 - controller design 182
 - dynamic performance 188
 - fifth-order harmonic loop 174
 - fundamental current loop 188
 - stability 188
 - system model 172, 179
- current rating 421
- current ripple 433
- DC bus 85
 - capacitance 148, 269–270
 - negative pole 86
 - positive pole 86
 - power 148
 - voltage fluctuation 148–149, 169
- DC-bus voltage 308, 388, 397
 - rotor-side crowbar 365
 - three-phase fault voltage recovery 319
- DC chopper 25
- DC-link voltage, *see* DC-bus voltage
- DC voltage fluctuation control
 - control model 272
 - control scheme 271
 - DC current calculation 270
 - modular design 269
- demagnetizing current control
 - control scheme 350
 - controllable range 353
 - demagnetizing coefficient 349–350
 - limitation 352
- DFIG system 397
- DFIG test system
 - overcurrent protection 444
 - overvoltage protection 448
 - shutdown 444
 - starting sequence 441
- direct bond copper (DBC) 392
- distributed power generation 59
 - FRT ability 61
 - grid limitation 59
 - power control 60
- dq rotating transformation 89
- driving inverter 418–419
- duty cycle 88, 390
- dynamic loss, *see* switching loss
- dynamic model
 - converters 85
 - DFIG 80
 - balanced voltage dips 301
 - symmetrical voltage dip 300
 - rotor-side crowbar 366
- dynamic performance 127–128
 - capacitor current control 270
 - feedforward control 360
 - multiple-loop control 188
 - resonant control 221, 230
 - SRF-PLL 344, 348

456 INDEX

- dynamic performances, conventional current control 214
- dynamic response 52
 - current harmonics control 213
 - GSC 292
 - harmonic loop 183
 - sequence-separation method 346
- dynamic thermal impedance 394
- efficiency 40
- electrical energy 6
- electrolytic capacitor 260
 - core temperature 256, 267
 - lifetime 247
- electromagnetic torque 28–29, 85, 162
 - flux linkage tracking control 357
- fundamental fluctuation
 - components 243
 - recurring grid faults 325, 369, 374
 - second-order fluctuation 243, 249
- electromagnetic torque fluctuations 309, 358, 374–375, 379
- electromotive force (EMF) 304
 - rotor 68, 304, 333
 - stator 70
- emergency supply equipment 57
- energy crisis 3
- energy storage systems 16
- equivalent circuit 70
 - filter
 - L filter 87
 - LCL filter 92
 - DFIG
 - dynamic 80
 - steady-state 70
 - voltage dip 300–301
 - forced machine 301
 - natural machine 301
- fault current 39, 316, 320
- fault-detection algorithm 365
- fault duration 52, 431
- fault ride-through (FRT) 10, 18, 299
 - high voltage ride-through (HVRT) 55
 - low voltage ride-through (LVRT) 52
 - recurring fault ride-through 55
- feedforward control 435
 - controllable range 361
 - feedforward term 360
 - scheme 361
- filters
 - capacitance 433
 - inductor 389
 - low pass filter (LPF) 171
 - second-order Butterworth LPF 174
- flux observer 350, 356, 360
- flux trajectory 303
 - asymmetrical grid fault 303
 - symmetrical voltage dips 301
 - voltage recovery 317–318
- Foster structure thermal model 395
- frequency variation 47, 218, 437
- FRT strategy 349
 - hardware solutions 364
 - improved control 348
 - recurring grid fault 372
- fundamental frequency 85, 145, 198, 388
- gearbox 6–7
- generator 6–7
 - asynchronous 10
 - caged generator (CG) 7
 - doubly fed induction generator (DFIG) 7, 9
 - permanent magnet synchronous generator (PMSG) 7
 - synchronous 10
- greenhouse gas emissions 4
- grid
 - frequency deviation 44
 - grid current 143–144
 - power factor 49
 - power quality 141
 - rated frequency 44
 - rated voltage 44
 - stability 48
 - voltage amplitude 314
 - voltage deviation 44
- grid code 43
 - frequency range 45
 - harmonic current 58
 - harmonic voltage 40
 - islanding detection 62
 - voltage range 45

- grid emulator 313, 418, 431
 - DC-bus capacitance 434
 - filter inductance 433
 - switching devices 432
 - switching frequency 433
- grid fault 25, 37, 44, 51
 - asymmetrical 37, 40, 302
 - fault angles 39, 328
 - first grid fault 322, 325, 328, 338, 369–370, 379
 - recurring grid fault 44
 - single-phase-ground fault 56
 - single-phase short circuit to earth 56
 - three-phase short circuit 56
 - two-phase short circuit 56
- grid fault model 315
- grid inductance 163
- grid integration 11, 15
- grid-side converter (GSC) 85
 - fundamental active power 246
 - second-order fluctuation active power 246
 - voltage vector equation 244
- grid synchronization
 - grid side converter 102, 129
 - rotor side converter 124
- grid voltage 37
 - 3rd-order harmonic 40, 141
 - 11th grid harmonic 144
 - 13th grid harmonic 144
 - amplitude 343
 - asymmetrical rate 57
 - d components 342
 - dip 313
 - negative fifth grid harmonic 143
 - negative-sequence 238, 302, 305, 343
 - phase angle 342–343
 - positive components 346
 - positive-sequence 238, 302, 343
 - positive seventh grid harmonic 143
 - q components 342
 - relationship 346
 - swells 55
 - THD 58
 - unbalanced 57
 - unbalance factor 255
 - vector trajectory 343
 - zero-sequence 237, 302
- grid voltage disturbance 143, 149, 155, 201, 273
- hardware design
 - charging circuits 422
 - DC-bus capacitance 422
 - DC-bus voltage 422
 - filter inductance 422
 - grid emulator 431
 - IGBT chips 421
 - switching frequency 421
- hardware protection 25
- hardware solutions
 - DC chopper 367
 - rotor-side crowbar 364
 - series dynamic braking resistor 367
- harmonic angular speed 167
- harmonics distortion
 - active power 146, 156
 - DC-Bus voltage 147, 158
 - electromagnetic torque 158
 - frequency component 156
 - grid current 145
 - reactive power 147, 156
 - rotor current 152
 - stator current 154
- HCPL-316J 445
- high voltage ride-through (HVRT) 55
- HVDC transmission 17
- hydraulic system 57
- hydropower 4
- IEEE 1547 62
- inductances
 - filter 89, 422
 - grid 163
 - leakage 68
 - magnetizing 70
 - mutual 68, 77
 - stray 270
- inner current loop
 - GSC 113
 - rotor side converter 132
 - RSC
 - power-control mode 121
 - speed-control mode 125
 - starting mode 133
- inrush current 9, 422

458 INDEX

- installed capacity 59
- isolated breakers 320
- junction temperature 388, 392
 - fluctuation 395, 401, 407
 - grid-side converter 400
 - LVRT 407
 - rotor-side converter 400
- lifetime
 - capacitor 248, 260
 - capacitors 206
 - DFIG system 267
 - estimated 267
 - generation unit 11
 - models 407
 - power converters 412
 - power semiconductor 394
- line impedance 37
 - asymmetrical 40
- line-side converter (LSC) 25
- loss dissipation 387, 392
- loss model 387
 - freewheeling diode 387
 - grid-side converter 390
 - IGBT 387
 - rotor-side converter 390
- low-pass filters (LPF) 142, 280, 282
 - second-order Butterworth 174
- low voltage ride-through (LVRT) 402
- magnetic saturation 141
- magnetizing current 136
- mean values 14
- mechanical angular speed 8, 68
- mechanical energy 6
- mechanical power 73
- mechanical rotating speed 28
- mechanical stress 10, 22–23
- mechanical torque 28–29
- multicell converter 13
- multiple-pole synchronous generators 7
- mutual inductance matrix 76
- negative flux, asymmetrical grid faults 303
- negative-sequence 40, 312
- negative-sequence current 237
- negative-sequence dq frame 238
- negative-sequence flux 303, 307
- negative-sequence impedance 237
- negative-sequence voltage 237
- non-hydropower renewable generation 4
- non-ideal grid 51, 418
- non-zero vector 388
- nonlinear load 40, 141
- on-state loss, *see* conduction loss
- on-time 388, 396
- operating mode
 - sub-synchronous 74
 - super-synchronous 74
 - synchronous 74
- outer voltage loop
 - GSC 111
 - RSC 133
- overcompensation 55
- overcurrent 52, 309, 348, 366
- overexcited current 409
- overexcited reactive power 409
- overheating 40
- overvoltage 52, 309, 348, 367
- PCC, *see* point of common coupling
- permanent magnets 24
- phase angle 388
- phase delay 111
- phase-locked loop (PLL) 102
 - loop filter (LP) 102
 - phase detector (PD) 102
 - SRF-PLL 103
 - voltage-controlled oscillator (VCO) 103
- phase margin 188, 214, 219, 221
- phasor diagram 389
 - rotor 391
 - stator 391
- physical-meaning-based Cauer
 - structure 393
- PI controller
 - corner frequency 112
 - transfer function 174
- pitch angle 26–28
- PLECS software 400
- pneumatic system 57
- point of common coupling 34, 37, 45
- polynomial expression 388
- power control loop 198, 228, 379

- power converter 6–7, 387
- power density 392
- power electronic converter 6
 - full-scale 24
 - generator-side converter 25
 - grid-side converter 23
 - line-side converter 25
 - partial-scaled 23
 - rotor-side converter 23
- power flow 6
- power loss 388
 - grid-side converter 399
 - LVRT 406
 - rotor-side converter 399
- power quality 40, 141, 146
- power scale 163
- power semiconductor 14
- power semiconductor device 15, 387
 - IGBT modules 14–15
 - JFET 15
 - Schottky barrier diode 15
 - SiC MOSFET 15
- power system 35
- power system stabilizer (PSS) 51
- primary control 47
- primary voltage 34
- protection
 - gate driving 445
 - response speed 447
 - sampling 447
 - software 448
- pulse-width-modulation 10
- PWM pulses 108
- PWM waveform 85
- reactive control
 - power factor control 49
 - Q Control 49
 - voltage control 49
- reactive current 366
 - LVRT 403
 - recurring grid fault ride through 375
- reactive current injection (RCI) 402
- reactive power 32, 35, 44, 90, 144, 147, 156, 397, 408
 - LVRT 404
- reactive power control loop
 - grid side converter 107
 - rotor side converter 121
- reactive power support 32, 44, 49, 52, 371
- recurring grid faults 369
 - asymmetrical 332
 - durations 330
 - first grid fault 321, 341
 - one-phase-to-ground 332
 - second grid fault 330
- reference frame
 - $\alpha\beta$ 82, 343
 - abc 76, 103, 172, 179, 354, 424, 449
 - dq 82
 - negative fifth-order 173
 - seventh-order 179
 - relationship 82
- rejection capability 201
- reliability 11, 394
- renewable energy 3–4
- resistances
 - AC 89
 - breaker 367
 - crowbar 312
 - parasitic 75, 92
 - rotor 68, 163
 - stator 68, 116, 163
 - thermal 394–395
- resonant control
 - closed-loop transfer function 215
 - control effect 201
 - control model 199
 - control scheme 198
 - control target 197
 - design procedure 222
 - dynamic performance 221
 - normal control loop 215
 - phase compensation methods 223
 - Lead 224
 - Lead–Lag 227
 - phase margin 223
 - stability 218
 - static performance 215
- resonant controller
 - crossover frequency 223
 - cut-off frequency 195
 - frequency response 196
 - gain 195–196
 - mathematical model 195
 - resonant frequency 195
 - transfer function 195

460 INDEX

- reverse-recovery energy 388
- rotational speed
 - rotor 26, 31, 68
 - stator flux 68
 - wind turbine 27
- rotor 70, 163
- rotor current 32, 70, 309, 357
 - first grid fault 325
 - LVRT 405
 - negative-sequence 312
 - recurring grid fault 371
 - rotor-side crowbar 365
 - second grid fault 326
- rotor current control loop 198
- rotor EMF 305, 318, 360
- rotor equivalent circuit 359
- rotor flux linkage
 - dq reference frame 356
 - flux linkage tracking control 356
- rotor flux vector 76
- rotor forced current 375
- rotor natural current 307–308, 349
- rotor natural voltage 311
- rotor-side converter (RSC) 24, 85
- rotor-side crowbar 25, 309, 429
 - DC-side resistor 365
 - DC switch 365
 - rectifier 365
 - three-phase resistor 365
 - three-phase switches 365
- rotor speed 23, 29, 335
 - demagnetizing current control 353
 - feedforward control 361
- rotor time constant 311
- rotor voltage vector 76
- RSC control mode
 - MPPT mode 124
 - power-control mode 99
 - speed-control mode 99
 - starting mode 128
 - switching 135
- safety limit 378
- safety operation area (SOA) 378
- saw-tooth waveform 103
- scheme
 - DFIG test system 420
 - grid emulator 431
 - series dynamic braking resistor 369
 - test bench 417
- secondary voltage 34
- second fault 371
- second grid fault 375
- serial port 440
- short circuits 37
- short-term energy storage 50
- single-phase short-term interruption (STI) 55
- sinusoidal current 388
- soft-start contactor 422
- soft starter 9
- soft-start resistors 422
- soft-start sequence 425
- space vector modulation 388
- speed ratio 26–27
- squirrel cage induction generator(SCIG) 23
- SRF-PLL
 - dynamic response 345
 - grid fault 342
 - LPF 345
 - sequence separation 345
 - time-delayed 345
- stand-by mode 31
- star configuration 68
- static synchronized serious compensator (SSSC) 369
- stator active power 391
 - fundamental active power 241
 - second-order fluctuation component 241
- stator breaker 136
- stator current 307, 309
 - first grid fault 325
 - negative-sequence 312
 - recurring grid fault 371
- stator current balancing control
 - control scheme 260
 - control targets 260
 - resonant controller 261
- stator current harmonics control loop 198
- stator flux 307
 - flux trajectory 303
 - flux vector 76, 300
 - rotational speed 68
 - stator forced flux 301, 357
 - stator natural flux 301, 357

- stator negative flux 357
 - voltage dip 301
- stator-forced flux
 - recurring grid faults 322
 - voltage recovery 315
- stator natural current 333
- stator natural flux 311, 369
 - asymmetrical fault recovery 320
 - asymmetrical grid faults 303
 - damping 363
 - demagnetizing current control 349
 - feedforward control 360
 - FRT 300
 - non-instant fault 315
 - recurring grid faults 322, 333, 371, 377, 379
 - symmetrical voltage dip 312
 - three-phase fault voltage
 - recovery 318–320
 - three-phase-to-ground fault
 - recovery 320
- stator reactive power
 - fundamental 242
 - second-order fluctuation 242
- stator time constant 54, 304, 311, 369, 373
 - demagnetizing current control 349
 - series dynamic braking resistor 368
- stator voltage 307, 368
- stator winding 67
- sub-synchronous operation 389
- sub-synchronous speed 312
- super-synchronous operation 389
- super-synchronous speed 123
- superposition principle 144, 301
- suppression effect 162
 - stator current 155
 - vector control 154
- switch bridge 85
- switching energy 388
- switching frequency 164, 390–391, 397, 433
- switching functions 88
- switching loss 387–388
 - freewheeling diode 388
 - IGBT 388
- switching period 388
- switching period averaging 88
- switching ripple current 267
- symmetrical sequence 388
- synchronous frequency 70
- synchronous generators 36, 43
- synchronous inertia 50
- temperature level 393
- terminal voltage
 - wind power system 37, 369
 - wind turbine 35
- test bench 417
- thermal capacitance 396
- thermal coupling 393
- thermal cycling 14, 411
 - long-term 395
 - short-term 395
- thermal impedance
 - cooling method 394
 - dynamic 394
 - power module 393–394
 - TIM 394
- thermal interface material (TIM) 392
- thermal model 392
 - Foster structure 393, 395
 - power device 393
- thermal performance 392
- thermal resistance 396
 - steady-state 394
- thermal stress 387, 392, 412
- thermal time constant 394
- three-phase sources 85
- thyristor 9
- time-varying system 75
- tip speed ratio 31
- torque 23
- torque fluctuations 152, 325
- total harmonic distortion (THD) 141
- transfer function 153
 - closed-loop 110, 120, 132
 - open-loop 110–111, 132, 152
- transformer 6–7
- transient current 362
 - feedforward control 360
 - recurring grid fault 369
 - rotor-side crowbar 365
 - series dynamic braking resistor (SDBR) 368
- turbine rotor radius 26
- turbine torque 28
- turn-off energy 388
- turn-off loss 398

462 INDEX

- turn-on energy 388
- turn-on loss 398
- turns ratio 205
- two-level 10

- unbalanced grid voltage 40, 57, 237
 - control limitations 249–250, 253
 - DC-bus current 246
 - DC-bus voltage 247
 - electromagnetic torque 243
 - grid current 244
 - GSC active power 246
 - negative effects 248
 - negative-sequence 237
 - positive-sequence 237
 - rotor current 239
 - stator active power 241
 - stator current 240
 - stator reactive power 241
 - zero-sequence 237
- unit quantity 94
- up-level control 439

- vector control 141, 143–144, 307, 371
- voltage dip 51
 - active current 54
 - active power restoration speed 55
 - asymmetrical 305
 - balanced voltage dips 301
 - generator 313
 - level 301
 - non-instant 313
 - reactive current 54
 - recovery 54–55, 315
 - response time 54
 - serious dips 309
 - single-phase 238
 - small dips 308
 - symmetrical 52, 300–301
 - tolerance 52
 - transient time 313
 - two-phase 238
 - unbalanced 57, 260
- voltage dip level 52, 308, 319
 - first grid fault 323, 326, 333
 - recurring grid fault 371
 - second grid fault 326
- voltage drop 388

- voltage rating 15
- voltage recovery, recurring grid fault 369
- voltage recovery time 37
- voltage-source-converter 10

- wind energy 4, 6
- wind farm 17, 34
- wind power generation system 7, 21
- wind power installation 4
- wind power penetration 44
- wind power plants 16, 46
- wind power system 5, 21
 - capacity 12
 - copper loss 72
 - cost 11
 - equivalent dynamic circuit 83
 - levelized cost of energy(LCOE) 11
 - lifetime 11
 - mechanical power 73
- model
 - $\alpha\beta$ 77
 - abc 75
 - dq 81
 - relationship 82
- reliability 13
- rotor current 70
- rotor power 72
- rotor reactive power 72
- rotor voltage 70
- rotor winding 67
- slip ratio 72
- stability 44
- stator power 72
- stator reactive power 73
- steady-state equivalent circuit 68
- steady-state model 67
- wind speed 14, 26–27, 31
- wind turbine 7, 26
 - cut-In speed 31
 - cut-off speed 31
 - fixed-speed 21, 23
 - horizontal 6
 - nacelle 6, 394
 - rotational speed 31
 - shaft 6
 - structure 6
 - variable-speed 22–23, 26
- wind turbine system 6
- wind turbine system (WTS) 6

INDEX **463**

- wind turbine system
 - control scheme 29
 - fixed-speed 7
 - Maximum power point tracking (MPPT) 31
 - variable-speed 8
 - wind turbine model 26
- winding ratio 409
- WPP, *see* wind power plants
- WPS, *see* wind power system
- Y connection 75
- zero-vector 388